Append string

Add text at the end

```
string name = "Kaush";
name.append(" Lakhotia");
cout << name;
```

Kaush Lakhotia.

Substr(Start, end) — index. length.

Substring (Extract part of string)

```
string word = "Programming";
cout << word.substr(0,8);
```

Progra

Erase part of string erase()

```
string word = "helloworld";
word.erase(5,5);
cout << word
```

hello.

find character or word find()

```
string text = "hello world";
cout << text.find("world");
```

6

It returns the index position.

Convert string to int

stoi()

```
string num = "1.2.3";
int x = stoi(num)
```

Convert int to string.

to_string()

```
int num = 50;
string s = to_string(num);
```

upper case:	toupper();
lower case:	tolower();
Check number:	~~Check number()~~ isdigit();
Check alphabet:	isalpha();

Problem statement: Palindrome checker.

finding length of string

use length() or size()

```
string word = "Kavish";
cout << word.length();
```

#5

Joining of string

use + operator.

```
string first = "Kavish";
string last = "Lakhotia";
string full = first + " " + last;
cout << full;
```

Kavish Lakhotia.

String comparison.

```
string a = "apple";
string b = "apple";
if (a==b){
    cout << "same";
}
```

same.

String (loop)

```
string name = "Kavish";
for (int i = 0; i < name.length(); i++){
    cout << name[i] << endl;
}
```

y.

K
K
I
S
h

- used for reversing
- counting characters.
- palindrome checkes.

Taking string as input

```
string name;
cin >> name;
cout << name;
```

input: Kush lakhotia.

output is only Kush
(only first word is stored)

So we use getline() [Best method]

// Read the full line including spaces

```
string name;
getline (cin, name);
    cout << name;
```

input: Kush lakhotia
Output: //

Accessing character of A string

We can access character using index
Index start from 0.

Ex HELLO
01234

Ex

```
#include <iostream>
#include <string>
using namespace std;
int main (){
    string word = "HELLO";
    cout << word[0] << endl;
    cout << word[1] << endl;
```

H
L

```
void showBalance
    Cout << balance ;
  }
};
int main () {
    bank b1;
    b1.setBalance(5000);
    b1. showBalance ();
  }.
```

- Output: 5000
- balance is private
- It cannot be access directly.
- we use function to access it.

$\boxed{\text{b1.balance = 5000; (this will give error)}}$

Problem statement: Bank Account using OOP.

Day-13 (Strings)

A string is a sequence of characters used to store text
Example: hello, Krish, C++

In C++ we use the string class from the string library

```
#include <iostream>
#include <string>
using namespace std ;
int main () {
    string name = "Krish" ;
    Cout << name ;
  }.
```