```
        name = n;
    }
    void display() {
        cout << id << " " << name << endl;
    }
};

int main() {
    Student S1;          // default values
    Student S2(101);     // partial
    Student S3(102, "Krish");  // full
    S1.display();
    S2.display();
    S3.display();
```

how it works?

- no arguements → all default values
- one arguements → rest will be default
- full arguements → override defaults;

Important rule

Default arguement must be given from right to left

```
// correct
student(int p, string n = "unknown");

// wrong
student(int i=0, string n);
```

Problem statement: Create a class Book

- no input → name = "unknown", price = 0
- one input → set name.
- Two input → set Both.

Book class initilization with Default Arguements.

How it works?

- Same constructor name (same as class)
- Different parameter list.
- Compiler decide which one to calls based on arguments

Key Point
- constructor can be overload like functions
- must differ in numbers or type of parameters
- Return type does not matter.

Problem statement : ~~Class~~ Volume Box using constructor overloading

Day 28 (Constructor with default arguments)

A constructor with default arguments allows you to assign default values to parameters, so objects can be created with zero, one or full arguments.

Why use it?
- Reduce multiple constructor
- Make code cleaner
- flexible object creation.

Syntax

```
ClassName ( type arg1 = value1 , type arg2 = value2 )
        {   //initilization

    }.
```

Example

```
#include <iostream>
using namespace std;
Class Student {
  public :
    int id ;
    string name;
  Student ( int i= 0, string n = "unknown" ){
        id= i;
```