

```

A getx(int x) {
    this → x = x;
    return *this;
}

```

# Method chaining (future)

Problem statement 1: student marks

Problem statement 2: Rectangle dimension.

Problem statement 3: Employee detail;

Using namespace std;  
class Student {

public:

int marks;

void setData (int marks) {

this->marks = marks;

// Current object

void display () {

cout << "Marks: " << marks << endl;

}

int main () {

Student s;

s.setData (90);

s.display ();

}

Why this need in above.

void setData (int marks) {

marks = marks;

}

hence both are same, variable → confusion.

return a garbage value.

to fix.

this->marks = marks;

that Point to current Obj.

## # Returning object

class A {

public:

int x;

$(ptr + i) \rightarrow \text{name}$ . (Both are same.)

### Important

Student \*ptr = new Student[n]

This does;

Allocate memory

Call constructors for each object

(Never modify original  
current  
(ptr++) using dynamic  
array)

### Deleting memory

delete[] ptr

Just use [] because:

- Its an array.
- Free all object

Super

Practice Problem: Student Record System.

- Requirement  $\rightarrow$  create a class student with  
• name, marks.

- In main  $\rightarrow$

- take number of student
- Create dynamic array
- Take input
- Display details.
- find and display student with highest marks.

### # Day 4 IC this Pointer in C++

this is a pointer that points to the current obj

Why is it used?

To reference to the current object variable and function.

### Basic Example