```
int student :: count = 0; →
```

Default it is zero, But we can start also like count = 1000; But only here not in class cont.

```
int main () {
    Student s1, s2;
      s1.setData ();
      s2. setData ();
    Cout << "Total student:" << student::count << endl;

    return 0;
}
```

you can call like this

Only one copy of count
All object share it
Must define outside the class.

Static member function

- Belong to class not object
- Can access only static members.
- Cannot access non static variables.

Ex

```
Class student {
    public:
        static int count;
        static void showCount() {
            Cout << "Total Student: " << Count << endl
        }
};
int student :: count = 0;
int main () {
    Student :: count = 5;
    Student :: showcount () ;   // call without object
}
```

Problem statement : Employee counter system.

Problem statement: Shop item list
- add items
- store them as object
- display all items.

Day-16 (static members and static member function)

Static means shared
→ Instead of every object have its own copy
→ all object can share one common function or variable.

Static data member

A static data member is a variable that is
- shared amoung all objects
- created only once.
- stored separately (not inside each object)

Example

```
#include <iostream>
using namespace std;
class Student {
  public:
    int id;
    static int count; // static data member.

    void setdata() {
        cout << "Enter id: " ;
        cin >> id;
        count++;
    }

    void showData () {
        cout << "ID: " << id << endl;
    }
};
```