

# Wrapper Methods

May 23, 2021

## 1 1 - Forward Feature Selection

```
[2]: # Forward Feature Selection
from mlxtend.feature_selection import SequentialFeatureSelector
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression

dataset = pd.read_csv('dataset1.csv')
X= dataset.drop(columns='Result')
Y= dataset['Result']
dataset.head()
```

```
[2]:   Links_in_tags  Abnormal_URL  Submitting_to_email  SFH  ...  on_mouseover
RightClick  Redirect  Result
0           0           0           -1           1   1  ...           1
1          -1           1           -1           1   1  ...           1
1           1           -1           1           1   1  ...           1
1          -1           1           -1           1   1  ...           1
2           1           -1           -1           1   1  ...           1
1           0           1           -1           1  -1  ...          -1
3           -1           -1           -1           1  -1  ...          -1
-1          -1           0           -1           1  -1  ...          -1
4           0           -1           -1           1  -1  ...          -1
-1          -1           -1           -1           1  -1  ...          -1
```

[5 rows x 10 columns]

```
[12]: X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.2)

lr = LogisticRegression(class_weight='balanced', solver='lbfgs',
    random_state=42, n_jobs=-1, max_iter=500)
ffs = SequentialFeatureSelector(lr, k_features='best', forward=True, n_jobs=-1)
ffs.fit(X,Y)
features = list(ffs.k_feature_names_)
features = list(map(str, features))
```

```
print(features)
```

```
['Links_in_tags', 'Abnormal_URL', 'SFH', 'Iframe', 'onmouseover', 'RightClick', 'Redirect']
```

Above algorithm have drop two features - Submitting\_to\_email - popUpWidnow

```
[ ]:
```

```
[ ]:
```

## 2 2 - Backward Feature Selection

```
[15]: # Backward Feature Selection
from mlxtend.feature_selection import SequentialFeatureSelector
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression

dataset = pd.read_csv('dataset1.csv')
X= dataset.drop(columns='Result')
Y= dataset['Result']
# X.head()

lr = LogisticRegression(class_weight='balanced', solver='lbfgs',
    ↳random_state=42, n_jobs=-1, max_iter=500)
bfs = SequentialFeatureSelector(lr, k_features='best', forward=False, n_jobs=-1)
bfs.fit(X,Y)
features = list(bfs.k_feature_names_)
features = list(map(str, features))

print(features)

# lr.fit(X_train[features], Y_train)
# y_pred = lr.predict(X_train[features])
# print(y_pred)
```

```
['Links_in_tags', 'Abnormal_URL', 'SFH', 'onmouseover', 'RightClick', 'Redirect']
```

Above algorithm have drop 3 features - Submitting\_to\_email - Iframe - popUpWidnow

```
[ ]:
```

```
[ ]:
```

### 3 3 - Exhaustive Feature Selection

```
[17]: # Exhaustive Feature Selection
from mlxtend.feature_selection import ExhaustiveFeatureSelector
from sklearn.model_selection import train_test_split
from sklearn.ensemble import RandomForestClassifier
import pandas as pd

dataset = pd.read_csv('dataset1.csv')
X= dataset.drop(columns='Result')
Y= dataset['Result']

X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.2)

# create the exhaustive feature selector object
efs = ExhaustiveFeatureSelector(RandomForestClassifier(),
                                min_features=4,
                                max_features=8,
                                scoring='roc_auc',
                                cv=2)

efs = efs.fit(X,Y)

selected_features = X_train.columns[list(efs.best_idx_)]
print(selected_features)
```

Features: 381/381

```
Index(['Links_in_tags', 'Abnormal_URL', 'SFH', 'onmouseover', 'RightClick',
      'Redirect'],
      dtype='object')
```

Above algorithm have drop 3 features - Submitting\_to\_email - Iframe - popUpWidnow

```
[ ]:
```

```
[ ]:
```

### 4 4 - Recursive Feature Elimination

```
[19]: #Recursive Feature Elimination
import pandas as pd
from sklearn.feature_selection import RFE

dataset = pd.read_csv('dataset1.csv')
X= dataset.drop(columns='Result')
Y= dataset['Result']
```

```

X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.2)

rfe = RFE(lr, n_features_to_select=7) #choose number of columns to be selected
rfe = rfe.fit(X_train,Y_train)

# summarize all features
for i in range(X.shape[1]):
    print('Column: %d, Selected %s, Rank: %.3f col_name: %s' % (i, rfe.
↪support_[i], rfe.ranking_[i], X_train.columns[i]))

```

```

Column: 0, Selected True, Rank: 1.000 col_name: Links_in_tags
Column: 1, Selected True, Rank: 1.000 col_name: Abnormal_URL
Column: 2, Selected True, Rank: 1.000 col_name: Submitting_to_email
Column: 3, Selected False, Rank: 3.000 col_name: SFH
Column: 4, Selected True, Rank: 1.000 col_name: Iframe
Column: 5, Selected True, Rank: 1.000 col_name: popUpWidnow
Column: 6, Selected True, Rank: 1.000 col_name: on_mouseover
Column: 7, Selected True, Rank: 1.000 col_name: RightClick
Column: 8, Selected False, Rank: 2.000 col_name: Redirect

```

Above algorithm have drop 2 features - SFH - Redirect