

ADVANCE DEVOPS EXP 6

Name:Laksh Vijay Sodhai

Class:D15A

Roll No:59

Aim:To Build, change, and destroy AWS / GCP /Microsoft Azure/ DigitalOcean infrastructure Using Terraform.
(S3 bucket or Docker) fdp.

Part A:Creating docker image using terraform

Prerequisite:

1) Download and Install Docker Desktop from <https://www.docker.com/>

Step 1:Check Docker functionality

```
Microsoft Windows [Version 10.0.22631.4037]
(c) Microsoft Corporation. All rights reserved.

C:\Users\student>docker

Usage:  docker [OPTIONS] COMMAND

A self-sufficient runtime for containers

Common Commands:
run      Create and run a new container from an image
exec     Execute a command in a running container
ps       List containers
build    Build an image from a Dockerfile
pull     Download an image from a registry
push     Upload an image to a registry
images   List images
login    Log in to a registry
logout   Log out from a registry
search   Search Docker Hub for images
version  Show the Docker version information
info     Display system-wide information

Management Commands:
builder  Manage builds
buildx*  Docker Buildx
checkpoint Manage checkpoints
compose* Docker Compose
container Manage containers
context  Manage contexts
debug*   Get a shell into any image or container
desktop* Docker Desktop commands (Alpha)
dev*     Docker Dev Environments
extension* Manages Docker extensions
feedback* Provide feedback, right in your terminal!
```

Check for the docker version with the following command.

```
C:\Users\student>docker --version
Docker version 27.1.1, build 6312585

C:\Users\student>|
```

Now, create a folder named ‘Terraform Scripts’ in which we save our different types of scripts which will be further used in this experiment.

Step 2: Firstly create a new folder named ‘Docker’ in the ‘TerraformScripts’ folder. Then create a new docker.tf file using Atom editor and write the following contents into it to create a Ubuntu Linux container.

Script:

```
terraform {
  required_providers {
    docker = {
      source = "kreuzwerker/docker"
      version = "2.21.0"
    }
  }
}

provider "docker" {
  host = "npipe:////./pipe/docker_engine"
}

# Pull the image
resource "docker_image" "ubuntu" {
  name = "ubuntu:latest"
}

# Create a container
resource "docker_container" "foo" {
  image = docker_image.ubuntu.image_id
  name = "foo"
  command = ["sleep", "3600"]
}
```

}

```
docker.tf X
docker.tf
1 terraform {
2   required_providers {
3     docker = {
4       source = "kreuzwerker/docker"
5       version = "2.21.0"
6     }
7   }
8 }
9
10 provider "docker" {
11   host = "npipe:////./pipe/docker_engine"
12 }
13
14 # Pull the image
15 resource "docker_image" "ubuntu" {
16   name = "ubuntu:latest"
17 }
18
19 # Create a container
20 resource "docker_container" "foo" {
21   image = docker_image.ubuntu.image_id
22   name = "foo"
23   command = ["sleep", "3600"]
24 }
25
```

Step 3: Execute Terraform Init command to initialize the resources

```
PS C:\Users\Admin\TerraformScripts> cd Docker
PS C:\Users\Admin\TerraformScripts\Docker> terraform init
Initializing the backend...
Initializing provider plugins...
- Finding kreuzwerker/docker versions matching "2.21.0"...
- Installing kreuzwerker/docker v2.21.0...
- Installed kreuzwerker/docker v2.21.0 (self-signed, key ID BD080C4571C6104C)
Partner and community providers are signed by their developers.
If you'd like to know more about provider signing, you can read about it here:
https://www.terraform.io/docs/cli/plugins/signing.html
Terraform has created a lock file .terraform.lock.hcl to record the provider
selections it made above. Include this file in your version control repository
so that Terraform can guarantee to make the same selections by default when
you run "terraform init" in the future.

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.

If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.
```

Step 4: Execute Terraform plan to see the available resources

```
PS C:\Users\Admin\TerraformScripts\Docker> terraform plan
```

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:

- + create

Terraform will perform the following actions:

docker_container.foo will be created

```
+ resource "docker_container" "foo" {
  + attach      = false
  + bridge      = (known after apply)
  + command     = [
    + "sleep",
    + "3600",
  ]
  + container_logs = (known after apply)
  + entrypoint    = (known after apply)
  + env          = (known after apply)
  + exit_code     = (known after apply)
  + gateway       = (known after apply)
  + hostname      = (known after apply)
  + id            = (known after apply)
  + image         = (known after apply)
  + init          = (known after apply)
  + ip_address    = (known after apply)
  + ip_prefix_length = (known after apply)
  + ipc_mode      = (known after apply)
  + log_driver    = (known after apply)
  + logs          = false
  + must_run      = true
  + name          = "foo"
  + network_data  = (known after apply)
  + read_only     = false
  + remove_volumes = true
  + restart       = "no"
  + rm            = false
```

```
  + runtime       = (known after apply)
  + security_opts = (known after apply)
  + shm_size      = (known after apply)
  + start         = true
  + stdin_open    = false
  + stop_signal    = (known after apply)
  + stop_timeout  = (known after apply)
  + tty           = false
```

```
  + healthcheck (known after apply)
```

```
  + labels (known after apply)
}
```

docker_image.ubuntu will be created

```
+ resource "docker_image" "ubuntu" {
  + id          = (known after apply)
  + image_id    = (known after apply)
  + latest      = (known after apply)
  + name        = "ubuntu:latest"
  + output      = (known after apply)
  + repo_digest = (known after apply)
}
```

Plan: 2 to add, 0 to change, 0 to destroy.

Step 5: Execute Terraform apply to apply the configuration, which will automatically create and run the Ubuntu Linux container based on our configuration. Using command :
“terraform apply”

```
● PS C:\Users\Admin\TerraformScripts\Docker> terraform apply
```

```
Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:  
+ create
```

```
Terraform will perform the following actions:
```

```
# docker_container.foo will be created  
+ resource "docker_container" "foo" {  
  + attach      = false  
  + bridge      = (known after apply)  
  + command     = [  
    + "sleep",  
    + "3600",  
  ]  
  + container_logs = (known after apply)  
  + entrypoint    = (known after apply)  
  + env          = (known after apply)  
  + exit_code     = (known after apply)  
  + gateway      = (known after apply)  
  + hostname     = (known after apply)  
  + id           = (known after apply)  
  + image        = (known after apply)  
  + init         = (known after apply)  
  + ip_address    = (known after apply)  
  + ip_prefix_length = (known after apply)  
  + ipc_mode     = (known after apply)  
  + log_driver    = (known after apply)  
  + logs         = false  
  + must_run     = true  
  + name         = "foo"  
  + network_data = (known after apply)  
  + read_only    = false
```

```
  + remove_volumes = true  
  + restart        = "no"  
  + rm             = false  
  + runtime        = (known after apply)  
  + security_opts  = (known after apply)  
  + shm_size       = (known after apply)  
  + start          = true  
  + stdin_open     = false  
  + stop_signal    = (known after apply)  
  + stop_timeout   = (known after apply)  
  + tty           = false  
  
  + healthcheck (known after apply)  
  
  + labels (known after apply)  
}
```

```
# docker_image.ubuntu will be created  
+ resource "docker_image" "ubuntu" {  
  + id          = (known after apply)  
  + image_id    = (known after apply)  
  + latest      = (known after apply)  
  + name        = "ubuntu:latest"  
  + output      = (known after apply)  
  + repo_digest = (known after apply)  
}
```

```
Plan: 2 to add, 0 to change, 0 to destroy.
```

```
Do you want to perform these actions?
```

```
Terraform will perform the actions described above.  
Only 'yes' will be accepted to approve.
```

```
Enter a value: yes
```

```

docker_image.ubuntu: Creating...
docker_image.ubuntu: Creation complete after 9s [id=sha256:edbf74c41f8a3501ce542e137cf28ea04dd03e6df8c9d66519b6ad761c2598aubuntu:latest]
docker_container.foo: Creating...
docker_container.foo: Creation complete after 2s [id=01adf07e5918931fee9b90073726a03671037923dd92032ce0e15bbb764a6f24]

Apply complete! Resources: 2 added, 0 changed, 0 destroyed.

```

Docker images, Before Executing Apply step:

```

PS C:\Users\Admin\TerraformScripts\Docker> docker images

```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
------------	-----	----------	---------	------

Docker images, After Executing Apply step:

```

PS C:\Users\Admin\TerraformScripts\Docker> docker images

```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
ubuntu	latest	edbf74c41f8	3 weeks ago	78.1MB

Step 6: Execute Terraform destroy to delete the configuration, which will automatically delete the Ubuntu Container.

```

PS C:\Users\Admin\TerraformScripts\Docker> terraform destroy
docker_image.ubuntu: Refreshing state... [id=sha256:edbf74c41f8a3501ce542e137cf28ea04dd03e6df8c9d66519b6ad761c2598aubuntu:latest]
docker_container.foo: Refreshing state... [id=01adf07e5918931fee9b90073726a03671037923dd92032ce0e15bbb764a6f24]

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
- destroy

Terraform will perform the following actions:

# docker_container.foo will be destroyed
- resource "docker_container" "foo" {
  - attach      = false -> null
  - command     = [
    - "sleep",
    - "3600",
  ] -> null
  - cpu_shares  = 0 -> null
  - dns         = [] -> null
  - dns_opts    = [] -> null
  - dns_search  = [] -> null
  - entrypoint  = [] -> null
  - env         = [] -> null
  - gateway     = "172.17.0.1" -> null
  - group_add   = [] -> null
  - hostname    = "01adf07e5918" -> null
  - id          = "01adf07e5918931fee9b90073726a03671037923dd92032ce0e15bbb764a6f24" -> null
  - image       = "sha256:edbf74c41f8a3501ce542e137cf28ea04dd03e6df8c9d66519b6ad761c2598a" -> null
  - init        = false -> null
  - ip_address  = "172.17.0.2" -> null
  - ip_prefix_length = 16 -> null
  - ipc_mode    = "private" -> null
  - links       = [] -> null
  - log_driver  = "json-file" -> null
  - log_opts    = {} -> null
  - logs        = false -> null
  - max_retry_count = 0 -> null
}

```

```

- memory           = 0 -> null
- memory_swap      = 0 -> null
- must_run         = true -> null
- name             = "foo" -> null
- network_data     = [
  - {
    - gateway           = "172.17.0.1"
    - global_ipv6_prefix_length = 0
    - ip_address        = "172.17.0.2"
    - ip_prefix_length  = 16
    - network_name      = "bridge"
    # (2 unchanged attributes hidden)
  },
] -> null
- network_mode      = "default" -> null
- privileged        = false -> null
- publish_all_ports = false -> null
- read_only         = false -> null
- remove_volumes   = true -> null
- restart           = "no" -> null
- rm               = false -> null
- runtime           = "runc" -> null
- security_opts     = [] -> null
- shm_size         = 64 -> null
- start            = true -> null
- stdin_open       = false -> null
- stop_timeout      = 0 -> null
- storage_opts      = {} -> null
- sysctls          = {} -> null
- tmpfs            = {} -> null
- tty              = false -> null
# (8 unchanged attributes hidden)
}

```

```

# docker_image.ubuntu will be destroyed
- resource "docker_image" "ubuntu" {
  - id           = "sha256:edbfe74c41f8a3501ce542e137cf28ea04dd03e6df8c9d66519b6ad761c2598aubuntu:latest" -> null
  - image_id     = "sha256:edbfe74c41f8a3501ce542e137cf28ea04dd03e6df8c9d66519b6ad761c2598a" -> null
  - latest       = "sha256:edbfe74c41f8a3501ce542e137cf28ea04dd03e6df8c9d66519b6ad761c2598a" -> null
  - name         = "ubuntu:latest" -> null
  - repo_digest  = "ubuntu@sha256:8a37d68f4f73ebf3d4efafbcf66379bf3728902a8038616808f04e34a9ab63ee" -> null
}

```

Plan: 0 to add, 0 to change, 2 to destroy.

Do you really want to destroy all resources?

Terraform will destroy all your managed infrastructure, as shown above.
There is no undo. Only 'yes' will be accepted to confirm.

Enter a value: yes

```

docker_container.foo: Destroying... [id=01adf07e5918931fee9b90073726a03671037923dd92032ce0e15bbb764a6f24]
docker_container.foo: Destruction complete after 0s
docker_image.ubuntu: Destroying... [id=sha256:edbfe74c41f8a3501ce542e137cf28ea04dd03e6df8c9d66519b6ad761c2598aubuntu:latest]
docker_image.ubuntu: Destruction complete after 1s

```

Destroy complete! Resources: 2 destroyed.

Docker images After Executing Destroy step

```

PS C:\Users\Admin\TerraformScripts\Docker> docker images

```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
------------	-----	----------	---------	------