

Technical Implementation Manual: AI-Driven Real World Asset Tokenization Platform

July 16, 2025

Abstract

This document provides a comprehensive technical manual for the AI-Driven Real World Asset Tokenization Platform, a sophisticated system designed to streamline the verification and tokenization of Real World Assets (RWAs). Leveraging an agentic AI framework, the platform integrates Large Language Models (LLMs) for data extraction, specialized verification agents for asset assessment, and a tokenization module for blockchain integration. This manual details the system architecture, database schema, and Python module functionalities, with accurate code snippets and explanations.

Contents

1	Introduction	2
1.1	Challenges in RWA Tokenization	2
1.2	Solution Overview	2
2	System Architecture	2
3	Setup & Prerequisites	2
3.1	Environment Setup	2
3.2	Required Packages	3
4	Technical Implementation	3
4.1	Database Schema (database.py)	3
4.1.1	Explanation	3
4.2	LLM Utilities (llm_utils.py)	3
4.2.1	Explanation	5
4.3	Verification Agent (verification_agent.py)	5
4.3.1	Explanation	5
4.4	Modular Agents (agents_modular.py)	5
4.4.1	Explanation	7
4.5	Tokenization Agent (tokenization_agent.py)	7
4.5.1	Explanation	8
4.6	Main Application (main.py)	8
4.6.1	Explanation	9
5	Conclusion	9

1 Introduction

The tokenization of Real World Assets (RWAs) transforms physical assets into digital tokens, enhancing liquidity and accessibility. However, traditional processes are manual and inefficient. This platform automates RWA verification and tokenization using advanced AI techniques.

1.1 Challenges in RWA Tokenization

- **Data Extraction and Standardization:** Unstructured asset data requires significant effort to process into temporal Processing.
- **Verification Complexity:** Ensuring authenticity, value, and compliance demands expertise.
- **Interoperability:** Integrating asset data with blockchain systems is challenging.
- **Scalability:** Manual processes limit throughput.

1.2 Solution Overview

The platform automates the RWA pipeline with:

- **LLM Integration:** Extracts structured data from unstructured inputs.
- **Modular Verification Agents:** Assess asset aspects (e.g., completeness, value, jurisdiction).
- **Tokenization Agent:** Generates mock blockchain tokens.
- **Centralized Database:** Manages user, asset, and transaction data.
- **Flask Backend API:** Orchestrates workflows.

2 System Architecture

The platform features a modular, scalable design:

1. **User Interface (Frontend):** Web-based asset submission.
2. **Backend API (Flask):** Manages requests and agent coordination.
3. **Database (SQLite):** Stores platform data.
4. **AI Agents Layer:**
 - LLM Utility
 - Verification Agents (BasicInfoAgent, ValueAgent, etc.)
 - Tokenization Agent
5. **Blockchain Layer (Mock):** Simulates blockchain operations.

3 Setup & Prerequisites

3.1 Environment Setup

- **Python:** Virtual environment recommended.
- **Flask:** Web framework.
- **SQLite:** Development database.

3.2 Required Packages

Install via `pip install flask python-dotenv google-generativeai flask-sqlalchemy flask-cors`.

4 Technical Implementation

4.1 Database Schema (`database.py`)

```
1 from flask_sqlalchemy import SQLAlchemy
2 from datetime import datetime
3 import json
4
5 db = SQLAlchemy()
6
7 class User(db.Model):
8     id = db.Column(db.Integer, primary_key=True)
9     wallet_address = db.Column(db.String(42), unique=True, nullable=False)
10    email = db.Column(db.String(120), nullable=True)
11    kyc_status = db.Column(db.String(20), default='pending')
12    jurisdiction = db.Column(db.String(10), nullable=True)
13    created_at = db.Column(db.DateTime, default=datetime.utcnow)
14
15 class Asset(db.Model):
16     id = db.Column(db.Integer, primary_key=True)
17     user_id = db.Column(db.Integer, db.ForeignKey('user.id'), nullable=False)
18     asset_type = db.Column(db.String(50), nullable=False)
19     description = db.Column(db.Text, nullable=False)
20     estimated_value = db.Column(db.Float, nullable=False)
21     location = db.Column(db.String(100), nullable=False)
22     verification_status = db.Column(db.String(20), default='pending')
23     token_id = db.Column(db.String(64), nullable=True)
24     requirements = db.Column(db.Text, default='{}')
25     created_at = db.Column(db.DateTime, default=datetime.utcnow)
26     updated_at = db.Column(db.DateTime, default=datetime.utcnow, onupdate=datetime.utcnow)
27
28 class Transaction(db.Model):
29     id = db.Column(db.Integer, primary_key=True)
30     asset_id = db.Column(db.Integer, db.ForeignKey('asset.id'), nullable=False)
31     transaction_type = db.Column(db.String(50), nullable=False)
32     transaction_hash = db.Column(db.String(64), nullable=True)
33     status = db.Column(db.String(20), nullable=False)
34     details = db.Column(db.Text, nullable=True)
35     created_at = db.Column(db.DateTime, default=datetime.utcnow)
```

4.1.1 Explanation

- **User:** Stores user details (e.g., wallet address). - **Asset:** Holds asset data with verification and tokenization status. - **Transaction:** Logs operations like verification and tokenization.

4.2 LLM Utilities (`llm_utils.py`)

```

1 import os
2 import json
3 import re
4 from dotenv import load_dotenv
5 import google.generativeai as genai
6
7 load_dotenv()
8 GENAI_API_KEY = os.getenv("GEMINI_API_KEY")
9 genai.configure(api_key=GENAI_API_KEY)
10 model = genai.GenerativeModel("gemini-2.0-flash")
11
12 def extract_asset_info_with_llm(user_input: str) -> dict:
13     prompt = f"""
14     You are an intelligent assistant that extracts structured information
15     from asset descriptions.
16     Extract and return the following fields in JSON:
17     - asset_type: One of [real_estate, vehicle, artwork, equipment,
18       commodity]
19     - estimated_value: A number (preferably in INR, or fallback to USD), no
20       commas or currency symbol
21     - location: City or region (e.g., 'Mumbai, India')
22     - description: The original user input
23
24     USER INPUT:
25     \"{user_input}\"
26
27     Return only valid JSON:
28     {{
29       "asset_type": "...",
30       "estimated_value": ...,
31       "location": "...",
32       "description": "..."
33     }}
34     """
35     try:
36         response = model.generate_content(prompt)
37         content = clean_llm_output(response.text.strip())
38         data = json.loads(content)
39         asset_type = data.get("asset_type", "unknown") or
40           fallback_asset_type(user_input)
41         return {
42             "asset_type": asset_type,
43             "estimated_value": float(data.get("estimated_value", 0)),
44             "location": data.get("location", "unknown"),
45             "description": data.get("description", user_input)
46         }
47     except Exception as e:
48         asset_type = fallback_asset_type(user_input)
49         return {
50             "asset_type": asset_type,
51             "estimated_value": 0,
52             "location": "unknown",
53             "description": user_input
54         }

```

4.2.1 Explanation

Extracts structured data using Gemini LLM, with fallback logic for asset type categorization.

4.3 Verification Agent (`verification_agent.py`)

```
1 from typing import Dict, List
2 from app.agents.agents_modular import CoordinatorAgent
3
4 class VerificationAgent:
5     def __init__(self):
6         self.verification_threshold = 0.7
7         self.coordinator = CoordinatorAgent()
8
9     def verify_asset(self, asset_data: Dict) -> Dict:
10        try:
11            verification_result = self.coordinator.verify(asset_data)
12            result = {
13                'overall_score': verification_result.get('overall_score',
14                0.0),
15                'status': verification_result.get('status', 'pending'),
16                'breakdown': verification_result.get('breakdown', {}),
17                'agent_notes': verification_result.get('agent_notes', []),
18                'recommendations': self._generate_recommendations(
19                    verification_result),
20                'next_steps': self._define_next_steps(verification_result.
21                    get('status', 'pending')),
22                'issues': []
23            }
24        except Exception as e:
25            result = {
26                'overall_score': 0.0,
27                'status': 'error',
28                'breakdown': {},
29                'agent_notes': [],
30                'recommendations': [],
31                'next_steps': [],
32                'issues': [f"Verification error: {str(e)}"]
33            }
34        return result
```

4.3.1 Explanation

Orchestrates verification using the 'CoordinatorAgent', providing scores, status, and recommendations.

4.4 Modular Agents (`agents_modular.py`)

```
1 import os
2 import json
3 import re
4 from dotenv import load_dotenv
5 import google.generativeai as genai
6
7 load_dotenv()
8 GENAI_API_KEY = os.getenv("GEMINI_API_KEY")
9 genai.configure(api_key=GENAI_API_KEY)
```

```

10 llm_model = genai.GenerativeModel("gemini-2.0-flash")
11
12 class BasicInfoAgent:
13     def assess(self, asset):
14         prompt = f"""
15         You are an AI agent checking if all basic asset information is
16         present and complete.
17         Asset fields:
18         - Type: {asset.get('asset_type')}
19         - Value: {asset.get('estimated_value')}
20         - Location: {asset.get('location')}
21         - Description: {asset.get('description')}
22         Score 1.0 if all fields are present and detailed, 0.5 if some are
23         missing, 0.0 if mostly missing. Explain.
24         Respond as JSON: {"score": float, "notes": "..."}
25         """
26         return call_llm(prompt)
27
28 class ValueAgent:
29     def assess(self, asset):
30         prompt = f"""
31         You are an AI agent evaluating if the asset's estimated value is
32         plausible for its type and location.
33         Asset fields:
34         - Type: {asset.get('asset_type')}
35         - Value: {asset.get('estimated_value')}
36         - Location: {asset.get('location')}
37         - Description: {asset.get('description')}
38         Score 1.0 if value is plausible, 0.4 if too low, 0.6 if too high,
39         0.5 if unknown. Explain.
40         Respond as JSON: {"score": float, "notes": "..."}
41         """
42         return call_llm(prompt)
43
44 class JurisdictionAgent:
45     def assess(self, asset):
46         prompt = f"""
47         You are an AI agent verifying the jurisdiction/location of the
48         asset.
49         Asset fields:
50         - Location: {asset.get('location')}
51         Score 0.9 if location is specific and recognized (especially any
52         Indian city/state/UT), 0.5 if vague or missing. Explain.
53         Respond as JSON: {"score": float, "notes": "..."}
54         """
55         return call_llm(prompt)
56
57 class AssetSpecificAgent:
58     def assess(self, asset):
59         prompt = f"""
60         You are an AI agent checking if the asset description contains type
61         -specific details and keywords.
62         Asset fields:
63         - Type: {asset.get('asset_type')}
64         - Description: {asset.get('description')}
65         Score 1.0 if many relevant details/keywords, 0.5 if some, 0.0 if
66         none. Explain.
67         Respond as JSON: {"score": float, "notes": "..."}

```

```

60         """
61         return call_llm(prompt)
62
63 class CoordinatorAgent:
64     def __init__(self):
65         self.agents = [
66             ("basic_info", BasicInfoAgent()),
67             ("value_assessment", ValueAgent()),
68             ("jurisdiction", JurisdictionAgent()),
69             ("asset_specific", AssetSpecificAgent())
70         ]
71
72     def verify(self, asset):
73         results = {}
74         explanations = []
75         for key, agent in self.agents:
76             agent_result = agent.assess(asset)
77             results[key] = agent_result.get("score", 0.5)
78             explanations.append(f"{key}: {agent_result.get('notes', '')}")
79         avg_score = sum(results.values()) / len(results)
80         status = "verified" if avg_score >= 0.7 else ("requires_review" if
81             avg_score >= 0.5 else "rejected")
82         return {
83             "overall_score": round(avg_score, 2),
84             "status": status,
85             "breakdown": results,
86             "agent_notes": explanations
87         }

```

4.4.1 Explanation

- **BasicInfoAgent**: Checks completeness of asset fields. - **ValueAgent**: Assesses value plausibility. - **JurisdictionAgent**: Verifies location specificity. - **AssetSpecificAgent**: Ensures type-specific details. - **CoordinatorAgent**: Aggregates agent results for final status.

4.5 Tokenization Agent (tokenization_agent.py)

```

1 import hashlib
2 import json
3 import time
4 from datetime import datetime
5 from typing import Dict
6 import uuid
7
8 class TokenizationAgent:
9     def __init__(self):
10         self.token_standard = "RWA-721"
11         self.network = "RWA-TestNet"
12
13     def tokenize_asset(self, asset_data: Dict, verification_result: Dict)
14     -> Dict:
15         if verification_result.get('status') != 'verified':
16             return {
17                 'success': False,
18                 'error': 'Asset must be verified before tokenization',
19                 'status': 'failed'

```

```

19         }
20     try:
21         token_metadata = self._generate_token_metadata(asset_data,
22             verification_result)
23         contract_data = self._create_mock_contract(asset_data,
24             token_metadata)
25         token_id = self._generate_token_id(asset_data)
26         transaction_hash = self._generate_transaction_hash(
27             contract_data)
28     return {
29         'success': True,
30         'token_id': token_id,
31         'contract_address': contract_data['address'],
32         'transaction_hash': transaction_hash,
33         'metadata': token_metadata,
34         'network': self.network,
35         'standard': self.token_standard,
36         'created_at': datetime.utcnow().isoformat(),
37         'status': 'minted'
38     }
39 except Exception as e:
40     return {
41         'success': False,
42         'error': f'Tokenization failed: {str(e)}',
43         'status': 'failed'
44     }

```

4.5.1 Explanation

Generates mock blockchain tokens for verified assets, including metadata and contract details.

4.6 Main Application (main.py)

```

1  import os
2  import sys
3  import json
4  import logging
5  from datetime import datetime
6  from flask import Flask, request, jsonify, render_template
7  from flask_sqlalchemy import SQLAlchemy
8  from flask_cors import CORS
9
10 sys.path.append(os.path.abspath(os.path.join(os.path.dirname(__file__), '..
11     ')))
12 from app.models.database import db, User, Asset, Transaction
13 from app.agents.verification_agent import VerificationAgent
14 from app.agents.tokenization_agent import TokenizationAgent
15 from app.agents.llm_utils import extract_asset_info_with_llm
16
17 app = Flask(__name__, template_folder='../templates', static_folder='../
18     static')
19 app.config['SECRET_KEY'] = 'your-secret-key-change-this'
20 app.config['SQLALCHEMY_DATABASE_URI'] = 'sqlite:///rwa_tokenization.db'
21 app.config['SQLALCHEMY_TRACK_MODIFICATIONS'] = False
22
23 db.init_app(app)
24 CORS(app)

```



```

23
24 verification_agent = VerificationAgent()
25 tokenization_agent = TokenizationAgent()
26
27 @app.route('/api/intake', methods=['POST'])
28 def asset_intake():
29     try:
30         data = request.get_json()
31         if not data or 'user_input' not in data or 'wallet_address' not in
            data:
32             return jsonify({'error': 'Missing required fields'}), 400
33         user_input = data['user_input']
34         wallet_address = data['wallet_address']
35         parsed_data = extract_asset_info_with_llm(user_input)
36         user = User.query.filter_by(wallet_address=wallet_address).first()
37         if not user:
38             user = User(wallet_address=wallet_address, email=data.get('
                email'))
39             db.session.add(user)
40             db.session.commit()
41         asset = Asset(
42             user_id=user.id,
43             asset_type=parsed_data.get('asset_type', 'unknown'),
44             description=parsed_data.get('description', user_input),
45             estimated_value=parsed_data.get('estimated_value', 0),
46             location=parsed_data.get('location', 'unknown'),
47             verification_status='requires_review',
48             requirements=json.dumps({})
49         )
50         db.session.add(asset)
51         db.session.commit()
52         return jsonify({'success': True, 'message': 'Asset submitted
            successfully.', 'asset': asset.to_dict()})
53     except Exception as e:
54         return jsonify({'error': 'Internal server error', 'details': str(e)
            }), 500

```

4.6.1 Explanation

The Flask app handles API requests, integrating LLM, verification, and tokenization processes.

5 Conclusion

This manual outlines a robust, AI-driven platform for RWA tokenization, featuring accurate agent implementations and code. Future enhancements could include real blockchain integration and expanded asset types.