

LAB-5

Aim: To Implement of Data Insertion, View Creation, and Multi-Table Join Operations in SQL

Q1. Insert new player Michale Clark with player ID 300311 in the table player

```
MySQL localhost:3306 ssl lakshay_match SQL INSERT INTO Player (PlayerID, FName, LName)
VALUES (300311, 'Michael', 'Clark');
Query OK, 1 row affected (0.0385 sec)
```

Q2. Insert new player Sam from India , Ahemdabad with player ID 406317 in the table player.

```
MySQL localhost:3306 ssl lakshay_match SQL INSERT INTO Player (PlayerID, FName, Country, Bplace) VALUES (406317, 'Sam', 'India', 'Ahmedabad');
Query OK, 1 row affected (0.0062 sec)
```

Q3. Creating View for Batsman.

CREATE VIEW Batsman (PID,FName,LName,Country,MID,Score)

AS SELECT PlayerID,FName,LName,Country,MatchID,NRuns

FROM Player,Batting

WHERE PlayerID=PID;

select * from Batsman;

```
MySQL localhost:3306 ssl lakshay_match SQL CREATE VIEW Batsman (PID, FName, LName, Country, MID, Score) AS
SELECT PlayerID, FName, LName, Country, MatchID, NRuns
FROM Player, Batting
WHERE PlayerID = PID;
Query OK, 0 rows affected (0.0104 sec)
```

```
MySQL localhost:3306 ssl lakshay_match SQL SELECT * FROM Batsman;
```

PID	FName	LName	Country	MID	Score
23001	Yuvraj	Singh	India	2755	0
25001	MS	Dhoni	India	2755	71
91001	Sanath	Jayasuriya	Sri Lanka	2755	60
94002	Chaminda	Vaas	Sri Lanka	2755	17
92002	Muthiah	Murlitharan	Sri Lanka	2755	1
89001	Sachin	Tendulkar	India	2689	91
23001	Yuvraj	Singh	India	2689	38
25001	MS	Dhoni	India	2689	36
99002	Adam	Gilchrist	Australia	2689	2
95001	Ricky	Ponting	Australia	2689	1
24001	Andrew	Symonds	Australia	2689	42
99001	Breet	Lee	Australia	2689	7
27001	Praveen	Kumar	India	2689	7
27001	Praveen	Kumar	India	2755	2
98002	Harbhajan	Singh	India	2689	3
98002	Harbhajan	Singh	India	2755	2

16 rows in set (0.0097 sec)

Q4. Creating View for Bowling.

```
CREATE VIEW Bowling2689 (PID,FName,LName,Country,NOvers,NWickets)
```

```
AS SELECT PlayerID,FName,LName,Country,NOvers,NWickets
```

```
FROM Player,Bowling
```

```
WHERE PlayerID=PID
```

```
AND MatchID=2689;
```

```
select * from Bowling2689;
```

```
MySQL localhost:3306 ssl lakshay_match SQL CREATE VIEW Bowling2689 (PID, FName, LName, Country, NOvers, NWickets) AS
SELECT PlayerID, FName, LName, Country, NOvers, NWickets
FROM Player, Bowling
WHERE PlayerID = PID
AND MatchID = 2689;
Query OK, 0 rows affected (0.0129 sec)
MySQL localhost:3306 ssl lakshay_match SQL SELECT * FROM Bowling2689;
MySQL localhost:3306 ssl lakshay_match SQL
```

PID	FName	LName	Country	NOvers	NWickets
99001	Breet	Lee	Australia	10	1
24001	Andrew	Symonds	Australia	3	1
23001	Yuvraj	Singh	India	3	0
98002	Harbhajan	Singh	India	10	1
23001	Yuvraj	Singh	India	3	0
98002	Harbhajan	Singh	India	10	1

```
6 rows in set (0.0249 sec)
```

Q5. Find name of all players who have scored 60 or more runs.

```
MySQL localhost:3306 ssl lakshay_match SQL SELECT DISTINCT P.FName, P.LName
FROM Player P
JOIN Batting B ON P.PlayerID = B.PID
WHERE B.NRuns >= 60;
```

FName	LName
MS	Dhoni
Sanath	Jayasuriya
Sachin	Tendulkar

```
3 rows in set (0.0014 sec)
```

Q6. Find the names of bowlers that have not taken any wickets in ODI match 2689 .

```
MySQL localhost:3306 ssl lakshay_match SQL SELECT DISTINCT P.FName, P.LName
FROM Player P
JOIN Bowling BW ON P.PlayerID = BW.PID
WHERE BW.MatchID = 2689
AND BW.NWickets = 0;
```

FName	LName
Yuvraj	Singh

1 row in set (0.0010 sec)

Q7. Define a view NPlayer for obtaining the names of the countries & number of players from each country.

```
MySQL localhost:3306 ssl lakshay_match SQL CREATE VIEW NPlayer (Country, NumPlayers) AS
SELECT Country, COUNT(*) AS NumPlayers
FROM Player
GROUP BY Country;
```

Query OK, 0 rows affected (0.0068 sec)

```
MySQL localhost:3306 ssl lakshay_match SQL SELECT * FROM NPlayer;
```

Country	NumPlayers
India	11
Australia	5
West Indies	1
Sri Lanka	3
Pakistan	2
Zimbabwe	1
South Africa	4
New Zealand	2
England	1
NULL	1

10 rows in set (0.0015 sec)