

Codeforces Round 962 (Div. 3)

A. Legs

2 seconds, 256 megabytes

It's another beautiful day on Farmer John's farm.

After Farmer John arrived at his farm, he counted n legs. It is known only chickens and cows live on the farm, and a chicken has 2 legs while a cow has 4.

What is the minimum number of animals Farmer John can have on his farm assuming he counted the legs of all animals?

Input

The first line contains single integer t ($1 \leq t \leq 10^3$) — the number of test cases.

Each test case contains an integer n ($2 \leq n \leq 2 \cdot 10^3$, n is even).

Output

For each test case, output an integer, the minimum number of animals Farmer John can have on his farm.

input
3
2
6
8
output
1
2
2

B. Scale

2 seconds, 256 megabytes

Tina has a square grid with n rows and n columns. Each cell in the grid is either 0 or 1.

Tina wants to reduce the grid by a factor of k (k is a divisor of n). To do this, Tina splits the grid into $k \times k$ nonoverlapping blocks of cells such that every cell belongs to exactly one block.

Tina then replaces each block of cells with a single cell equal to the value of the cells in the block. **It is guaranteed that every cell in the same block has the same value.**

For example, the following demonstration shows a grid being reduced by factor of 3.

Original grid

0	0	0	1	1	1
0	0	0	1	1	1
0	0	0	1	1	1
1	1	1	0	0	0
1	1	1	0	0	0
1	1	1	0	0	0

Reduced grid

0	1
1	0

Help Tina reduce the grid by a factor of k .

Input

The first line contains t ($1 \leq t \leq 100$) — the number of test cases.

The first line of each test case contains two integers n and k ($1 \leq n \leq 1000$, $1 \leq k \leq n$, k is a divisor of n) — the number of rows and columns of the grid, and the factor that Tina wants to reduce the grid by.

Each of the following n lines contain n characters describing the cells of the grid. Each character is either 0 or 1. It is guaranteed every k by k block has the same value.

It is guaranteed the sum of n over all test cases does not exceed 1000.

Output

For each test case, output the grid reduced by a factor of k on a new line.

input

```
4
4 4
0000
0000
0000
0000
6 3
000111
000111
000111
111000
111000
111000
6 2
001100
001100
111111
111111
110000
110000
8 1
11111111
11111111
11111111
11111111
11111111
11111111
11111111
11111111
```

output

```
0
01
10
010
111
100
11111111
11111111
11111111
11111111
11111111
11111111
11111111
11111111
11111111
```

C. Sort

5 seconds, 256 megabytes

You are given two strings a and b of length n . Then, you are (forced against your will) to answer q queries.

For each query, you are given a range bounded by l and r . In one operation, you can choose an integer i ($l \leq i \leq r$) and set $a_i = x$ where x is any character you desire. Output the minimum number of operations you must perform such that $\text{sorted}(a[l..r]) = \text{sorted}(b[l..r])$. **The operations you perform on one query does not affect other queries.**

For an arbitrary string c , $\text{sorted}(c[l..r])$ denotes the substring consisting of characters c_l, c_{l+1}, \dots, c_r sorted in lexicographical order.

Input

The first line contains t ($1 \leq t \leq 1000$) — the number of test cases.

The first line of each test case contains two integers n and q ($1 \leq n, q \leq 2 \cdot 10^5$) — the length of both strings and the number of queries.

The following line contains a of length n . It is guaranteed a only contains lowercase latin letters.

The following line contains b of length n . It is guaranteed b only contains lowercase latin letters.

The following q lines contain two integers l and r ($1 \leq l \leq r \leq n$) — the range of the query.

It is guaranteed the sum of n and q over all test cases does not exceed $2 \cdot 10^5$.

Output

For each query, output an integer, the minimum number of operations you need to perform in a new line.

input
3
5 3
abcde
edcba
1 5
1 4
3 3
4 2
zzde
azbe
1 3
1 4
6 3
uwuwuw
wuwuwu
2 4
1 3
1 6
output
0
1
0
2
2
1
1
0

For the first query, $\text{sorted}(a[1..5]) = \text{abcde}$ and $\text{sorted}(b[1..5]) = \text{abcde}$, so no operations are necessary.

For the second query, you need to set $a_1 = e$. Then, $\text{sorted}(a[1..4]) = \text{sorted}(b[1..4]) = \text{bcde}$.

D. Fun

2 seconds, 256 megabytes

Counting is Fun!

— satyam343

Given two integers n and x , find the number of triplets (a, b, c) of **positive integers** such that $ab + ac + bc \leq n$ and $a + b + c \leq x$.

Note that order matters (e.g. $(1, 1, 2)$ and $(1, 2, 1)$ are treated as different) and a, b, c must be strictly greater than 0.

Input

The first line contains a single integer t ($1 \leq t \leq 10^4$) — the number of test cases.

Each test case contains two integers n and x ($1 \leq n, x \leq 10^6$).

It is guaranteed that the sum of n over all test cases does not exceed 10^6 and that the sum of x over all test cases does not exceed 10^6 .

Output

Output a single integer — the number of triplets (a, b, c) of positive integers such that $ab + ac + bc \leq n$ and $a + b + c \leq x$.

input
4
7 4
10 5
7 1000
900000 400000
output
4
10
7
1768016938

In the first test case, the triplets are $(1, 1, 1)$, $(1, 1, 2)$, $(1, 2, 1)$, and $(2, 1, 1)$.

In the second test case, the triplets are $(1, 1, 1)$, $(1, 1, 2)$, $(1, 1, 3)$, $(1, 2, 1)$, $(1, 2, 2)$, $(1, 3, 1)$, $(2, 1, 1)$, $(2, 1, 2)$, $(2, 2, 1)$, and $(3, 1, 1)$.

E. Decode

2 seconds, 256 megabytes

In a desperate attempt to obtain your ~~wifu~~ favorite character, you have hacked into the source code of the game. After days of struggling, you finally find the binary string that encodes the gacha system of the game. In order to decode it, you must first solve the following problem.

You are given a binary string s of length n . For each pair of integers (l, r) ($1 \leq l \leq r \leq n$), count the number of pairs (x, y) ($l \leq x \leq y \leq r$) such that the amount of 0 equals the amount of 1 in the substring $s_x s_{x+1} \dots s_y$.

Output the sum of counts over all possible (l, r) modulo $10^9 + 7$.

Input

The first line contains t ($1 \leq t \leq 1000$) — the number of test cases.

Each test case contains a binary string s ($1 \leq |s| \leq 2 \cdot 10^5$). It is guaranteed s only contains characters 0 and 1.

It is guaranteed the sum of $|s|$ over all test cases does not exceed $2 \cdot 10^5$.

Output

For each test case, output an integer, the answer modulo $10^9 + 7$.

input
4
0000
01010101
1100111001
11000000111
output
0
130
147
70

F. Bomb

2 seconds, 256 megabytes

Sparkle gives you two arrays a and b of length n . Initially, your score is 0. In one operation, you can choose an integer i and add a_i to your score. Then, you must set $a_i = \max(0, a_i - b_i)$.

You only have time to perform k operations before Sparkle sets off a nuclear bomb! What is the maximum score you can acquire after k operations?

Input

The first line contains t ($1 \leq t \leq 1000$) — the number of test cases.

The first line of each test case contains n and k ($1 \leq n \leq 2 \cdot 10^5, 1 \leq k \leq 10^9$) — the length of the arrays and the number of operations you can perform.

The following line contains n integers a_1, a_2, \dots, a_n ($1 \leq a_i \leq 10^9$).

The following line contains n integers b_1, b_2, \dots, b_n ($1 \leq b_i \leq 10^9$).

It is guaranteed that the sum of n for all test cases does not exceed $2 \cdot 10^5$.

Output

For each test case, output an integer, the maximum score you can acquire after k operations.

input
5
3 4
5 6 7
2 3 4
5 9
32 52 68 64 14
18 14 53 24 8
5 1000
1 2 3 4 5
5 4 3 2 1
1 1000000
1000000
1
10 6
3 3 5 10 6 8 6 8 7 7
6 1 7 4 1 1 8 9 3 1
output
21
349
27
500000500000
47

G. Penacony

3 seconds, 512 megabytes

On *Penacony, The Land of the Dreams*, there exists n houses and n roads. There exists a road between house i and $i + 1$ for all $1 \leq i \leq n - 1$ and a road between house n and house 1. All roads are bidirectional. However, due to the crisis on Penacony, the overseeing family has gone into debt and may not be able to maintain all roads.

There are m pairs of friendships between the residents of Penacony. If the resident living in house a is friends with the resident living in house b , there must be a path between houses a and b through maintained roads.

What is the minimum number of roads that must be maintained?

Input

The first line contains t ($1 \leq t \leq 10^4$) — the number of test cases.

The first line of each test case contains two integers n and m ($3 \leq n \leq 2 \cdot 10^5, 1 \leq m \leq 2 \cdot 10^5$) — the number of houses and the number of friendships.

The next m lines contain two integers a and b ($1 \leq a < b \leq n$) — the resident in house a is friends with the resident in house b . It is guaranteed all (a, b) are distinct.

It is guaranteed the sum of n and m over all test cases does not exceed $2 \cdot 10^5$.

Output

For each test case, output an integer, the minimum number of roads that must be maintained.

input
7
8 3
1 8
2 7
4 5
13 4
1 13
2 12
3 11
4 10
10 2
2 3
3 4
10 4
3 8
5 10
2 10
4 10
4 1
1 3
5 2
3 5
1 4
5 2
2 5
1 3
output
4
7
2
7
2
3
3

For the first test case, the following roads must be maintained:

- $8 \longleftrightarrow 1$
- $7 \longleftrightarrow 8$
- $1 \longleftrightarrow 2$
- $4 \longleftrightarrow 5$

