SocialFlow

Designing a scalable social media platform

Lakshitha Wijerathne · Engineer Track — Month 6 Capstone

System design · C4 architecture · Microservices POC

1 · Problem statement

What we are building

- Mobile-first social network
- Posts (text, images, video), follow graph
- Personalised **home feed**
- Likes, comments, shares
- Real-time notifications, DMs
- Search & content moderation

Constraint	Target
Users	1M MAU · 100K DAU · +50%/yr
Concurrency	100K users
Feed load	**p95 < 200 ms**
Post publish	**p95 < 500 ms**
Availability	**99.9%** (43 min/month)
Data	No loss · GDPR

> The hard part: a **read-heavy feed (100:1)** where some authors have millions of followers.


Capacity estimation

	Average	Design peak
Post writes	500K/day → **6/s**	~30/s
Reads	50M/day → **580/s**	**~3,000/s**
Timeline inserts (×200 followers)	100M/day → 1,200/s	~6,000/s
Media storage	~50–125 GB/day	**~20–45 TB/yr** (S3 + CDN)
Hot timelines in Redis	100K active × 500 ids	**~5 GB**


The brief says 1,000 rps peak, but 50M reads/day is already 580 rps on average, so I size for ~3,000 rps.

Takeaways: writes are cheap, reads and fan-out dominate, and media is the biggest storage cost, so it goes straight to S3 and the CDN.

2 · Architecture overview — C4 Level 1: System Context



C4 Level 2: Containers



Architecture in one slide

- **Edge:** CloudFront → ALB → **Kong** (JWT, rate limit, routing, correlation id)
- **Domain services**, each owns its data: User · Post · Feed · Notification · Message · Media · Search · Moderation
- **Sync** REST for request/response; **async Kafka events** for everything after the response: `post.created` → fan-out, search index, moderation, notifications, analytics
- **Storage per need:** Postgres (correctness) · Redis (speed) · Cassandra (append-heavy) · Elasticsearch · S3
- **Discovery:** Consul — self-registration + health checks; Kong resolves via Consul DNS

Decision	Instead of	Why
Microservices	Monolith	Different scaling & failure profiles
Kafka + outbox	Dual write / RabbitMQ	Durable, replayable, no lost events
Hybrid fan-out	Pure push / pull	Fast reads, no celebrity write storms

3 · Deep dive: the Feed Service — hybrid fan-out

Push for normal authors (≤ 10K followers)
→ write post id into each follower's timeline
→ read = **one Redis** `ZREVRANGE`

Pull for celebrities (> 10K followers)
→ store once in `author_posts`
→ merged into readers' feeds at read time


Warm-only pushes
→ Redis updated only for active users
→ cold timelines rebuilt from durable store

	Read	Write
Pull	❌ N queries	✅ 1
Push	✅ 1 query	❌ 1M for celebs
Hybrid	✅ 1 + few	✅ bounded

Trade-offs accepted

- More complex read path (merge + dedupe)
- Eventual consistency: fan-out lag target p95 < 5 s
- Durable timelines grow fast → TTL 30 days, Cassandra

C4 Level 3: Feed Service components



Feed read path — staying under 200 ms

1. **Timeline Cache** — Redis ZSET (~2 ms)
2. *Miss* → `feed_items` + async re-warm
3. **Content Aggregator** — merge celebrity posts
4. Hydrate 20 posts in **one batch call** — behind a **circuit breaker**
5. **Ranking Engine**

   `(1 + 0.3·ln(1+likes)) × 0.5^(age/6h)`
6. Opaque cursor → stable mobile paging

Step	Budget
Kong	5 ms
Redis timeline	2 ms
Celebrity pulls	5 ms
Hydration	20 ms
Rank + serialise	5 ms
Server total	**≈ 40 ms**

Measured in the POC (laptop, through Kong):

p50 ≈ 23 ms · p95 ≈ 41 ms

feed-service internal p95 ≈ 25 ms

4 · Scalability strategy

Horizontal scaling

- Stateless services + HPA; scale-out needs **no gateway change** (Consul DNS)
- Kafka consumers scale to partition count
- WebSocket tier: ~25K connections/node

Caching tiers

- CDN for media (> 95% hit)
- Redis: timelines, post bodies, follow lists
- Event-driven invalidation + TTL safety net

Database scaling path

1. Primary + sync standby + read replicas
2. PgBouncer, partition `posts` by month; timelines/DMs → Cassandra
3. **Shard by user/author id** (64 logical shards), Snowflake ids

At 10× (10M MAU, ~30K rps)

Same shape, more capacity: Redis 10–15 shards, 48 partitions, active-active EU/US.

Reliability — designing for failure

Failure	What happens	Mechanism
Post Service down	Feed still served from cached post bodies (`degraded: true`)	**Circuit breaker** + fallback
Redis down / evicted	Feed served from durable store, re-warmed	Cache-aside
Kafka down at publish	Post saved; event published later	**Transactional outbox** + relay
User Service down	Fan-out pauses, nothing lost	Kafka retry, idempotent consumer
Instance dies	Removed from routing in ≤ 5 s	Consul health checks
Consul loses state	Instances re-register themselves	Registration watchdog

CAP per domain: accounts / posts → **CP** · feeds, counters, notifications → **AP**

GDPR: export & erasure via `user.deleted` events, crypto-shredding, EU residency

5 · Demo — working microservices

```
docker compose up -d --build          # Kong, Consul, Kafka, Postgres, Redis + 3 services
docker compose up -d --scale post-service=2
node scripts/demo.mjs --chaos
```

What you will see

1. 3 services registered & healthy in Consul
2. Users, follows, posts through **Kong** (JWT: no token → 401)
3. Kafka fan-out → feed `source: db` → `cache`
4. Celebrity post **pulled** at read time
5. Redis key deleted → DB fallback
6. Load balanced across 2 post-service replicas

Chaos: stop post-service

```
req 1-4  200 OK degraded=true  CLOSED
req 5    200 OK degraded=true  OPEN
req 6-7  200 OK degraded=true  OPEN (rejected fast)
restart → breaker CLOSED, degraded=false
```

14 unit tests: ranking, cursors, fan-out push/pull, breaker behaviour, JWT verification

Summary

- **Requirements first:** 100:1 reads, celebrity skew, < 200 ms feed, 99.9% availability
- **Hybrid fan-out** + Redis timelines are the core of the design
- **Events (Kafka + outbox)** decouple the 500 ms publish path from fan-out, search, moderation
- **Every dependency can fail** without taking the feed down: breakers, fallbacks, cache-aside
- **POC proves the patterns:** Kong gateway with JWT auth, Consul discovery, circuit breakers, Kafka fan-out
- **Scales 10× without changing shape**, only capacity and storage engines

Artifacts: design doc · C4 L1–L3 (draw.io + PNG) · 6 ADRs · POC repo

6 · Questions?

Why Kafka over RabbitMQ? · Why not pure push? · How do you handle unfollows? · What breaks first at 10×?

Lakshitha Wijerathne · Thank you