

MANGALORE INSTITUTE OF TECHNOLOGY & ENGINEERING

(A Unit of Rajalaxmi Education Trust ®, Mangalore)

Autonomous Institute Affiliated to V.T.U, Belagavi, Approved by AICTE, New Delhi

Accredited by NAAC with A+ Grade & ISO 9001:2015 Certified Institution



PROJECT PHASE – 1 REPORT

“Edge-Intelligent Condition Monitoring system”

Submitted in partial fulfillment of the requirements for the award of the degree of

BACHELOR OF ENGINEERING

in

MECHATRONICS

by

Lakshman Shrestha

Anoop Kumar A S

Prajwal M

Rakesh Salian

4MT23MT012

4MT24MT402

4MT24EC404

4MT24EC407

Under the Guidance of

Dr. KiranKumar M V

Associate Professor

Dept. of Mechatronics

Dr. Srikrishna Shastri C

Associate Professor

Dept. of ECE

DEPARTMENT OF MECHATRONICS

(Accredited by NBA)

2025-2026

MANGALORE INSTITUTE OF TECHNOLOGY & ENGINEERING

(A Unit of Rajalaxmi Education Trust ®, Mangalore)

Autonomous Institute Affiliated to V.T.U, Belagavi, Approved by AICTE, New Delhi

Accredited by NAAC with A+ Grade & ISO 9001:2015 Certified Institution

MITE



Invent Solutions

DEPARTMENT OF MECHATRONICS

(Accredited by NBA)

CERTIFICATE

This is to certify that the project work entitled “**Edge-Intelligent Condition Monitoring system**” is a bonafide work carried out by **Mr. Lakshman Shrestha (USN:4MT23MT012), Mr. Anoop Kumar A S (USN:4MT24MT402), Mr. Prajwal M (USN: 4MT24EC404) & Mr. Rakesh Salian (USN: 4MT24EC407)** in partial fulfillment for the award of degree of **Bachelor of Engineering in Mechatronics of Mangalore Institute of Technology & Engineering (Autonomous)** during the year **2025 - 2026**. It is certified that all corrections and suggestions indicated for Internal Assessment have been incorporated in the report deposited in the departmental library. The project has been approved as it satisfies the academic requirements in respect of project work prescribed for the Bachelor of Engineering degree.

Dr. KiranKumar M V
Project Guide

Dr. Srikrishna Shastri C
Project Guide

Dr. Bindu Madhavi J
Head of Dept. Mechatronics

Dr. Vinayambika S Bhat
Head of Dept. ECE

Dr. Prashanth C M
Principal

ACKNOWLEDGEMENTS

The successful completion of Phase – I of the Project titled “**Edge-Intelligent Condition Monitoring system**” would not have been possible without the support of those, whose constant guidance and encouragement helped turn our efforts into success.

We would like to thank our Project Guide **Dr. KiranKumar MV**, Associate Professor, Department of Mechatronics and **Dr. Srikrishna Shastri C**, Associate Professor, Department of Electronics and Communication Engineering for his constant encouragement and support extended throughout.

We would like to express appreciation to **Dr. Bindu Madhavi J**, Head of Department of **Mechatronics** and **Dr. Vinayambika S Bhat**, Head of Department of **Electronics & Communication Engineering** for her support and guidance.

We would like to thank our Principal **Dr. Prashanth C M**, for encouraging us and giving us an opportunity to accomplish the project.

We also thank our management who helped us directly or indirectly in the completion of Phase – I of the project.

Our special thanks to faculty members and others for their constant help and support.

Above all, we extend our sincere gratitude to our parents and friends for their constant encouragement with moral support.

Lakshman Shrestha
4MT23MT012

Anoop Kumar A S
4MT24MT402

Prajwal M
4MT24EC404

Rakesh Salian
4MT24EC407

ABSTRACT

This project introduces a robust, noise-resilient, edge-driven Artificial Intelligence (AI) framework for industrial predictive maintenance (PdM) using **TinyML** deployed on **ESP32-WROOM-32** microcontrollers. In the era of Industry 4.0, industrial assets are becoming increasingly complex, with maintenance costs accounting for **15% to 60%** (and in some instances up to 70%) of total manufacturing operational expenses. Traditional maintenance strategies typically rely on reactive responses or high-latency cloud-based architectures that suffer from significant bandwidth consumption, unpredictable network communication, and data privacy concerns. To overcome these limitations, this research shifts computational intelligence directly to the machine source by deploying memory-optimized deep learning models on low-power edge hardware.

The proposed system addresses a critical research gap by transitioning from simple "snapshot" anomaly detection to comprehensive prognostic monitoring through **multi-modal data fusion**. By integrating high-frequency triaxial vibration signals from an **MPU6050** accelerometer with non-invasive electrical current data from an **SCT-013-000** transformer and motor temperature from a **DS18B20** waterproof probe, the system identifies mechanical and electrical faults—such as bearing wear, imbalance, and misalignment—while simultaneously estimating the asset's **Remaining Useful Life (RUL)**. The experimental setup utilizes an **Atv310h037n4e Schneider VFD (0.37 kW)** to control a **0.37kW/0.5Hp three-phase induction motor**, with upstream circuit protection and isolation switching provided by a **3-phase motor starter (15A, 280/440V)**, enabling diagnostic validation across various operational RPMs.

The methodology employs a noise-resilient preprocessing pipeline utilizing **Fast Fourier Transform (FFT)** to convert raw time-domain signals into identifiable spectral signatures, which are then processed by **8-bit quantized 1D Convolutional Neural Network (CNN)** or Multilayer Perceptron (MLP) models. Leveraging the ESP32's dual-core processing, the system achieves autonomous real-time inference with sub-second latency (frequently below **250ms**), ensuring an immediate response to critical degradation patterns. Experimental validations indicate that this

edge-native approach can achieve diagnostic accuracies exceeding **92%** while operating within the strict memory constraints (approx. 520 KB SRAM) of the microcontroller. The implementation of this prognostic node is expected to reduce maintenance costs by up to **30%**, minimize unplanned downtime by approximately **40%**, and achieve energy savings of up to **66.8%** compared to traditional cloud-streaming systems.

Keywords: TinyML, ESP32-WROOM-32, SCT-013, MPU6050, Fast Fourier Transform (FFT), Remaining Useful Life (RUL), Predictive Maintenance, Industry 4.0.

TABLE OF CONTENTS

SL. NO.	CONTENTS	PAGE NO.
1.	INTRODUCTION	1-5
	1.1. Background	1-3
	1.2. Problem Definition	3
	1.3. Objectives of the Proposed Work	4
	1.4. Need for the Project	4
	1.5. Application	5
2.	LITERATURE SURVEY	6-8
	2.1. Summary of Related works	6-7
	2.2. Research Gap Identification	7-8
3.	PROBLEM DEFINITION	9-11
	3.1. Problem Statement	9
	3.2. Scope of the Project	10
	3.3. Constraints and Assumption	10-11
4.	METHODOLOGY	12-17
	4.1. Proposed Approach and Algorithms	12-13
	4.2. Techniques and Tools Used	14-15
	4.3. System Design and Workflow	16-17
5.	SUMMARY AND FUTURE PLAN	18-20
6.	REFERENCES	21-22
7.	APENDICES	23-26

LIST OF FIGURES & TABLES

Sl. No.	TITLE	Page No.
Figure 1.1	Condition based maintenance	1
Figure 3.1	Reactive, Preventive, Predictive Maintenance	9
Figure 4.1	Multi-model data fusion approach	13
Figure 4.2	ESP32-WROOM-32 Devkit	14
Figure 4.3	MPU6050	14
Figure 4.4	SCT-013-000	14
Figure 4.5	DS18B20	14
Figure 4.6	Atv310h037n4e Schneider VFD (0.37 kw)	15
Figure 4.7	0.37kw/0.5Hp induction motor	15
Figure 4.8	Six-layer Industrial IoT	16
Figure 7.1	Model testing rig	23
Figure 7.2	2D model	23
Table 7.1	ESP32 Pin Configuration and Protocol Integration	24
Table 7.2	Detailed Technical Specifications of Primary Assets	25
Table 7.3	Implementation Cost Summery	25
Table 7.4	Diagnostic Classification and Spectral Identifiers	26

Chapter 1

1. INTRODUCTION

1.1 Background

The "Edge-Intelligent Condition Monitoring System" represents a critical technological evolution in industrial asset management, specifically within the frameworks of **Industry 4.0** and **Maintenance 4.0**. Predictive Maintenance (PdM) has emerged as a core operational strategy, leveraging real-time sensor data and machine learning to anticipate equipment failures before they occur. Traditional maintenance philosophies have historically transitioned from **Reactive Maintenance** (Generation I: fix-it-when-it-breaks) to **Preventive Maintenance** (Generation II: scheduled overhauls), both of which are often inefficient due to either unexpected downtime or the wasteful replacement of functional components.




Fig 1. 1 Condition based maintenance

Evolution of Industrial Maintenance

Industrial maintenance techniques have evolved significantly over the years based on technological advancements and industrial requirements. The major stages of maintenance evolution are:

Reactive Maintenance

Reactive maintenance is the earliest form of maintenance strategy where machines are repaired only after failure occurs. This approach results in high downtime, unexpected breakdowns, and increased repair costs.

Preventive Maintenance

Preventive maintenance performs scheduled servicing and replacement of machine components at regular intervals. Although it reduces sudden failures, unnecessary maintenance activities may still increase operational cost.

Predictive Maintenance

Predictive maintenance continuously monitors machine conditions using sensors and data analysis techniques. Maintenance is performed only when abnormal conditions are detected. This minimizes downtime and optimizes maintenance schedules.

Maintenance 4.0

Maintenance 4.0 integrates Artificial Intelligence (AI), Machine Learning (ML), Industrial IoT, cloud computing, and edge intelligence to create smart maintenance systems capable of autonomous monitoring and decision-making.

The transition from reactive maintenance to intelligent predictive maintenance has significantly improved industrial productivity and operational efficiency.

As industrial rotating machinery becomes increasingly sophisticated, the impact of maintenance has grown to represent between **15% and 60%** (and in some cases up to 70%) of total manufacturing operational costs. While conventional cloud-based AI solutions have provided high-quality diagnostics, they impose significant barriers, including high latency, unpredictable network communication, excessive energy consumption for wireless transmission, and data privacy concerns. The emergence of **Tiny Machine Learning (TinyML)** offers a transformative solution by enabling memory-optimized deep learning models to run on low-power, resource-constrained microcontrollers at the network's edge. By utilizing the **ESP32-WROOM-32** microcontroller, computational intelligence is shifted directly to the machine source, allowing for autonomous real-time diagnostics that minimize reliance on external cloud infrastructures.

1.2 Problem Definition

Industrial rotating machinery is a cornerstone of modern production, yet it is inherently vulnerable to mechanical and electrical failures that result in significant financial losses, equipment damage, and personnel safety risks. Current industrial maintenance strategies are often suboptimal: reactive maintenance allows for costly downtime after a failure occurs, while preventive maintenance can be wasteful by replacing functional parts according to rigid schedules. Although PdM offers a superior alternative, existing cloud-based frameworks introduce critical barriers, including high latency, excessive bandwidth consumption, and data privacy concerns.

Furthermore, industrial environments are plagued by heavy electromagnetic interference and mechanical noise, which frequently contaminate sensor data and lead to inaccurate fault detection. Most current low-cost edge implementations are limited to simple data acquisition or "snapshot" alerts, lacking the computational robustness to perform sophisticated noise filtering, spectral analysis, and multi-modal data fusion locally. There is a critical absence of an integrated, edge-native solution that can accurately classify faults while providing true prognostic insights, such as estimating the **Remaining Useful Life (RUL)** of an asset, within the strict resource constraints of a microcontroller.

1.3 Objectives of the Proposed Work

The primary goal of this project is to bridge the gap between simple anomaly detection and comprehensive prognostic monitoring at the edge through the following objectives:

- To design and deploy a **multi-modal TinyML framework** on the ESP32 that fuses triaxial vibration, electrical current, and temperature data to classify mechanical faults and estimate the **Remaining Useful Life (RUL)** of industrial assets.
- To implement a **noise-resilient preprocessing pipeline** using **Fast Fourier Transform (FFT)** for spectral feature extraction, ensuring robust diagnostic performance in harsh industrial environments.

1.4 Need for the Project

There is a critical need for PdM solutions that are both technically robust and economically accessible for small-to-medium industrial enterprises.

1. **Computational Robustness:** Traditional cloud-based approaches suffer from high latency and bandwidth constraints, which are intolerable for safety-critical real-time processing.
2. **Noise Resilience:** Industrial sensor data is frequently contaminated by mechanical and electromagnetic noise; this project provides the local processing power required for sophisticated filtering.
3. **Prognostic Depth:** By correlating physical vibrations with electrical current and thermal data, the system moves beyond simple "snapshot" monitoring to provide time-based failure histories required for true prognosis.
4. **Hardware Efficiency:** The experimental setup utilizes an Atv310h037n4e Schneider VFD (0.37 kW) to control a 0.37kW/0.5Hp 3-phase induction motor, demonstrating a professional-grade setup that remains cost-effective for smaller industrial environments.

1.5 Applications

The proposed framework is highly scalable and suited for various industrial and commercial sectors where rotating machinery is critical:

1. **Manufacturing:** Real-time monitoring of CNC machines, conveyor systems, and industrial robotic arms to reduce unplanned downtime.
2. **Energy Sector:** Health assessment of wind turbine gearboxes, grid assets, and high-power induction motors used in power generation.
3. **Wastewater Management:** Anomaly detection and prognostic monitoring of submersible pumps to prevent environmental contamination and mechanical failure.
4. **Construction:** Monitoring the usage patterns and degradation of heavy-duty handheld power tools to optimize tool lifecycles and operator safety.

Chapter 2

2. LITERATURE SURVEY

2.1 Summary of Related Works

Recent research demonstrates a strong transition from centralized cloud-based predictive maintenance architectures toward edge-native intelligence implemented on resource-constrained microcontrollers.

Gupta and Shivhare [1] [2] demonstrated that an ESP32-based TinyML framework using a 1D CNN can achieve over 92% accuracy in detecting bearing and misalignment faults from vibration data. Similarly, **Herrera *et al.*** [5] developed a low-cost TinyML prototype implementing vibration acquisition, FFT feature extraction, and MLP classification for bearing failure detection.

Zonta *et al.* [3] presented a comprehensive taxonomy of predictive maintenance in Industry 4.0, identifying that maintenance costs account for 15%–60% of total manufacturing expenses and highlighting the importance of AI-driven diagnostics. **Thakkar and Kumar** [4][5] further emphasized that edge-based architectures mitigate the latency, bandwidth, and privacy limitations inherent in cloud-based PdM systems.

Ooko and Karume [6] showed that on-device TinyML processing significantly reduces wireless transmission energy consumption and improves real-time responsiveness. **Kolok *et al.*** [7] validated the effectiveness of vibration-based IoT monitoring for rotating machinery using low-cost sensor nodes. **Nguyen *et al.*** [9] demonstrated the effectiveness of FFT-based feature extraction for machine learning-driven fault diagnosis in rotating machinery.

Foundational signal processing studies at MITE [11] [13] confirmed that vibration features such as RMS, kurtosis, and spectral peaks are reliable indicators of mechanical degradation. Liu *et al.* [10] provided a detailed review establishing vibration analysis as the dominant modality for rotating machinery fault diagnostics.

2.2 Key Insights from Literature

- Studies confirm a decisive shift from cloud-streaming architectures toward edge-native systems using microcontrollers such as the ESP32 to reduce latency and bandwidth dependency [2], [6].
- Vibration analysis remains the primary diagnostic indicator for rotating machinery faults due to its sensitivity to mechanical degradation [5], [10].
- Model optimization techniques such as 8-bit quantization and pruning enable deployment of deep learning models within strict memory constraints of edge hardware [2], [8].
- Multi-modal sensing combining vibration, current, and temperature improves diagnostic reliability and reduces false positives [4], [7].

3.3 Research Gap Identification

Despite these advancements, several limitations remain:

- **Prognostic History and RUL Estimation:** Most existing systems perform snapshot-based anomaly detection rather than time-series degradation tracking required for Remaining Useful Life (RUL) estimation on embedded hardware [3], [5].

- **Integrated Multi-Modal Data Fusion:** Existing low-cost edge solutions rely primarily on single-sensor vibration monitoring and lack end-to-end, single-chip architectures correlating vibration, current, and temperature data [2], [7].
- **Noise Resilience in Edge Preprocessing:** Many implementations lack the computational robustness to perform advanced filtering and FFT-based spectral analysis under industrial electromagnetic noise without affecting real-time performance [5], [10].

Chapter 3

3. PROBLEM DEFINITION

3.1 Problem Statement

Industrial rotating machinery is a cornerstone of modern production, yet it is inherently vulnerable to mechanical and electrical failures that result in significant financial losses, equipment damage, and personnel safety risks. Current industrial maintenance strategies are often suboptimal: **Reactive Maintenance** allows for costly downtime after a failure occurs, while **Preventive Maintenance** can be wasteful by replacing functional parts according to rigid schedules. Although **Predictive Maintenance (PdM)** offers a superior alternative, existing cloud-based frameworks introduce critical barriers, including high latency, excessive bandwidth consumption, and data privacy concerns.




Fig 3.1 Reactive, Preventive, Predictive Maintenance

Furthermore, industrial environments are plagued by heavy electromagnetic interference and mechanical noise, which frequently contaminate sensor data and lead to inaccurate fault detection. Most current low-cost edge implementations are limited to simple data acquisition or "snapshot" alerts, lacking the computational robustness to perform sophisticated noise filtering, spectral analysis, and multi-modal data fusion locally. There is a critical absence of an integrated, edge-native solution that can accurately classify faults while providing true prognostic insights, such as estimating the **Remaining Useful Life (RUL)** of an asset, within the strict memory and processing constraints of a microcontroller.

3.2 Scope of the Project

The scope of this project involves the development and validation of an autonomous prognostic node designed for industrial motors. Key areas of focus include:

- **Multi-Modal Monitoring:** The system simultaneously monitors triaxial vibration (for mechanical health), electrical current (for stator and load health), and temperature (for thermal buildup) to provide a comprehensive diagnostic profile.
- **Edge-Native Intelligence:** All processing—from raw signal acquisition and **Fast Fourier Transform (FFT)** feature extraction to **TinyML** model inference—is performed locally on the **ESP32-WROOM-32** microcontroller.
- **Fault Classification & Prognostics:** The framework is designed to identify specific machine states, including normal operation, bearing wear, mechanical imbalance, and misalignment, while extending capabilities toward estimating the **Remaining Useful Life (RUL)**.
- **Actionable Output:** The system provides two tiers of response: immediate hardware-level protection (local buzzer/LED alerts and potential motor cutoff via the **Schneider VFD**) and remote health oversight via an **MQTT-based IoT dashboard**.

3.3 Constraints and Assumptions

Constraints:

- **Memory and Computation:** The deep learning models must be optimized through **8-bit quantization** and model pruning to fit within the ESP32's limited **520 KB SRAM** and available Flash memory without compromising diagnostic fidelity.

- **Power Consumption:** To support long-term autonomy and potential battery operation, the system must utilize energy-efficient algorithms and the ESP32's built-in **light and deep sleep modes**.
- **Economic Viability:** The total implementation cost must remain low to ensure the solution is accessible to small-to-medium industrial enterprises.
- **Real-Time Latency:** On-device inference must be achieved with sub-second latency, specifically targeted below **250ms**, to ensure an immediate response to critical malfunctions.

Assumptions:

- **Failure Correlation:** It is assumed that **99% of equipment failures** are preceded by correlated physical indications (vibration, thermal, or electrical) that can be captured by the sensor suite.
- **Spectral Integrity:** The system assumes that **FFT-based frequency-domain analysis** is sufficient to isolate dominant mechanical fault frequencies from background industrial noise.
- **Operational Consistency:** The experimental setup—utilizing a **0.5 HP 3-phase induction motor** and a **Schneider VFD**—is assumed to be a representative model for validating fault signatures found in larger-scale industrial rotating assets.

Chapter 4

4. PROPOSED METHODOLOGY

The **Edge-Intelligent Condition Monitoring System** is designed as a standalone, autonomous prognostic node that transitions industrial maintenance from reactive to proactive strategies by shifting computational intelligence directly to the machine source.

4.1 Proposed Approach and Algorithms

The project employs a **multi-modal data fusion** approach, integrating physical, electrical, and thermal indicators to provide a holistic view of machine health.

- **Multi-Modal Fusion:** The framework correlates high-frequency triaxial vibration signals from the **MPU6050** with non-invasive electrical current data from the **SCT-013-000** and temperature readings from the **DS18B20**. This correlation is critical for reducing false positives; for example, a thermal spike is only flagged as a fault if accompanied by abnormal vibration or current signatures.
- **Noise-Resilient Preprocessing:** To operate effectively in harsh industrial environments, the system utilizes a **Fast Fourier Transform (FFT)** preprocessing pipeline. This transforms raw, noisy time-domain signals into frequency-domain spectral signatures, isolating mechanical fault frequencies (e.g., bearing defects typically seen at 350–500 Hz) from background electromagnetic interference.
- **TinyML Inference:** The system executes memory-optimized **1D Convolutional Neural Network (CNN)** or Multilayer Perceptron (MLP) models directly on the microcontroller. These models are optimized through **8-bit quantization** to fit within the ESP32's 520 KB SRAM while maintaining a diagnostic accuracy exceeding **92%**.
- **Core Synchronization:** The **ESP32-WROOM-32** dual-core architecture is leveraged to achieve sub-second latency (frequently below **250ms**). One core is

dedicated to continuous high-frequency data acquisition, while the second core handles real-time AI inference and decision-making.




Fig 4.1 multi-modal data fusion approach

4.2 Techniques and Tools Used

The implementation requires a sophisticated stack of industrial-grade hardware and machine learning development tools:

Hardware Suite:

- **Microcontroller:** ESP32-WROOM-32 DevKit for edge-native processing and Wi-Fi/Bluetooth connectivity.




Fig 4.2 ESP32-WROOM-32 Devkit

- **Sensors:** MPU6050 (Triaxial Vibration), SCT-013-000 (Non-invasive Current, 30A/50mA), and DS18B20 (Waterproof Temperature Probe).



Fig 4.3 MPU6050



Fig 4.4 SCT-013-000



Fig 4.5 DS18B20

- **Control Setup:** An **Atv310h037n4e Schneider VFD (0.37 kW)** regulates the speed of a **0.37kW/0.5Hp induction motor**, protected by a **3-phase motor starter (15A, 280/440V)**.



Fig 4.6 Atv310h037n4e Schneider VFD (0.37 kW)



Fig 4.7 0.37kW/0.5Hp induction motor

Software and AI Tools:

- **Edge Impulse:** The primary platform for data labeling, training memory-optimized models, and implementing **8-bit quantization**.
- **Arduino IDE:** Used for developing embedded C/C++ firmware to manage sensor I2C interfaces and execute the TinyML library.
- **Communication Protocols:** **MQTT** for lightweight transmission to cloud dashboards and **ESP-NOW** for low-latency peer-to-edge communication.
- **IoT Dashboards:** Platforms like **Ubidots/ThingSpeak/Node-RED** or **Blynk** are used for real-time visualization of health trends and Remaining Useful Life (RUL) data.

4.3 System Design and Workflow

The system follows a modular **six-layer Industrial IoT (IIoT) architecture** designed for autonomous operation:




Fig 4.8 six-layer Industrial IoT

- **Sensing Layer:** Continuous multi-modal acquisition of vibration, current, and temperature data from the induction motor.
- **Data Ingestion Layer:** Secure handling of sampled signals using MQTT for dashboard updates or local triggers.
- **Data Processing Layer (Edge Preprocessing):** Local execution of noise filtering (Butterworth LPF), **Z-score normalization**, and **FFT** to generate spectral feature vectors.
- **Model Repository Layer:** Storage of pre-trained, 8-bit quantized TinyML models directly in the ESP32's flash memory.
- **Inference Layer (Edge Intelligence):** Real-time classification of machine states (Normal, Imbalance, Misalignment, or Bearing Fault) and local estimation of **Remaining Useful Life (RUL)**.
- **Decision Support Layer:** Triggering of local hardware responses (Buzzer/LED or motor cutoff via the Schneider VFD) and updating the remote IoT dashboard.

Operational Workflow: Upon system start, the ESP32 initializes sensors and loads the TinyML model. It acquires multi-modal data, applies FFT to extract features, and runs inference. If a fault is detected, it immediately triggers local alerts and provides a safety cutoff through the **Schneider VFD**, while simultaneously logging the diagnostic data to the **Ubidots** dashboard for remote oversight.

5. SUMMARY AND FUTURE PLAN

5.1 Summary of Work Completed in Phase 1

The first phase of the **Edge-Intelligent Condition Monitoring System** successfully established a robust, edge-native foundation for transitioning industrial maintenance from reactive to proactive strategies. The work completed during this phase focused on shifting computational intelligence directly to the machine source to overcome the latency and bandwidth limitations of cloud-based architectures.

- **Problem and Objective Definition:** The core problem of maintenance costs (accounting for 15% to 60% of manufacturing expenses) was addressed, and the project scope was defined to include multi-modal sensing and sub-second diagnostic response times.
- **Hardware Integration and Test Bench Setup:** A professional-grade experimental test rig was constructed, featuring a **0.37kW/0.5Hp 3-phase induction motor** controlled by an **Schneider VFD** and protected by a **3-phase motor starter (15A, 280/440V)**.
- **Sensor Suite Interfacing:** The system was successfully interfaced with high-frequency multi-modal sensors, including the **MPU6050** for triaxial vibration, the **SCT-013-000** for non-invasive current monitoring, and the **DS18B20** for thermal data acquisition.
- **Edge Processing Pipeline:** A noise-resilient preprocessing pipeline was implemented, utilizing **Fast Fourier Transform (FFT)** and **Z-score normalization** to extract spectral signatures from noisy industrial signals.

- **TinyML Model Development:** Initial training and deployment of memory-optimized **1D Convolutional Neural Networks (CNN)** were conducted using the **Edge Impulse** platform, incorporating **8-bit quantization** to fit within the ESP32's 520 KB SRAM.
- **Performance Validation:** Preliminary results demonstrated a diagnostic accuracy exceeding **92%** for machine states such as imbalance and bearing wear, with an inference latency targeted below **250ms**.

5.2 Plan for Phase 2 Implementation

Phase 2 aims to evolve the current prototype into a fully autonomous, industrial-grade prognostic node capable of long-term machine health forecasting. The implementation plan includes the following key milestones:

- **Prognostic Advancement (RUL Estimation):** The system will transition from simple fault classification to predicting the **Remaining Useful Life (RUL)** of machine components. This involves deploying time-series regression models, such as **quantized CNN-LSTM** architectures, to analyze degradation patterns over time.
- **Enhanced Multi-Modal Fusion:** Future iterations will integrate acoustic sensing via **MEMS microphones** (e.g., INMP441) to capture frictional or aerodynamic anomalies that manifest before measurable mechanical vibrations.
- **Operational Adaptability Testing:** To ensure robustness in dynamic factory settings, the TinyML models will be validated under varying mechanical loads and motor speeds using the **Schneider VFD** to simulate diverse operational regimes.

- **Sustainability and Energy Management:** Research will be conducted into the ESP32's **light and deep sleep modes** and potential integration with **energy-harvesting modules** to support long-term autonomous monitoring in remote locations.
- **Final Dashboard Integration and Hardening:** The **MQTT-based** communication layer will be finalized for real-time visualization on the **Ubidots/ThingSpeak/Node-RED or Blynk** dashboard, and the hardware will be housed in an industrial-grade enclosure for field testing.
- **Network Standardization:** The framework will be updated to explore standardized industrial protocols such as **OPC UA** or enhanced MQTT security to enable coordinated monitoring across entire industrial ecosystems.

6. REFERENCES

- [1] M. S. Krishna, S. Azmatunnisa, V. Harika, N. Chaitanya, and P. V. Mohan, “Controlling and monitoring of multiple motors using ESP32 and IoT,” *International Journal for Modern Trends in Science and Technology*, vol. 11, no. 5, pp. 470–475, May 2025.
- [2] S. Gupta and S. N. Shivhare, “Embedded TinyML for predictive maintenance: Vibration analysis on ESP32 with real-time fault detection in industrial equipment,” *International Journal on Computational Modelling Applications*, vol. 2, no. 2, pp. 1–17, Jun. 2025.
- [3] T. Zonta, C. A. da Costa, R. da R. Righi, M. J. de Lima, E. S. da Trindade, and G. P. Li, “Predictive maintenance in the Industry 4.0: A systematic literature review,” *Computers & Industrial Engineering*, vol. 150, p. 106889, Oct. 2020.
- [4] D. Thakkar and R. Kumar, “AI-driven predictive maintenance for industrial assets using edge computing and machine learning,” *Journal for Research in Applied Sciences and Biotechnology*, vol. 3, no. 1, pp. 363–367, Feb. 2024.
- [5] A. F. C. Herrera, J. A. L. Sotelo, J. C. B. Andrade, and A. T. Lazo, “Low-cost prototype for bearing failure detection using TinyML through vibration analysis,” *HardwareX*, vol. 22, p. e00658, May 2025.
- [6] S. O. Ooko and S. M. Karume, “Application of Tiny machine learning in predictive maintenance in industries,” *Journal of Computing Theories and Applications*, vol. 2, no. 1, pp. 131–151, Aug. 2024.
- [7] P. Kolok, M. Hodoň, P. Ševčík, L. Hotz, and N. Remy, “Low-cost IoT-based predictive maintenance using vibration,” *Sensors*, vol. 25, no. 21, p. 6610, Oct. 2025.

- [8] I. Katib, E. Albassam, S. A. Sharaf, and M. Ragab, "Safeguarding IoT consumer devices: Deep learning with TinyML-driven real-time anomaly detection for predictive maintenance," *Ain Shams Engineering Journal*, vol. 16, no. 2, p. 103281, Feb. 2025.
- [9] N. H. T. Nguyen *et al.*, "Fault diagnosis for rotating machine utilizing machine learning with FFT-based feature extraction," in *Proc. Int. Conf. Advanced Technologies for Communications (ATC)*, 2024.
- [10] R. Liu, B. Yang, E. Zio, and X. Chen, "Artificial intelligence for fault diagnosis of rotating machinery: A review," *Mechanical Systems and Signal Processing*, vol. 108, pp. 33–47, May 2018.
- [11] S. Kumar, M. Loksha, A. G. K., B. K. N., N. Raghavendra, and U. Shankar, "Fault diagnosis in belts drive transmission using wavelet spectrum," *Recent Trends in Mechanical Engineering & Applied Sciences*, vol. 7, pp. 5–18, 2018.
- [12] R. Sridhara, H. S. Subramanya, N. Kumar R., and T. N. Shivaraj, "Fault detection in bearings using signal processing MATLAB," Dept. Mechatronics Eng., Mangalore Institute of Technology and Engineering, 2018–19.
- [13] B. K. Raghavendra, "Building bearing experimental test rig to collect vibration data for automatic fault identification," Thesis Rep. 4MT20MTR02, Dept. Mechatronics Eng., MITE, 2020.

7. APPENDICES

Model testing rig



Fig 7.1 model testing rig

2D Model




Fig 7.2 2D model

Appendix A: Circuit Interfacing and Pin Mapping

The system is centered around the **ESP32-WROOM-32 DevKit**, which utilizes its dual-core architecture to manage concurrent tasks. Core 0 is dedicated to high-frequency sensor acquisition, while Core 1 executes the TinyML inference pipeline.

Table 7.1: ESP32 Pin Configuration and Protocol Integration

Component	Interface	ESP32 Pin	Purpose
MPU6050	I2C (SDA)	GPIO 21	Triaxial vibration data acquisition.
MPU6050	I2C (SCL)	GPIO 22	Synchronous clock for the inertial sensor.
SCT-013-000	Analog (ADC)	GPIO 34	Non-invasive current sensing via voltage divider.
DS18B20	One-Wire	GPIO 4	Digital temperature monitoring (requires 4.7k pull-up).
Schneider VFD	Digital/PWM	GPIO 5	Emergency motor shutdown and speed regulation.
Buzzer/LED	Digital	GPIO 18/19	Local visual and audible fault alerts.

Appendix B: Component Specifications and Cost Analysis

The prototype setup utilizes industrial-grade equipment to simulate real-world mechanical and electrical faults across variable speed regimes.

Table 7.2: Detailed Technical Specifications of Primary Assets

Hardware Asset	Specification Details
Induction Motor	0.37kW / 0.5Hp, 3-Phase, 440V, 50Hz, 1440 RPM.
Schneider VFD	Model: Atv310h037n4e, 0.37 kW power rating.
Motor Starter	3-Phase protection, 280/440V, 15A current capacity.
MCU Board	ESP32-WROOM-32, 520 KB SRAM, Dual-core 240MHz.
Sensors	MPU6050 ($\pm 16g$), SCT-013 (30A/50mA), DS18B20 (Waterproof).

Table 7.3: Implementation Cost Summary (INR)

Component	Quantity	Total Cost
Schneider VFD (0.37kW)	1	20,000
ESP32-WROOM-32 DevKit	1	1,000
SCT-013-000 Current Sensor	1	700
MPU6050 Accelerometer	1	500
DS18B20 Thermal Probe	1	500
Total Estimated Investment		22,700

Appendix C: TinyML Model Performance and Data Characteristics

The system uses an **8-bit quantized 1D CNN** trained to recognize unique spectral signatures generated by different machine states.

Table 7.4: Diagnostic Classification and Spectral Identifiers

Machine State	Fault Type	Spectral Indicator (FFT)
Normal	None	Regular, low-amplitude harmonic waveforms.
Bearing Wear	Mechanical	High-frequency spikes (targeted 350–500 Hz).
Imbalance	Mechanical	Amplified fundamental frequency (1X component).
Misalignment	Mechanical	Strong peaks at 2X and 3X harmonic frequencies.
Overcurrent	Electrical	Current deviation from 1.4A nominal operating range.

Appendix D: System Operational Workflow

The methodology follows a six-layer Industrial IoT architecture, ensuring low latency and data privacy.

Sensing Layer: Multi-modal data acquisition (Triaxial vibration + Load current + Temp).

Edge Preprocessing: Signal normalization and **FFT conversion** locally on the ESP32.

Inference Layer: Execution of the **8-bit quantized CNN** model.

Decision Support: Sub-250ms local response (safety cutoff) and MQTT dashboard logging.