Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Mohammed Altaf Raza
Last Name	
Email	altafmohammed6036@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-02-14 11:09:38
Time Spent (Approx.)	73:01
Percentage	70%
Percentile	87.95%
Score	7
Status	Pass

Share result on Social Network

Answer Sheet

1

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 10

```
SELECT AuditID, YEAR(AuditTime) AuditYear
FROM Audits
WHERE YEAR(AuditTime) >= 2024
```

2

Write a query to display details of patients who never visited using the above tables.

Patients:

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DEF		
3	4	HIJ		
4	5	Xyz		
5	6	KLM		

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Vitals:

VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80
5	125	90
8	130	90

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Answer

Word counts: 26

```
SELECT P.PATIENTID, PATIENTNO, INITIALS
FROM PATIENTS P  WITH(NOLOCK)
LEFT JOIN VISITS V WITH(NOLOCK) ON P.PATIENTID = V.PATIENTID
WHERE V.PATIENTID IS NULL
```

3

Write the SQL to produce the following report on the vital signs data. Order by patient number and visit number to fill the below table columns.

PatientNo	VisitNo	VisitDate	Systolic	Diastolic

Note: refer below listed Patient, Visit, & Vitals tables.

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Visits:			
VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00

7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Vitals:

VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80
5	125	90
8	130	90

Answer

Word counts: 35

```
SELECT P.PATIENTNO, VISITNO, VISITDATE, VT.SYSTOLIC, DIASTOLIC
FROM PATIENTS P WITH(NOLOCK)
INNER JOIN VISITS V  WITH(NOLOCK) ON V.PATIENTID = P.PATIENTID
INNER JOIN VITALS VT  WITH(NOLOCK) ON VT.VISITID = V.VISITID
```

4

List the patient number and initials for every patient who has never had a headache.

Note: Refer the below tables

AE Table:

Patientid	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Answer

Word counts: 26

```
SELECT *
FROM PATIENTS P WITH(NOLOCK)
WHERE NOT EXISTS (SELECT 1
                  FROM AE A WITH(NOLOCK)
                  WHERE A.PATIENTID  = P.PATIENTID
                  AND A.AE IN ('HEADACHE', 'NAUSEA')
                  )
```

5

Update the Medications table to populate the “TakenFor” column with the corresponding adverse event (AE) from the AES table.

Medication:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Answer

Word counts: 27

```
UPDATE M
SET M.TAKENFOR = A.AE
FROM MEDICATION M
INNER JOIN AE A WITH(NOLOCK) ON M.VISITID = A.VISITID
WHERE ISNULL(A.MED, '') <> ''
```

6

Write a query to find and replace the special characters in the below subjects/patients table. The query should be generic rather the hardcoded.

Note: we may have special characters in the Initial column.

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DE_F		
3	4	HIJ		
4	5	Xyz		
5	6	KL$M		

Answer

Word counts: 33

```
SELECT CASE WHEN INITIALS LIKE '%_%' THEN REPLACE(INITIALS, '_', '')
WHEN INITIALS LIKE '%$%' THEN REPLACE(INITIALS, '$', '') ELSE INITIALS
END INITIALS
FROM PATIENTS P WITH(NOLOCK)
```

7

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (
    OrderID INT PRIMARY KEY,
    ProductName NVARCHAR(50),
    Quantity INT
);
-- Insert initial data
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product A', 10);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product B', 20);
GO
BEGIN TRANSACTION;
BEGIN TRY
```

```
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product C', 30);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product D', 40);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product E', 50);

COMMIT TRANSACTION;

END TRY

BEGIN CATCH

 ROLLBACK TRANSACTION;

SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS ErrorMessage;

END CATCH;
```

Answer

Word counts: 72

First we are creating OrdersData table and then inserting the values for Product A and B without any begin try and transaction block.
there is syntax error in begin transaction block because we need to use transaction command inside the begin try and end try block. also we are trying to insert duplicate value "1" for OrderId field but will get primary constraint error.

Output will be: syntax error and Primary violation error

8

What would be the output of the below SQL query?

```
IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id = Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (String NVARCHAR(2000), Code NVARCHAR(2000))

IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id = Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (ID INT IDENTITY, String NVARCHAR(2000), Code NVARCHAR(2000))
```

Answer

Word counts: 15

Output will be : Last temp table will be created with these columns (ID, STRING, CODE)

9

Using a while loop, Write a query to print the ProjectID, ProjectName, and ProjectActive from the below Projects Table.

ProjectID	ProjectName	ProjectActive
205	A011_20130279	1
37	A145678_20120136	1
30	A827_20120103	0
141	A102_20120142	1

Answer

Word counts: 54

```
DECLARE @I INT, @X INT, @PROJECTID INT, @PROJECTNAME
NVARCHAR(200), @PROJECTACTIVE BIT
SELECT @I = 1, @X = COUNT(1)
FROM PROJECTS  WITH(NOLOCK)

WHILE (@I <= @X)
BEGIN
	--RESET VARIABLES
	SELECT @PROJECTID = NULL, @PROJECTNAME = NULL,
@PROJECTACTIVE = NULL

	SELECT @PROJECTID = PROJECTID, @PROJECTNAME =
PROJECTNAME, @PROJECTACTIVE = PROJECTACTIVE
	FROM PROJECTS
	WHERE ID = @I
```

10

Produce the following report, showing each adverse event and the details of the medication taken for that adverse event. Include all adverse events, even those for which no medication was taken. Output must be in the given format.

PatientNo	AE	Med	MedDate

Note: Refer the below tables to code

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 46

```
SELECT P.PATIENTNO, A.AE, A.MED, MEDDATE
FROM VISITS V WITH(NOLOCK)
INNER JOIN PATIENTS P WITH(NOLOCK) ON P.PATIENTID = V.PATIENTID
LEFT JOIN MEDICATIONS M  WITH(NOLOCK) ON M.VISITID = V.VISITID
LEFT JOIN AE A WITH(NOLOCK) ON A.VISITID = V.VISITID
```

1 2 3 4 5 6 7 8 9 10 View All

Powered by TechKshetra Info