Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Bandlamudi
Last Name	Naveen Kumar
Email	bnaveenkumar2828@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-02-19 11:01:59
Time Spent (Approx.)	48:36
Percentage	80%
Percentile	94.07%
Score	8
Status	Pass

Share result on Social Network

Answer Sheet

1

Write an SQL query to get the maximum AuditID for each AuditSubCategoryID.

AuditSubCategoryID:

AuditSubCategoryID	Name
1	EnteredEmpty
2	Entered
3	EnteredNonConfomant
4	EnteredByDdeAutoReconcile
7	CommentAdd
8	CommentEdit
9	QueryOpen
10	QueryAnswer
11	QueryCancel
12	QueryClose
13	ReviewRequired

Audits:

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID	Guid	Ser
1				-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	19 00
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	19 00
3				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	19 00

4				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	19 00
5				-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	19 00
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	19 00
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	19 00
8		LastName|Import		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	19 00
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-525172a147e7	19 00
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-9923a0f3bc08	19 00

Answer

Word counts: 27

```
select asd.AuditSubCategoryID, max( ad.AuditID) as Max_Auditid
from AuditSubCategoryID as asd
inner join Audits as ad on asd.AuditSubCategoryID = ad.AuditSubCategoryID
group by asd.AuditSubCategoryID
```

2

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4

6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 10

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE YEAR(AuditTime) >= 2024
```

3

Produce the following report, showing each adverse event and the details of the medication taken for that adverse event. Include all adverse events, even those for which no medication was taken. Output must be in the given format.

PatientNo	AE	Med	MedDate

Note: Refer the below tables to code

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz

5	6	KLM

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 44

```
SELECT P.PATIENTNO, A.AE, M.MEDICATION AS MED,M.MEDDATE
FROM AE AS A
LEFT  JOIN Visits AS V ON V.VISITID=A.VISITID
LEFT JOIN Medications AS M ON M.VISITID=A.VISITID
LEFT JOIN PATIENT P ON P.PATIENTID=V.PATIENTID
```

4

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (
    OrderID INT PRIMARY KEY,
    ProductName NVARCHAR(50),
    Quantity INT
);
-- Insert initial data
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product A', 10);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product B', 20);
GO
BEGIN TRANSACTION;
BEGIN TRY
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product C', 30);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product D', 40);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product E', 50);
COMMIT TRANSACTION;
END TRY
BEGIN CATCH
 ROLLBACK TRANSACTION;
SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS ErrorMessage;
END CATCH;
```

Answer

Word counts: 43

Step1: OrdersData Table will be created
Step2: Productid's 1 and 2 data will be inserted
Step3: Next transaction is going to be failed as we are trying to insert productid 1 data again as productid is a primary key column which will not allow duplicate values.

5

Analyze and provide the number of records count for

Inner Join

Left join

Right Join

Full outer join

Self join for both Table 1 & 2

Table 1		Table 2
ID		ID
1		1
1		2
1		1
1		1
1		0

Answer
Word counts: 90

```
Inner join query:
select * from table1 as t1
inner join table2 as t2 on t1.id=t2.id
output: 15 rows

Left join query:
select * from table1 as t1
left join table2 as t2 on t1.id=t2.id
output: 15 rows

Right join query:
select * from table1 as t1
right join table2 as t2 on t1.id=t2.id
output: 17 rows
```

6

Write a SQL query to pull the records that have integer related data only in the table below for the Data column.

ID	SubjectName	Data	Flag
1	New Subject	9001	0
2	New Subject	9002	0
152	_001-005	_001	0
153	_001-005	005	0
154	_001-005	SRI	0
155	_001-005	_001-005	1
1215	003-00001	003	0
1216	003-00001	00001	0
1217	003-00001	JR	0
1218	003-00001	003-00001	1
1219	003-00001	Y	0

Answer
Word counts: 6

```
select * from table1 where isnumeric(data)=1
```

7

List the patient number and initials for every patient who has never had a headache.

Note: Refer the below tables

AE Table:

Patientid	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Answer

Word counts: 31

```
select p.Patientno,p.Initials from patients as  p
inner join (select * from AE where patientid not in (select distinct patientid from
AE where  AE='Headache')) a
a.patientid=p.patientid
```

8

Write a SQL query to create a clustered index on the table below.

Create table #temp_Audits(AuditID int identity primary key, StudyID INT, Text nvarchar(4000))

Insert into #temp_Audits(StudyID, Text)

Select 10,'Study Created'

Answer

Word counts: 25

We can not create clustered index on this table as clustered index is already created on AuditID column as we declared it as primary key.

9

Write an SQL query to generate the “ByPassNumber” column data for the ID column in the table below.

Table 1: DuplicatePatient		Table 2:	
ID		ID	ByPassNumber
1		1	1
2		2	1
3		3	2
4		4	2
5		5	3
6		6	3
7		7	4
8		8	4
9		9	5
10		10	5

Answer

Word counts: 27

```
select id,case when id<=2 then 1
when id in (3,4) then 2
when id in (5,6) then 3
when id in (7,8) then 4
when id in (9,10) then 5 end as ByPassNumber
from Table1
```

10

What would be the output of the below SQL query?

```
IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (String NVARCHAR(2000), Code
NVARCHAR(2000))

IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (ID INT IDENTITY, String NVARCHAR(2000),
Code NVARCHAR(2000))
```

Answer

Word counts: 10

It throws an error because tempdb does not have sysobjects

1 2 3 4 5 6 7 8 9 10 View All

Powered by TechKshetra Info