Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Siva Prasad
Last Name	Gosi
Email	gsp.sql@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-04-15 17:25:55
Time Spent (Approx.)	47:15
Percentage	70%
Percentile	87.95%
Score	7
Status	Pass

Share result on Social Network

Answer Sheet

1

Write a query to find and replace the special characters in the below subjects/patients table. The query should be generic rather the hardcoded.

Note: we may have special characters in the Initial column.

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DE_F		
3	4	HIJ		
4	5	Xyz		
5	6	KL$M		

Answer

Word counts: 15

```
select
PatientID,PatientNo,replace(Initials,'%^[a-z]%','') as Initials
,Systolic,Diastolic
from patients
```

2

Write a query to find the department with no employees.

Employee Table:

EMPID	DeptID
1	10
2	20
3	20
4	30
5	40
6	10
7	10

Departmen Table:

DeptID
20
30
40
50
10

Answer

Word counts: 39

```
select d.DeptID from Departmen  d where
d.DeptID not in (select distinct e.DeptID  from  Employee e)


sol2:

select  d.deptid from
Departmen  d   left join employee e on d.deptid=e.deptid where
e.empid is null
```

3

Update the Medications table to populate the “TakenFor” column with the corresponding adverse event (AE) from the AES table.

Medication:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Answer

Word counts: 24

```
update a set a.TakenFor=b.AE
from Medication a inner join   AE  b on a.VisitID=b.VisitID and
a.Medication=b.Med
```

4

Write a query to mask(XXXX) the date only in the VisitDate column in the below Visits table.

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 0

5

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear
```

FROM Audits

WHERE AuditTime >= 2024

Answer

Word counts: 25

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE year(AuditTime )>= 2024

sol2

if  you want records

SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE year(AuditTime )<= 2024
```

6

Write a SQL query to create a clustered index on the table below.

Create table #temp_Audits(AuditID int identity primary key, StudyID INT, Text nvarchar(4000))

Insert into #temp_Audits(StudyID, Text)

Select 10,'Study Created'

Answer

Word counts: 10

```
create cluster index  audit_cl_stuid
on #temp_Audits(StudyID)
```

7

Write the SQL to produce the following report on the vital signs data. Order by patient number and visit number to fill the below table columns.

PatientNo	VisitNo	VisitDate	Systolic	Diastolic

Note: refer below listed Patient, Visit, & Vitals tables.

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Visits:			
VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Vitals:		
VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80
5	125	90
8	130	90

Answer

Word counts: 38

```
select
a.PatientNo, b.VisitNo ,b.VisitDate,c.Systolic,c.Diastolic
from
Patients a  inner join  Visits b   on a.Patientid=b.Patientid
 left join Vitals c on  b.VisitID=c.VisitID
order by a.PatientNo, b.VisitNo
```

8

Analyze and provide the number of records count for

Inner Join

Left join

Right Join

Full outer join

Self join for both Table 1 & 2

Table 1		Table 2
ID		ID
1		1
1		2
1		1
1		1
1		0

Answer
Word counts: 15

Inner Join =15

Left join=15

Right Join=17

Full outer join=15

Self join Table 1 =25
Self join Table 2 =11

9

What would be the output of the below SQL query?

```
IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (String NVARCHAR(2000), Code
NVARCHAR(2000))

IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (ID INT IDENTITY, String NVARCHAR(2000),
Code NVARCHAR(2000))
```

Answer
Word counts: 11

it will create the temptable in tempdb with name of Temptable

10

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (
    OrderID INT PRIMARY KEY,
    ProductName NVARCHAR(50),
    Quantity INT
);
-- Insert initial data
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product A', 10);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product B', 20);
GO
BEGIN TRANSACTION;
BEGIN TRY
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product C', 30);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product D', 40);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product E', 50);
COMMIT TRANSACTION;
END TRY
BEGIN CATCH
 ROLLBACK TRANSACTION;
SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS ErrorMessage;
END CATCH;
```

Answer

Word counts: 34

when u try to excute above query it will rollback the entire transaction due to the error occurs in insert table due to primery key vilation.it will give the result set errornumber,ErrorMessage.

1 2 3 4 5 6 7 8 9 10 View All

Powered by TechKshetra Info