Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Murali Mukku
Last Name	
Email	murali.mukku2025@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-04-18 14:03:43
Time Spent (Approx.)	63:57
Percentage	80%
Percentile	95.10%
Score	8
Status	Pass

Share result on Social Network

Answer Sheet

1

Update the Medications table to populate the “TakenFor” column with the corresponding adverse event (AE) from the AES table.

Medication:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Answer

Word counts: 24

```
UPDATE med
SET med.TakenFor = a,AE
FROM Medication med
        INNER JOIN AE a on med.VisitId = a.VisitId and med.Medication = a.Med
```

2

Write the SQL to produce the following report on the vital signs data. Order by patient number and visit number to fill the below table columns.

PatientNo	VisitNo	VisitDate	Systolic	Diastolic

Note: refer below listed Patient, Visit, & Vitals tables.

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Visits:			
VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Vitals:		
VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80

5	125	90
8	130	90

Answer

Word counts: 38

```
select
            p.PatientNo,
            v.VisitNo,
            v.VisitDate,
           vit.Systolic,
            vit.Diastolic

from Patients p
          inner join Visits v on p.PatientID = v.PatientID
         inner join Vitals vit on v.VisitID = vit.VisitID
order by   p.PatientNo, v.VisitNo
```

3

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 39

There is a issue in where clause condition is the wrong. We have to apply year function to get only year for condition.

Please find the below queryBelow query

```
SELECT AuditID, YEAR(AuditTime) AuditYear
FROM Audits
WHERE YEAR(AuditTime) >= 2024
```

4

Write a query to mask(XXXX) the date only in the VisitDate column in the below Visits table.

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 44

I am unsdersatnding exact requirement. Please find below queries as i feel

```
-- This is for showing year only in Visitdate column

select year(VisitDate)
from Visit

-- showing XXX in Date

select
      replicate('X', len(cast(VisitDate as date))) as VisitDate
from Visit
```

5

Write a SQL query to pull the records that have integer related data only in the table below for the Data column.

ID	SubjectName	Data	Flag
1	New Subject	9001	0
2	New Subject	9002	0
152	_001-005	_001	0

153	_001-005	005	0
154	_001-005	SRI	0
155	_001-005	_001-005	1
1215	003-00001	003	0
1216	003-00001	00001	0
1217	003-00001	JR	0
1218	003-00001	003-00001	1
1219	003-00001	Y	0

Answer

Word counts: 5

```
select *
from Subject
isnumeric(Data) = 1
```

6

Using a while loop, Write a query to print the ProjectID, ProjectName, and ProjectActive from the below Projects Table.

ProjectID	ProjectName	ProjectActive
205	A011_20130279	1
37	A145678_20120136	1
30	A827_20120103	0
141	A102_20120142	1

Answer

Word counts: 55

```
DECLARE @start int = 1,
            @Count INT,
            @projectid int,
            @ProjectName varchar(100),
            @ProjectActive bit

select @Count = count(*)
from project

select row_number() over(order by projectId) as Rno, *
into #Project
from  project

while=(@start <= @count)
Begin
```

7

Write the query to display the values in the Project Name after Underscore (_). An example for A011_20130279 should display only 20130279.

ProjectID	ProjectName	ProjectActive
205	A011_20130279	1
37	A145678_20120136	1
30	A827_20120103	0
141	A102_20120142	1

Answer

Word counts: 13

```
select
  substring(ProjectName, charindex('_',ProjectName)+1,LEN(ProjectName)) as
ProjectName
from Project
```

8

What would be the output of the below SQL query?

```
IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (String NVARCHAR(2000), Code
NVARCHAR(2000))

IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (ID INT IDENTITY, String NVARCHAR(2000),
Code NVARCHAR(2000))
```

Answer

Word counts: 4

```
#Temptable table  will create
```

9

List the patient number and initials for every patient who has never had a headache.

Note: Refer the below tables

AE Table:

Patientid	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Answer

Word counts: 21

```
SELECT
            p.PatientNo,
           p.Initials

FROM Patients p
WHERE P.PatientID NOT IN (
                                SELECT DISTINCT PatientID FROM AE WHERE AE
= 'Headache'
                                 )
```

10

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (

   OrderID INT PRIMARY KEY,

   ProductName NVARCHAR(50),

   Quantity INT

);

-- Insert initial data

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product A', 10);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product B', 20);

GO

BEGIN TRANSACTION;

BEGIN TRY

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product C', 30);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product D', 40);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product E', 50);

COMMIT TRANSACTION;

END TRY

BEGIN CATCH

 ROLLBACK TRANSACTION;

SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS ErrorMessage;

END CATCH;
```

Answer

Word counts: 71

There is primary key created in OrderID column. It wil not allowed to insert duplicate values. Intialy orderId column 1 is inserted before transaction. In transaction, We are trying to insert a orderId with 1 in third insert statement in transaction. So we are getting primary key validation error. It will go to catch black and It will rollback previous inserted records from transaction and showing error with error number and error message.