Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Sai Niranjan
Last Name	Bandla
Email	Niranjan.bandla253@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-04-25 15:15:34
Time Spent (Approx.)	51:02
Percentage	70%
Percentile	89.05%
Score	7
Status	Pass

Share result on Social Network

Answer Sheet

1

Analyze and provide the number of records count for

Inner Join

Left join

Right Join

Full outer join

Self join for both Table 1 & 2

Table 1		Table 2
ID		ID
1		1
1		2
1		1
1		1
1		0

Answer

Word counts: 8

```
Inner Join : 15
Left Join   : 15
Right Join : 17
Full Outer : 17
```

2

Update the Medications table to populate the “TakenFor” column with the corresponding adverse event (AE) from the AES table.

Medication:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Answer

Word counts: 24

```
UPDATE  M
SET M.TakenFor = A.AE
 FROM Medication M
INNER JOIN AE  A  ON M.VisitID =  A.VisitID
AND M.Medication = A. Med
```

3

Using a while loop, Write a query to print the ProjectID, ProjectName, and ProjectActive from the below Projects Table.

ProjectID	ProjectName	ProjectActive
205	A011_20130279	1
37	A145678_20120136	1
30	A827_20120103	0
141	A102_20120142	1

Answer

Word counts: 25

```
DECLARE @ProjectID  INT = 1 ,
                @RANGE INT

SELECT  @RANGE = COUNT(ProjectID) FROM Projects

WHILE  @ProjectID <= @RANGE

BEGIN

SELECT ProjectID, ProjectName,  ProjectActive
FROM Projects

SET   @ProjectID = @ProjectID +1

END
```

4

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 11

```
SELECT AuditID, YEAR(AuditTime) AS AuditYear

FROM Audits

WHERE YEAR(AuditTime) >= 2024
```

5

Write a SQL query to pull the records that have integer related data only in the table below for the Data column.

ID	SubjectName	Data	Flag
1	New Subject	9001	0
2	New Subject	9002	0
152	_001-005	_001	0
153	_001-005	005	0
154	_001-005	SRI	0
155	_001-005	_001-005	1
1215	003-00001	003	0
1216	003-00001	00001	0
1217	003-00001	JR	0
1218	003-00001	003-00001	1
1219	003-00001	Y	0

Answer

Word counts: 8

```
SELECT  Data
FROM TABLE
WHERE IS_NUMERIC(ID) = 0
```

6

Write a query to get the position of the second occurrence of the letter 'a' from the end of a string.

Ex String - ‘Vijay Kumar Goud’

Answer

Word counts: 13

```
DECLARE @STR VARCHAR(20) = 'Vijay Kumar Goud'
SELECT   RIGHT (PATINDEX (@STR,'a',2),len(@STR))
```

7

List the patient number and initials for every patient who has never had a headache.

Note: Refer the below tables

AE Table:

Patientid	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Answer

Word counts: 22

```
SELECT  P.PatientNo ,  P.Initials
FROM Patients P
INNER JOIN AE ON P.Patientid = A.PatientID
WHERE A.AE NOT IN ('Headache')
```

8

Write an SQL query to generate the “ByPassNumber” column data for the ID column in the table below.

Table 1: DuplicatePatient		Table 2:	
ID		ID	ByPassNumber
1		1	1
2		2	1
3		3	2
4		4	2
5		5	3
6		6	3
7		7	4
8		8	4
9		9	5
10		10	5

Answer

Word counts: 15

```
SELECT T2.ByPassNumber
FRM TABLE1 T1
 INNER JOIN TABLE2 T2 ON T1.ID = T2.ID
```

9

What would be the output of the below SQL query?

```
IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (String NVARCHAR(2000), Code
NVARCHAR(2000))

IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (ID INT IDENTITY, String NVARCHAR(2000),
Code NVARCHAR(2000))
```

Answer

Word counts: 22

If the table #Temptable is available in database then table #Temptable will dropped and created again with ID, String and Code columns

10

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (

    OrderID INT PRIMARY KEY,

    ProductName NVARCHAR(50),

    Quantity INT

);

-- Insert initial data

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product
A', 10);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product
B', 20);

GO

BEGIN TRANSACTION;

BEGIN TRY

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product
C', 30);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product
D', 40);
```

```
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product
E', 50);

COMMIT TRANSACTION;

END TRY

BEGIN CATCH

 ROLLBACK TRANSACTION;

SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS
ErrorMessage;

END CATCH;
```

Answer
Word counts: 56

It will throw an error message in the catch block. as the column OrderID has primary key in the table.

in the above scriptwe are trying to inser data with the OrderID as 1 as multiple times.
and the primary will not allow the duplicate values so it will rollback the transactions with in the try block

Powered by TechKshetra Info