Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	KALPESH PATEL
Last Name	
Email	patelkalpeshkumar810@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-05-08 16:04:54
Time Spent (Approx.)	57:04
Percentage	70%
Percentile	87.95%
Score	7
Status	Pass

Share result on Social Network

Answer Sheet

1

Using a while loop, Write a query to print the ProjectID, ProjectName, and ProjectActive from the below Projects Table.

ProjectID	ProjectName	ProjectActive
205	A011_20130279	1
37	A145678_20120136	1
30	A827_20120103	0
141	A102_20120142	1

Answer

Word counts: 54

```
Declare @ProjectName varchar(100) , @ProjectActive BIT


WHILE (@min < = @max )
BEGIN
   select @projectName = ProjectName,@ProjectActive = ProjectActive FROM
Projects where ProjectId = @min ;


  Print @MIn AS ProjectId, @projectName AS @projectName,@ProjectActive
AS ProjectActive

  SET @min = (select  min(ProjectID) from Projects where ProjectId > @min)

END ;
```

2

Write a query to display details of patients who never visited using the above tables.

Patients:

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DEF		
3	4	HIJ		
4	5	Xyz		
5	6	KLM		

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Vitals:

VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80
5	125	90
8	130	90

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Answer

Word counts: 34

```
select pat.*
from Patients pat
left join Visits vs ON pat.PatientID = vs.PatientID
where vs.PatientID  IS NULL



Or anotherway is

select *
from Patients where PatientID not in (select distinct PatientID from Visits ) ;
```

3

Produce the following report, showing each adverse event and the details of the medication taken for that adverse event. Include all adverse events, even those for which no medication was taken. Output must be in the given format.

PatientNo	AE	Med	MedDate

Note: Refer the below tables to code

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 55

```
SELECT
   P.PatientNo,
   AE.AE,
   M.Medication AS Med,
   M.MedDate
FROM AE
JOIN Visits V ON AE.VisitID = V.VisitID
JOIN Patients P ON V.PatientID = P.PatientID
LEFT JOIN Medications M
   ON AE.VisitID = M.VisitID AND
      UPPER(LTRIM(RTRIM(AE.Med))) = UPPER(LTRIM(RTRIM(M.Medication)))
ORDER BY P.PatientNo, AE.AE;
```

4

Analyze and provide the number of records count for

Inner Join

Left join

Right Join

Full outer join

Self join for both Table 1 & 2

Table 1		Table 2
ID		ID
1		1
1		2
1		1
1		1
1		0

Answer

Word counts: 23

Inner Join - 15
Left join - 15
Right Join - 17
Full outer join - 17
Self join on Table 1 - 25
Self join on Table 2 - 11

5

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (

   OrderID INT PRIMARY KEY,

   ProductName NVARCHAR(50),

   Quantity INT

);

-- Insert initial data

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product A', 10);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product B', 20);

GO

BEGIN TRANSACTION;

BEGIN TRY

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product C', 30);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product D', 40);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product E', 50);

COMMIT TRANSACTION;

END TRY

BEGIN CATCH

 ROLLBACK TRANSACTION;

SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS ErrorMessage;

END CATCH;
```

Answer

Word counts: 58

1 : Above code first create a table by name OrdersData
2 : Next it is inserting 2 raw in OrdersData table.
3 : Next it try to insert 3 raw using Transaction
4 : Due to Primar key violation error transaction is fail (OrderID =1 is duplicate)
5 : from catch block current transaction is rollback and error message will be generated.

6 : Finally, we have only 2 raw at the end

6

Write a SQL query to pull the records that have integer related data only in the table below for the Data column.

ID	SubjectName	Data	Flag
1	New Subject	9001	0
2	New Subject	9002	0
152	_001-005	_001	0
153	_001-005	005	0
154	_001-005	SRI	0
155	_001-005	_001-005	1
1215	003-00001	003	0
1216	003-00001	00001	0
1217	003-00001	JR	0
1218	003-00001	003-00001	1
1219	003-00001	Y	0

Answer

Word counts: 6

```
select *
from TableName
where ISNUMERIC(Data) = 1 ;
```

7

Update the Medications table to populate the “TakenFor” column with the corresponding adverse event (AE) from the AES table.

Medication:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Answer

Word counts: 24

```
Update md
set md.TakenFor = ae.AE
from Medication md
inner join AE ae ON ae.VisitID = md.VisitID AND ae.Med  = md.Medication
```

8

List the patient number and initials for every patient who has never had a headache.

Note: Refer the below tables

AE Table:

Patientid	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Patients:

PatientID	PatientNo	Initials
1	1	ABC

2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Answer

Word counts: 48

```
select pat.PatientNo, pat.Initials
from Patients pat
left join AE ae ON ae.Patientid = pat.Patientid AND ae.AE = 'Headache'
where ae.Patientid IS NULL



2 : another way is

select pat.PatientNo, pat.Initials
from Patients pat
where  Patientid not in (select Patientid from AE  where AE='headache')
```

9

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 32

In where condition above given query is comparing Datetime with Int value 2024, so it will return an error.

correct query should be :

```
SELECT AuditID, YEAR(AuditTime) AuditYear
FROM Audits
WHERE YEAR(AuditTime) >= 2024
```

10

Write an SQL query to generate the “ByPassNumber” column data for the ID column in the table below.

Table 1: DuplicatePatient		Table 2:	
ID		ID	ByPassNumber
1		1	1
2		2	1
3		3	2
4		4	2
5		5	3
6		6	3
7		7	4
8		8	4
9		9	5
10		10	5

Answer

Word counts: 11

```
select NTILE (Id,2) OVER (Order by Id )AS ByPassNumber
from Table
```


Powered by TechKshetra Info