Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Raghu Sri
Last Name	
Email	RaghuSri.BiDev@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-05-23 11:05:04
Time Spent (Approx.)	63:49
Percentage	70%
Percentile	89.95%
Score	7
Status	Pass

Share result on Social Network

Answer Sheet

1

Write an SQL query to generate the “ByPassNumber” column data for the ID column in the table below.

Table 1: DuplicatePatient		Table 2:	
ID		ID	ByPassNumber
1		1	1
2		2	1
3		3	2
4		4	2
5		5	3
6		6	3
7		7	4
8		8	4
9		9	5
10		10	5

Answer

Word counts: 24

```
Select a.ID, b.ByPassNumber
from [Table 1] a
join [Table 2] b on a.ID = b.


I didn't understand question clearly please cross check once
```

2

Write the SQL to produce the following report on the vital signs data. Order by patient number and visit number to fill the below table columns.

PatientNo	VisitNo	VisitDate	Systolic	Diastolic

Note: refer below listed Patient, Visit, & Vitals tables.

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Visits:			
VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Vitals:		
VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80

5	125	90
8	130	90

Answer

Word counts: 36

```
Select p.PatientNo ,     v.VisitNo,      v.VisitDate,    vt.Systolic,     vt.Diastolic
From Patients p
JOIN Visits v on p.PatientId=v.patientId
Join Vitals vt on v.VisitId=vt.VisitId
order by p.PatientNo ,  v.VisitNo
```

3

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (

   OrderID INT PRIMARY KEY,

   ProductName NVARCHAR(50),

   Quantity INT

);

-- Insert initial data

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product A', 10);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product B', 20);

GO

BEGIN TRANSACTION;

BEGIN TRY

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product C', 30);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product D', 40);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product E', 50);

COMMIT TRANSACTION;

END TRY

BEGIN CATCH

 ROLLBACK TRANSACTION;
```

```
SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS
ErrorMessage;

END CATCH;
```

Answer

Word counts: 46

Orderid Primarykey column it won't allows duplicate
Duplicate value is 1

it will through the primary key violation error
so catch block will be triggered and it will rollback the transaction and error details will be shown as per the select statement available in the catch block

4

Write an SQL query to get the maximum AuditID for each AuditSubCategoryID.

AuditSubCategoryID:

AuditSubCategoryID	Name
1	EnteredEmpty
2	Entered
3	EnteredNonConfomant
4	EnteredByDdeAutoReconcile
7	CommentAdd
8	CommentEdit
9	QueryOpen
10	QueryAnswer
11	QueryCancel
12	QueryClose
13	ReviewRequired

Audits:

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID	Guid	Ser
1				-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	19 00
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	19 00
3				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	19 00
4				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	19 00

5				-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	19 00
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	19 00
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	19 00
8		LastName|Import		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	19 00
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-525172a147e7	19 00
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-9923a0f3bc08	19 00

Answer

Word counts: 10

```
Select  AuditSubCategoryID,Max( AuditID ) MaxAuditID
From Audits
Group by AuditSubCategoryID
```

5

Write a query to mask(XXXX) the date only in the VisitDate column in the below Visits table.

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 31

```
Select  *, replace (Case when charindex(VisitDate,'%[/-]%')>0 then substring
(VisitDate,1,charindex(VisitDate,'%[/-]%')-1 )End, 'XXXX' )
+substring (VisitDate,charindex(VisitDate,'%[/-]%'),30 ) VisitDate_Masked
From Visits
```

6

Produce the following report, showing each adverse event and the details of the medication taken for that adverse event. Include all adverse events, even those for which no medication was taken. Output must be in the given format.

PatientNo	AE	Med	MedDate

Note: Refer the below tables to code

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 37

```
Select p.PatientNo,a.AE,a.Med,m.MedDate
FROM AE a
left join Visits vs on a.PatientID = vs.PatientID
Join  Medications m on m.VisitID = vs.VisitID
join Patient p on vs.Patientid = p.Patientid
```

7

Write a query to find and replace the special characters in the below subjects/patients table. The query should be generic rather the hardcoded.

Note: we may have special characters in the Initial column.

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DE_F		
3	4	HIJ		
4	5	Xyz		
5	6	KL$M		

Answer

Word counts: 40

```
Create function FnReplaceSplChar
(@String varchar(max))
returns varchar(max)
as
begin

   while patindex('%[^a-zA-Z0-9 ]%',@String)>0
   set @String = stuff(@String,patindex('%[^a-zA-Z0-9 ]%',@String),1,'')

return @String
end
```

8

Write a SQL query to pull the records that have integer related data only in the table below for the Data column.

ID	SubjectName	Data	Flag
1	New Subject	9001	0
2	New Subject	9002	0
152	_001-005	_001	0
153	_001-005	005	0
154	_001-005	SRI	0
155	_001-005	_001-005	1
1215	003-00001	003	0
1216	003-00001	00001	0
1217	003-00001	JR	0
1218	003-00001	003-00001	1
1219	003-00001	Y	0

Answer

Word counts: 6

```
Select * from Subjectstable
where isnumeric(Data)=1
```

9

Update the Medications table to populate the “TakenFor” column with the corresponding adverse event (AE) from the AES table.

Medication:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Answer

Word counts: 24

```
Update m
set TakenFor = a.AE
From Medication m
left join AE a on m.VisitID = a.VisitID
where isnull(a.Med,'')<>''
```

10

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4

10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29, 133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 10

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE year(AuditTime) >= 2024
```

1 2 3 4 5 6 7 8 9 10 View All

Powered by TechKshetra Info