Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Tirupathi Rao
Last Name	Gorala
Email	tirupathiraogorala351@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-05-27 14:05:31
Time Spent (Approx.)	35:03
Percentage	80%
Percentile	95.92%
Score	8
Status	Pass

Share result on Social Network

Answer Sheet

1

Analyze and provide the number of records count for

Inner Join

Left join

Right Join

Full outer join

Self join for both Table 1 & 2

Table 1		Table 2
ID		ID
1		1
1		2
1		1
1		1
1		0

Answer

Word counts: 10

Inner Join : 15
Left Join : 15
Right Join : 15
Full Join : 15
Self Join : 15

2

Write a query to find and replace the special characters in the below subjects/patients table. The query should be generic rather the hardcoded.

Note: we may have special characters in the Initial column.

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DE_F		
3	4	HIJ		
4	5	Xyz		
5	6	KL$M		

Answer
Word counts: 24

```
Select
PatientID,PatientNo,Initials,Systolic,diastolic,Replace(Replace(Replace(initials
COLLATE Latin1_General_BIN,
CHAR(9),''),Char(10),''),Char(13),'') AS CleanInitials From Patients
```

3

Write a query to get the position of the second occurrence of the letter 'a' from the end of a string.

Ex String - ‘Vijay Kumar Goud’

Answer

Word counts: 31

```
Declare @STR VARCHAR(100)='Vijay Kumar Goud'
Declare @Revstr Varchar(100)=ReverSE(@STR)
Declare @FirstA INT =CHARINDEX('a',@Revstr)
Declare @Seconda INT = CHARINDEX('a',@revstr,@Firsta+1)
Select len(@STR)-@Second+1 As PostionstringStartFrom
```

4

List the patient number and initials for every patient who has never had a headache.

Note: Refer the below tables

AE Table:

Patientid	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Answer

Word counts: 16

```
Select PatientNo,Initials from Patients where Patientiid NOT IN (Select Patientid
FROM AE where AE='HEADACHE')
```

5

Update the Medications table to populate the “TakenFor” column with the corresponding adverse event (AE) from the AES table.

Medication:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Answer

Word counts: 18

```
Update M
SET M.Takenfor=A.AE
From Medications M JOIN AE A ON M.Medication=A.med
```

6

Write a query to find the department with no employees.

Employee Table:

EMPID	DeptID
1	10
2	20
3	20
4	30
5	40
6	10
7	10

Departmen Table:

DeptID
20
30
40
50
10

Answer

Word counts: 20

```
Select d.deptid from Departmen  d left join Employee  e on e.deptid=d.deptid
where e.deptid is null;
```

7

Write an SQL query to get the maximum AuditID for each AuditSubCategoryID.

AuditSubCategoryID:

AuditSubCategoryID	Name
1	EnteredEmpty
2	Entered
3	EnteredNonConfomant
4	EnteredByDdeAutoReconcile
7	CommentAdd
8	CommentEdit
9	QueryOpen
10	QueryAnswer

11	QueryCancel
12	QueryClose
13	ReviewRequired

Audits:

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID	Guid	Ser
1				-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	1 00
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	1 00
3				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	1 00
4				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	1 00
5				-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	1 00
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	1 00
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	1 00
8		LastName|Import		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	1 00
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-525172a147e7	1 00
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-9923a0f3bc08	1 00

Answer

Word counts: 24

```
select a.AuditSubCategoryID,Max(aa.auditid)  as Max_AuditSubCategoryID
from AuditSubCategoryID a inner join Audits aa on
aa.AuditSubCategoryID=a.AuditSubCategoryID
Group by AuditSubCategoryID
```

8

Write a query to mask(XXXX) the date only in the VisitDate column in the below Visits table.

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 10

```
Select *,'XXXX' + right ( Convert( varchar ,visitdate,120),9 as maskedvisitDate
from Visits
```

9

Produce the following report, showing each adverse event and the details of the medication taken for that adverse event. Include all adverse events, even those for which no medication was taken. Output must be in the given format.

PatientNo	AE	Med	MedDate

Note: Refer the below tables to code

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz

5	6	KLM

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 0

10

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (
    OrderID INT PRIMARY KEY,
    ProductName NVARCHAR(50),
    Quantity INT
);
-- Insert initial data
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product A', 10);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product B', 20);
GO
BEGIN TRANSACTION;
BEGIN TRY
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product C', 30);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product D', 40);
INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product E', 50);
COMMIT TRANSACTION;
END TRY
BEGIN CATCH
 ROLLBACK TRANSACTION;
SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS ErrorMessage;
END CATCH;
```

Answer

Word counts: 33

1) Create Table then inserted records.
2) Used the Begin Transaction and Try,Catch.

Here the order id is primary key this causes a primary key violation and the entire transaction will fail and rollback

Powered by TechKshetra Info