Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Nakka
Last Name	Vijay Kumar
Email	nakkavijaykumar148@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-05-29 11:02:59
Time Spent (Approx.)	53:04
Percentage	70%
Percentile	89.72%
Score	7
Status	Pass

Share result on Social Network

Answer Sheet

1

Write the SQL to produce the following report on the vital signs data. Order by patient number and visit number to fill the below table columns.

PatientNo	VisitNo	VisitDate	Systolic	Diastolic

Note: refer below listed Patient, Visit, & Vitals tables.

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Visits:			
VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00

8	4	1	8/2/2018 0:00

Vitals:		
VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80
5	125	90
8	130	90

Answer

Word counts: 37

```
SELECT P.PatientNo,
        V.VisitNo,
        V.VisitDate,
        VT.Systolic,
        VT.Diastolic
FROM PATIENTS P JOIN VISITS V ON P.PATIENTID=V.PATIENTID
LEFT JOIN VITALS VT ON V.VISITID=VT.VISITID
ORDER BY P.PATIENTNO,V.VISITNO
```

2

Write an SQL query to generate the “ByPassNumber” column data for the ID column in the table below.

Table 1: DuplicatePatient		Table 2:	
ID		ID	ByPassNumber
1		1	1
2		2	1
3		3	2
4		4	2
5		5	3
6		6	3
7		7	4
8		8	4
9		9	5
10		10	5

Answer

Word counts: 8

```
SELECT ID,CEILING(ID/2.0) AS BYPASSNUMBER FROM DuplicatePatient
```

3

Write a query to get the position of the second occurrence of the letter 'a' from the end of a string.

Ex String - ‘Vijay Kumar Goud’

Answer

Word counts: 30

```
DECLARE @STR VARCHAR(100) = 'Vijay Kumar Goud'
DECLARE @REVSTR VARCHAR(100) = REVERSE(@STR)

DECLARE @firstA INT = CHARINDEX('a', @REVSTR)

DECLARE @secondA = CHARINDEX('a', @REVSTR,@firstA + 1 )

SELECT LEN(@STR) - @secondA + 1 As PositionFromEnd
```

4

Analyze and provide the output of the below-stored procedure

Table: Subjects

SubjectName	SubjectID
ABCD	1

```
Create Proc SP_getData(@ID INT)

As

Begin

Declare @Name nvarchar(100),

@SubjectID int

Select @Name = SubjectName, @SubjectID = SubjectID

from Subjects
```

```
where SubjectID = @ID

Select @Name + @SubjectID as SubjectDetails

End

go

Exec SP_getData @ID = 1
```

Answer

Word counts: 18

It will fail with the below erro.

Conversion fail when converting Nvarchar value 'ABCD' to data type int.

5

Write a query to find and replace the special characters in the below subjects/patients table. The query should be generic rather the hardcoded.

Note: we may have special characters in the Initial column.

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DE_F		
3	4	HIJ		
4	5	Xyz		
5	6	KL$M		

Answer

Word counts: 64

```
WITH CTE AS (
SELECT PATIENTID,PATIENTNO,INITIALS,CAST(INITIALS AS
VARCHAR(100)) AS CLEANEDINITIALS) FROM PATIENTS

UNION ALL

SELECT
PATIENTID,PATIENTNO,INITIALS,CAST(REPLACE(CLEANEDINITIALS,SUBST
RING(CLEANEDINITIALS)
PATINDEX('%[^a-zA-Z0-9)]%', CLEANEDINITIALS),1), '') AS VARCHAR(100))
FROM CLEANEDINITIALS
WHERE PATINDEX('%[^a-zA-Z0-9)]%',CLEANEDINITIALS) > 0 )

SELECT DISTINCT PATIENTID,PATIENTNO,INITIALS,CLEANEDINITIALS AS
CLEANANDNEATDATA
```

6

Analyze and provide the number of records count for

Inner Join

Left join

Right Join

Full outer join

Self join for both Table 1 & 2

Table 1		Table 2
ID		ID
1		1
1		2
1		1
1		1
1		0

Answer

Word counts: 26

```
INNER JOIN - 15 RECORDS
LEFT JOIN - 15 RECORDS
RIGHT JOIN - 17 RECORDS
FULL JOIN - 17 RECORDS
SELF JOIN A - 25 RECORDS
SELF JOIN B - 11 RECORDS
```

7

Write an SQL query to get the maximum AuditID for each AuditSubCategoryID.

AuditSubCategoryID:

AuditSubCategoryID	Name
1	EnteredEmpty
2	Entered
3	EnteredNonConfomant
4	EnteredByDdeAutoReconcile
7	CommentAdd
8	CommentEdit
9	QueryOpen
10	QueryAnswer
11	QueryCancel
12	QueryClose
13	ReviewRequired

Audits:

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID	Guid	Ser
1				-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	1 00
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3	7f67686f080-4c46-8549-6a8f8baa064f	1 00
3				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	1 00
4				-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	1 00
5				-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	1 00
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	1 00
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4	7f67686f080-1561-4dff-a-179-6a8f8baa064f	1 00
8		LastName|Import		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-6a8f8baa064f	1 00
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-525172a147e7	1 00
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4	7f67686f080-4c46-8549-9923a0f3bc08	1 00

Answer

Word counts: 11

```
SELECT AuditSubCategoryID,MAX(AuditID) AS MAXAUDITID FROM Audits
GROUP BY AuditSubCategoryID
```

8

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 14

```
SELECT AuditID, YEAR(AuditTime) as AuditYear

FROM Audits

WHERE AuditTime >= '2024-01-01'
```

9

Produce the following report, showing each adverse event and the details of the medication taken for that adverse event. Include all adverse events, even those for which no medication was taken. Output must be in the given format.

PatientNo	AE	Med	MedDate

Note: Refer the below tables to code

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

AE Table:

VisitID	AE	Med
1	Headache	Aspirin
1	Nausea	
3	Headache	Tylenol
4	High BP	
4	Heart bum	Zantac
7	High BP	Norvas

Medications:

VisitID	Medication	MedDate	TakenFor
1	ASPIRIN	11-Jan-05	
2	Tylenol	26-Jan-05	
4	ASPIRIN	1-Feb-05	
5	Norvasc	1-Feb-05	
6	ASPIRIN	11-Jan-05	

Visits:

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 58

```
SELECT P.PATIENTNO,ae.AE,COALESCE(m.Medication,ae.Med) as
Med,m.MedDate FROM AE ae
JOIN Visits v ON ae.VisitsID=v.visitID JOIN PATIENTS P ON
V.PATIENTID=P.PATIENTID
LEFT JOIN MEDICATION M ON ae.VisitID=m.VisitID
WHERE ae.AE IS NOT NULL AND ae.AE <> '' ORDER BY P.PATIENTID,ae.AE
```

10

Write a SQL query to pull the records that have integer related data only in the table below for the Data column.

ID	SubjectName	Data	Flag
1	New Subject	9001	0
2	New Subject	9002	0
152	_001-005	_001	0
153	_001-005	005	0
154	_001-005	SRI	0
155	_001-005	_001-005	1
1215	003-00001	003	0
1216	003-00001	00001	0
1217	003-00001	JR	0
1218	003-00001	003-00001	1
1219	003-00001	Y	0

Answer

Word counts: 14

```
SELECT DATA FROM TABLE_NAME WHERE TRY_CAST(DATA AS INT) IS NOT NULL
```

1 2 3 4 5 6 7 8 9 10 View All

Powered by TechKshetra Info