Assessment

Dashboard

Users

Question Bank

Quiz

Result

Study Material

Setting

Support

Landing Page

First Name	Anil Kumar
Last Name	Gadiparthi
Email	gadiparthianilkumar@gmail.com
Quiz Name	T-SQL (4-6 years) Automatic to deliver 10 Questions
Attempt Time	2025-06-10 11:15:00
Time Spent (Approx.)	51:03
Percentage	80%
Percentile	95.66%
Score	8
Status	Pass

Share result on Social Network

Answer Sheet

1

Using a while loop, Write a query to print the ProjectID, ProjectName, and ProjectActive from the below Projects Table.

ProjectID	ProjectName	ProjectActive
205	A011_20130279	1
37	A145678_20120136	1
30	A827_20120103	0
141	A102_20120142	1

Answer

Word counts: 78

```
DECLARE @Projjectid INT

DECLARE @projects Table ( ProjectID INT, ProjectName Varchar(50),
ProjectActive BIT );

INSERT INTO @projects (ProjectID, ProjectName, projectActive) values
(205,'A011_20130279',1),
(3,'A145678_20120136',1),
(30,'A827_20120103',0),
(141,'A102_20120142',1)

Declare @temp table ( rownum int IDENTITY (1,1) ,
    ProjectID int  ,
   Projectname varchar(50) , ProjectActive BIT)
```

2

Write the query to display the values in the Project Name after Underscore (_). An example for A011_20130279 should display only 20130279.

ProjectID	ProjectName	ProjectActive
205	A011_20130279	1
37	A145678_20120136	1
30	A827_20120103	0
141	A102_20120142	1

Answer

Word counts: 15

```
Select ProjectID , ProjectName , SUBSTRING (ProjectName , CHARINDEX
('_',ProjectName ) + 1, LEN(ProjectName))
as ExtractedPart from Projects
```

3

Write a query to find and replace the special characters in the below subjects/patients table. The query should be generic rather the hardcoded.

Note: we may have special characters in the Initial column.

PatientID	PatientNo	Initials	Systolic	Diastolic
1	1	ABC		
2	3	DE_F		
3	4	HIJ		
4	5	Xyz		
5	6	KL$M		

Answer

Word counts: 58

```
Select PatientID , PatientNum , Initials ,
(Select ' ' + SUBSTRING (P.initials ,num , 1) from Master.DBO.SPT_Values where
type = 'P' and num BETWEEN 1 LEN (P.initials)
and SUBSTRING (P.initials ,num , 1) LIKE '[A-Z a-z]'
Order by number FOR XML PATH (' ') , TYPE ).Value('.' , 'VARCHAR(MAX)' As
Cleaned Initials , Systolic , Diastolic from Patient P
```

4

Write a query to find the department with no employees.

Employee Table:

EMPID	DeptID
1	10
2	20
3	20
4	30
5	40
6	10
7	10

Departmen Table:

DeptID
20
30
40
50
10

Answer

Word counts: 20

```
Select D.DeptID from Department D Left join Employee E on D.DeptID =
E.DeptID where E.DeptID IS  NULL
```

5

Write a query to get the position of the second occurrence of the letter 'a' from the end of a string.

Ex String - ‘Vijay Kumar Goud’

Answer

Word counts: 21

```
Declare @STR VARCHAR(100) = 'Vijay Kumar Goud'
Select LEN (@STR) - CHARINDEX ('a ' , REVERSE(@STR) , CHARINDEX ('a',
REVERSE(@STR)) +1 ) +1 as SecondAfromEndPosition
```

6

Write a query to mask(XXXX) the date only in the VisitDate column in the below Visits table.

VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Answer

Word counts: 17

Select VisitID , Patientid , Visitno , 'XXXX ' + FORMAT (CAST (VisitDate)) AS DATETIME) , 'HH:mm') AS MASKEDVISITDATE from Visits

7

What would be the output of the below SQL query?

```
IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (String NVARCHAR(2000), Code
NVARCHAR(2000))

IF EXISTS (SELECT 1 FROM tempdb.dbo.sysobjects WHERE id =
Object_ID(N'tempdb.dbo.#Temptable') AND type = 'U')

DROP TABLE #Temptable

CREATE TABLE #Temptable (ID INT IDENTITY, String NVARCHAR(2000),
Code NVARCHAR(2000))
```

Answer

Word counts: 16

We will get below Error
There is Alreay an Object Named '#Temptable' in the database

8

Write the SQL to produce the following report on the vital signs data. Order by patient number and visit number to fill the below table columns.

PatientNo	VisitNo	VisitDate	Systolic	Diastolic

Note: refer below listed Patient, Visit, & Vitals tables.

Patients:

PatientID	PatientNo	Initials
1	1	ABC
2	3	DEF
3	4	HIJ
4	5	Xyz
5	6	KLM

Visits:			
VisitID	Patientid	Visitno	VisitDate
1	1	1	12/1/2018 0:00
2	1	2	23-01-2018 00:00
3	1	3	28-01-2018 00:00
4	2	1	1/2/2018 0:00
5	2	2	8/2/2018 0:00
6	3	1	3/2/2018 0:00
7	3	2	8/2/2018 0:00
8	4	1	8/2/2018 0:00

Vitals:		
VisitID	Systolic	Diastolic
1	120	80
2	110	80
3	100	90
4	140	80
5	125	90
8	130	90

Answer

Word counts: 37

```
Select P.PatientNo , V.VisitNo  , V.VisitDate ,VT.Systolic,VT.Diastolic From
Patients P JOIN Visits V ON P,patientID = V.PatientID
LEFT JOIN Vitals VT ON V.vistID = VT.visitID Order by P.PatientNo , V.VistNo
```

9

What is wrong with this SQL query? Correct it so it executes properly.

Note: Use the below Audits table for reference

AuditID	Property	Value	Readable	AuditUserID	AuditTime	ObjectID
1				-2	2016-03-31 18:40:29,100	3
2		PasswordExpires|12/31/9999 11:59:59 PM		-2	2016-03-31 18:40:29,100	3
3				-2	2016-03-31 18:40:29,133	4
4				-2	2016-03-31 18:40:29,133	4
5				-2	2016-03-31 18:40:29,133	4
6		InitialSiteGroup|1		-2	2016-03-31 18:40:29,133	4
7		FristName|Rave		-2	2016-03-31 18:40:29,133	4
8		LastName|Import		-2	2016-03-31 18:40:29,133	4
9		Login|RaveImport1		-2	2016-03-31 18:40:29,133	4
10		PasswordExpires|3/31/2017 6:40:29PM		-2	2016-03-31 18:40:29,133	4

SQL Query:

```
SELECT AuditID, YEAR(AuditTime) AuditYear

FROM Audits

WHERE AuditTime >= 2024
```

Answer

Word counts: 13

```
SELECT AuditID, YEAR(AuditTime) AuditYear
FROM Audits
WHERE AuditTime >= '2024-01-01'
```

10

Debug and explain the below code with output.

```
CREATE TABLE OrdersData (

    OrderID INT PRIMARY KEY,

    ProductName NVARCHAR(50),
```

```
    Quantity INT

);

-- Insert initial data

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product
A', 10);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (2, 'Product
B', 20);

GO

BEGIN TRANSACTION;

BEGIN TRY

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (3, 'Product
C', 30);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (4, 'Product
D', 40);

INSERT INTO OrdersData (OrderID, ProductName, Quantity) VALUES (1, 'Product
E', 50);

COMMIT TRANSACTION;

END TRY

BEGIN CATCH

 ROLLBACK TRANSACTION;

SELECT ERROR_NUMBER() AS ErrorNumber, ERROR_MESSAGE() AS
ErrorMessage;

END CATCH;
```

Answer
Word counts: 86

A table OrdersData is CReated with Three Columns
OrderID is the Primary Key So it Must be Uniq

Two Rows are inserted succesfully Into ordersData
In Transaction The First Two Inserts Inside the Transaction Works fine
(3, 'Product C', 30)
(4, 'Product D', 40)

The third Insert will fail it is attempting to insert a duplicate value orderID = 1 which alreay Exists
This Voilates the PRIMARY KEY Constraint , Triggering An Error

Voilation of PRIMARY KEY constraint 'PK_ConstaintName' . Canot Insert Duplicate Key in Objet 'DBO.OrdesData'
The Duplicate Key Value is (1).

1 2 3 4 5 6 7 8 9 10 View All

Powered by TechKshetra Info