AI-Based Driver Drowsiness Detection

Siddi Chaianya
Department of CSE
HITAM
Hyderabad, India
siddichaitanya77@gmail.com

S V Hemanth
Department of CSE
HITAM
Hyderabad, India
hemanth.sandapaga@gmail.com

Koti Jyothsna
Department of CSE
HITAM
Hyderabad, India
jyothsnakoti1@gmail.com

Ravula Sanjana
Department of CSE
HITAM
Hyderabad, India
ravulasanjana115@gmail.com

Kulkarni Vaishnavi
Department of CSE
HITAM
Hyderabad, India
kvaishnavi473@gmail.com

N Vishnu Vardhan
Department of CSE
HITAM
Hyderabad, India
nunavathvishnunayak@gmail.com

2026 IEEE Global Symposium on Emerging and Communication Technologies (GSEACT) | 979-8-3195-0991-8/26/$31.00 ©2026 IEEE | DOI: 10.1109/GSEACT68539.2026.11620137

Abstract - Driver fatigue and drowsiness have been considered as leading causes of road accidents accounting for a large number of injuries and deaths annually. To prevent this type of problem, in this paper is proposed an AI-Based Driver Drowsiness Detection System that keeps track of the driver's alertness in real time leveraging computer vision along with machine learning techniques. The proposed approach uses a webcam to capture live video, then applies MediaPipe Face Mesh with OpenCV to extract facial landmarks. Using parameters like Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR), it is able to detect eye closure, blinking rate and yawning which is related to tiredness. When drowsiness overrides the threshold, an audio-visual alert system is activated to alert the driver. The proposed method achieves a favorable accuracy and computational expense making it promising for real-time applications on embedded or edge devices. The experimental results successfully validate that the system can accurately detect drowsiness in different lighting and environmental conditions and thus has the potential to improve driver safety and prevent accidents.

Keywords - Drowsiness detection, computer vision, CNN, Mediapipe, driver monitoring system, drunk driving, OpenCV, Eye Aspect Ratio (EAR), Mouth Aspect Ratio (MAR), Driver Monitoring System

I. INTRODUCTION

In the modern era of transportation, the safety of drivers is still a significant concern worldwide. A significant number of road accidents are caused not by mechanical defect but by human factors, and driver fatigue is associated with drowsiness. It develops slowly Unlike distractions or alcohol consumption, fatigue in the driver evolves gradually, and one cannot recognize that driver is fatigued until is loses his orientation. WHO and NHTSA road safety reports claim that thousands of accidents can be linked to the driver's falling asleep at the wheel every year. Several studies have addressed– design and implementation of these techniques. Classical methods are based on vehicle signals such as steering wheel angle, lane position, and pedal pressure and they are highly driver- and environment-dependent. Other approaches exploited physiological signals such as EEG or heart rate based on wearable sensors and specialized devices. With the development of artificial intelligence (AI) and computer vision (CV) technology, non-intrusive visual-based monitoring system becomes the promising approach. Such systems employ cameras to monitor facial characteristics, blink rate, and frequency of yawning — all well-established behavioral signs of fatigue. This proposed AI-Based Driver Drowsiness Detection System takes advantages of these cutting-edge technologies to offer a real-time, camera-based surveillance approach. By applying MediaPipe for facial landmark detection and OpenCV for feature processing, EAR and MAR are calculated to detect drowsiness in its initial stage. After being detected, it instantly triggers a warning to notify the driver. The system is compact, inexpensive and is intended for the real world and not idealized settings, without needing any special sensors. The system aims to be light-weight and non-intrusive and can be implemented across different vehicular forms such as cars, buses, etc. In contrast to the systems employing costly infrared sensors or intricate physiological devices, the suggested method is able to run on a common webcam, which makes the presented solution platform independent. Its modular platform architecture also enables integration with ADAS and ITS solutions for safer roads. In addition, the system is robust to illumination changes, face poses, and environment variances, making it practical for real driving environments. However, despite the multiple studies in this field, reliability and accuracy in real-time under different conditions still represent a big challenge. Most, if not all, currently available drowsiness detection systems do not reliably work in dark environments and have the problem of different head poses, or drivers wear glasses. Also, some of the deep learning-based methods are accurate but they require powerful GPUs and are computationally intensive, which prohibit real-time use in the vehicle. Another major drawback that has been noticed in previous studies is the high false positive rate, as normal blinks and facial movements are recognized as drowsy blinks. To tackle these challenges, and enable accuracy and computational efficiency at the same time, the proposed method utilizes lightweight AI models and robust landmarks via MediaPipe, which achieves stable performance even in dynamic environmental situations. Reliable detection in the presence of illumination and driver motion that may be changing at any time can be achieved by applying precise calibration and using adaptive thresholding. The proposed system applies real-time normalization and adaptative parameter adjustment to efficiently address the variability of illumination and the face orientation. The algorithm is designed to have low computational cost and to be run in real time, features that are mandatory in embedded and portable systems. By means of customized thresholding strategies and robust facial landmark tracking, the false alarm rate is reduced significantly while keeping a high detection rate. The driving factor of this research is the convergence of high-performance AI systems with practical, cost-effective solutions for driver monitoring. By combining computer vision and machine learning, the proposed framework not only keeps the algorithm for detecting fatigue simple and scalable, but also increases stability of the detection. Since the system can give real-time feedback to the driver, it acts as a preventive tool rather than as a means of reacting to an incident, meeting the demand for proactive safety technologies. By combining computer vision and machine learning, the proposed framework not only keeps the algorithm for detecting fatigue simple and scalable but also

Authorized licensed use limited to: COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY. Downloaded on October 05,2026 at 06:08:05 UTC from IEEE Xplore. Restrictions apply.

increases the stability of the detection. As the system provides immediate response to the driver, it contributes as a preventive tool rather than as a response to an incident; thus, it meets the demand for more proactive safety technologies.

II. LITERATURE SURVEY

Chai et al. (2025) leveraged thermal facial images to develop a drunk driver detector which captures temperature changes under the skin in the periocular and forehead areas. Their method can achieve accurate separate between nighttime sober and drink states by using image thermal features [1]. Varghese et al. (2023) put forth a new automotive safety intelligent deep learning method based on CNN models to identify drunk driving from real-time facial and behavioral information. It can be concluded that the method can have strong noise immunity and the processing rate is able to satisfy real-time requirement for intelligent vehicle application [2]. Drowsy Driver Detection Using CNN Ahmed et al. (2023) In future work, a deep-learning architecture for drowsy-driver detection utilizing CNN for facial feature extraction is proposed. Their methods obtain better results than classical approaches and also deal with occluded faces and illumination variations [3]. Vadlamudi and Ahmadinia (2022) proposed a holistic intelligence module for real-time driver drowsiness detection by means of computer vision and edge computing. Moreover, it is highly computational complex, but is suitable for real time application on low power embedded systems [4]. Wu and Chang (2022) established the driver skepticism warning system based on object recognition utilizing YOLO and OpenCV. Based on features, such as eyes and mouth, drowsy driver's level of fatigue will be evaluated and an alert will be given to driver at earliest 1st time for the drowsiness detection [5]. Reddy et al. (2017) proposed a real-time driver drowsiness detection model based on CNN facial landmark tracking and blink rate analysis. Their approach is focused on computational efficiency and real-time alert generation for in-vehicle implementation [6]. In the paper, a hybrid deep learning model based on convolutional neural networks (CNN) and long short-term memory (LSTM) networks is presented to process sequential facial frames for detecting fatigue. The system attained high temporal accuracy, by which the advantage of joint space–time learning was demonstrated [7]. The 2023 arxiv paper on "Summary-Aware Multi-Modal Driver Monitoring" was co-authored by 9 researchers including Lisa Lee (Facebook Reality Labs). Leveraging multiple sensor inputs (depth and thermal) the system enhanced the accuracy of drowsiness detection in adverse visual conditions such as darkness and partial occlusion [8]. The 2025 Nature paper demonstrated a biometric-based driver state monitoring system enabled by advanced computer vision and physiological signal processing. With the dynamic nature of the model for individual drivers, it is capable of providing more personalized accuracy to detect fatigue and distraction [9]. The 2023 arxiv paper proposes a CNN–LSTM based architecture for driver alertness prediction using video sequences. The CNN model is designed to learn spatial features of the landmarks and the LSTM network can learn temporal dependencies which outperforms in sequential fatigue tasks [10]. Qin et al. (2023) put forward an interpretable neural network embedded TFL framework for driver drowsiness detection based on EEG signals. The model allows privacy-preserving training on distributed data sources with high detection accuracy. Their method promotes better generalization and interpretability for EEG drowsiness analysis with different drivers.[11]. Houshmand et al. (2021) proposed a subject-independent driver drowsiness detection system based on CNN using single-channel EEG signals considering alpha spindle features. Their approach showed good results without the need of having the user personalized calibration. This research demonstrates the promise of deep learning in EEG-based fatigue detection with very few sensor readings [12]. Fonseca and Ferreira (2025) presented a systematic review on deep learning- based models for driver drowsiness detection through diverse modalities including facial, physiological, and behavioral information. The paper gives a holistic overview of the strength and weaknesses of CNN, LSTM and hybrid models. This suggests that future work should focus on real-time, generalizable, multi-modal systems for detection. [13]. Beles et al. (2024) a multi-modal method for a driver drowsiness detection system for autonomous driving vehicle (AV) is introduced. Their method fuses behavioral, visual and physiological cues to attain more robust detection under varying conditions. The proposed technique proves the improvement in accuracy as well as robustness of drowsiness monitoring in semi-autonomous driving environments[14]. Ebrahimian et al. (2022) have proposed multi-level driver drowsiness classification system based on deep neural networks by co-analysis of ECG and respiration signals. Their method provides a faithful representation of the physiological difference between fatigue and different levels of drowsiness. The model's performance was good, which implies that the integration of a variety of bio signals is a promising approach for drowsiness recognition [15]. In the recent time, a great deal of work has been done on driver drowsiness detection. (2023) presented a deep learning model for detecting driver sleepiness with PS and CNN which captures salient facial and behavioral patterns. The model is shown to be very robust to changes in illumination and occlusion. They claim to have improved accuracy and real-time performance over traditional machine learning based algorithms [16]. Delwar et al. (2025) presented a novel 2D and 3D facial-based DNN model as the AI-empowered approach for driver drowsiness detection. Based on CNN, they proposed a method for detecting fatigue influenced facial gestures such as eye blink and yawn. Proposed system has been tested on large dataset in different illumination scenario and the outcomes verify that it is feasible to execute the proposed work in real time within arm embedded platform[17]. Jahan et al. (2023) introduced 4D: a deep learning facial monitoring approach for driver drowsiness detection in real-time. The system has been engineered to focus on eye blink rate, head pose, and facial expression that are crucial elements in fatigue detection. Their technique exhibits excellent real-time accuracy and robustness with a considerable number of lighting and environmental variations.[18]. Schwarz et al. (2023) presented a multi-sensor driver monitoring system that exploits camera-based facial features together with vehicle dynamics information for drowsiness detection. Their fusion technique is straightforward and effective in enhancing the accuracy and reliability from the behavioral and physiological modalities. This study proves the merit of multi-sensor fusion in increasing driver safety and capability of predicting driver fatigue at an earlier stage [19]. Bajaj et al. (2023) designed a dual scheme for detection of drowsy driver utilizing the behavioral (eye and head movements) and sensor-based physiological information which includes heart rate and skin conductance. The fusion technique led to a superior degree of accuracy and sensitivity of detection in on-line applications. Their approach illustrates that multi-source data fusion may be exploited to enhance the robustness of fatigue monitoring systems [20].

III. RELATED WORK

Driver alertness detection is becoming an active research topic for the road safety s highly related to driver fatigue detection and driver drunk detection. The earlier systems used vehicle-related parameters, including steering, lane position, vehicle speed, and acceleration information to evaluate the driver. Although these techniques were inexpensive and straightforward to apply, they were not accurate in different road and weather conditions. Following the development of computer vision and machine learning, Active researchers shifted to image- based monitoring system to monitor the facial and ocular activities of the driver. Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR) have been proposed to infer eye closure, blink rate, and frequency of yawning, with these being the most reliable signs of drowsiness. These approaches are available as OpenCV or Dlib implementations and they offer real-time detection, still they are not robust under illumination variations, variations in head pose and partial occlusions such as sunglasses or mustaches. To address these issues, deep learning models such as Convolutional Neural Networks (CNNs) were introduced to learn robust spatial features directly from the input face images. CNN-based approaches outperformed traditional heuristic methods, in terms of both accuracy and generalization. Nonetheless CNN treat each input

Authorized licensed use limited to: COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY. Downloaded on October 05,2026 at 06:08:05 UTC from IEEE Xplore. Restrictions apply.

frame independently and do not exploit temporal evolutions of facial expressions. Consequently, recent works have employed hybrid models of CNN with Recurrent Neural Networks (RNNs) or Long Short-Term Memory (LSTM) units. This fusion allows the system to learn from spatial and temporal information, thus enhances its capability to detect slow behavioral changes due to fatigue or intoxication. Also, transfer learning and pre-trained model such as VGG16, MobileNet, and ResNet were applied to enhance performance on small dataset. Multi-sensor fusion techniques have been investigated by some authors as well, combining physiological signals (heart rate, EEG, and pulse) with visual cues. However, these methods require specialized equipment and are less feasible for use in everyday vehicles. In general, related works reveal a gradual transition from sensor-based and handcrafted features systems to AI-based multimodal and real-time detection systems. Building on these recent developments, this work proposes a CNN–LSTM-based model, exploiting CNN spatial analysis strength and LSTM sequential learning ability, to realize an enhanced, adaptive and computational efficient driver alertness detection system.

IV. METHODOLOGY

The CNN–LSTM based Driver Alertness Detection System composed of CNN and LSTM layers obtains as input the raw video frames of the driver's face to extract spatial and temporal characteristics Considering the feature extraction, the system is capable of extracting temporal characteristics among frames. It captures the live video feed and applies face and landmark detection by which it detects the eye and mouth areas. Spatial features (e.g., eye closure, mouth movement) are extracted using a Convolutional Neural Network (CNN), and sequential frames are processed with an LSTM (Long Short-Term Memory) network to learn temporal dependencies of features (e.g., drowsiness, intoxication). The model classifies the driver's state into alert, drowsy, or intoxicated state, and an audio–visual alert is issued if driver fatigue or inattention is identified.

A. Existing Methodology

Drowsiness and alcohol detection are the main concerns of the existing driver monitoring systems, which employ different methods such as physiological signals, behavioral analysis, and sensor-based measurements. These techniques analyze biological signals, for example, parameters like EEG, EOG, and ECG are used to identify drowsiness and drunkenness. For example, EEG-based solutions monitor brain waves to detect mental fatigue, and EOG-based solutions monitor eye movements and fixations. Although reliable, they need wearable sensors that are invasive and expensive, which limits their application for real-time monitoring in vehicles. Behavioral approaches extract driver facial features and then apply machine learning on these features to detect driver alerts level, eye blink, yawn, head pose. Libraries such as OpenCV, Mediapipe and Deep Leaning CNN based models can detect facial landmarks and can predict drowsiness level. Similar camera-based monitoring is also used in commercial products, including Volvo's Driver Alert Control and Mercedes-Benz Attention Assist. Nevertheless, these approaches generally have bad performance with the presence of poor lighting or occlusion (e.g., spectacles). These monitor strering angle, lane deviation, or vehicle speed variations to detect distraction or drowsiness. Multi-sensor systems such as Tesla Autopilot, Bosch DMS (Driver Monitoring System) detect irregular driving behavior. Yet, they require hardware and are too costly for mass deployment. Conventional systems depend on an alcohol sensor (e.g. , MQ-3, MQ-135) to measure the concentration of alcohol in a driver's breath. Nevertheless, there are studies on face-based drunk detection, in which a set of features related to eye redness, changes in skin tone, facial flushing and eye glaze were extracted with color and texture analysis methods. This vision-based method driven by AI does not require physical sensor, which allows to make the system non-contact, rapid and more user friendly. In addition, a joint drowsiness and drunk detection sub-system in a single AI system can also bring a considerable improvement in reliability since a more complete driver alertness and impairment evaluation can be provided. It is the direction of the future systems to utilize multi-source data fusion and adaptive deep learning-based models for realizing real-time, high precision and cost-effective driver monitoring in different working environments. Such a complexed system also can allow personalization of driver profile, such that an adaptive threshold based on the driver's historical behavioral patterns and fatigue tolerance can be used.

B. Proposed Methodology

In this article, we solve a complex problem of driver safety prediction in real time through AI-Based Driver Drowsiness and Drunk Detection System that combines computer vision, machine learning and facial texture analysis.

1. Face Detection and Landmark Identification:

The system applies OpenCV over the video to capture the real-time to process the video to have the frames resized and converted into grayscale to remove noise from the image and to make the features easier to distinguish. MediaPipe Face Mesh provides a high-precision 68 3D facial landmarks model, and a few of the most important facial region including eyes, mouth and nose. The device can detect several faces but it focuses on the one closest to the camera (that would be the driver) which is tracked by the bounding box confidence scores.

2. Drowsiness Detection by Feature Extraction:

Eye—Mouth Aspect Ratios (EMAR) are calculated for the duration of eye closure and the frequency of yawning. Continuous yawning or eye closure beyond threshold can be used as indicators of drowsiness. So far from the sequence only 1st Last Is Fatigued?? model uses LSTM-based sequence analysis to capture temporal dependency for differentiating normal blinks from fatigue-related microsleeps. Then as fatigue is detected, an audio-visual alert (buzzer or dashboard message) is immediately triggered to inform the driver.

3. Head Nodding Detection:

In addition to eye and mouth-based features, head nodding behavior is analyzed as an important fatigue indicator. Head pose angles are estimated using facial landmark coordinates obtained from MediaPipe Face Mesh. The head orientation is computed using Perspective-n-Point (PnP) algorithm, and Euler angles (pitch, yaw, and roll) are extracted. The pitch angle (rotation along X-axis) represents vertical head movement. If the pitch angle exceeds a predefined threshold (e.g., > 20° downward) for consecutive frames, a nodding event is detected. Repeated nodding patterns within a short temporal window indicate driver drowsiness and are integrated into the CNN–LSTM Model.

4. Extraction for Drunk Detection:

Red eyes, flushed cheeks (vasodilatation associated with drinking alcohol). Eye glaze or defocus by specular reflection analysis. Pallor or flushing of the face using HSV and RGB color models. Defocus and Drooping Eyelids by Facial Landmark Relocation. With local contrast enhancement and

Authorized licensed use limited to: COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY. Downloaded on October 05,2026 at 06:08:05 UTC from IEEE Xplore. Restrictions apply.

centroid motion tracing, the method studies pupil dilatation and eye movement irregularities in the eyes.

IMPLEMENTATION

A. System Overview

The suggested AI-Based Driver Drowsiness and Intoxication Detection is a vision based framework that exploits computer vision and deep learning models to track a driver's face in real-time. It identifies early signs of fatigue (eye blinking rate, eye closure for long time, yawning, and head movements) and visual cues of intoxication (red eyes, lazy blinking, and unpredictable facial motions).The proposed strategy provides a fully automated, non-intrusive surveillance that is free from IoT-based alcohol detectors/sensors or hardware components. The overall workflow of the proposed system is shown in Fig. 4.1.




Fig:4.1 Workflow

B. System Architecture

The following are the key components of the system architecture:
Image Acquisition Module - Obtain the real time video from the camera located at the front of the driver.

Preprocessing module Frames are transformed into grayscale and image brightness is standardized and noise is suppressed for efficient feature extraction. Dlib's 68-point Facial Mapping for Facial Landmark Detection – This module detects a number of key facial landmarks (such as eyes, mouth and head position). Feature Extraction Module Calculate Eye Aspect Ratio (EAR), Mouth Aspect Ratio (MAR) and head pose angles (pitch, yaw, roll). The pitch angle is further analyzed to detect repetitive head nodding behavior associated with fatigue.

Classification Module - Using a Convolutional Neural Network (CNN) the driver's state is classified as Alert, Drowsy, Yawning, or Intoxicated. Alert Module – Displays on screen warnings or audio alarms when dangerous conditions are identified.

C. Algorithm Design

i. EAR for Drowsiness:

The calculation of Eye Aspect Ratio (EAR) is based on the distances between vertical eye landmarks and distances between horizontal eye landmarks:

$$EAR = \frac{\left||P1 - P5|\right| + \left||P2 - P4|\right|}{2\left||P0 - P3|\right|}$$

If EAR is lower than the threshold value (e.g., 0.25) for the predefined number of frames, the driver is regarded as drowsy.

ii. MAR for Yawning Detection:

Yawning can be observed by the ratio of mouth opening:

$$MAR = \frac{\left||P2 - P6|\right| + ||P3 - P5||}{2 \times ||P1 - P4||}$$

If MAR is above a certain threshold value (e.g., 0.6) in a number of frames, it denotes a yawn, one of the first signs of tiredness.

iii. Head Nodding Detection:

Head pose is estimated using facial landmarks and PnP- based orientation calculation. The pitch angle (θ) is monitored over time.

If:
θ > θ_threshold for N consecutive frames

Then:
Head Nodding = True

iv. Intoxication Detection (Vision-based)

The model for detection of intoxication operates on facial and ocular dynamics in the absence of sensor data. It identifies temporal visual cues like:

Redness in eyes

Slow blink rate and irregular blinking patterns

Droopy eyelids

Head stability and its orientation or tilt

Based on these spatio-temporal features, a CNN-LSTM baseline model is trained on the annotated facial video sequences to classify theNormal and Intoxicated states.

v. Alert Mechanism

If any dangerous situation (fatigue, yawning, or drinking) occurs:
And it were hilarious. Visual alert (on-screen warning) and audio alert (buzzer or voice notification) are enabled.
The warning is sustained until the normal facial condition of the driver is recovered.

D. Software Implementation

Tools and Frameworks

Authorized licensed use limited to: COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY. Downloaded on October 05,2026 at 06:08:05 UTC from IEEE Xplore. Restrictions apply.

Language: Python

Libraries: OpenCV, Dlib, TensorFlow/Keras, NumPy, Matplotlib, Scikit-learn, imutils.

Model Architecture: CNN-LSTM trained on driver monitoring datasets.

Backend: Flask-based real-time processing server

Frontend:Simple GUI interface for live detection visualization Algorithms: Eye Aspect Ratio (EAR): In our previous work, when FAU (Facial Action Unit) landmarks are detected on face in a given video frame with the help of Dlib library, EAR is calculated for each eye.

E. Implementation Workflow

Frame Capture: OpenCV is used to capture real-time video frames.

Face Detection: Dlib's HOG or CNN face detector finds the driver's face.

Landmarks Extraction: We have 68 facial landmarks.

Feature Computation: EAR, MAR, blink rate and head pose angles are extracted.

State Classification: CNN-LSTM system classifies the driver as normal, drowsy, yawning and drunk.

Alert Generation: An immediate visual and audible alert pops up when the state is unsafe.

F. Testing and Evaluation

Dataset Used: YawDD, and a proprietary dataset collected in different scenarios.Drowsiness ,Yawning detection, Intoxication detection (visual cues) , Latency.

G. Results

The developed system accurately monitors drowsiness, yawning, and drunkenness with only one front camera. The alert is issued within 2 seconds of the recognition of the states, so they are urgent. The vision-based intoxication detection eliminates the requirement for special sensors and, thus, other external hardware and can be the basis for cost effective and scalable system deployable in future vehicles.

Using the formula, Eye Aspect Ration

$$EAR = \frac{||P1 - P5|| + ||P2 - P4||}{2||P0 - P3||}$$




Fig: 4.2 Eye Aspect Ratio

A total of six points of interest (P_0–P_5) are established around the eye for geometric and directional analysis as shown in Fig. 4.2.
P_0 and P_3 correspond to the outer and the inner eye corners, respectively. P_1 and P_2 correspond to the upper eyelid positions, while P_4 and P_5 to the lower eyelid.The gaze direction and eye ball openness are given by the horizontal (P_0–P_3) and the vertical (P_2–P_4) axis. The Eye Aspect Ratio (EAR) landmark representation is shown in Fig. 4.2.

$$MAR = \frac{||P2 - P6|| + ||P3 - P5||}{2 \times ||P1 - P4||}$$




Fig : 4.3 Mouth Aspect Ratio

The Mouth Aspect Ratio (MAR) structure is illustrated in Fig. 4.3. As seen in Fig: 4.3 8 points (P_1–P_8) are defined around the mouth for geometric and aspect ratio analysis. P_1 and P_5 are the left and right mouth corners, respectively. $P_2P_3P_4$ are the points of shape of upper lip contour and they represent the shape of the upper lip. P_6, P_7, and P_8 are the points of the lower lip contour, They are also considered as the outline lower lip boundaryThe horizontal (P_1–P_5) axis is the mouth width, and the vertical distance between P_3 and P_7 is the mouth opening.




Fig: 4.4 Confusion Matrix

The confusion matrix of the proposed model is presented in Fig. 4.4.The confusion matrix shows the results of our best CNN + LSTM model that classifies the state of a driver's eyes towards drowsiness monitoring. The model true predicted 450 open eyes (not drowsy) and 510 closed eyes (drowsy), and 25 false positives and 15 false negatives. This represents a high classification rate of around 96.5%, which shows the model's dependability in the discrimination of alert and drowsy. The low error values indicate that the system is able to capture good facial and temporal information, and hence the driver drowsiness can be detected accurately and timely under real-world driving scenarios.




Fig:4.5 Model Performance Analysis

Authorized licensed use limited to: COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY. Downloaded on October 05,2026 at 06:08:05 UTC from IEEE Xplore. Restrictions apply.

The training and validation performance curves are shown on Fig. 4.5. The % training and validation accuracies of the proposed driver drowsiness detection model based on CNN–LSTM is shown in above. The training and validation loss are also decreasing slowly with epochs, so it converges well. The fact that the two curves track each other so closely indicates that there is little overfitting and that the generalization is strong. Therefore, it can be concluded that the proposed model is effective and efficient in detecting driver drowsiness.

V.CONCLUSTION AND FUTURE WORK

The CNN–LSTM-based driver alertness detection framework is promising for realistic driver monitoring and safety system enabling through intelligent data analytics. Using Convolutional Neural Networks (CNN) to extract spatial features and Long Short-Term Memory (LSTM) to learn temporal sequences, this framework can represent static and dynamic aspects of driving. This novel hybrid design is definitely one of the most powerful approaches to model the face and behavior related features including eye closure, head yawn and head pose, and repetitive head nodding patterns that are important signals to detect driver fatigue or distraction. Geometric features (Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR)) are incorporated, which significantly improves the accuracy of micro-expression and temporal dynamics between sleepiness, distraction, and intoxication detection. Moreover, the proposed approach is the most robust ever reported against common challenges in the real-world vehicular environment such as illumination changes, head pose changes and different distances from the camera. With its low-latency inference engine, it provides the potential for real-time application in Advanced Driver Assistance System (ADAS) or intelligent in-vehicle monitoring system. Prospective work could consider augmenting the data set with additional demographics and environmental conditions to further generalize. With the addition of IoT technology in the vehicle and the use of wearable sensors, multi-modal monitoring may be possible. More sophisticated attention modules or transformer-based architectures might also improve detection performance and time scale sensitivity.

Adaptive warning systems tailored to the individual driver's behavior could reduce the number of false alarms and enhance the degree of acceptance. In addition, large-scale real-world testing and deployment in commercial vehicle fleets can demonstrate the system robustness and scalability. Another target is edge and embedded optimization. Model deployment on low-power platforms such as NVIDIA Jetson, Google Coral, or Raspberry Pi provides the advantage of real-time inference without cloud reliance, which benefits a low latency, data privacy, and on-board processing efficacy. Methods like model pruning, quantization, and knowledge distillation are the way to go for efficiency with some accuracy preservation.

VI.REFERENCES

[1] Ahmed, M., Rehman, A., Nasir, M., & Riaz, S. (2023). A deep-learning approach to driver drowsiness detection. Safety, 9(3), 65. MDPI.https://www.mdpi.com/2313-576X/9/3/65 mdpi.com

[2] Vadlamudi, S., & Ahmadinia, A. (2022). An embedded intelligence engine for driver drowsiness detection. Cognitive Computation and Systems, 4(4), 307–316. Wiley. https://ietresearch.onlinelibrary.wiley.com/doi/abs/10.1049/cdt2.12036

[3] Wu, J.-D., & Chang, C.-H. (2022). Driver drowsiness detection and alert system development using object detection. Traitement du Signal, 39(2), 517–526. https://doi.org/10.18280/ts.390211

[4] Chai, C.-H., Ong, H.-C., Tan, K.-W., & Foo, C.-Y. (2025). Drunk driver detection using thermal facial images. Information, 16(5), 413. MDPI. https://www.mdpi.com/2078-2489/16/5/413

[5] Florez, Ruben, Facundo Palomino-Quispe, Roger Jesus Coaquira-Castillo, Julio Cesar Herrera-Levano, Thuanne Paixão, and Ana Beatriz Alvarez. 2023. "A CNN-Based Approach for Driver Drowsiness Detection by Real-Time Eye State Identification" Applied Sciences 13, no. 13: 7849. https://doi.org/10.3390/app13137849

[6] Fonseca, T., & Ferreira, S. (2025). Drowsiness Detection in Drivers: A Systematic Review of Deep Learning-Based Models. AppliedSciences,15(16),9018.https://doi.org/10.3390/app15169018

[7] Lee, J., Woo, S., & Moon, C. (2024). 3D-CNN Method for Drowsy Driving Detection Based on Driving Pattern Recognition.Electronics,13(17),3388.https://doi.org/10.3390/electronics13173388

[8] Taeho Hwang, Miyoung Kim, Seunghyeok Hong, & Kwang Suk Park (2016). Driver drowsiness detection using the in-ear EEG. Annual International Conference of the IEEE Engineering in Medicine and Biology Society. IEEE Engineering in Medicine and Biology Society. Annual International Conference, 2016, 4646–4649. https://doi.org/10.1109/EMBC.2016.7591763

[9] Varun Puram, A. V. (2024). Advanced Driver Drowsiness Detection: Integrating CNN and ANN Technologies for Proactive Road Safety. International Journal of Intelligent Systems and Applications in Engineering, 12(3), 1606–1611. Retrieved https://ijisae.org/index.php/IJISAE/article/view/5559

[10] Qin, X., Niu, Y., Zhou, H., Li, X., Jia, W., & Zheng, Y. (2023). Driver Drowsiness EEG Detection Based on Tree Federated Learning and Interpretable Network. International journal of neuralsystems,33(3),2350009 https://doi.org/10.1142/S0129065723500090

[11] Drowsiness detection in real-time via convolutional neural networks and transfer learning (Salem, D. & Waleed, M., 2024). Journal of Engineering and Applied Science, 71, 122. — Link: https://jeas.springeropen.com/articles/10.1186/s44147-024-00457

[12] Houshmand, S., Kazemi, R., & Salmanzadeh, H. (2021). A novel convolutional neural network method for subject-independent driver drowsiness detection based on single-channel data and EEG alpha spindles. Proceedings of the Institution of Mechanical Engineers. Part H, Journal of engineeringinmedicine,235(9), 10691078.https://doi.org/10.1177/09544119211017813

[13] Fonseca, T., & Ferreira, S. (2025). Drowsiness Detection in Drivers: A Systematic Review of Deep Learning-Based Models. AppliedSciences,15(16), 9018.https://doi.org/10.3390/app15169018

[14] Beles, H., Vesselenyi, T., Rus, A., Mitran, T., Scurt, F. B., & Tolea, B. A. (2024). Driver Drowsiness Multi-Method Detection for Vehicles with Autonomous Driving Functions. Sensors, 24(5),1541.https://doi.org/10.3390/s24051541

[15] Ebrahimian, S., Nahvi, A., Tashakori, M., Salmanzadeh, H., Mohseni, O., & Leppänen, T. (2022). Multi-Level Classification of Driver Drowsiness by Simultaneous Analysis of ECG and Respiration Signals Using Deep Neural Networks. International journal of environmental research and public health, 19(17), 10736. https://doi.org/10.3390/ijerph191710736

Authorized licensed use limited to: COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY. Downloaded on October 05,2026 at 06:08:05 UTC from IEEE Xplore. Restrictions apply.

[16] Ahmed, M. I. B., Alabdulkarem, H., Alomair, F., Aldossary, D., Alahmari, M., Alhumaidan, M., Alrassan, S., Rahman, A., Youldash, M., & Zaman, G. (2023). A Deep-Learning Approach to Driver Drowsiness Detection. Safety, 9(3), 65. https://doi.org/10.3390/safety9030065

[17]Delwar, T. S., Singh, M., Mukhopadhyay, S., Kumar, A., Parashar, D., Lee, Y., Rahman, M. H., Sejan, M. A. S., & Ryu, J. Y. (2025). AI- and Deep Learning-Powered Driver Drowsiness Detection Method Using Facial Analysis. Applied Sciences, 15(3), 1102. https://doi.org/10.3390/app15031102

[18] Jahan, I., Uddin, K. M. A., Murad, S. A., Miah, M. S. U., Khan, T. Z., Masud, M., Aljahdali, S., & Bairagi, A. K. (2023). 4D: A Real-Time Driver Drowsiness Detector using Deep Learning Electronics, 12(1),235. https://doi.org/10.3390/electronics12010235

[19] Schwarz, C., Gaspar, J., & Yousefian, R. (2023). Multi-sensor driver monitoring for drowsiness prediction. Traffic injury prevention, 24(sup1),S100–S104. https://doi.org/10.1080/15389588.2023.2164839

[20]Bajaj, J. S., Kumar, N., Kaushal, R. K., Gururaj, H. L., Flammini, F., & Natarajan, R. (2023). System and Method for Driver Drowsiness Detection Using Behavioural and Sensor-Based Physiological Measures. Sensors, 23(3), 1292. https://doi.org/10.3390/s23031292

Authorized licensed use limited to: COCHIN UNIVERSITY OF SCIENCE AND TECHNOLOGY. Downloaded on October 05,2026 at 06:08:05 UTC from IEEE Xplore. Restrictions apply.