

8/10/26

1. Randbetween(): returns a random number
blw the numbers we specify

Syntax: =RANDBETWEEN (bottom, top)

Ex: =RANDBETWEEN ("01-09-2026"; "30-11-2026")

2. workday(): returns the serial number of the
date before or after a specified number
of workdays

Syntax: =workdays (start-date, days, [holidays])

Ex: =workday (08-10-2026, 15, 13-10-2026,
20-10-2026)

o/p: 02-11-2026

By default Saturday Sunday is excluded

3 `workday.INTL()`: similar to `workday`, but allows us to choose which days are weekends
Syntax: `=workday.INTL (start-date, days [weekend], [holiday])`

Ex: `=workday.INTL (8-10-2026, 15, 11, 13-10-2026, 20-10-2026)`

o/p: 28-10-2026

(11) means here Sunday only

4 `Networkdays()`: calculate the number of working days b/w 2 dates, excluding Saturday and Sunday

Syntax: `=Networkdays (start-date, end-date, [holiday])`

Ex: `=Networkdays (01-06-2026, 08-10-2026, 09:10:13)`

o/p: 92

5 `Networkdays.INTL()`: calculate the number of working days b/w 2 dates, but allows us to specify which days are weekends

Syntax: `=Networkdays.INTL (start-date, end-date, [weekend], [holidays])`

Ex: `=Networkdays.INTL (01-06-2026, 08-10-2026, 14, 09:10:13)`

here (14) means only wednesday
o/p : 107

Information functions

1 **ISTEXT ()** : checks whether a value is text
Syntax : = ISTEXT (value)
Ex : = ISTEXT ("Sahana")
o/p : TRUE

2 **ISNONTEXT ()** : checks whether a value is not text
Syntax : = ISNONTEXT (value)
Ex : = ISNONTEXT (100)
o/p : TRUE

3 **ISNUMBER ()** : checks whether a value is a number
Syntax : = ISNUMBER (value)
Ex : = ISNUMBER (200)
o/p : True

4 **ISEVEN()**: checks whether a number is even

Syntax: =ISEVEN (Number)

Ex: =ISEVEN (23)

O/p: FALSE

5 **ISODD()**: checks whether a number is odd

Syntax: =ISODD (number)

Ex: =ISODD (15)

O/p: True

6 **ISFORMULA()**: checks whether a cell contains a formula

Syntax: =ISFORMULA (reference)

Ex: =ISFORMULA (A2)

O/p: TRUE (if A2 has formula)

7 **ISLOGICAL()**: checks whether a value is TRUE or FALSE

Syntax: =ISLOGICAL (value)

Ex: =ISLOGICAL (TRUE)

O/p: TRUE

If in case in ISODD and ISEVEN the reference column is string, if the value is error to display some message then use IFERROR

IFERROR(): Returns value if error if expression is an error and the value of the expression itself otherwise.

Syntax: =IFERROR (value, value-if error)

Ex: =IFERROR (ISODD (A7), "Invalid Input")

O/p: Invalid Input