WINDOW FUNCTION

A window function performs a calculation accross a set of related row while keeping each individual row in the result

OVER () clause

The OVER () clause tells SQL how to apply a window function to rows

Scanned with OKEN Scanner

DATE: PAGE:

```
SELECT ename, salary
    RANK() OVER (ORDER BY Salary DESC)
AS salary_rank
FROM employee;
```

OVER() - defines the window for the calculation

Types of ranking function

1. RANK()
2. DENSE_RANK()
3. ROW_NUMBER()

1. RANK(): assigs a rank to each row, If two employee have the same salary, they receive the same rank, and the ~~nex~~ next rank is skipped

```
Ex: SELECT ename, salary
      RANK() over (ORDER BY salary DESC)
    AS salary_rank
    FROM employee;
```

DATE: PAGE:

o/p: Employee | Salary | Salary_Rank (GAP)

Arun	50000	1
Priya	40000	2
Rahul	40000	2
Divya	30000	4

2 DENSE_RANK(): This also gives the same rank to employees with equal salaries, but it does not skip the next rank

Ex: SELECT ename, salary
DENSE_RANK() OVER (ORDER BY salary DESC)
AS salary_rank
FROM employee;

o/p: Employee | Salary | Salary_rank (NO GAP)

Arun	50000	1
Priya	40000	2
Rahul	40000	2
Divya	30000	3

3 ROW_NUMBER(): assigns a unique no to every row, even when salaries are equal

Scanned with OKEN Scanner

DATE: PAGE:

Ex: SELECT ename, salary
ROW_NUMBER() OVER (ORDER BY salary DESC, ename)
AS row_num
FROM employee;

Here, ename is an additional sorting column to make the order of employees with equal salaries predictable

O/p:

Employee	Salary	Row_Num
Arun	50000	1
Priya	40000	2
Rahul	40000	3
Divya	50000	4

Functions	Same salary gets same rank?	Skips ranks?
RANK()	Yes	Yes
DENSE_RANK()	Yes	No
ROW_NUMBER()	No	No

Scanned with OKEN Scanner

DATE: PAGE:

PARTITION BY: This divides rows into groups and perform a window calculation separately within each group. unlike GROUP BY, it keeps all original row

Ex: SELECT ename, department, salary,
RANK() OVER (PARTITON BY department
ORDER BY salary DESC)
AS salary-rank
FROM employee;

Imagine the employee table has a department column

Employee	Department	Salary
Arun	IT	50000
Priya	IT	40000
Rahul	HR	45000
Divya	HR	30000
Kiran	Sales	35000

Suppose we want to rank employees within each department, rather than accross the entire company

Scanned with OKEN Scanner

DATE: PAGE:

o/p:

Employee	Department	Salary	Rank
Arun	IT	50000	1
Priya	IT	40000	2
Rahul	HR	45000	1
Divya	HR	30000	2
Kiran	Sales	35000	1

Rahul receives rank 1 even though arun earns more why? Because PARTITION BY department starts a separate ranking for each department without PARTITION BY, all employees would be ranked together

GROUP BY	PARTITION BY
• Combines rows into groups	• Divides rows into calculation groups
• Usually returns one row per group when used with aggregate functions	• Keeps individual rows
• Commonly used with aggregate functions	• used with window function

Scanned with OKEN Scanner

DATE: PAGE:

GROUP BY: This resturs one row per department

PARTITION BY: This returns every employee, along with their department

Scanned with OKEN Scanner