24/10/26 DATE: PAGE:

3. HLOOKUP

Looks for a value in the top row of a table or array of values and returns the values in the same column from a row you specify.
It searches for a value in the first row of a table.

Syntax : =HLOOKUP (lookup-value, table-array, row-index-num , [range-lookup])

	A	B	C	D
11 Ex:	emp code	1	3	8
12	emp name	JPKumar	Priya Agarwal	Manisha
13	city	Mumbai	0	Kolkata
14	Basic	10000	11250	6275

=HLOOKUP (B$11 , B1 : U7 , MATCH ($A12 , A1 : A7, 0), 0)

B$11 = (1) searches for emp id in the first row of the selected range
B1 : U7 = selects the whole horizontal table
$A12 = contains emp name headings
$A1 : A7 = it include all the heading columns

Disadvantage

- It searches only in the first row of the selected table

Scanned with OKEN Scanner

DATE: PAGE:

- It returns values only from rows below the lookup row
- Inserting or deleting row can affect the row index number
- It returns only the first matching results when duplicate exist

4. XLOOKUP

Used to search for a value in one row or column and returns the corresponding value from another row or column

It can search both vertically and horizontally, and it can return results from either the left or right side of the lookup column.

Syntax : =XLOOKUP(lookup_value, lookup_array, return_array, [if_not_found], [match_mode], [search_mode])

lookup_array: lookup value's whole row or column

return_array : The row or column containing the result we want

if_not_found : optional message or value if no match is found.

match_mode : specifies exact match or other matching

DATE: PAGE:

options

search_mode : specifies the direction or method of searching

Ex : =XLOOKUP ($J2 , A2 : A21, B2 : $D $21 , "NP", 0)

A2 : A21 = J2's entier row

B2 : D21 = this column is selected because these 3 column ans is required as result.

5. INDEX MATCH

It is a combination of two excel functions used to find and return a specific value from a dataset.

Index returns a value from a specified position in a range.

Match finds the position of a particular value in a row or column.

Together, they help us find information such as employee name, cities & salaries using emp ID

Syntax : =INDEX (array , row_num , [column_num])

=MATCH (lookup_value , lookup_array , match_type)

Scanned with OKEN Scanner

DATE: PAGE:

Ex: = INDEX (A1 : $G : $21 , MATCH ($J7, A1 : A21, 0), MATCH (K$5, A1 : G1 , 0))

1st match is used to find row_num
2nd match is used to find column_num.

emp code	emp name	city	department
1	JP Kumar	Mumbai	training
4	R vasu	chennai	R&D
9	Arjun Jain	Mumbai	training

Scanned with OKEN Scanner