DATE: PAGE:

Ex: =TIME (18, 51, 44)

O/P: 18:51:44

To print only time from now()

Syntax Ex: =NOW - TODAY()

O/P: 18:51:44

8/10/26

1. RANDBETWEEN() : returns a random number b/w the numbers we specify.

Syntax : =RANDBETWEEN (bottom, top)

Ex: =RANDBETWEEN ("01-09-2026", "30-11-2026")

2. WORKDAY() : returns the serial number of the date before or after a specified number of workdays.

Syntax: =WORKDAY(start_date, days, [holidays])

Ex: =WORKDAY (08-10-2026, 15, 13-10-2026, 20-10-2026)

O/P: 02-11-2026

By default saturday sunday is excluded

3. WORKDAY.INTL() : similar to WORKDAY, but allows us to choose which days are weekends

DATE: PAGE:

Syntax : =workday.INTL (start_date, days, [weekend], [holiday])

Ex : =workday.INTL (8-10-2026, 15, 11, 13-10-2026, 20-10-2026)

O/p : 28-10-2026

(11) means here sunday only

4. Networkdays () : calculate the number of working days b/w 2 dates, excluding saturday and sunday

Syntax : =Networkdays (start_date, end_date, [holiday])

Ex : =Networkdays (01-06-2026, 08-10-2026, $10:$13)

O/p : 92

5. Networkdays.INTL() : calculate the number of working days b/w 2 dates, but allows us to specify which days are weekends.

Syntax : =Networkdays.INTL (start_date, end_date, [weekend], [holidays])

Ex : =Networkdays.INTL (01-06-2026, 08-10-2026, 14, $10:$13)

here (14) means only wednesday

O/p : 104

Scanned with OKEN Scanner

DATE: PAGE:

Information functions

1. ISTEXT() : Checks whether a value is text

Syntax : =ISTEXT(value)

Ex: =ISTEXT("sanjana")

O/p: TRUE

2. ISNONTEXT() : checks whether a value is not text.

Syntax : =ISNONTEXT(value)

Ex : =ISNONTEXT(100)

O/p : TRUE

3. ISNUMBER() : checks whether a value is a number

syntax : =ISNUMBER(value)

Ex : =ISNUMBER(200)

O/p: TRUE

4. ISEVEN() : checks whether a number is even

syntax : =ISEVEN(number)

Ex : =ISEVEN(23)

O/p : FALSE

5. ISODD() : checks whether a number is odd

Scanned with OKEN Scanner

DATE: PAGE:

syntax : =ISODD (number)
Ex : =ISODD (15)
o/p : TRUE

6. ISFORMULA () : checks whether a cell contains a formula
syntax : =ISFORMULA (reference)
Ex : =ISFORMULA (A2)
o/p : TRUE (if A2 has formula)

7. ISLOGICAL () : checks whether a value is TRUE or FALSE
syntax : =ISLOGICAL (value)
Ex : =ISLOGICAL (TRUE)
o/p : TRUE

If in case in ~~iso~~ o ISODD and ISEVEN the reference column is string, if the value is error to display some message there use IFERROR()

IFERROR() : Returns value if error if expression is an error and the value of the expression itself otherwise
syntax : =IFERROR (value, value_if_error)
Ex : =IFERROR (ISODD("A"), "Invalid Input")
o/p : Invalid Input

Scanned with OKEN Scanner