apsara

Date: __/__/____

SQL Functions.

Numeric	character	String	Date
MOD()	LENGTH()	TRIM()	CURRENT_DATE()
POWER()	ASCII()		SYSDATE()
ABS()	UPPER()	Aggregate	NOW()
SQRT()	LOWER()	MAX()	YEAR()
FLOOR()	SUBSTR()	MIN()	
CEIL()	REPLACE()	SUM()	Conversion / Date
ROUND()	INSTR()	AVG()	DATE_FORMAT()
	REVERSE()	COUNT()	DATE_ADD()
		COUNT(DISTINCT)	DATE_SUB()

Numeric functions.

→ **MOD()** : returns the remainder after division

```
SELECT sal, MOD(sal, 3) FROM emp;
```

→ **POWER()** : returns a number raised to a specified power

```
SELECT POWER(2,4);
```

→ **ABS()** : Returns the absolute value of a number, removing the negative sign

```
SELECT ABS(-15);
```

Page No.: _____

Scanned with OKEN Scanner

apsara

Date: —·—·——

→ SQRT() : Returns the square root of a no.

SELECT SQRT (16);

→ FLOOR () : ~~Returns the largest integer~~

Rounds a number down to the nearest integer

SELECT FLOOR (number);

→ CEIL () : Rounds a number up to the nearest integer

SELECT CEIL (number);

→ ROUND() : Rounds a number to the nearest integer when no decimal position is specified

SELECT ROUND (5.6); o/p : 6

* CHARACTER / string functions

→ LENGTH () : returns the no. of characters in a string

SELECT ename, LENGTH (ename) FROM emp;

→ ASCII () : returns the ASCII value of the first characters

SELECT ASCII ('Ammu');

Page No.: ...

Scanned with OKEN Scanner

Since the first character is A :
ASCII ('A') = 65

→ UPPER () : converts text into uppercase
SELECT UPPER ('ashwin');

→ LOWER() : converts text into lowercase
SELECT LOWER ('ASHWIN')

→ SUBSTR() : Extracts a part of a string.
Ex: SELECT ename , SUBSTR (ename , 2, 3) FROM emp;
Sy: SUBSTR (string, starting_position, num_of_chars)

→ REPLACE (): replace one characters or piece of text with another
SELECT REPLACE ('Ashwini' , 'S' , 'a')

→ REVERSE () : reverses the characters in a string
SELECT REVERSE ('TOM Jerry') ;
O/P : yrreJ MOT

→ INSTR () : returns the position of a substring char inside a string.
SELECT INSTR ('TOM JERRY' , 'J');
O/P: 5

Scanned with OKEN Scanner

apsara

Date: __/__/____

AGGREGATE FUNCTIONS

This function performs calculations on multiple row and returns a single results.

→ MAX() : finds the highest value

```
SELECT max(sal) FROM emp;
```

→ MIN() : finds the smallest salary

```
SELECT MIN(sal) FROM emp;
```

→ SUM() : calculates the total of numeric values

```
SELECT SUM(sal) FROM emp;
```

calculates total salary.

→ AVG() : calculates the average value

```
SELECT AVG(sal) FROM emp;
```

→ COUNT() : counts the no of row values

```
SELECT COUNT(*) FROM emp;
```

counts the total no. of rows in emp

→ COUNT(DISTINCT) : counts only unique values

```
SELECT COUNT(DISTINCT deptno) FROM emp;
```

counts how many different departments exists

Scanned with OKEN Scanner

apsara

Date: __/__/____

CONVERSION / DATE FUNCTIONS

→ **Date_format()** : converts a date into specified format.

```
SELECT hiredate,
DATE_FORMAT (hiredate, '%m-%d-%Y')
FROM emp;
```

→ **DATE_ADD()** : adds a specified amt of time to a date

```
SELECT DATE-ADD ( current_date(),
INTERVAL 100 DAY);
```

→ **DATE_SUB()** : ~~adds~~ subtracts a specified amt of time from a date.

```
SELECT DATE_SUB (CURDATE(), INTERVAL 100 DAY);
```

→ **STR_TO_DATE()** : converts a text into a date according to specified format

```
SELECT STR_TO_DATE ('30-04-2026', '%d-%m-%Y');
```

→

Page No.: _____

Scanned with OKEN Scanner

apsara

Date: —/—/——

DATE FUNCTION

→ CURRENT_DATE() : returns current date

```
SELECT CURRENT_DATE();
```

→ SYSDATE() : returns the current date and time according to the database system's clock.

```
SELECT SYSDATE();
```

→ NOW() : returns current date & time

```
SELECT NOW();
```

→ YEAR() : Extracts the year from a date

```
SELECT YEAR (NOW());
```


Scanned with OKEN Scanner