

Example Intent Map (Synthetic)

Author: Lakshmi Sagar S P

Data Safety Disclaimer

This is a fully synthetic example created solely to demonstrate the Intent Mapping for Risk Detection framework.

- *No real customer data*
 - *No real transactions*
 - *No real thresholds*
 - *No proprietary systems*
-

Case Context (Abstracted)

- ***Case Type:*** *Suspicious Account Behaviour Review*
 - ***Review Trigger:*** *Manual review based on behavioural sequence*
 - ***Analysis Period:*** *~18 months (synthetic timeline)*
 - ***Overall Risk Assessment:*** *High*
-

Behavioural Flags Observed

Flag	Description
<i>Dormancy Break</i>	<i>Account becomes active after an extended period of inactivity</i>
<i>Burst Credits</i>	<i>Multiple inbound credits in a short window</i>
<i>Self FIFO</i>	<i>Rapid credit → debit cycles</i>
<i>Unknown P2P Spike</i>	<i>Sudden increase in unfamiliar counterparties</i>
<i>Device Change</i>	<i>Change in access environment</i>
<i>Inactivity Patch</i>	<i>Deliberate low activity after execution</i>

Intent Map (Phase-wise)

Phase	Time Window	Behavioural Flags	Summary	Inferred Intent	Risk Assessment	Likely Next Action
--------------	--------------------	--------------------------	----------------	------------------------	------------------------	---------------------------

<i>Phase 1</i>	<i>Month 0–6</i>	<i>None</i>	<i>Account opened and remained inactive</i>	<i>Staging / Account Preparation</i>	<i>Low</i>	<i>Reactivation after a cooling period</i>
<i>Phase 2</i>	<i>Month 7–8</i>	<i>DormancyBreak, Self FIFO</i>	<i>Low-value self-loops following inactivity</i>	<i>Testing detection boundaries</i>	<i>Medium</i>	<i>Scale testing or pause</i>
<i>Phase 3</i>	<i>Month 9–11</i>	<i>Inactivity Patch</i>	<i>Minimal activity to preserve the account</i>	<i>Cooling-off / Risk reset</i>	<i>Low</i>	<i>Re-entry with external parties</i>
<i>Phase 4</i>	<i>Month 12–14</i>	<i>Device Change, Unknown P2P Spike</i>	<i>Small inflows from unfamiliar senders</i>	<i>Pilot mule operations</i>	<i>High</i>	<i>Expand counterparties</i>
<i>Phase 5</i>	<i>Month 15</i>	<i>Inactivity Patch</i>	<i>Reduced activity post-pilot</i>	<i>Evasion / Wait mode</i>	<i>Medium</i>	<i>Burst execution</i>
<i>Phase 6</i>	<i>Month 16</i>	<i>Burst Credits, Self FIFO</i>	<i>Consolidation of multiple inflows</i>	<i>Execution / Fund Aggregation</i>	<i>Very High</i>	<i>Cash-out or abandonment</i>
<i>Phase 7</i>	<i>Month 17–18</i>	<i>Inactivity Patch</i>	<i>Minimal residual activity</i>	<i>Post-execution dormancy</i>	<i>Medium</i>	<i>Possible reuse</i>

Detection Opportunity

- **Early signal:** Dormancy Break + Self FIFO (Phase 2)
- **Stronger escalation:** Device Change + Unknown P2P Spike (Phase 4)
- **Late-stage detection:** Burst Credits + FIFO (Phase 6)

Primary gap identified: Lack of behavioural sequencing across inactivity, testing, and execution phases.

Rule / Hypothesis Output

Detection Hypothesis: If an account shows a **dormancy break followed by repeated self-routing**, and later introduce **unknown counterparties after a cooling period**, it may indicate **structured mule preparation**.

Rule Definition (Abstracted)

- **Objective:** Detect staged mule behaviour before execution
- **Applicable Behaviour / Persona:** Prepared mule / aggregator
- **Core Logic:**
 - Dormancy Break
 - Self FIFO
 - Subsequent Unknown P2P Spike

- ***Expected Detection Behaviour:*** *Early escalation prior to burst execution*
 - ***False Positive Risk:*** *Medium (requires sequencing validation)*
-