3) Ping:- ensure a stable and reliable internet connection is crucial for seamless navigation and efficient communication in the world of linux.
"Ping" command is a powerful tool that allows users to check the status of their internet connection and diagnose, network-related issues.

Syntax: ping [options] host_or_IP_address.

example: ping www.google.com

4) traceroute:- used to trace the path network packets take from the source to a destination host or IP address. It is one of the most widely used tool for network troubleshooting and diagnostics in linux.

Syntax: traceroute -g 192.168.43.45 google.com.

example: traceroute www.google.com

5) whois:- command-line utility used in linux systems to retrieve information about domain names, IP address, and network devices registered with the internet corporation for assigned names and numbers. The data received by whois consists of the name and contact information of the domain or IP address owner.

Syntax: whois [-h Hostname] [.][!][*] {name [....]

example: whois example.com

2/1/25

EXPERIMENT NO :: 2

System calls used for network programming

Aim: System calls used for network programming
To familiarize and understand, the use and functioning of system calls used for network programming in Linux.

1) fork ()
2) EXECV ()

Theory

1) fork () :- The fork system call allows the creation of a new process. when a process calls the fork, it duplicates itself, resulting in two processes running at the same time. The new process that is created is called child process. copy of the parent process. It has some features such as parallel processing, multitasking etc.

2) EXECV () :- It replaces the currently executing program with a newly loaded program image. This occurs within one process, the process id is unchanged. The argument strings should be copied into the new process as the array. The process file table & current working directory.

int execv (const char* file, char* const argv[]).