WWW.IJRPR.COM

International Journal of Research Publication and Reviews

Journal homepage: www.ijrpr.com ISSN 2582-7421

AI POWERED CYBER DECEPTION:ENHANCING DEFENSIVE STRATEGIES WITH ADAPTIVE HONEYPOTS AND DECOYS

Likhitha Ponnada

IT Department,GMRIT,Rajam

ABSTRACT:

The growing complexity of cyber-attacks has outpaced traditional security systems such as firewalls and intrusion detection tools. Attackers increasingly use advanced, intelligent, and deceptive techniques to breach networks undetected. This paper introduces an *AI-based adaptive cyber deception framework* that utilizes honeypots, honeytokens, and simulated user environments to detect and mislead attackers. The proposed system employs machine learning to analyze attacker behavior and automatically adjust deceptive responses in real time. This dynamic adaptation strengthens network defense and produces valuable threat intelligence. Experimental observations indicate that AI-driven deception provides improved flexibility, detection accuracy, and resilience across cloud platforms, IoT systems, and enterprise networks. Overall, the integration of AI with cyber deception provides a proactive, intelligent, and scalable approach for modern digital defense.

Keywords*:* Cyber deception, Artificial Intelligence (AI), Adaptive traps, Cybersecurity, Honeypots, Decoys

1.INTRODUCTION:

The dependency on digital technology across sectors such as healthcare, finance, and defense has made cybersecurity a critica1 concern. However, attackers are continuously evolving, using sophisticated techniques that easily bypass traditional detection systems. Standard defenses like firewalls and signature-based intrusion systems struggle to identify these advanced,stealthythreats.

To overcome these challenges, *cyber deception* has emerged as a novel approach where fake systems, files, and credentials are intentionally deployed to lure and observe attackers. *Honeypots* and *decoys* act as imitation assets that divert attackers away from real infrastructure, allowing defenders to study intrusion patterns and collect intelligence.

Conventional honeypots, however, have fixed configurations and limited adaptability, making them predictable over time. The introduction of *Artificial Intelligence (AI)* and *Machine Learning (ML)* provides an opportunity to transform deception systems into adaptive, evolving environments. AI can analyze attacker interactions, recognize behavioral patterns, and automatically modify decoys to appear authentic and unpredictable. This continuous adaptation increases engagement time, improves threat visibility, and strengthens the organization's defensive posture.

2. LITERATURE SURVEY:

[1]Narayana Gaddam, "AI-enhanced honeypots for advanced cyber deception strategies". QIT Press - International Journal of Cyber Security Research and Development (QITP-IJCSRD), 5(1), 9–19,2025

[2]Bekir Tolga Tutuncuoglu , "Silent Shields: AI-Powered Behavioral Defense Against Real-Time Cyber Threats in Web Hosting Environments",IEEE Artificial Intelligence Journel, 1-20,2025

[3]Shihab Ahmed, ABM Mohaimenur Rahman; Md Morshed Alam; Md Sajidul Islam Sajid,
"SPADE:Enhancing Adaptive Cyber Deception Strategies with Generative AI and StructuredPrompt Engineering'', IEEE Cybersecurity and DeepLearning Journel, 2025

[4]Adewunmi Ebunoluwa, A James,"AI-Powered Honeypots: Enhancing Deception Technologies for Cyber Defense" Research Gate Cyber Threats Journel,1-5,2025

[5]Quanyan Zhu , "Game Theory for Cyber Deception",NewYork University Brooklyn, April 2–3, 2019

[6]Tahani Gazdar, Lara Murad, Safana Al-Jahdali, Fai Zwawi, Reman Mandili (2025).TangleNet: An Advanced Cyber Deception Model Based on Reinforcement Learning.Journal: Romanian Journal of Information Technology and Automatic Control, 35(1), pp. 23–36.

[7]Ahmed H. Anwar, Charles A. Kamhoua, Nandi O. Leslie, Christopher Kiekintveld (2022).Honeypot Allocation for Cyber Deception Under Uncertainty.Journal: IEEE Transactions on Network and Service Management, 19(3).

[8]Md Abu Sayed, Ahmed Hemida, Christopher Kiekintveld, Charles Kamhoua (2024).Strategic Honeypot Allocation in Dynamic Networks: A Game-Theoretic Approach.Conference: GameSec 2023 (published 2024).

[9]Redeer Avdal Saleh, Omar Sedqi Kareem (2025).Artificial Intelligence for Deception Detection: A Multimodal Review….Journal: Engineering and Technology Journal, 10(4).

[10]Vikram Kulothungan, Deepti Gupta, Laxima Niure Kandel (2025).Democratizing Cybercrime: Risks and Countermeasures of AI-Enabled Attacks.Conference: WF-IoT 2025.
[11]Matthew Walsh, Clarence Worrell, Thomas Scanlon (2024).Toward the Use of Artificial Intelligence (AI) for Advanced Persistent Threat Detection.Publisher: Carnegie Mellon Software Engineering Institute.
[12]Charles Liscomb (2021). Effective Defensive Cyber Deception.Type: Master's Capstone, Utica College.
[13]Anıl Sezgin, Aytuğ Boyacı (2025). DecoyPot: A Large Language Model-Driven Web API Honeypot….Journal: Computers & Security, Vol. 154, Article 104458.
[14]Arnolnt Spyros, Ilias Koritsas, Angelos Papoutsis, et al. (2025).AI-Based Holistic Framework for Cyber Threat Intelligence Management.journal: IEEE Access, Vol. 13, pp. 20820–20846.
[15]Zillay Huma, Anas Raheem (2024).Automated Cyber Deception: Intelligent Honeypots and Moving-Target Defenses.Journal: International Journal of Cybersecurity Intelligence & Cybercrime (IJCIC).

3. METHODOLOGY:

The proposed system establishes multiple layers of deception throughout the network, including fake servers, documents, and login credentials. These decoys simulate genuine targets, capturing attacker activities such as commands, timing, and access patterns. The collected data is analyzed to extract significant behavioral indicators and anomaly patterns.
Machine learning algorithms then process these indicators to identify malicious intent and automatically adjust the deceptive environment. By continuously updating and regenerating traps, the system remains unpredictable and effective in misdirecting attackers. The threat intelligence gathered from these interactions supports proactive defense planning and improved response strategies.

Algorithms:

1.Q-Learning
A feedback-based algorithm that allows the deception system to learn optimal defensive responses by evaluating the outcomes of past attacker interactions. Over time, it refines its strategy to deploy traps that maximize security efficiency.





Fig 1: Flowchat of Q-Learning Algorithm

2.Generative Adversarial Networks (GANs)

GANs use a pair of neural networks—a generator and a discriminator—to produce realistic synthetic data or system responses. In this context, GANs create convincing fake files, network traffic, and user behaviors to deceive intruders.



3. Deep Q-Network (DQN)

Combines deep learning with reinforcement principles to manage complex deception policies. It enables real-time adaptability in dynamic environments, ensuring accurate and context-aware responses against unpredictable attacks.




Fig 3: Architecture of Deep Q Networks

1) High-level architecture (overview)

Deception Layer:

Includes simulated assets such as honeypots and honey files, which mimic legitimate services to attract attackers.

Data Collection & Logging:

All attacker actions are logged and analyzed using monitoring tools to track intrusion patterns.

Feature Extraction:

Identifies statistical and behavioral features—like command frequency, access time, and IP reputation—to detect anomalies.

AI/ML Decision Engine:

The core module processes extracted data to classify sessions as benign or malicious and dynamically generate new decoys.

Response and Orchestration:

When malicious activity is detected, the system deploys customized decoys, isolates attacker IPs, and alerts security teams.

Threat Intelligence Feedback:

The results are used to retrain the models, continuously improving detection accuracy and deception realism.

3) Deployment & scaling notes

- *Containerize* each component; use Docker + docker-compose for local lab. Use Kubernetes for scale.
- *Logging*: push raw session logs to Kafka → ELK stack (Elasticsearch + Kibana) for indexing & visualization.
- *Model Serving*: use lightweight model server (FastAPI + joblib) or MLFlow for versioning. Keep inference latency low.
- *Firewalls / Response*: don't auto-block without analyst verification. Prefer to add suspicious IPs to watchlists and throttle.
- *Data retention & privacy*: obey laws/campus policies; store only what you




Fig 4:Flowchat of Cyber Deception and its working

2) Key design choices & rationale

1.Low interaction honeypots for scale (listen & log) + *high-interaction* on-demand for deep analysis.
2.*Privacy & legal*: store only metadata + consented lab data; do not intercept private traffic beyond scenario.
3.*ML choice*: start with an interpretable model (RandomForest or LightGBM) for easy feature importance; later upgrade to sequence models for command sequences.
4.*Decoy realism*: auto-generate realistic decoy files with embedded honeytokens (track via callbacks), so when an attacker opens them you get callback telemetry.




Fig 5:Working of Honeypots and Decoys

Conclusion:

In today's rapidly evolving cyber threat landscape, traditional security measures such as firewalls, antivirus software, and intrusion detection systems are often insufficient to fully protect organizations from sophisticated attacks. AI-powered cyber deception emerges as a vital approach to enhance cy-

bersecurity by proactively misleading, detecting, and analyzing potential threats. By integrating AI with deceptive techniques such as honeypots, decoys, and fake assets, organizations can create dynamic and adaptive defense mechanisms that not only protect critical systems but also gather valuable intelligence on attacker behavior.

As cyber threats grow in sophistication, static security mechanisms are no longer sufficient to ensure digital protection. Integrating *Artificial Intelligence with cyber deception* introduces a proactive defense layer that detects, delays, and misguides attackers while collecting intelligence for better decision-making.

The proposed adaptive deception model dynamically evolves based on attacker behavior, providing real-time insights and enhancing overall network resilience. AI-driven deception not only reduces the success rate of cyberattacks but also transforms security systems from reactive to predictive and intelligent. This approach paves the way for next-generation cybersecurity strategies that emphasize adaptability, automation, and continuous learning.

REFERENCES:

[1]Narayana Gaddam, "AI-enhanced honeypots for advanced cyber deception strategies". QIT Press - International Journal of Cyber Security Research and Development (QITP-IJCSRD), 5(1), 9–19,2025

[2]Bekir Tolga Tutuncuoglu , "Silent Shields: AI-Powered Behavioral Defense Against Real-Time Cyber Threats in Web Hosting Environments",IEEE Artificial Intelligence Journel, 1-20,2025

[3]Shihab Ahmed, ABM Mohaimenur Rahman; Md Morshed Alam; Md Sajidul Islam Sajid,
"SPADE:Enhancing Adaptive Cyber Deception Strategies with Generative AI and StructuredPrompt Engineering'', IEEE Cybersecurity and DeepLearning Journel, 2025

[4]Adewunmi Ebunoluwa, A James,"AI-Powered Honeypots: Enhancing Deception Technologies for Cyber Defense" Research Gate Cyber Threats Journel,1-5,2025

[5]Quanyan Zhu , "Game Theory for Cyber Deception",NewYork University Brooklyn, April 2–3, 2019