

Practice-2

Machine Learning Techniques

Karthik Thiagarajan

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \quad \cdots \quad \alpha_n]^T$.

Q-11


- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \quad \cdots \quad \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \quad 1 \quad -1 \quad -1]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^0 = [0 \ 0]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^0 = [0 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	
$(0, -1)$	1	
$(0, 1)$	-1	
$(-1, -1)$	-1	

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^0 = [0 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	1

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^0 = [0 \ 0]^T$$


\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	1

$$\mathbf{w}^1 = \mathbf{w}^0 + \mathbf{x}_i y_i$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^0 = [0 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	1

$$\mathbf{w}^1 = \mathbf{w}^0 + \mathbf{x}_3 y_3$$

$$= \begin{bmatrix} 0 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix}(-1)$$


$$= \begin{bmatrix} 0 \\ -1 \end{bmatrix}$$

$$\mathbf{w}^1 = [0 \ -1]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^0 = [0 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	1

$$\mathbf{w}^1 = \mathbf{w}^0 + \mathbf{x}_3 y_3$$

$$= \begin{bmatrix} 0 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix}(-1)$$


$$= \begin{bmatrix} 0 \\ -1 \end{bmatrix}$$

$$\mathbf{w}^1 = [0 \ -1]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^1 = [0 \ -1]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	
$(0, -1)$	1	
$(0, 1)$	-1	
$(-1, -1)$	-1	

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^1 = [0 \ -1]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	-1
$(-1, -1)$	-1	1

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^1 = [0 \ -1]^T$$

\mathbf{x}	y	\hat{y}
(1, 0)	1	1
(0, -1)	1	1
(0, 1)	-1	-1
(-1, -1)	-1	1

$$\mathbf{w}^2 = \mathbf{w}^1 + \mathbf{x}_4 y_4$$

$$= \begin{bmatrix} 0 \\ -1 \end{bmatrix} + \begin{bmatrix} -1 \\ -1 \end{bmatrix} (-1)$$


$$= \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

$$\mathbf{w}^2 = [1 \ 0]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^2 = [1 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	
$(0, -1)$	1	
$(0, 1)$	-1	
$(-1, -1)$	-1	

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^2 = [1 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	-1

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^2 = [1 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	-1

$$\mathbf{w}^3 = \mathbf{w}^2 + \mathbf{x}_3 y_3$$

$$= \begin{bmatrix} 1 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix}(-1)$$


$$= \begin{bmatrix} 1 \\ -1 \end{bmatrix}$$

$$\mathbf{w}^3 = [1 \ -1]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^3 = [1 \ -1]^T$$

\mathbf{x}	y	\hat{y}
(1, 0)	1	
(0, -1)	1	
(0, 1)	-1	
(-1, -1)	-1	

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^3 = [1 \ -1]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	-1
$(-1, -1)$	-1	1

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^3 = [1 \ -1]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	-1
$(-1, -1)$	-1	1

$$\mathbf{w}^4 = \mathbf{w}^3 + \mathbf{x}_4 y_4$$

$$= \begin{bmatrix} 1 \\ -1 \end{bmatrix} + \begin{bmatrix} -1 \\ -1 \end{bmatrix}(-1)$$


$$= \begin{bmatrix} 2 \\ 0 \end{bmatrix}$$

$$\mathbf{w}^4 = [2 \ 0]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^4 = [2 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	
$(0, -1)$	1	
$(0, 1)$	-1	
$(-1, -1)$	-1	

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$




$$\mathbf{w}^4 = [2 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	-1

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^4 = [2 \ 0]^T$$

\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	1
$(-1, -1)$	-1	-1

$$\mathbf{w}^5 = \mathbf{w}^4 + \mathbf{x}_3 y_3$$

$$= \begin{bmatrix} 2 \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix}(-1)$$


$$= \begin{bmatrix} 2 \\ -1 \end{bmatrix}$$

$$\mathbf{w}^5 = [2 \ -1]^T$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$



$$\mathbf{w}^5 = [2 \ -1]^T$$


\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	-1
$(-1, -1)$	-1	-1

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$

$$\mathbf{w}^* = [2 \ -1]^T$$




\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	-1
$(-1, -1)$	-1	-1

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$

$$\mathbf{w}^* = [2 \ -1]^T$$



\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	-1
$(-1, -1)$	-1	-1


$$\begin{aligned} \mathbf{w}^* &= 0 \cdot x_1 y_1 + 0 \cdot x_2 y_2 + 3 \cdot \mathbf{x}_3 y_3 + 2 \cdot \mathbf{x}_4 y_4 \\ &= 3 \cdot \begin{bmatrix} 0 \\ 1 \end{bmatrix} \cdot (-1) + 2 \cdot \begin{bmatrix} -1 \\ -1 \end{bmatrix} \cdot (-1) \\ &= \begin{bmatrix} 2 \\ -1 \end{bmatrix} \end{aligned}$$

Q-11

- Train a perceptron
- Cycle through the points from left to right
- If $\mathbf{w}^* = \sum_{i=1}^n \alpha_i \mathbf{x}_i y_i$, find $\alpha = [\alpha_1 \ \dots \ \alpha_n]^T$.

$$\mathbf{X} = \begin{bmatrix} 1 & 0 & 0 & -1 \\ 0 & -1 & 1 & -1 \end{bmatrix}, \mathbf{y} = [1 \ 1 \ -1 \ -1]^T$$

$$\mathbf{w}^* = [2 \ -1]^T$$



\mathbf{x}	y	\hat{y}
$(1, 0)$	1	1
$(0, -1)$	1	1
$(0, 1)$	-1	-1
$(-1, -1)$	-1	-1

$$\begin{aligned} \mathbf{w}^* &= 0 \cdot x_1 y_1 + 0 \cdot x_2 y_2 + 3 \cdot \mathbf{x}_3 y_3 + 2 \cdot \mathbf{x}_4 y_4 \\ &= 3 \cdot \begin{bmatrix} 0 \\ 1 \end{bmatrix} \cdot (-1) + 2 \cdot \begin{bmatrix} -1 \\ -1 \end{bmatrix} \cdot (-1) \\ &= \begin{bmatrix} 2 \\ -1 \end{bmatrix} \end{aligned}$$

$$\alpha = [0 \ 0 \ 3 \ 2]^T$$


Q-12

Is this a hard-margin or soft-margin SVM?

What are the maximum number of support vectors for this problem?

Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?



Q-12

Is this a hard-margin or soft-margin SVM?


What are the maximum number of support vectors for this problem?

Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?

$$(\mathbf{w}^{*T} \mathbf{x}_i) y_i + \xi_i^* \geq 1 \quad (1)$$

$$\xi_i^* \geq 0 \quad (2)$$



Q-12

Is this a hard-margin or soft-margin SVM?

What are the maximum number of support vectors for this problem?


Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?

$$(\mathbf{w}^{*T} \mathbf{x}_i) y_i + \xi_i^* \geq 1 \quad (1)$$

$$\xi_i^* \geq 0 \quad (2)$$

$$\alpha_i^* \cdot [1 - (\mathbf{w}^{*T} \mathbf{x}_i) y_i - \xi_i^*] = 0 \quad (1)$$



Q-12

Is this a hard-margin or soft-margin SVM?


What are the maximum number of support vectors for this problem?

Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?

$$(\mathbf{w}^{*T} \mathbf{x}_i) y_i + \xi_i^* \geq 1 \quad (1)$$

$$\xi_i^* \geq 0 \quad (2)$$



$$\alpha_i^* \cdot \left[1 - (\mathbf{w}^{*T} \mathbf{x}_i) y_i - \xi_i^* \right] = 0 \quad (1)$$

$$\beta_i^* \cdot \xi_i^* = 0 \quad (2)$$

Q-12

Is this a hard-margin or soft-margin SVM?


What are the maximum number of support vectors for this problem?

Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?

$$(\mathbf{w}^{*T} \mathbf{x}_i) y_i + \xi_i^* \geq 1 \quad (1)$$

$$\xi_i^* \geq 0 \quad (2)$$



$$\alpha_i^* \cdot \left[1 - (\mathbf{w}^{*T} \mathbf{x}_i) y_i - \xi_i^* \right] = 0 \quad (1)$$

$$\beta_i^* \cdot \xi_i^* = 0 \quad (2)$$

$$\alpha_i^* + \beta_i^* = C \quad (3)$$

Q-12

Is this a hard-margin or soft-margin SVM?

What are the maximum number of support vectors for this problem?

Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?

$$(\mathbf{w}^{*T} \mathbf{x}_i) y_i + \xi_i^* \geq 1 \quad (1)$$


$$\xi_i^* \geq 0 \quad (2)$$

$$\alpha_i^* \cdot [1 - (\mathbf{w}^{*T} \mathbf{x}_i) y_i - \xi_i^*] = 0 \quad (1)$$

$$\beta_i^* \cdot \xi_i^* = 0 \quad (2)$$

$$\alpha_i^* + \beta_i^* = C \quad (3)$$

$$\leq n(\text{SV}) \leq$$



Q-12

Is this a hard-margin or soft-margin SVM?

What are the maximum number of support vectors for this problem?

Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?

$$(\mathbf{w}^{*T} \mathbf{x}_i) y_i + \xi_i^* \geq 1 \quad (1)$$


$$\xi_i^* \geq 0 \quad (2)$$

$$\alpha_i^* \cdot [1 - (\mathbf{w}^{*T} \mathbf{x}_i) y_i - \xi_i^*] = 0 \quad (1)$$

$$\beta_i^* \cdot \xi_i^* = 0 \quad (2)$$

$$\alpha_i^* + \beta_i^* = C \quad (3)$$

$$4 \leq n(\text{SV}) \leq$$



Q-12

Is this a hard-margin or soft-margin SVM?


What are the maximum number of support vectors for this problem?

Which of these points are certainly support vectors?

What is the value of α_i^* for these trustworthy vectors?

$$(\mathbf{w}^{*T} \mathbf{x}_i) y_i + \xi_i^* \geq 1 \quad (1)$$

$$\xi_i^* \geq 0 \quad (2)$$



$$\alpha_i^* \cdot [1 - (\mathbf{w}^{*T} \mathbf{x}_i) y_i - \xi_i^*] = 0 \quad (1)$$


$$\beta_i^* \cdot \xi_i^* = 0 \quad (2)$$

$$\alpha_i^* + \beta_i^* = C \quad (3)$$

$$4 \leq n(\text{SV}) \leq 9$$

Q-12

Since we have the image of the feature space given to us, it would be worthwhile to look at the **primal picture**. We have three cases:



Beyond the margin

$$\boxed{(\mathbf{w}^{*T} \mathbf{x}_i) y_i > 1} \rightarrow \left[1 - (\mathbf{w}^{*T} \mathbf{x}_i) y_i - \xi_i^* \right] \neq 0 \rightarrow \boxed{\alpha_i^* = 0}$$

$$\xi_i^* = 0$$

On the margin

$$\boxed{(\mathbf{w}^{*T} \mathbf{x}_i) y_i = 1} \rightarrow \boxed{0 \leq \alpha_i^* \leq C}$$

$$\xi_i^* = 0$$

Margin violation

$$\boxed{(\mathbf{w}^{*T} \mathbf{x}_i) y_i < 1} \rightarrow \beta_i^* = 0 \rightarrow \boxed{\alpha_i^* = C}$$


$$\xi_i^* > 0$$

Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.

Q-13


- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.



Q-13



- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.

$$x_1 < 0$$





Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.






Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.



Q-13

- (a) Deep trees perform well on the training data.
- (b) Deep trees perform well on both training and test data.
- (c) Deep trees perform well on the training data but do not perform well on the test data.
- (d) Deep trees perform poorly on both training and test data.



Q-14

- Vector output by some hidden layer in a neural network:
 $[0.1 \quad 0.8 \quad 0. \quad 0.5 \quad 0.7 \quad 0.9]^T$
- How many neurons does this layer have?
- What is the activation function used in this layer?
- How many neurons does the next layer have?

Q-14

- Vector output by some hidden layer in a neural network:
 $[0.1 \quad 0.8 \quad 0. \quad 0.5 \quad 0.7 \quad 0.9]^T$
- How many neurons does this layer have?
- What is the activation function used in this layer?
- How many neurons does the next layer have?

$$\textcircled{h_1} \quad 0.1$$

$$\textcircled{h_2} \quad 0.8$$

$$\textcircled{h_3} \quad 0$$

$$\textcircled{h_4} \quad 0.5$$

$$\textcircled{h_5} \quad 0.7$$

$$\textcircled{h_6} \quad 0.9$$

Q-14

- Vector output by some hidden layer in a neural network:
 $[0.1 \quad 0.8 \quad 0. \quad 0.5 \quad 0.7 \quad 0.9]^T$
- How many neurons does this layer have?
- What is the activation function used in this layer?
- How many neurons does the next layer have?

$$(h_1)$$

0.1

$$(h_2)$$

0.8

$$(h_3)$$

0

$$(h_4)$$

0.5

$$(h_5)$$

0.7

$$(h_6)$$

0.9

$$\text{ReLU}(z) = \max(0, z)$$

$$\text{ReLU}(z) \geq 0$$

Q-14

- Vector output by some hidden layer in a neural network:
 $[0.1 \quad 0.8 \quad 0. \quad 0.5 \quad 0.7 \quad 0.9]^T$
- How many neurons does this layer have?
- What is the activation function used in this layer?
- How many neurons does the next layer have?

$$\begin{array}{c} \textcircled{h_1} \end{array} \quad 0.1$$

$$\begin{array}{c} \textcircled{h_2} \end{array} \quad 0.8$$

$$\begin{array}{c} \textcircled{h_3} \end{array} \quad 0$$

$$\begin{array}{c} \textcircled{h_4} \end{array} \quad 0.5$$

$$\begin{array}{c} \textcircled{h_5} \end{array} \quad 0.7$$

$$\begin{array}{c} \textcircled{h_6} \end{array} \quad 0.9$$

$$\text{ReLU}(z) = \max(0, z)$$

$$\text{ReLU}(z) \geq 0$$

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

$$0 < \sigma(z) < 1$$

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logistic loss
- Modified hinge loss

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logistic loss
- Modified hinge loss

$u =$

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \quad 0 \quad -1]^T$ and $\mathbf{x} = [2 \quad 3 \quad 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0 – 1		
Squared loss		
Hinge loss		
Logisitc loss		
Modified hinge loss		

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	
Squared loss		
Hinge loss		
Logisitc loss		
Modified hinge loss		

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	
Squared loss	$(u - 1)^2$	
Hinge loss		
Logisitc loss		
Modified hinge loss		

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitic loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	
Squared loss	$(u - 1)^2$	
Hinge loss	$\max(0, 1 - u)$	
Logisitic loss		
Modified hinge loss		

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	
Squared loss	$(u - 1)^2$	
Hinge loss	$\max(0, 1 - u)$	
Logisitc loss	$\ln(1 + e^{-u})$	
Modified hinge loss		

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	
Squared loss	$(u - 1)^2$	
Hinge loss	$\max(0, 1 - u)$	
Logisitc loss	$\ln(1 + e^{-u})$	
Modified hinge loss	$\max(0, -u)$	

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	1
Squared loss	$(u - 1)^2$	
Hinge loss	$\max(0, 1 - u)$	
Logisitc loss	$\ln(1 + e^{-u})$	
Modified hinge loss	$\max(0, -u)$	

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	1
Squared loss	$(u - 1)^2$	4
Hinge loss	$\max(0, 1 - u)$	
Logisitc loss	$\ln(1 + e^{-u})$	
Modified hinge loss	$\max(0, -u)$	

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	1
Squared loss	$(u - 1)^2$	4
Hinge loss	$\max(0, 1 - u)$	2
Logisitc loss	$\ln(1 + e^{-u})$	
Modified hinge loss	$\max(0, -u)$	

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	1
Squared loss	$(u - 1)^2$	4
Hinge loss	$\max(0, 1 - u)$	2
Logisitc loss	$\ln(1 + e^{-u})$	1.313
Modified hinge loss	$\max(0, -u)$	

Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss

$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	1
Squared loss	$(u - 1)^2$	4
Hinge loss	$\max(0, 1 - u)$	2
Logisitc loss	$\ln(1 + e^{-u})$	1.313
Modified hinge loss	$\max(0, -u)$	1


Q-15

Compute the loss for a linear classifier with $\mathbf{w} = [1 \ 0 \ -1]^T$ and $\mathbf{x} = [2 \ 3 \ 1]^T, y = -1$

- 0-1 loss
- Squared loss
- Hinge loss
- Logisitc loss
- Modified hinge loss


$$u = (\mathbf{w}^T \mathbf{x}) \cdot y = -1$$

Loss	$L(u)$	$L(-1)$
0-1	$\begin{cases} 0, & u \geq 0 \\ 1, & u < 0 \end{cases}$	1
Squared loss	$(u - 1)^2$	4
Hinge loss	$\max(0, 1 - u)$	2
Logisitc loss	$\ln(1 + e^{-u})$	1.313
Modified hinge loss	$\max(0, -u)$	1



Q-16


- Logistic regression model
- Threshold is 0.5
- Order the probabilities
- Find the predictions



Q-16

- Logistic regression model
- Threshold is 0.5
- Order the probabilities
- Find the predictions

$$p_i = P(y = 1 \mid \mathbf{x}_i) = \sigma(\mathbf{w}^T \mathbf{x}_i) = \frac{1}{1 + e^{-\mathbf{w}^T \mathbf{x}_i}}$$




Q-16

- Logistic regression model
- Threshold is 0.5
- Order the probabilities
- Find the predictions

$$p_i = P(y = 1 \mid \mathbf{x}_i) = \sigma(\mathbf{w}^T \mathbf{x}_i) = \frac{1}{1 + e^{-\mathbf{w}^T \mathbf{x}_i}}$$

$$p_1 < p_2 < p_3 < p_4$$




Q-16

- Logistic regression model
- Threshold is 0.5
- Order the probabilities
- Find the predictions

$$p_i = P(y = 1 \mid \mathbf{x}_i) = \sigma(\mathbf{w}^T \mathbf{x}_i) = \frac{1}{1 + e^{-\mathbf{w}^T \mathbf{x}_i}}$$

$$p_1 < p_2 < p_3 < p_4$$

$$\hat{y} = \begin{cases} 1, & \sigma(\mathbf{w}^T \mathbf{x}_i) \geq T \\ 0, & \sigma(\mathbf{w}^T \mathbf{x}_i) < T \end{cases}$$




Q-16

- Logistic regression model
- Threshold is 0.5
- Order the probabilities
- Find the predictions

$$p_i = P(y = 1 \mid \mathbf{x}_i) = \sigma(\mathbf{w}^T \mathbf{x}_i) = \frac{1}{1 + e^{-\mathbf{w}^T \mathbf{x}_i}}$$


$$p_1 < p_2 < p_3 < p_4$$

$$\hat{y} = \begin{cases} 1, & \sigma(\mathbf{w}^T \mathbf{x}_i) \geq T \\ 0, & \sigma(\mathbf{w}^T \mathbf{x}_i) < T \end{cases} \quad \hat{y} = \begin{cases} 1, & \mathbf{w}^T \mathbf{x}_i \geq 0 \\ 0, & \mathbf{w}^T \mathbf{x}_i < 0 \end{cases}$$



Q-16

- Logistic regression model
- Threshold is 0.5
- Order the probabilities
- Find the predictions



$$p_i = P(y = 1 \mid \mathbf{x}_i) = \sigma(\mathbf{w}^T \mathbf{x}_i) = \frac{1}{1 + e^{-\mathbf{w}^T \mathbf{x}_i}}$$

$$p_1 < p_2 < p_3 < p_4$$


$$\hat{y} = \begin{cases} 1, & \sigma(\mathbf{w}^T \mathbf{x}_i) \geq T \\ 0, & \sigma(\mathbf{w}^T \mathbf{x}_i) < T \end{cases} \quad \hat{y} = \begin{cases} 1, & \mathbf{w}^T \mathbf{x}_i \geq 0 \\ 0, & \mathbf{w}^T \mathbf{x}_i < 0 \end{cases}$$

$$\hat{\mathbf{y}} = [0 \ 0 \ 1 \ 1]$$

Q-17

Choose the model that can be trained to achieve zero training error on all datasets in \mathbb{R}^2 :


- Logistic regression
- Soft-margin Linear-SVM
- Soft-margin Kernel-SVM with cubic kernel
- Decision Tree



Q-17

Choose the model that can be trained to achieve zero training error on all datasets in \mathbb{R}^2 :

- Logistic regression
- Soft-margin Linear-SVM
- Soft-margin Kernel-SVM with cubic kernel
- Decision Tree



Q-18

- Choose initial centers as mid-point of top two and bottom two data-points
- Run Lloyd's with $k = 2$
- Find the loss for this configuration



Q-18


- Choose initial centers as mid-point of top two and bottom two data-points
- Run Lloyd's with $k = 2$
- Find the loss for this configuration



b

Q-18


- Choose initial centers as mid-point of top two and bottom two data-points
- Run Lloyd's with $k = 2$
- Find the loss for this configuration



$$\left(\frac{b}{2}\right)^2 + \left(\frac{b}{2}\right)^2 + \left(\frac{b}{2}\right)^2 + \left(\frac{b}{2}\right)^2 = b^2$$

Q-18


- Choose initial centers as mid-point of top two and bottom two data-points
- Run Lloyd's with $k = 2$
- Find the loss for this configuration



$$\left(\frac{b}{2}\right)^2 + \left(\frac{b}{2}\right)^2 + \left(\frac{b}{2}\right)^2 + \left(\frac{b}{2}\right)^2 = b^2$$


Q-18

- Choose initial centers as mid-point of top two and bottom two data-points
- Run Lloyd's with $k = 2$
- Find the loss for this configuration



Q-18

- Choose initial centers as mid-point of top two and bottom two data-points
- Run Lloyd's with $k = 2$
- Find the loss for this configuration



Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is Beta(3, 7)
- Find the MAP estimate

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is Beta(3, 7)
- Find the MAP estimate

Posterior \propto Prior \times Likelihood

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times$$

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times p^3(1-p)^3$$

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times p^3(1-p)^3$$

$$\propto p^5(1-p)^9$$

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times p^3(1-p)^3$$

$$\propto p^5(1-p)^9$$

$$\propto \text{Beta}(6, 10)$$

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

$$\log(\text{posterior}) = 5 \log p + 9 \log(1 - p)$$

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times p^3(1-p)^3$$

$$\propto p^5(1-p)^9$$

$$\propto \text{Beta}(6, 10)$$

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

$$\log(\text{posterior}) = 5 \log p + 9 \log(1 - p)$$

$$\hat{p}_{MAP} = \arg \max_p \text{posterior}(p)$$

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times p^3(1-p)^3$$

$$\propto p^5(1-p)^9$$

$$\propto \text{Beta}(6, 10)$$

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

$$\log(\text{posterior}) = 5 \log p + 9 \log(1 - p)$$

$$\hat{p}_{MAP} = \arg \max_p \text{posterior}(p)$$

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times p^3(1-p)^3$$

$$\propto p^5(1-p)^9$$

$$\propto \text{Beta}(6, 10)$$

$$\frac{5}{p} - \frac{9}{1-p} = 0$$

$$5 - 5p - 9p = 0$$

$$\hat{p}_{MAP} = \frac{5}{14}$$

Q-19

- $D = \{1, 0, 1, 0, 1, 0\}$
- Prior is $\text{Beta}(3, 7)$
- Find the MAP estimate

$$\log(\text{posterior}) = 5 \log p + 9 \log(1 - p)$$

$$\hat{p}_{MAP} = \arg \max_p \text{posterior}(p)$$

Posterior \propto Prior \times Likelihood

$$\propto \frac{p^2(1-p)^6}{B(3, 7)} \times p^3(1-p)^3$$

$$\propto p^5(1-p)^9$$

$$\propto \text{Beta}(6, 10)$$

$$\frac{5}{p} - \frac{9}{1-p} = 0$$

$$5 - 5p - 9p = 0$$





$$\hat{p}_{MAP} = \frac{5}{14}$$

If $\alpha, \beta > 1$, then mode of $\text{Beta}(\alpha, \beta)$ is:

$$\frac{\alpha - 1}{\alpha + \beta - 2}$$

Q-20





- Soft-Margin Linear-SVM
- Map C_i to $[0.01, 0.1, 1, 10]$ for $1 \leq i \leq 4$



Q-20

- Soft-Margin Linear-SVM
- Map C_i to $[0.01, 0.1, 1, 10]$ for $1 \leq i \leq 4$

$$\min_{\mathbf{w}} \frac{\|\mathbf{w}\|^2}{2} + C \sum_{i=1}^n \max[0, 1 - (\mathbf{w}^T \mathbf{x}_i) y_i]$$







Q-20

- Soft-Margin Linear-SVM
- Map C_i to $[0.01, 0.1, 1, 10]$ for $1 \leq i \leq 4$

$$\min_{\mathbf{w}} \frac{\|\mathbf{w}\|^2}{2} + C \sum_{i=1}^n \max[0, 1 - (\mathbf{w}^T \mathbf{x}_i) y_i]$$

Loss = Margin + Hinge-loss







Q-20

- Soft-Margin Linear-SVM
- Map C_i to $[0.01, 0.1, 1, 10]$ for $1 \leq i \leq 4$

$$\min_{\mathbf{w}} \frac{\|\mathbf{w}\|^2}{2} + C \sum_{i=1}^n \max[0, 1 - (\mathbf{w}^T \mathbf{x}_i) y_i]$$

Loss = Margin + Hinge-loss

Ideal: Small $\|\mathbf{w}\|$ and small hinge loss



Q-20





- Soft-Margin Linear-SVM
- Map C_i to $[0.01, 0.1, 1, 10]$ for $1 \leq i \leq 4$

$$\min_{\mathbf{w}} \frac{\|\mathbf{w}\|^2}{2} + C \sum_{i=1}^n \max[0, 1 - (\mathbf{w}^T \mathbf{x}_i) y_i]$$

Loss = Margin + Hinge-loss

Ideal: Small $\|\mathbf{w}\|$ and small hinge loss

Large $\|\mathbf{w}\| \Rightarrow$ Narrow margin \Rightarrow Small hinge loss



Q-20

- Soft-Margin Linear-SVM
- Map C_i to $[0.01, 0.1, 1, 10]$ for $1 \leq i \leq 4$

$$\min_{\mathbf{w}} \frac{\|\mathbf{w}\|^2}{2} + C \sum_{i=1}^n \max[0, 1 - (\mathbf{w}^T \mathbf{x}_i) y_i]$$

Loss = Margin + Hinge-loss

Ideal: Small $\|\mathbf{w}\|$ and small hinge loss

Large $\|\mathbf{w}\| \Rightarrow$ Narrow margin \Rightarrow Small hinge loss

Small $\|\mathbf{w}\| \Rightarrow$ Wide margin \Rightarrow Large hinge loss

