

Module 22

Database Management Systems

Module 22: Relational Database Design/2

Partha Pratim Das

Department of Computer Science and Engineering Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

Partha Pratim Das 22.1

Module Recap

Module 22

Partha Pratir Das

Objectives & Outline

unctional Dependencie Closure of FD

Closure of FDs

- Identified the features of good relational design
- Familiarized with the First Normal Form

Module Objectives

Module 22

Partha Pratin Das

Objectives & Outline

Functional Dependencie Closure of FD:

Closure of FDs

• To Introduce Functional Dependencies

Module Outline

Module 22

Partha Pratim Das

Objectives & Outline

-unctional Dependencies Closure of FDs

4 1 1 6

Functional Dependencies



Module 22

Partha Pratim Das

Objectives &

Functional Dependencies

Functional Dependencies

Database Management Systems Partha Pratim Das 22.5



Goal: Devise a Theory for Good Relations

Module 22

Partha Pratim Das

Objectives Outline

Functional Dependencies Closure of FDs

Aodule Summai

- Decide whether a particular relation *R* is in "good" form.
- In the case that a relation R is not in "good" form, decompose it into a set of relations $\{R_1, R_2, \ldots, R_n\}$ such that
 - o each relation is in good form
 - o the decomposition is a lossless-join decomposition
- The theory is based on:
 - Functional dependencies
 - Multivalued dependencies
 - o Other dependencies



Functional Dependencies

Module 22

Partha Pratin Das

Objectives Outline

Functional Dependencies Closure of FDs

lodule Summary

- Constraints on the set of legal relations
- Require that the value for a certain set of attributes determines uniquely the value for another set of attributes
- A functional dependency is a generalization of the notion of a key



Functional Dependencies (2)

Module 22

Partha Pratin Das

Objectives Outline

Functional Dependencies Closure of FDs

Module Summar

• Let *R* be a relation schema

$$\alpha \subseteq R \text{ and } \beta \subseteq R$$

• The functional dependency or FD

$$\alpha \to \beta$$

holds on R if and only if for any legal relations r(R), whenever any two tuples t_1 and t_2 of r agree on the attributes α , they also agree on the attributes β . That is,

$$t_1[\alpha] = t_2[\alpha] \Rightarrow t_1[\beta] = t_2[\beta]$$

• Example: Consider r(A, B) with the following instance of r.

Α	В
1	4
1	5
3	7

22.8

• On this instance, $A \to B$ does **NOT** hold, but $B \to A$ does hold. So we cannot have tuples like (2, 4), or (3, 5), or (4, 7) added to the current instance.

Partha Pratim Das



Functional Dependencies (3)

Module 22

Partha Pratim Das

Objectives Outline

Functional Dependencies Closure of FDs

Module Summar

- ullet K is a superkey for relation schema R if and only if K o R
- \bullet K is a candidate key for R if and only if
 - \circ $K \rightarrow R$ and
 - \circ for no $\alpha \subset K$, $\alpha \to R$
- Functional dependencies allow us to express constraints that cannot be expressed using superkeys. Consider the schema:

inst_dept(<u>ID</u>, name, salary, dept_name, building, budget)

• We expect these functional dependencies to hold:

 $dept_name o building$

 $dept_name \rightarrow budget$

 $ID \rightarrow budget$

but would not expect the following to hold:

 $dept_name \rightarrow salary$



Functional Dependencies (4)

Module 22

Partha Pratim Das

Objectives Outline

Functional Dependencies Closure of FDs

Module Summa

- We use functional dependencies to:
 - o test relations to see if they are legal under a given set of functional dependencies.
 - ▶ If a relation r is legal under a set F of functional dependencies, we say that r satisfies F
 - specify constraints on the set of legal relations
 - ▶ We say that F holds on R if all legal relations on R satisfy the set of functional dependencies F
- **Note**: A specific instance of a relation schema may satisfy a functional dependency even if the functional dependency does not hold on all legal instances
 - \circ For example, a specific instance of instructor may, by chance, satisfy $name
 ightarrow \mathit{ID}$
 - \circ In such cases we do not say that F holds on R



Functional Dependencies (5)

Module 22

Partha Pratim Das

Objectives Outline

Functional Dependencies

Madula Summan

• A functional dependency is trivial if it is satisfied by all instances of a relation

o Example:

 \triangleright *ID*, name \rightarrow *ID*

hd name
ightarrow name

• In general, $\alpha \to \beta$ is trivial if $\beta \subseteq \alpha$.

Functional Dependencies (6)

Module 22

Partha Pratin Das

Objectives Outline

Functional
Dependencies
Closure of FDs

Module Summar

• Functional dependencies are:

StudentID	Semester	Lecture	TA
1234	6	Numerical Methods	John
1221	4	Numerical Methods	Smith
1234	6	Visual Computing	Bob
1201	2	Numerical Methods	Peter
1201	2	Physics II	Simon

 \circ StudentID \rightarrow Semester StudentID, Lecture \rightarrow TA $\{StudentID, Lecture\} \rightarrow \{TA, Semester\}$

Functional Dependencies (7)

Module 22

Partha Pratin Das

Objectives Outline

Functional Dependencies

Module Summar

• Functional dependencies are:

Employee ID	Employee Name	Department ID	Department Name
0001	John Doe	1	Human Resources
0002	Jane Doe	2	Marketing
0003	John Smith	1	Human Resources
0004	Jane Goodall	3	Sales

 \circ EmployeeID \rightarrow EmployeeName

 $\textit{EmployeeID} \rightarrow \textit{DepartmentID}$

 $DepartmentID \rightarrow DepartmentName$



Functional Dependencies (9): Closure of a Set of FDs

Module 22

Partha Pratin Das

Objectives Outline

Functional
Dependencies
Closure of FDs

Closure of FDs

- $F = \{A \rightarrow B, B \rightarrow C\}$
- $F^+ = \{A \rightarrow B, B \rightarrow C, A \rightarrow C\}$



Module Summary

Module 22

Module Summary

• Introduced the notion of Functional Dependencies

Slides used in this presentation are borrowed from http://db-book.com/ with kind permission of the authors. Edited and new slides are marked with "PPD".