

# Classification

Machine Learning Techniques

Karthik Thiagarajan

# Classification

$$D = \{(\mathbf{x}_1, y_1), \cdots, (\mathbf{x}_n, y_n)\}$$

# Classification

$$D = \{(\mathbf{x}_1, y_1), \cdots, (\mathbf{x}_n, y_n)\}$$

$$y_i \in \{0, 1\} \quad \text{OR} \quad y_i \in \{-1, 1\}$$

# Classification

$$D = \{(\mathbf{x}_1, y_1), \cdots, (\mathbf{x}_n, y_n)\}$$

$$y_i \in \{0, 1\} \quad \text{OR} \quad y_i \in \{-1, 1\}$$

$$h : \mathbb{R}^d \rightarrow \{0, 1\}$$

$$h(\mathbf{x}) = y$$

# Classification

$$D = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_n, y_n)\}$$

**0-1 Loss**

$$y_i \in \{0, 1\} \quad \text{OR} \quad y_i \in \{-1, 1\}$$

$$h: \mathbb{R}^d \rightarrow \{0, 1\}$$


$$\text{Loss}(h) = \frac{1}{n} \cdot \sum_{i=1}^n \mathbf{1}[h(\mathbf{x}_i) \neq y_i]$$

$$h(\mathbf{x}) = y$$

# Linear Classifiers

class-1


class-0



# Linear Classifiers

class-1


class-0



# Linear Classifiers

class-1

class-0






# Linear Classifiers

class-1

class-0




$$h_{\mathbf{w}}(\mathbf{x}) = \text{sign}(\mathbf{w}^T \mathbf{x})$$

$$= \begin{cases} 1, & \mathbf{w}^T \mathbf{x} > 0 \\ 0, & \mathbf{w}^T \mathbf{x} \leq 0 \end{cases}$$

# Linear Classifiers

class-1

class-0



$$h_{\mathbf{w}}(\mathbf{x}) = \text{sign}(\mathbf{w}^T \mathbf{x})$$

$$= \begin{cases} 1, & \mathbf{w}^T \mathbf{x} > 0 \\ 0, & \mathbf{w}^T \mathbf{x} \leq 0 \end{cases}$$


$$\mathcal{H}_{\text{linear}} = \{ h_{\mathbf{w}} \mid h_{\mathbf{w}}(\mathbf{x}) = \text{sign}(\mathbf{w}^T \mathbf{x}) \}$$

Linear Classifiers

# Linear Classifiers

class-1

class-0



$$h_{\mathbf{w}}(\mathbf{x}) = \text{sign}(\mathbf{w}^T \mathbf{x})$$


$$= \begin{cases} 1, & \mathbf{w}^T \mathbf{x} > 0 \\ 0, & \mathbf{w}^T \mathbf{x} \leq 0 \end{cases}$$

$$\mathcal{H}_{\text{linear}} = \{ h_{\mathbf{w}} \mid h_{\mathbf{w}}(\mathbf{x}) = \text{sign}(\mathbf{w}^T \mathbf{x}) \}$$

Linear Classifiers

$$\min_{h \in \mathcal{H}_{\text{linear}}} \frac{1}{n} \cdot \sum_{i=1}^n \mathbf{1}[h(\mathbf{x}_i) \neq y_i]$$


# Classification as Regression



# Classification as Regression

$$\mathbf{w}^* = \arg \min_{\mathbf{w}} \frac{1}{n} \cdot \sum_{i=1}^n (\mathbf{w}^T \mathbf{x}_i - y_i)^2$$


$$h_{\mathbf{w}^*}(\mathbf{x}) = \text{sign}(\mathbf{w}^{*T} \mathbf{x})$$



# Classification as Regression

$$\mathbf{w}^* = \arg \min_{\mathbf{w}} \frac{1}{n} \cdot \sum_{i=1}^n (\mathbf{w}^T \mathbf{x}_i - y_i)^2$$

$$h_{\mathbf{w}^*}(\mathbf{x}) = \text{sign}(\mathbf{w}^{*T} \mathbf{x})$$




- Sensitive to outliers

# Classification as Regression

$$\mathbf{w}^* = \arg \min_{\mathbf{w}} \frac{1}{n} \cdot \sum_{i=1}^n (\mathbf{w}^T \mathbf{x}_i - y_i)^2$$

$$h_{\mathbf{w}^*}(\mathbf{x}) = \text{sign}(\mathbf{w}^{*T} \mathbf{x})$$



- Sensitive to outliers
- Natural ordering is absent
  - example: spam, work, family