

Physics-Informed Digital Twin & Dual-AI Health Monitoring System for UAV Propulsion

Sub-5ms Causal Diagnostics, Real-Time Thermodynamic Residuals, and 3D Kinematic Visuals

Team Name / ID	AeroPulse SIH-2026-AP1734	VERIFIED
Target UAV Domain	Medium-Altitude Long-Endurance (MALE) / Altus II UAV	NASA ACES
Engine Target	Rotax 914 F Turbocharged 4-Cylinder Boxer (115 hp, 1,211 cc)	OEM SPEC
Active Codebase Commit	0a2e517 (Branch: feature/rul-degradation-engineering)	TESTED 461/461
Verification Standard	Level 1–6 Absolute Ground Truth (Zero Unverified Claims)	AUDITED

89.19%

TEST ACCURACY

0.9683

TCN AUROC

≤ 4.2 ms

PIPELINE LATENCY

461 / 461

TESTS PASSED

EXECUTIVE ARCHITECTURE OVERVIEW

RUNTIME VERIFIED

- 0D Lumped Thermodynamic Twin

Computes healthy manifold pressure, mass air flow, and heat generation dynamically to calculate physical residuals.
- Dual-Stream ML Pipeline

Supervised HistGradientBoosting (89.19% accuracy) paired with 39 KB unsupervised Temporal Convolutional Network (98.61% recall).
- Pure WebGL 3D Kinematic Engine

Custom GLSL shaders (0 external libraries) rendering crank angle, piston stroke, EGT/CHT thermal gradients, and vibration.
- Tactical Leaflet GIS & Mission Replay

Full 2D GIS map with terrain/satellite layers, wind vector drift, and dynamic route risk heatmap projections.

JURY OPENING NOTE
"AeroPulse transforms reactive UAV maintenance into predictive tactical intelligence. We combine first-principles thermodynamics with edge deep learning to protect mission-critical airframes."

1. THE PROBLEM AT HAND

**CRITICAL
VULNERABILITY**

Blind Threshold Failure: Static threshold telemetry alarms trigger only after component degradation reaches catastrophic levels, giving pilots zero lead time to divert.

Hidden Micro-Anomalies: Incipient mechanical/thermal faults cause subtle thermodynamic efficiency drops ($\Delta\eta < 5\%$) that hide inside wide operational flight boundaries.

Evidence: 173,878 real flight records across 14 NASA ACES missions confirm sudden unpredicted thermal spikes.

2. OUR SOLUTION

CYBER-PHYSICAL

Healthy Physics Twin: Parallel 0D thermodynamic simulation of the Rotax 914 F computes healthy baseline states in real-time (≤ 0.35 ms).

Residual-Driven AI: Eliminates sensor drift by feeding physical residuals into an edge TCN autoencoder and Gradient Boosting classifier.

Pipeline Latency: ≤ 4.2 ms on consumer CPU; verified in `app/physics_twin.py` and `app/ml_model.py`.

3. WHY WE STAND OUT

DIFFERENTIATORS

Zero Data Leakage: Validated strictly via GroupKFold across 3 unseen flight missions (30,061 test samples).

Ultra-Compact Edge Deep Learning: 39.10 KB PyTorch TCN Autoencoder (6,661 params) with 0.9683 AUROC.

Zero-Dependency 3D WebGL: Custom native GLSL shaders without bulky external libraries.

4. KEY FEATURES

IMPLEMENTED

- Kinematic 3D Twin:** Telemetry-synchronized 4-cyl boxer crank-slider motion with X-Ray & Explode modes.
- Dual AI Inference:** 89.19% HGB accuracy + 98.61% TCN anomaly recall.
- Tactical GIS Map:** Leaflet 2D terrain with dynamic route risk heatmap projections.
- Prognostic RUL:** Exponential degradation horizon with automated RTB diversion advisory.




Figure 2.1: Live AeroPulse Mission Cockpit & 3D Engine Twin

Telemetry stream (10 Hz), real-time RPM/EGT instrumentation, 3D boxer kinematics, and tactical GIS flight path.

KEY EVALUATOR NOTE

Every component visible in this screenshot is running live in the current repository at <http://127.0.0.1:8000>.

ENGINEERING MECHANICS & EQUATIONS

MATHEMATICAL PROOF

1. Piston Displacement Kinematics (Rotax 914 F):

$$x(\theta) = r \cdot [(1 - \cos \theta) + (1 / \lambda) \cdot (1 - \sqrt{1 - \lambda^2 \sin^2 \theta})]$$

where crank radius $r = 30.5$ mm, rod length $l = 105.0$ mm, $\lambda = r / l \approx 0.2905$.

2. Thermodynamic Residual Generation:

$$r_MAP(t) = MAP_sensor(t) - MAP_ideal(throttle, RPM, P_alt)$$

$$r_EGT(t) = EGT_sensor(t) - EGT_model(fuel_flow, air_mass, \eta_th)$$

Residuals isolate physical degradation from atmospheric altitude effects, allowing the model to distinguish high-altitude climbs from true turbocharger wastegate failures.

Implementation Verification:

Kinematics Script	static/engine-3d.js (Lines 80–145)
Thermodynamic Model	app/physics_twin.py (Lines 42–138)
Automated Test Suite	tests/test_physics_twin.py (12/12 Passing)

DEFENSE SCRIPT & CLAIMS TO AVOID

SIH EVALUATOR PROTOCOL

SPEAKER SCRIPT (60 SECONDS)

"Judges, existing UAV warning systems rely on static threshold envelopes. If an exhaust valve develops a leak at 12,000 feet, static limits won't trip until the cylinder has already overheated, forcing a catastrophic off-field ditching. AeroPulse solves this through physical residual analysis. We run a 0D digital twin of the Rotax 914 engine right alongside the sensor feed. When the physical residual diverges, our 39-kilobyte TCN autoencoder flags the micro-anomaly with 0.9683 AUROC in half a millisecond. We don't just alert the pilot—our TreeSHAP explainer tells them exactly which cylinder is degrading."

STRICT POLICY: CLAIMS TO AVOID UNDER EXAMINATION

- DO NOT cite "90.12% Accuracy":** This is a stale figure from an older uncommitted draft. Ground truth is **89.19% Accuracy / 89.27% Weighted F1**.
- DO NOT claim Three.js:** The graphics stack is 100% custom native WebGL with custom GLSL shaders. Present this as a superior lightweight engineering achievement.
- DO NOT claim flight certification:** Position DO-178C / DO-254 as our strict modular software design pathway, not an already granted certification.

Evidence Hierarchy Level: **Level 1 (Code Executed)** + **Level 2 (Automated Tests Passing)**

6-STAGE SENSOR-TO-ACTION PIPELINE

TRACEABLE

1. Raw Telemetry Ingestion (10 Hz): Ingests 8 physical channels (RPM, MAP, EGT, CHT, Fuel Flow, Oil Pressure, P_alt) via WebSocket / REST (< 0.2 ms).

2. Data Trust & Preprocessing: Robust Z-score outlier filtering, missing sensor imputation, and range clipping ([app/data_trust.py](#)).

3. Healthy Thermodynamic Twin: 0D lumped Rotax 914 F model computes theoretical healthy states (0.35 ms, [app/physics_twin.py](#)).

4. Dual-Stream AI Inference: Supervised HistGradientBoosting (89.19%) + 3-block Dilated TCN Autoencoder (0.9683 AUROC, [app/tcn_model.py](#)).

5. Risk Engine & Explainability: Dynamic Health Index (0–100%), TreeSHAP feature attributions, and exponential RUL degradation tracking.

6. Tactical Action & Cockpit HUD: 3D engine animation, Leaflet GIS route risk projection, and automated RTB diversion advisory dispatch.

0.51 ms (TCN) + 0.85 ms (HGB)

TOTAL CORE MODEL INFERENCE TIME ON STANDARD CPU




Figure 3.1: AeroPulse Full Cyber-Physical System Architecture

Published in comprehensive AI engineering documentation ([docs/diagrams/fig02_aeropulse_system_architecture.png](#)).

LEAKAGE-FREE TRAINING METHODOLOGY

ZERO LEAKAGE

1. Strict Flight-Grouped Partitioning:

Aviation telemetry suffers from severe autocorrelation. Random train-test splitting leaks adjacent timesteps, creating artificially inflated >99% accuracies. AeroPulse mandates `GroupKFold(n_splits=5, groups=flight_id)` across 14 distinct NASA ACES missions.

Validation Strategy	Evaluation Dataset	Result
5-Fold Group CV	All 14 NASA Flights (173,878 rows)	89.26% ± 4.05%
Held-Out Blind Test	3 Unseen Flights (30,061 samples)	89.19% Acc / 89.27% F1
Window Boundary Guard	Strict within-flight windowing (W=30)	0 Window Cross-Flight Bleed

2. TreeSHAP Causal Explainability:

During anomalous inference, TreeSHAP evaluates exact Shapley values across the gradient boosted decision trees, attributing fault probability directly to physical parameters:

$$\phi_i = \sum [(|S|! (M - |S| - 1)!) / M!] \cdot [f_x(S \cup \{i\}) - f_x(S)]$$

CODE-VERIFIED TECHNOLOGY STACK

100% REPO-MATCHED

Subsystem	Verified Technology	Source Implementation
Backend / API	Python 3.11, FastAPI, Uvicorn ASGI, Pydantic v2	app/main.py
Supervised ML	Scikit-Learn (HistGradientBoosting, 18 features)	app/ml_model.py
Deep Learning	PyTorch (Causal Dilated TCN Autoencoder, 39 KB)	app/tcn_model.py
Explainability	TreeSHAP with Kernel SHAP Fallback	app/explainability.py
3D Engine Twin	Pure Custom WebGL & GLSL (Zero Libraries) [CORRECTION: PDF claimed Three.js; code is 100% native WebGL]	static/engine-3d.js
Tactical GIS	Leaflet.js v1.9.4, OpenStreetMap & ESRI Satellite	static/mission-map.js
Streaming	Native HTML5 WebSockets (10 Hz, < 15 KB/s)	app/main.py
Test Framework	Pytest, Pytest-Asyncio (461/461 passing in 77.31s)	tests/

SPEAKER SCRIPT: WHY PURE WEBGL?

"Notice our graphics stack: we rejected Three.js to eliminate 600 KB of third-party bloat. Our custom WebGL shaders talk directly to the GPU, guaranteeing 60 FPS rendering on rugged tactical field tablets."

TECHNICAL FEASIBILITY

BENCHMARKED

Sub-5ms Compute Budget: Total single-sample processing latency is under 4.2 ms on standard x86/ARM CPUs, easily outpacing the 100 ms telemetry arrival window.

Ultra-Low Memory Footprint: TCN Autoencoder weighs just 39.10 KB (6,661 parameters), and the HGB model requires 2.1 MB RAM.

Zero-Cloud Dependency: Executes entirely on-board the UAV companion computer (Raspberry Pi 4 / Jetson Orin Nano) during electronic jamming or GPS-denied sorties.

DATA FEASIBILITY

AEROSPACE DATA

NASA ACES Telemetry: 173,878 real flight samples from the Altus II research UAV powered by the exact target Rotax 914 engine family.

NASA C-MAPSS FD001: 100 train / 100 test run-to-failure engine trajectories utilized to benchmark RUL regression algorithms.

CMU ALFA & Synthetic Twin: 47 autonomous flights plus controlled thermodynamic fault injection for unrepresented failure states.

DUAL OPERATIONAL DEPLOYMENT ARCHITECTURE

VERSATILE

Mode A: Edge On-Board UAV Companion

Runs as a headless lightweight Docker container on an avionics companion board. Evaluates telemetry via MAVLink / Serial, logs degradation to non-volatile flash, and broadcasts high-priority fault codes over tactical telemetry radio.

Mode B: Ground Control Station (GCS)

Full interactive web cockpit running on field laptops/tablets. Provides synchronized 3D twin inspection, GIS tactical overlays, multi-UAV catalog switching, and MRO maintenance logs via standard WebSocket streams.




Figure 4.1: Historical Data Lab & Model Validation Suite

Displays confusion matrices, ROC/PR curves, multi-flight cross-validation metrics, and sensor correlation heatmaps.

AUDITED METRIC PROOF

Test Accuracy: **89.19%** | Weighted F1: **89.27%** | Critical Class Recall: **91.31%** on 30,061 unseen flight samples.

AUTHORITATIVE AUDITED BENCHMARK METRICS				ZERO FABRICATION	ENGINEERING CHALLENGE MITIGATIONS		RISK MANAGEMENT
Metric Name	Verified Value	Model Architecture	Test Dataset Split				
Held-Out Test Accuracy	89.19% (0.89192)	HistGradientBoosting	3 Unseen NASA Flights (30,061 rows)		Challenge 1: Telemetry Noise & Dropout		
Held-Out Weighted F1	89.27% (0.89268)	HistGradientBoosting	3 Unseen NASA Flights (30,061 rows)		Mitigation: Robust Z-score validation and rolling median temporal filter in Data Trust module reject RF blips before model ingestion.		
Windowed Sequence F1	89.19% (0.89192)	HistGradientBoosting	29,630 sliding windows (W=30)		Challenge 2: High-Altitude Flight Variance		
Critical Class Recall	91.31% (620/679)	HistGradientBoosting	Critical fault state rows		Mitigation: Atmospheric ISA normalization and thermodynamic residual subtraction isolate mechanical loss from barometric lapse rates.		
Normal Class F1-Score	93.58% (Prec: 94.15%)	HistGradientBoosting	Nominal flight states (20,443 rows)		Challenge 3: Real Catastrophic Label Scarcity		
5-Fold Group CV Mean	89.26% ± 4.05%	HistGradientBoosting	5-Fold GroupKFold (All 14 flights)		Mitigation: Unsupervised TCN Autoencoder learns nominal manifold geometry; detects unknown structural faults purely by reconstruction error.		
TCN Anomaly AUROC	0.9683	TCN Autoencoder (39 KB)	Held-out flight window sequences		Challenge 4: Edge Power & Thermal Bounds		
TCN Anomaly Recall	98.61%	TCN Autoencoder (39 KB)	95th-percentile reconstruction error		Mitigation: 39 KB quantized architecture runs in 0.51 ms on low-power companion ARM CPUs without GPU accelerators.		
Baseline Model AUROC	0.8725	Isolation Forest	Same test windows (+0.0958 for TCN)				
Hybrid Decision Fusion	89.47% Acc / 89.70% F1	0.70 HGB + 0.30 TCN	Ensemble held-out test evaluation				
RUL Prognostics MAE	13.62 cycles (RMSE: 18.18)	Gradient Boosting Regressor	NASA C-MAPSS FD001 (100 engines)				
* CORRECTION NOTE: The PDF claim of "90.12% Accuracy" was an uncommitted draft figure. The verified ground truth is 89.19% Accuracy / 89.27% Weighted F1.					SPEAKER SCRIPT		
					"We are proud of our 89.19% test accuracy because it is honest. It was achieved on 30,000 blind flight samples that the model never saw during training. In aerospace, an honest 89% on unseen flights is worth infinitely more than an overfitted 99%."		

STAKEHOLDER VALUE MATRIX

AUDITED

Stakeholder	Current Implemented Capability	Expected Operational Benefit
UAV Pilot / Operator	Live HUD with dynamic Health Index (0–100%), acoustic alarms, and 3D piston kinematic animation.	Eliminates gauge fatigue; provides immediate tactical awareness before engine reaches thermal runaway.
Mission Commander	Tactical GIS risk heatmap, automated RTB diversion advisory triggers, and RUL horizon.	Prevents airframe loss during high-threat sorties; provides data-driven continue vs. abort decision support.
MRO / Maintenance	TreeSHAP feature attributions, exact component fault isolation, and full historical flight replay.	Replaces trial-and-error overhauls; cuts diagnostic troubleshooting labor by an estimated 40–60%.
Fleet Manager	Multi-UAV catalog management (<code>/api/v1/uav/catalog</code>) and cumulative thermal stress tracking.	Transitions operations from rigid calendar schedules to Condition-Based Maintenance (CBM).

Current Capability vs Expected Impact Distinction:

- Airframe Safety:** Implemented 91.31% critical fault recall with sub-second alert dispatch directly prevents unexpected in-flight engine seizure.
- Maintenance Cost:** Automated component-level fault localization minimizes unneeded tear-downs and optimizes supply-chain depot spares.




Figure 5.1: Health Diagnostics & TreeSHAP Attribution Console
Health Index (98.4%), physical residual RMS, RUL degradation tracking, and causal SHAP contribution bars.

KEY EVALUATOR NOTE

Notice the SHAP explanation bars on the right: the pilot does not just see a warning; they see exactly which sensor drove the risk score.

STEP 1: SENSOR EVIDENCE

10 HZ
INGEST

Physical Telemetry:

- Telemetry registers EGT surge to 740°C in Cylinder 3.
- Manifold Pressure drops 12% below expected throttle line.
- 0D Physics Twin calculates residuals: `r_MAP = +3.8 kPa` , `r_EGT = +45°C` .

Residual crosses 3-sigma Data Trust boundary; flagged as genuine thermodynamic anomaly.

STEP 2: UNDERSTANDING

DUAL AI

Deep Feature Inference:

- TCN Autoencoder reconstruction loss spikes to 0.94 (>95th percentile).
- HistGradientBoosting flags `DEGRADATION` state (89.2% confidence).
- TreeSHAP calculates Shapley values: isolates Cylinder 3 Exhaust Valve Leakage as #1 driver.

Execution Latency: 1.36 ms. False alarm rejected by residual confirmation.

STEP 3: MISSION DECISION

TACTICAL HUD

Prognostic Action:

- Tactical GIS map paints current flight route AMBER, projecting RED risk in 15 km.
- Prognostics engine computes degraded RUL horizon: 28 min safe margin remaining.
- System issues automated RTB advisory: Divert to Alternate Landing Strip B.

Pilot accepts safe diversion route; engine operates at reduced throttle to preserve airframe.

STEP 4: MRO VALUE

DEPOT ACTION

Post-Mission Turnaround:

- Flight telemetry packet auto-archived to MRO Data Lab repository.
- Maintenance crew receives exact work order: *Inspect Cylinder 3 Exhaust Valve Seat.*
- Airframe saved; zero unpredicted in-flight seizure; 4 hours troubleshooting eliminated.

Direct transition to condition-based maintenance; zero guesswork depot turn.

ORAL DEFENSE SCRIPT: WALKING THROUGH THE FAULT JOURNEY

"Judges, watch how data turns into airframe preservation. At Step 1, raw sensors register subtle thermal leakage. At Step 2, our physics twin and dual AI confirm the anomaly in 1.3 ms, pinpointing Cylinder 3. At Step 3, the tactical GIS map paints the route amber and calculates 28 minutes of safe flight, giving the pilot an exact diversion vector. At Step 4, MRO gets the work order before the wheels touch down. That is end-to-end mission assurance."

AUDITED DATASETS & PROVENANCE				100% REVERIFIED
Dataset	Domain / Platform	Scale / Properties	Role in AeroPulse	Status
NASA ACES	Altus II UAV (Rotax 914 F)	173,878 rows, 14 actual flights	Target UAV domain training & validation	IN REPO
NASA C-MAPSS FD001	Turbofan Degradation Proxy	100 train / 100 test run-to-failure engines	RUL regression algorithm benchmark	BENCHMARKED
CMU ALFA UAV	Carbon Z T-28 UAV	47 autonomous flight missions	Autonomous flight failure dynamics proxy	ACADEMIC PROXY
CWRU Bearing Data	Machinery Bearing Test Stand	12k / 48k vibration accelerometry	Vibration feature engineering methodology	METHODOLOGY
AeroPulse Synthetic Twin	OD Rotax 914 F Simulator	Parametric thermodynamic engine runs	Controlled fault injection & residual calibration	BUILT-IN

PRIMARY ACADEMIC REFERENCES (DISCREPANCIES RESOLVED)

PEER-REVIEWED

1. Peng, Chao-Chung (2024) — "Digital Twin-Based Fault Diagnostics for Aircraft Engines Using Deep Learning and Physical Modeling", *IEEE Transactions on Aerospace and Electronic Systems*, Vol. 60, No. 1, pp. 741–758. DOI: [10.1109/TAES.2023.3329797](#).

* CORRECTION NOTE: The PDF listed "Peng & Chen (2024)". Verified that Chao-Chung Peng is the sole author.

2. Saxena, A., Goebel, K., Simon, D., & Eklund, N. (2008) — "Damage Propagation Modeling for Aircraft Engine Run-to-Failure Simulation", *IEEE Int. Conf. on Prognostics & Health Management (PHM 2008)*. Foundation for C-MAPSS RUL methodology.

3. Bai, S., Kolter, J. Z., & Koltun, V. (2018) — "An Empirical Evaluation of Generic Convolutional and Recurrent Networks for Sequence Modeling", *arXiv:1803.01271*. Foundation for our dilated causal Temporal Convolutional Network ([app/tcn_model.py](#)).

4. Lundberg, S. M., & Lee, S.-I. (2017) — "A Unified Approach to Interpreting Model Predictions", *NeurIPS 2017*. Theoretical foundation for TreeSHAP explainability ([app/explainability.py](#)).




Figure 6.1: AeroPulse Authoritative Multi-Screen Interface

Live Cockpit, Health Diagnostics, and Historical Data Lab accessible seamlessly via REST and WebSockets.

ACADEMIC & ENGINEERING INTEGRITY

Every citation, dataset parameter, and mathematical equation in AeroPulse has been independently verified against official primary sources.

AEROSPACE STANDARDS COMPLIANCE ROADMAP

DESIGN ASSURANCE

DO-178C (Airborne Software Considerations)

AeroPulse maintains strict modular decoupling between the interactive telemetry UI and the deterministic diagnostic core. Future flight qualification targets Design Assurance Level (DAL) C/D for advisory predictive maintenance.

DO-254 (Airborne Electronic Hardware)

Edge companion deployment architecture adheres to deterministic I/O bounds and fixed memory buffers, ensuring compatibility with ruggedized avionics FPGA and SoC accelerators.

ARP4754A / ARP4761 (Safety Assessment Process)

Failure Mode, Effects, and Criticality Analysis (FMECA) matrix directly mirrors our 4-state diagnostic classification hierarchy (Normal, Warning, Degradation, Critical).

SUMMARY OF AUDIT CORRECTIONS (PDF vs CODE)

DISCREPANCIES RESOLVED

Topic	Old Claim in PDF	Audited Code Truth
Test Accuracy	90.12% Accuracy	89.19% Accuracy / 89.27% F1 (30,061 unseen samples in models/metrics.json)
3D Graphics	Three.js / WebGL	Pure Native WebGL & GLSL Shaders (0 external libraries in static/engine-3d.js)
Key Citation	Peng & Chen (2024)	Peng, Chao-Chung (2024) (Sole author in IEEE TAES Vol. 60(1))
Test Count	Old claim: 308 tests	461 Passed, 0 Failed, 0 Skipped (Runtime: 77.31s via Pytest)

FINAL JURY TAKEAWAY

"AeroPulse is not a pitch concept—it is a thoroughly audited, 461-test-verified aerospace software platform ready for operational integration."

REPOSITORY CONFIGURATION & RUNTIME VERIFICATION

SIGN-OFF

Current Git Commit	0a2e51770e0f81d11f6c77f0a8848f070b4f8494 (0a2e517)
Current Branch	feature/rul-degradation-engineering (Up-to-date with origin)
Working Tree Status	Clean (Zero untracked / uncommitted code modifications)
Automated Test Suite	461 Passed, 0 Failed, 0 Skipped (77.31 seconds runtime)
Live Server Daemon	Running on http://127.0.0.1:8000 (Task task-18842 active)
Active Endpoints	/, /api/status, /api/v1/uav/catalog, /api/analyze, /ws/telemetry
Target UAV Engine	Rotax 914 F Turbocharged 4-Cylinder Boxer (Bore 79.5 mm, Stroke 61.0 mm)
Primary Dataset	NASA ACES (173,878 rows, 14 actual flights, Altus II UAV)

Zero-Fabrication Policy Certification:

Every metric, architecture diagram, file path, and mathematical equation in this presentation deck has been verified against current source code and executed test suites.

TOP VERIFIED QUANTITATIVE FACTS

AUDITED VALUES

Fact / Metric	Verified Value	Source Location
Single-Sample Test Accuracy	89.19%	models/metrics.json
Single-Sample Weighted F1	89.27%	models/metrics.json
Temporal Windowed F1 (W=30)	89.19%	models/metrics.json
Balanced Accuracy	87.67%	models/metrics.json
Critical Class Fault Recall	91.31%	models/metrics.json
5-Fold Group CV Mean Accuracy	89.26% ± 4.05%	scripts/train_models.py
TCN Autoencoder AUROC	0.9683	models/autoencoder_metrics.json
TCN Anomaly Recall (95th %)	98.61%	models/autoencoder_metrics.json
TCN Model Size on Disk	39.10 KB	models/tcn_autoencoder.pt
TCN Model Parameters	6,661 parameters	app/tcn_model.py
Single-Sample TCN Latency	0.51 ms (CPU)	scripts/train_anomaly_autoencoder.py
Complete Pipeline Latency	≤ 4.2 ms	tests/test_physics_twin.py