



[Curso](#) > [Week 6...](#) > [Proble...](#) > Proble...

Audit Access Expires 5 de ago de 2020

You lose all access to this course, including your progress, on 5 de ago de 2020.

Problem 5

Problem Set due Jul 30, 2020 20:30 -03 *Completo*

Problem 5

1/1 point (graded)

You have 2 attempts for this problem.

Here is code for linear search that uses the fact that a set of elements is sorted in increasing order:

```
def search(L, e):
    for i in range(len(L)):
        if L[i] == e:
            return True
        if L[i] > e:
            return False
    return False
```

Consider the following code, which is an alternative version of `search`.



```
def newsearch(L, e):  
    size = len(L)  
    for i in range(size):  
        if L[size-i-1] == e:  
            return True  
        if L[i] < e:  
            return False  
    return False
```

Which of the following statements is correct? You may assume that each function is tested with a list `L` whose elements are sorted in increasing order; for simplicity, assume `L` is a list of positive integers.

- ☐ `search` and `newsearch` return the same answers for all `L` and `e`.
- ☐ `search` and `newsearch` return the same answers provided `L` is non-empty.
- ☐ `search` and `newsearch` return the same answers provided `L` is non-empty and `e` is in `L`.
- ☐ `search` and `newsearch` never return the same answers.
- ☒ `search` and `newsearch` return the same answers for lists `L` of length 0, 1, or 2.
- ☐ `search` and `newsearch` return the same answers for lists `L` of length 0 or 1.



Enviar

You have used 2 of 2 attempts

Problem 5

Topic: Problem Set 6 / Problem 5

Ocultar discussão

Add a Post

Show all posts ▼

por atividade recente



? [STAFF] Resolved --- I believe there is an error in the answer

3 new_

I think there is an error in the answer to this question. I used up both my attempts with the same...

© All Rights Reserved

