

- `$min` and `$max` operators that perform conditional update depending on the relative size of the specified value and the current value of a field.
- `$push` operator has enhanced support for the `$sort`, `$slice`, and `$each` modifiers and supports a new `$position` modifier.
- `$currentDate` operator to set the value of a field to the current date.
- The `$mul` operator for multiplicative increments for insert and update operations.

See also:

Update Operator Syntax Validation (page 861)

New Write Operation Protocol

A new write protocol integrates write operations with write concerns. The protocol also provides improved support for bulk operations.

MongoDB 2.6 adds the write commands `insert`, `update`, and `delete`, which provide the basis for the improved bulk insert. All officially supported MongoDB drivers support the new write commands.

The `mongo` shell now includes methods to perform bulk-write operations. See `Bulk()` for more information.

See also:

Write Method Acknowledgements (page 857)

MSI Package for MongoDB Available for Windows

MongoDB now distributes MSI packages for Microsoft Windows. This is the recommended method for MongoDB installation under Windows.

Security Improvements

MongoDB 2.6 enhances support for secure deployments through improved SSL support, x.509-based authentication, an improved authorization system with more granular controls, as well as centralized credential storage, and improved user management tools.

Specifically these changes include:

- A new *authorization model* (page 324) that provides the ability to create custom *User-Defined Roles* (page 325) and the ability to specify user privileges at a collection-level granularity.
- Global user management, which stores all user and user-defined role data in the `admin` database and provides a new set of commands for managing users and roles.
- x.509 certificate authentication for *client authentication* (page 361) as well as for *internal authentication* (page 363) of sharded and/or replica set cluster members. x.509 authentication is only available for deployments using SSL.
- Enhanced SSL Support:
 - *Rolling upgrades of clusters* (page 350) to use SSL.
 - *MongoDB Tools* (page 350) support connections to `mongod` and `mongos` instances using SSL connections.
 - *Prompt for passphrase* (page 345) by `mongod` or `mongos` at startup.