

Option	Maximum Length
<code>SOURCE_SSL_CA</code>	511
<code>SOURCE_SSL_CAPATH</code>	511
<code>SOURCE_SSL_CERT</code>	511
<code>SOURCE_SSL_CRL</code>	511
<code>SOURCE_SSL_CRLPATH</code>	511
<code>SOURCE_SSL_KEY</code>	511
<code>SOURCE_SSL_CIPHER</code>	511
<code>SOURCE_TLS_VERSION</code>	511
<code>SOURCE_TLS_CIPHERSUITES</code>	4000
<code>SOURCE_PUBLIC_KEY_PATH</code>	511
<code>SOURCE_COMPRESSION_ALGORITHMS</code>	99
<code>NETWORK_NAMESPACE</code>	64

13.4.2.4 MASTER_POS_WAIT() Statement

```
SELECT MASTER_POS_WAIT('source_log_file', source_log_pos [, timeout][, channel])
```

This is actually a function, not a statement. It is used to ensure that the replica has read and executed events up to a given position in the source's binary log. See [Section 12.24, “Miscellaneous Functions”](#), for a full description.

13.4.2.5 RESET REPLICA | SLAVE Statement

```
RESET {REPLICA | SLAVE} [ALL] [channel_option]
```

channel_option:
FOR CHANNEL *channel*

RESET REPLICA | SLAVE makes the replica forget its position in the source's binary log. From MySQL 8.0.22, use **RESET REPLICA** in place of **RESET SLAVE**, which is deprecated from that release. In releases before MySQL 8.0.22, use **RESET SLAVE**.

This statement is meant to be used for a clean start; it clears the replication metadata repositories, deletes all the relay log files, and starts a new relay log file. It also resets to 0 the replication delay specified with the **SOURCE_DELAY | MASTER_DELAY** option of the **CHANGE REPLICATION SOURCE TO** statement (from MySQL 8.0.23) or **CHANGE MASTER TO** statement (before MySQL 8.0.23).



Note

All relay log files are deleted, even if they have not been completely executed by the replication SQL thread. (This is a condition likely to exist on a replica if you have issued a **STOP REPLICA | SLAVE** statement or if the replica is highly loaded.)

For a server where GTIDs are in use (**gtid_mode** is **ON**), issuing **RESET REPLICA | SLAVE** has no effect on the GTID execution history. The statement does not change the values of **gtid_executed** or **gtid_purged**, or the **mysql.gtid_executed** table. If you need to reset the GTID execution history, use **RESET MASTER**, even if the GTID-enabled server is a replica where binary logging is disabled.

RESET REPLICA | SLAVE requires the **RELOAD** privilege.