



STATIC DIMENSIONS in mm			
	HT1.0	HT1.5	SW1.5
A	2718	2718	2718
B	1730	1731	1700
C	1502	1650	1650
D	3021	3136	3219
E	730	785	784
F	789	701	785
G	335	385	678
H	1246	1326	1322
I	1671	1849	2291
J	2762	3136	3219
K	789	785	785
L	471	701	784
M	1575	1546	N/A
N	2486	2486	N/A
O	3010	3010	N/A
P	1116	1300	1300
Q	271	271	272
R	2718	2718	2718



NC Engineering (Hamiltonsbawn) Ltd
2 Killyrudden Road
Hamiltonsbawn, Richhill
Co. Armagh
Northern Ireland
BT61 9SF
Tel: +44 (0) 28 38 871970
Fax: +44 (0) 28 38 870362
E-Mail: sales@nc-engineering.com
Web: www.nc-engineering.com

We reserve the right to change the above specification without prior notice Rev 2.0 - April 2019

CAPACITY:	HT1.0	HT1.5*	SW1.5*
Max. safe load:	1000kg	1500kg	1500kg
Unladen Weight:	1390kg	1495kg	1440kg
Heaped:	505L	805L	815L
Struck:	405L	600L	605L
Water:	300L	420L	480L

ENGINE:	
Kubota D1105	
Displacement:	1.1 L
Max. power:	18.2kW/24.4bhp @ 3000 rpm
Max. torque:	72Nm @ 2000 rpm
Emissions to:	(EU) 2016/1628

TRANSMISSION:	
Hydrostatic automotive "Twin Lock"	
Permanent 4 wheel drive	
Acceleration by foot pedal	
Braking hydrostatic retardation	

DRIVE CHARACTERISTICS:	
Forward / Reverse	0-14 km/h(0-8.6 mph) 0-11km/h*(0-7mph*)
Steering angle:	+/- 36°
Turning Circle:	(HT1.0) 5.78m (HT,SW 1.5) 6.46m
Gradeability:	50%
Tyres:	10.0 / 75 / 15.3 (traction Profile)
Steering:	Priority load sensing
Working brakes:	Hydrostatic retardation
Park brake:	Automatic in rear wheel motors

NOISE LEVELS:	
LWA	99dB(A)
LPA	82dB(A)

TANK CAPACITIES:	
Fuel:	28L
Hydraulic:	24L

SKIP:	
Hydraulically operated tipping skip	
Heavy duty skip with 5mm thick steel	

ELECTRICAL:	
Heavy duty H075 Battery: 12V, 550CCA, 60Ah	
Wiring harness in protective sleeving	
Reversing alarm	

HYDRAULICS:	
Automotive control hydrostatic pump	
8cc Gear pump	
Hydraulic test points fitted as standard	
Easy access return oil filter on top of tank	

SEATING & CONTROLS:	
Adjustable suspension seat	
Clear access across dumper	
Super bright instrument display	
Steel console for extra leg protection	
Column mounted directional control lever	
Anti-slip floor	

SERVICE ACCESS:	
Easy access for service maintenance	
Lockable hinged engine cover	
Battery mounted inside the engine bay	

Optional Extras

Base unit:
Hardox Skip
Special Colour RAL (yellow parts only)

Safety:
Green Light Seat belt warning System
Road lighting
7 pin Towing Socket
Scharmuller Tow Hitch
Wheel Choc
Mirrors

Tyres:
Narrow Access 700 x 12 (HT1.0 only)
Grass Pattern 10 X 75 X 15.3

Environment:
Panolin Bio in Lieu of HVI 46

Security:
Cesar Datatag
Telematic Tracking



Rev 3.0 - August 2019



NC Engineering (Hamiltonsbawn) Ltd
2 Killyrudden Road
Hamiltonsbawn, Richhill
Co. Armagh
Northern Ireland
BT61 9SF
Tel: +44 (0) 28 38 871970
Fax: +44 (0) 28 38 870362
E-Mail: sales@nc-engineering.com
Web: www.nc-engineering.com

www.nc-engineering.com

Site Dumpers

HT1.0
HT1.5
SW1.5



www.nc-engineering.com



Clear dashboard layout



Twin lever control



Excellent service access



Protected hose lines



Unrivalled operator protection

Folding ROPS

Single pedal control



Joystick control

Twin cylinder power swivel



180° Swivel



Fully adjustable seat with recoil safety belt

Heavy duty parallel linkage

Twin lift cylinders



Galvanised ergonomic steps



Four wheel drive Twinlock system



5mm Skip

NC HT 1.0