Machine learning for porous materials

ML MolSim foundations

Advanced Methods in Digital Chemistry
11 November 2026
Kevin Maik Jablonka

Understanding the MOF gas-prediction notebook

Recorded summary (Loom)

Our first marimo notebook

00-getting-started.py

Change one input. Predict which cells will change.

```
concentration = 2.0
prediction = slope * concentration + intercept
```

Save your own notebook copy.

Where machine learning enters

Structure — Interactions — Simulation — **Uptake**

Descriptors — Learned surrogate — **Predicted uptake**

Our labels come from completed simulations.

What are we trying to predict?

X —— **Model** —— **y**

Geometric descriptors

Simulated CO_2 uptake

298 K, 16 bar, mmol/g

A structure becomes a row of numbers

Structure

Descriptors

Material	Density	Pore volume	Pore size
A			
B			

8 inputs: 3 pore diameters, density, 2 surface areas, 2 pore volumes

Which chemical information have we discarded?

A split defines the prediction task

Training: 900	Validation: 300	Test: 300
Fit	Choose	Assess

What counts as a genuinely new material?

Fitting adjusts the model parameters

$$\hat{y} = w_0 + w_1 x$$

Predictions



Training loss



Compare with training targets, then update the parameters.

Several descriptors give a linear model

$$\hat{y}_i = w_0 + w_1 x_{i1} + \ldots + w_p x_{ip}$$

Here: 8 geometric descriptors

The model fits the weights and intercept using training rows.

A baseline and one error calculation


Baseline: median training uptake

MAE = mean absolute prediction error

Residuals: –2, 0, +1 mmol/g

MAE =

Training error can keep falling



Which curve will predict the next observation?

Regularisation constrains the fit

Fitting objective = training loss + α × penalty

Small α

Large α

Validation helps choose the strength α.

Nonlinear features can bend a linear model

Features: x, x^2

$$\hat{y} = w_0 + w_1 x + w_2 x^2$$



Linear in the
fitted coefficients

A kernel gives us a way to work with a richer feature space.

The Gaussian kernel compares descriptor vectors


$$k(x, z) = \exp(-\gamma \, \|x - z\|^2)$$

x and z each contain the same 8 descriptors.

Larger γ gives a narrower neighbourhood.

A kernel describes similarity

One contribution centred on each training input



Width changes
what “near” means.

A kernel prediction adds fitted contributions

Training point	Fitted coefficient	Similarity to query	Contribution
1	2	0.8	
2	−1	0.2	
3	3	0.05	

Prediction =

Illustrative numbers, arbitrary target units

Units change numerical distances

Difference in density	**0.1 g/cm^3**
Difference in surface area	**100 m^2/g**

Squared distance =

Standardisation uses training statistics

$$z = (x - \mu) / \sigma$$

One mean and standard deviation for each feature

μ and σ come from the training data.

Validation and test use the same transformation.

A pipeline keeps scaling and fitting together

Training rows —— Fit scaler —— Fit model

Validation rows —— Transform —— Predict and score

make_pipeline(StandardScaler(), KernelRidge(...))

Validation and test use the scaler fitted on training rows.

Validation chooses the settings

Training data

Fit model parameters

Validation data

Compare candidate settings

Test data stay outside this decision.

The notebook compares four candidates

Model	Scaling	Prediction	Validation MAE
Training median	None	Constant	
Ridge	Training statistics	Linear	
KRR	None	Gaussian kernel	
KRR	Training statistics	Gaussian kernel	

Ridge and KRR: $\alpha = 1$. Both KRR candidates: $\gamma = 0.1$.

Which comparison isolates the effect of scaling?

Cross-validation repeats the comparison

Fit 1	Validate	Train	Train	Train	Train
Fit 2	Train	Validate	Train	Train	Train
Fit 3	Train	Train	Validate	Train	Train
Fit 4	Train	Train	Train	Validate	Train
Fit 5	Train	Train	Train	Train	Validate


Held-out scores

Mean =


CV extends the notebook’s single validation split.

Reading the notebook’s prediction plots

Parity plot



Residual plot



Validation rows. All values in mmol/g.

The final test answers a narrower question

Record the model choice, then reveal the test result.

Which materials does this result describe?

300 held-out rows. MAE in mmol/g.

Hands-on with the ML MolSim material

03-mof-uptake.py

Baseline

Unscaled and scaled KRR

Record the validation comparison before the test.

Supported practical: 2 December, 12:00–16:00

A project starts with a chemical question

What would you like to find out?

Which data could you use?

What would be a useful first comparison?

Add an idea to the document in the course email.