Machine learning for porous materials

Advanced Methods in Digital Chemistry
11 November 2026, 12:10–16:00
Kevin Maik Jablonka

Understanding the MOF gas-prediction notebook

The uv commands we will use

macOS/Linux: Terminal. Windows: Ubuntu in WSL 2.
Use your usual browser, including your Windows browser with WSL.

`cd digital-chemistry-course`	Enter the extracted folder
`uv --version`	Check that uv is installed
`uv sync --locked`	Install the course environment
`uv run --locked marimo edit --headless`	Start the local notebook server

uv uses uv.lock by default; --locked requires it to be up to date.

--headless: start the server without automatically opening a browser.

Open the printed URL in your browser. Save; Ctrl+C stops marimo.

Our first marimo notebook

00-getting-started.py

Change one input. Predict which cells will change.

```
concentration = 2.0
prediction = slope * concentration + intercept
```

Save your own notebook copy.

Where machine learning enters

Structure — Interactions — Simulation — **Uptake**

Descriptors — Learned surrogate — **Predicted uptake**

Our labels come from completed simulations.

A published MOF prediction study

Article | Open access | Published: 13 August 2020

Understanding the diversity of the metal-organic framework ecosystem

Seyed Mohamad Moosavi, Aditya Nandy, Kevin Maik Jablonka, Daniele Ongari, Jon Paul Janet, Peter G. Boyd, Yongjin Lee, Berend Smit & Heather J. Kulik

Nature Communications **11**, Article number: 4068 (2020) | Cite this article

Shared ingredients

Structural descriptors
Kernel ridge regression
Standardisation
Held-out evaluation

Paper: geometry + RACs, several adsorption tasks

Our practical: 8 geometric features, CO_2 uptake at 16 bar

Moosavi et al., Nature Communications 11, 4068 (2020). doi.org/10.1038/s41467-020-17755-8

Article screenshot, cropped. CC BY 4.0: creativecommons.org/licenses/by/4.0/

What are we trying to predict?

X —— **Model** —— **y**

Geometric descriptors

Simulated CO_2 uptake

298 K, 16 bar, mmol/g

A structure becomes a row of numbers

Structure

Descriptors

Material	Density	Pore volume	Pore size
A			
B			

8 inputs: 3 pore diameters, density, 2 surface areas, 2 pore volumes

Which chemical information have we discarded?

RACs add chemistry to the representation

Revised autocorrelations describe the bonding graph.

Atomic properties

Bond distances

Combine products or differences within selected graph environments.

Original MolSim: geometry + RACs

Compact class notebook: 8 geometric features

Why we split the data

Training: 900	Validation: 300	Test: 300
Fit	Choose	Assess

Fitting uses the training answers to reduce their error.

Held-out rows test predictions on answers unused in fitting.

What counts as a genuinely new material?

Fitting adjusts the model parameters

Predictions



Training loss



Compare with training targets, then update the parameters.

Several descriptors give a linear model

Here: 8 geometric descriptors

The model fits the weights and intercept using training rows.

A baseline and one error calculation

Baseline: median training uptake

MAE =

A test error is an empirical estimate

What we want to know


Average error over future MOFs from the intended population.

What we can calculate

Average error on 300 reserved rows.

Keep the model fixed. A new test sample can give a different estimate.

Training error can keep falling



Which curve will predict the next observation?

Bias and variance explain different failures

Bias

The average fit misses
the relationship.



Variance

The fit changes when
the training sample changes.



Draw fresh training sets and refit the same learning procedure.

Regularisation constrains the fit

Ridge example

Weak regularisation


Strong regularisation

Validation helps choose the regularisation strength.

Why add nonlinear features?

One feature


One threshold cannot separate the two groups.



Feature map

Add a squared feature

Now a straight boundary can separate the same points.



For regression

Toy classification example. Feature expansion can also give curved regression fits.

The kernel trick avoids explicit feature expansion

Two input coordinates become three feature coordinates.

Evaluate the inner product without constructing the features.

Two calculations give the same kernel value

Vectors to compare

Using expanded features

Using the original coordinates


The Gaussian kernel compares descriptor vectors

x and z each contain the same 8 descriptors.

Larger gamma gives a narrower neighbourhood.

A kernel describes similarity

One contribution centred on each training input



Width changes
what “near” means.

A kernel prediction adds fitted contributions

Training point	Fitted coefficient	Similarity to query	Contribution
1	2	0.8	
2	−1	0.2	
3	3	0.05	

Prediction =

Illustrative numbers, arbitrary target units

Units change numerical distances

Difference in density	**0.1 g/cm^3**
Difference in surface area	**100 m^2/g**

Squared distance =

Standardisation uses training statistics

One mean and standard deviation for each feature

Estimate both statistics from the training rows.

Validation and test use the same transformation.

A pipeline keeps scaling and fitting together

Training rows ——— Fit scaler ——— Fit model

Validation rows —— Transform ——— Predict and score

make_pipeline(StandardScaler(), KernelRidge(...))

Validation and test use the scaler fitted on training rows.

Validation chooses the settings

Training data

Fit model parameters

Validation data

Compare candidate settings

The lowest validation error can partly reflect luck.

Use validation to choose; use the untouched test to assess.

The notebook compares four candidates

Model	Scaling	Prediction	Validation MAE
Training median	None	Constant	
Ridge	Training statistics	Linear	
KRR	None	Gaussian kernel	
KRR	Training statistics	Gaussian kernel	

Ridge: alpha = 1. Both KRR models: alpha = 1, gamma = 0.1.

Which comparison isolates the effect of scaling?

Cross-validation repeats the comparison

Fit 1	Validate	Train	Train	Train	Train
Fit 2	Train	Validate	Train	Train	Train
Fit 3	Train	Train	Validate	Train	Train
Fit 4	Train	Train	Train	Validate	Train
Fit 5	Train	Train	Train	Train	Validate


Held-out scores

Mean =


CV extends the notebook's single validation split.

Reading the notebook's prediction plots

Parity plot



Residual plot



Validation rows. All values in mmol/g.

The final test answers a narrower question

Record the model choice, then reveal the test result.

Which materials does this result describe?

300 held-out rows. MAE in mmol/g.

Hands-on with the ML MolSim material

03-mof-uptake.py

Baseline

Unscaled and scaled KRR

Record the validation comparison before the test.

Explore the MOF notebook whenever you are ready
Optional group help: week of 16 November, details to follow
Continue together: 2 December, 12:00–16:00

A project starts with a chemical question

What would you like to find out?

Which data could you use?

What would be a useful first comparison?

Add a project idea to the shared document.

Feedback: what helped, what was unclear, how was the pace?