Why the $\forall\mathsf{PO}$-Free Fragment Is Decidable

A Guide for the Tableau-Minded

Michael Wessel — with Claude Opus 4.8 and Claude Opus 5 (Anthropic)*

2026-08-29, revised 2026-09-14, 2026-10-08 and 2026-11-11

*Opus 4.8 wrote this explainer in July 2026; Opus 5 revised it in August after the fragment was machine-certified, in September after a further cold review, and in October after the Astra 6 review; Claude Fable 5.2 corrected and updated it in November 2026. The routes it describes are due to several models and are attributed individually in §8.

A companion to the $\mathcal{ALCI}_{\mathrm{RCC5}}$ decidability project, pitched one level more technical than `WHY_ITS_HARD.md`*: for a reader who knows basic description logics, tableau calculi, and blocking, but not automata theory or model theory. The goal is not to walk you through the proofs — it is to put enough intuition and enough hard, checkable facts in front of you that you can honestly say "yes, I believe that."*

Honesty note (updated 2026-08-29): *the fragment is now* ***machine-certified decidable across all four quadrants****, including the mixing one (*$\exists\mathsf{PO} + \exists\mathsf{PP}$*) that was open when this explainer was first written. The capstones are in Lean 4 (*`formal/POFreeLift.lean`*, ∼45,400 lines,* ***zero sorries****, axioms* `propext/Classical.choice/Quot.sound`*): `decidableFSat` on* raw *input with negation, `decidableSat_cone` on NNF concepts, and `decidableSetSat` under* concrete set *semantics — with fragment membership the only hypothesis in each. They were reached by a* third *route, distinct from the two argued in this explainer: a finite control graph of signatures, a monotone elimination to a greatest fixed point, and a fresh-occurrence unfolding in which no node is ever reused. It does not use the $K(C_0)$ bound, so the two arguments here remain theorem-level and independently worth reading. Three independent cold reviews (2026-08-29) attacked the trusted base, completeness, and soundness respectively, and* ***none found a counterexample or a defect in the fragment result****.* Full-logic *decidability stays* ***open****. One caveat is complexity, not correctness: the procedure is decidable but* ***not runnable****, the signature space being doubly exponential. This supersedes the 2026-08-06 "three of four quadrants" status; see* `ASSEMBLY_DESIGN.md` *§§267–297.*

Update (2026-09-14): *the certified result now has its own focused paper,* `papers/pofree_fragment_arxiv.pdf`*. Two published theorems of Lutz and Wolter (2006) are credited there and here: every RCC5 structure is representable by regions (their Theorem 23, of which the certified abstract-versus-sets equivalence is a special case), and the logic coincides with its substructure logic over regular closed regions of $\mathbb{R}^n$ (Theorem 24), so the fragment result holds verbatim in that topological reading too.*

Update (2026-10-08): *an external review by Astra 6 proved, and the artifact now certifies (`erase_equisat`, `decidableSat_dfrag`, §299), a strict extension: concepts* containing $\forall\mathsf{PO}$ *are also decided, provided $\exists\mathsf{PP}$, $\exists\mathsf{PO}$ and $\forall\mathsf{DR}$ are absent — erase each $\forall\mathsf{PO}.D$ to $\top$ and run the certified procedure. Inside that fragment the $\forall\mathsf{PO}$ restrictions are provably vacuous (the witness forest has no PO pair at all), so the boundary story of this explainer is unchanged: $\forall\mathsf{PO}$ is harmless exactly where it cannot bite. (Since 2026-11-11 a slice in which it does bite is decided by import; see the next update.)*

Update (2026-11-11; unreviewed): *one further session changed what is known just* outside *the fragment; nothing certified here is affected (`POFreeLift.lean`, now* 46,032 *lines, is unchanged). (i) The concepts that use* $\exists\mathsf{DR}$ *only inside* $\exists\mathsf{PO}.C \sqcup \exists\mathsf{DR}.C$ *and* $\forall\mathsf{PO}$ *only inside* $\forall\mathsf{PO}.C \sqcap \forall\mathsf{DR}.C$ *have the same satisfiability problem as two-variable logic over strict partial orders with unary predicates (Lean: `poset_bridge`, `patsys_to_rcc5` in `formal/PosetBridge.lean`; one textbook normal-form step is not formalized). General satisfiability of that logic is open, so the full logic contains an open problem of two-variable logic; no reduction the other way is known. (ii) Through that bridge two slices containing* $\forall\mathsf{PO}$ *are decided by published theorems — not by this project and not in Lean — and in one of them a* $\forall\mathsf{PO}$ *conjunct can change the answer, unlike in the erasure fragment above. (iii) Outside the fragment infinity needs no vertical witness. That was already in the 2003 report (its §5.2); a second such concept, with no* $\exists\mathsf{PP}$ *and no* $\exists\mathsf{PPI}$ *and inside the fragment of (i), is now Lean-checked. (iv) The cover-tree tableau is incomplete: it answers* UNSAT *on a satisfiable concept that contains* $\forall\mathsf{PO}$*; and a cited theorem on two-variable logic turned out to have been withdrawn. See `ERRATA.md` and `papers/poset_bridge/README.md`.*

1 The claim

Theorem (∀PO-free fragment). Concept satisfiability for the $\forall\mathsf{PO}$-free fragment of $\mathcal{ALCI}_{\mathrm{RCC5}}$ — concepts in NNF containing **no subformula of the form** $\forall\mathsf{PO}.D$ — is decidable, with a computable live-width bound $K(C_0) = (1+m)^2\, 2^{2^m}$, where $m = |\mathrm{cl}(C_0)|$.

On raw input. Stating the fragment over NNF concepts is not a restriction, but the correct condition on *raw* concepts is polarity-sensitive and is easy to get wrong: pushing a negation through $\exists\mathsf{PO}.D$ produces $\forall\mathsf{PO}$, so the condition is **no** $\forall\mathsf{PO}$ **in positive position and no** $\exists\mathsf{PO}$ **in negative position**. The certified route carries the normalization and the preservation theorem, so this is a theorem rather than a convention (`nnfP_correct`, `decidableFSat`).

Read the fine print, because it is generous. The fragment **keeps**:

- $\exists\mathsf{PO}.D$ — "overlaps something satisfying D";
- $\forall\mathsf{DR}.D$ and $\exists\mathsf{DR}.D$ — universal *and* existential disjointness;
- all vertical modalities — $\exists\mathsf{PP}$, $\forall\mathsf{PP}$, $\exists\mathsf{PPI}$, $\forall\mathsf{PPI}$, nested to any depth;
- infinite models — $\exists\mathsf{PP}.\top \sqcap \forall\mathsf{PP}.\exists\mathsf{PP}.\top$ is in the fragment and is satisfiable only in models with an infinite ascending PP-chain.

The *only* thing removed is the universal restriction over partial overlap. That is a strikingly thin excision, and the whole story of this document is why the difficulty that has defeated every full-logic attempt is concentrated in exactly that one constructor.

A calibration point that matters: the fragment is **not** a toy that dodges the hard diagnostics. The concept

$$C_{\mathrm{force}} \;=\; \exists\mathsf{PP}.(\exists\mathsf{DR}.A) \sqcap \forall\mathsf{DR}.\neg A$$

is $\forall\mathsf{PO}$-free and UNSAT — because $x\,\mathsf{PP}\,y$ and $y\,\mathsf{DR}\,z$ *force* $x\,\mathsf{DR}\,z$ ($\mathrm{comp}(\mathsf{PP},\mathsf{DR}) = \{\mathsf{DR}\}$), and then $\forall\mathsf{DR}.\neg A$ kills the required $z : A$. Every naive tableau that ignores forced edges accepts it wrongly. So a decision procedure for the fragment must still do genuine composition-table reasoning; it just never has to fight the one battle that has defeated every full-logic attempt.

2 The setting, and why your tableau instincts don't directly apply

Three facts about $\mathcal{ALCI}_{\mathrm{RCC5}}$ that break the standard playbook. (Strong-EQ semantics throughout: EQ means identity, so between distinct elements only $\mathsf{DR}, \mathsf{PO}, \mathsf{PP}, \mathsf{PPI}$ occur.)

Fact 1: every model is a complete graph. The five RCC5 relations are jointly exhaustive and pairwise disjoint. Any two elements of any model stand in exactly one of them — there is no "unrelated." In $\mathcal{ALC}$, a tableau builds a *tree* and elements in different branches simply have nothing to do with each other. Here, every pair of nodes you ever create carries a relation, whether you asked for it or not, and the composition table

$$\rho(x, z) \in \mathrm{comp}(\rho(x, y), \rho(y, z)) \qquad \text{for all } x, y, z$$

constrains all of them, globally. Adding one node adds n new edges, each of which must close every triangle it participates in.

Fact 2: no finite model property. $\exists \mathsf{PP}.\top \sqcap \forall \mathsf{PP}.\exists \mathsf{PP}.\top$ forces an infinite strictly ascending chain of regions (PP is a strict order under strong EQ — a PP-cycle would collapse by composition into $x\ \mathsf{PP}\ x$, which is impossible). So you cannot hope to enumerate finite models: satisfiable concepts may have none.

Fact 3: local blocking is unsound or incomplete. In $\mathcal{ALC}$, blocking works because "same label set" means "same future obligations." Here a node's future obligations depend on its relations to *the whole graph built so far* (Fact 1), which no fixed-arity local summary captures. The project tried subset blocking, triangle blocking, quadruple types, profile blocking, double blocking — each fails on a concrete diagnostic. This is not a technicality; it is the same obstruction the full logic's open width question (F6) runs into.

Without blocking, the tableau instinct does work, as a semi-decision procedure. The complete-graph tableau of Wessel's MiDeLoRa system, with EQ as identity, is sound and complete: it answers on every unsatisfiable concept and on every concept with a finite model, and runs forever exactly on the satisfiable concepts all of whose models are infinite (a paper proof, unreviewed, typeset in the overview paper and in `papers/midelora_calculus/`; a Python re-implementation is `src/midelora_tableau.py`). Termination is blocking, and a sound blocking condition for the full logic is the open problem.

So the fragment result has to earn its termination some other way. That way is the *finite-certificate architecture*, and it is worth understanding on its own before either proof route, because both routes are instances of it.

3 The architecture: finite certificates for infinite models

When models are legitimately infinite, "decidable" cannot mean "search for a model." It means:

> **Replace "model" by "finite blueprint of a model," so that (a) a computer can enumerate and check blueprints, (b) every blueprint that checks out**

really describes a model, and (c) every satisfiable concept has a blueprint of computably bounded size.

Call the blueprint a **certificate**. A decidability proof in this architecture always has exactly three parts:

1. **A finite certificate format** with finitely many *finitely checkable* conditions (type coherence, witness presence, triangle closure on the finite object, ...). Checking a candidate certificate is trivially decidable.
2. **Soundness (unfolding).** If a certificate passes the checks, the possibly-infinite structure it *generates* — obtained by unrolling its loops — is a genuine model of the concept. This is the direction that must not cheat: the checks are finite, the generated object is infinite, and you must prove the finite checks control the infinite unfolding.
3. **Completeness (extraction + compression).** If the concept has *any* model, you can extract from it a certificate within the computable size bound. This is where "run out of colors" pigeonhole arguments live — and where a bound on the certificate's size must come from.

Given all three, the decision procedure is embarrassing: enumerate all certificates up to the bound, check each, answer SAT iff one passes. All the mathematics is in (2) and (3); the algorithm itself is a for-loop.

Four remarks that make this concrete for a tableau reader.

A blocked tableau *is* a certificate. When your $\mathcal{ALC}$ tableau stops because node y is blocked by ancestor x, the finished tree with its blocking pointers is precisely a finite certificate: the "model" it describes is the infinite unraveling in which y's subtree "continues like x's." Soundness of blocking = the unfolding lemma. So the architecture is not exotic; it is what blocking always secretly was.

Loops are generators, not quotients. One subtlety is promoted to a design principle here. The blocking loop must be read as "*the pattern continues like this*" (unfold the loop into infinitely many distinct copies), never as "*y equals x*" (bend the edge back). Under strong EQ the second reading is inconsistent for vertical loops — it would make a region a proper part of itself. The certificate has a PP-self-loop; the model it generates has an infinite chain of *distinct* elements. Finite generator, infinite unfolding, no finite quotient.

Under abstract semantics, model-checking is triangle-checking. A gift of the composition-table semantics: an interpretation is *any* set with a total labelling ρ satisfying (i) $\rho(d, d) = \mathsf{EQ}$ and strong EQ, (ii) converse coherence, (iii) composition closure. Nothing else. So "the unfolding is a model" reduces to "every triangle of the unfolding is closed under the table" — a purely combinatorial statement, exactly the kind of thing one can prove by case analysis on where the three corners sit, and exactly what is kernel-checked in `POFreeLift.lean`. (For networks that are only partially specified, RCC5's *patchwork property* — path-consistent atomic networks are globally consistent, Renz–Nebel 1999 — completes the missing edges; for a fully labelled unfolding the network *is* the model outright.)

Live width: what has to be bounded. The size bound in (3) is the whole game. The key observation is that most of a certificate's edges cost nothing: an edge whose value is *forced* by composition from other edges (a "shadow") need not be stored or chosen — it is recoverable. What must be bounded is the number of **live** edges: genuinely free choices attached to each part of the certificate. The conjecture that every satisfiable $\mathcal{ALCI}_{\mathrm{RCC5}}$ concept admits a presentation of computably bounded live width is **F6** — the open keystone of the project's principal full-logic certificate route. It is *not* itself a Lean hypothesis: the certified conditional theorem assumes a complete enumeration of certificates, and F6 is the argued but unformalized route to that premise. **The $\forall\mathsf{PO}$-free fragment is the place where a live-width bound is proved** (at theorem level, by both routes below) rather than conjectured — though the route that finally certified the fragment needs no width bound at all.

With the architecture fixed, both proofs of the fragment theorem can be stated in one sentence each:

- **Route 1 (two-tier quotient):** vertical blocking gives a finite set of chain-descriptors; the composition table makes every witness's relation to a chain *stabilize*, so one certificate edge can honestly summarize infinitely many model edges — for $\mathsf{DR}, \mathsf{PP}, \mathsf{PPI}$ always, and for PO exactly when no $\forall\mathsf{PO}$ constraint watches.
- **Route 2 (ordered-disjoint normal form):** an RCC5 model *is* just a strict order plus a well-behaved disjointness relation, with PO as the unconstrained residual; $\forall\mathsf{PP}/\forall\mathsf{PPI}/\forall\mathsf{DR}$ obligations are order- and disjointness-closure conditions that propagate deterministically, and no propagation ever manufactures a $\forall\mathsf{PO}$ obligation — so a standard tree tableau with blocking terminates.

The rest of this document unpacks those two sentences.

4 The algebraic heart: four forced cells, and the relation that is never forced

Everything in both routes reduces to a handful of cells of the RCC5 composition table. You can check each mentally with blobs, and each is machine-verified from finite set semantics (and, for those used in the Lean artifacts, kernel-checked).

The four singleton cells among proper relations:

$$\begin{aligned}
\mathrm{comp}(\mathsf{PP}, \mathsf{PP}) &= \{\mathsf{PP}\} && \text{nesting is transitive}\\
\mathrm{comp}(\mathsf{PPI}, \mathsf{PPI}) &= \{\mathsf{PPI}\} && \ldots \text{in both directions}\\
\mathrm{comp}(\mathsf{PP}, \mathsf{DR}) &= \{\mathsf{DR}\} && \text{a part of something disjoint from } e \text{ is disjoint from } e\\
\mathrm{comp}(\mathsf{DR}, \mathsf{PPI}) &= \{\mathsf{DR}\} && \ldots \text{converse form}
\end{aligned}$$

The third one deserves a picture: if the table is far from the moon, the coin *on* the table is far from the moon. Disjointness rains **down** into parts, deterministically. Together with transitivity of nesting, these four cells are the *only* deterministic machinery the whole algebra offers between distinct proper relations.

The two cells that define the problem:

$$\text{comp}(\mathsf{PP}, \mathsf{PO}) = \{\mathsf{PP}, \mathsf{PO}, \mathsf{DR}\}, \qquad \text{comp}(\mathsf{PPI}, \mathsf{PO}) = \{\mathsf{PPI}, \mathsf{PO}\} \qquad \text{— not singletons.}$$

Picture the first: a cake y partially overlaps a plate e. Now take a crumb x of the cake ($x\ \mathsf{PP}\ y$). Where is the crumb relative to the plate? Maybe on the plate (PP), maybe straddling its rim (PO), maybe on the tablecloth (DR). *Partial overlap tells you nothing determinate about parts.* The second cell is the upward version: if something inside y overlaps e, then y overlaps e or contains it — two options, not one.

And one global fact you can scan the whole table for:

No cell of the table equals {PO}. Partial overlap is never the uniquely forced outcome of any single composition. DR is forced by two cells, PP and PPI by transitivity — but no *single* path x–y–z ever pins $x\ \mathsf{PO}\ z$. PO is forced by nothing.

And the dual: PO is available wherever anything is. Scan the table again: every *non*-singleton proper cell **contains** PO — and this propagates along paths (of the ten composition-sets reachable by composing along paths of any length, every non-singleton one contains PO; machine-checked, `wp26`). Moreover every entry of the PO row and column contains PO, and $\text{comp}(\mathsf{PO}, \mathsf{PO})$ is everything — so PO, once present, stays available in every direction, and an all-PO region constrains nothing. Put the two facts together and every pair of elements faces a clean dichotomy: either some composition path *pins* it (a singleton — forced, deterministic, a recoverable "shadow"), or **PO is among its options**. PO is the algebra's escape valve: never forced on you, always offered where anything is. The only way a logic can close that valve is to make PO-edges *illegal* — and the only constructor that can do so is $\forall\mathsf{PO}$. That, in one sentence, is why its removal is worth a decidability theorem: in the fragment, the escape valve is structurally un-closable, and the unfolding's unboundedly many unpinned pairs all take the value that is always permitted and never watched.

Calibration, learned the hard way. That last fact is about *single* compositions. The *intersection* of several path constraints CAN force a PO edge — e.g. $\text{comp}(\mathsf{DR}, \mathsf{PO}) \cap \text{comp}(\mathsf{PPI}, \mathsf{PO}) = \{\mathsf{DR}, \mathsf{PO}, \mathsf{PP}\} \cap \{\mathsf{PPI}, \mathsf{PO}\} = \{\mathsf{PO}\}$. An earlier version of the project's prose overstated "PO is never forced," and a cold review caught it (the 16th, with a concrete two-path witness). Neither proof route below relies on the overstated version: both enforce *full* composition closure on every triangle, which subsumes multi-path forcing. Where "PO is loose" is used below, it is always in the precise single-cell sense above.

Yes, PO can be forced — and it is harmless. Do not read the caveat as fragility. Even inside the fragment, PO edges can be pinned: algebraically by joint paths (above), and logically by the *allowed* universals clashing out the alternatives. In

$$C \;=\; \forall\mathsf{PP}.\neg A \sqcap \forall\mathsf{DR}.\neg A \sqcap \exists\mathsf{PP}.(\neg A \sqcap \exists\mathsf{PO}.A)$$

the demanded $e : A$ sits at $\text{comp}(\mathsf{PP}, \mathsf{PO}) = \{\mathsf{PP}, \mathsf{PO}, \mathsf{DR}\}$ from the root; $\forall\mathsf{PP}.\neg A$ strikes PP, $\forall\mathsf{DR}.\neg A$ strikes DR, and $\rho(\text{root}, e) = \mathsf{PO}$ is *forced* (and the concept is satisfiable — $x = \{1, 2\}$, $y = \{1, 2, 3\}$, $e = \{2, 3, 4\}$). So the fragment can steer edges *into* PO. Why is that safe, when

steering was the full logic's downfall? Because a forced PO edge is **doubly inert**. *Logically inert:* the only constructor that fires on a PO edge — at either endpoint; PO is self-converse and the safety test is two-sided — is ∀PO, and none exists in the input or in any label that propagation will ever write (§6). The forced edge lands, and nothing happens. *Compositionally, it never forces onward alone:* PO is an argument of **no** singleton cell (look at the four: PP; PP, PP; DR, PPI; PPI, DR; PPI — PO appears in none), so a PO edge never single-handedly pins another edge; it can narrow options in joint configurations, and full triangle closure tracks exactly that. Contrast forcing DR: a forced DR edge can fire a waiting ∀DR at its far endpoint — that is literally C_{force} — real consequences, but *deterministic* ones the singleton cells propagate. Forcing PO has no consequences at all. Steering into the watched relations is trackable; steering into the unwatched one is a dead end for any adversarial concept.

Now the punchline of the whole section. A universal restriction $\forall R.D$ is a *standing obligation*: it must hold of every R-neighbor, including R-neighbors that arise *indirectly*, forced by composition, at any distance, at any time. Whether such an obligation is manageable depends entirely on whether the algebra moves R-neighbors around predictably:

- $\forall \mathsf{DR}.D$ **is manageable** because DR propagates deterministically downward ($\text{comp}(\mathsf{PP}, \mathsf{DR}) = \{\mathsf{DR}\}$): the set of DR-neighbors of a region grows in a controlled, forced, *monotone* way as you descend the nesting order. You always know where the obligation will land next.
- $\forall \mathsf{PP}.D$ **and** $\forall \mathsf{PPI}.D$ **are manageable** for the same reason via transitivity.
- $\forall \mathsf{PO}.D$ **is the wild one**: PO-neighborhoods are not transported determinately in *either* vertical direction (the two non-singleton cells), and PO is never created by any single composition — so the obligation must be re-verified against a set of neighbors that the algebra refuses to pin down. The recurring failure shape across this project's twenty-two-review history — jointly coordinating horizontal edges against universal obligations at a gluing step — is only *hard* for edges no singleton cell controls; and PO is the relation with no singleton cell anywhere.

The fragment theorem is the statement that once ∀PO is gone, the remaining obligations are exactly the ones the four singleton cells can carry. Two independent routes cash this in.

5 Route 1: the two-tier quotient (the chain-and-phase argument)

(Sources, under `papers/`: `two_tier_quotient_ALCIRCC5.tex` — Claude, April 2026, four revisions under GPT-5.4 review — and the fragment specialization `po_free_fragment_ALCIRCC5.tex`. Soundness crux certified 2026-07-18 in `formal/POFreeLift.lean`.)

5.1 The certificate

Since models contain infinite PP-chains, start where the infinity is. Walk up an infinite chain $d_0\ \mathsf{PP}\ d_1\ \mathsf{PP}\ d_2 \cdots$ and record each element's Hintikka type. There are at most 2^m types, so the sequence of types is eventually periodic — familiar pigeonhole, exactly the intuition behind blocking. Call the recurring cyclic pattern of types $(\tau_1, \ldots, \tau_p)$ a **period descriptor**. There are at most 2^{2^m} descriptors.

The certificate ("two-tier quotient") is:

- **Tier 1:** finitely many period descriptors, one **kernel** node per descriptor carrying its cyclic type pattern with a PP-self-loop (a generator: unfolds to the infinite chain, per §3);
- **Tier 2:** finitely many **designated witnesses** — at most one per existential demand per descriptor — with **one constant relation** recorded between each witness and each kernel: a single edge "kernel $\leftrightarrow e : R$".

Plus finite checks: types are Hintikka, every $\exists$ demand has its witness, every recorded triangle is composition-closed, every recorded edge respects the universals in both endpoint types (the Safe test).

5.2 The crux: when can one edge summarize infinitely many?

Here is the exact point where this differs from $\mathcal{ALC}$ blocking, and where the reader should slow down. When the kernel unfolds into the infinite chain $d_0\,\mathsf{PP}\,d_1\,\mathsf{PP}\cdots$, the certificate's single edge "kernel $\leftrightarrow e : R$" must stand for *infinitely many* model edges: $\rho(d_i, e)$ for every i. The certificate records one value; the model needs a value at every rung. For the summary to be honest, the witness's relation to the chain must be **the same at every rung that matters** — otherwise a finite certificate with constant interfaces simply cannot express the model.

Does the algebra cooperate? Watch a fixed external region e against a growing chain $d_0 \subset d_1 \subset d_2 \subset \cdots$, using $\mathrm{comp}(\mathsf{PPI}, \cdot)$ to step up the chain:

$$\begin{aligned} \text{from } \mathsf{DR}: &\ \text{next} \in \{\mathsf{DR}, \mathsf{PO}, \mathsf{PPI}\} \\ \text{from } \mathsf{PO}: &\ \text{next} \in \{\mathsf{PO}, \mathsf{PPI}\} \\ \text{from } \mathsf{PPI}: &\ \text{next} \in \{\mathsf{PPI}\} \quad \text{(absorbing)} \\ \text{from } \mathsf{PP}: &\ \text{next} \in \{\mathsf{PP}, \mathsf{PO}, \mathsf{PPI}\} \end{aligned}$$

Read it as a picture: the chain elements grow; a fixed e can go from disjoint, to overlapping, to *swallowed* (PPI) — and never backward. The relation **stabilizes**: after finitely many monotone switches it is constant forever. This is the "external-relation stabilization" lemma, and it is checkable from the table by eye.

Stabilization alone is not enough — the certificate needs the relation to be right at *all* phases, not just eventually. This is where the singleton cells become load-bearing, one relation at a time:

- DR — **backward forcing.** Suppose an $\exists$DR-demand is satisfied by witness e at a late chain position d_i. Then for every earlier $j < i$: $d_j\,\mathsf{PP}\,d_i$ and $d_i\,\mathsf{DR}\,e$ give $\rho(d_j, e) \in \mathrm{comp}(\mathsf{PP}, \mathsf{DR}) = \{\mathsf{DR}\}$. **Forced.** A DR-witness picked late enough (past the point where all recurrent types have appeared) is automatically a DR-witness at every phase. The constant edge "kernel $\leftrightarrow e : \mathsf{DR}$" is honest, for free.
- PP — **same cell, same argument.** If e contains d_i, then by $\mathrm{comp}(\mathsf{PP}, \mathsf{PP}) = \{\mathsf{PP}\}$ it contains every d_j below. Constant edge honest.
- PPI — **forward absorption.** If e is inside d_i, it is inside every d_j above ($\mathrm{comp}(\mathsf{PPI}, \mathsf{PPI}) = \{\mathsf{PPI}\}$). Constant edge honest.

So for $\mathsf{DR}, \mathsf{PP}, \mathsf{PPI}$ the composition table itself *converts* a one-position witness into an all-position witness. The finite summary is not an approximation; it is exact. If you believe those three singleton cells — and you can check them with blobs in a margin — you believe the constant-interface certificate is sound and complete for these three relations. That is the "yes!" moment for Route 1.

5.3 Where PO breaks it — a concrete satisfiable villain

For PO, *neither* direction is forced: $\mathrm{comp}(\mathsf{PP}, \mathsf{PO}) = \{\mathsf{PP}, \mathsf{PO}, \mathsf{DR}\}$ says earlier positions are free; $\mathrm{comp}(\mathsf{PPI}, \mathsf{PO}) = \{\mathsf{PPI}, \mathsf{PO}\}$ says later ones are. A PO-witness at one phase need not be a PO-witness at any other. And this is not a hypothetical weakness of the proof — the two-tier paper exhibits a satisfiable concept that *provably defeats* the constant-interface architecture.

Take a chain with alternating types, τ_A at even positions demanding $\exists\mathsf{PO}.A$, τ_B at odd positions demanding $\forall\mathsf{PO}.\neg A$. Satisfiable? Yes — by **wandering witnesses**. For each k, witness w_k (satisfying A) is:

DR	to the chain positions below $2k$	(disjoint from the small ones)
PO	at exactly position $2k$	(overlaps that one)
PPI	to the positions above $2k$	(swallowed by the big ones)

Each w_k slides through the chain: disjoint, then transiently overlapping *exactly one* rung, then swallowed forever. Every even rung gets its $\exists\mathsf{PO}.A$ witness; every odd rung has *no* PO-neighbor at all, so $\forall\mathsf{PO}.\neg A$ holds vacuously; all the transitions are exactly the monotone ones from the table above; and the witnesses are pairwise DR by forced composition. A perfectly good infinite model.

But no *constant-interface* certificate describes it: a witness with recorded edge "kernel $\leftrightarrow w : \mathsf{PO}$" would be PO to the τ_B-rungs too, violating $\forall\mathsf{PO}.\neg A$. The demand at every phase is real, but no *single* witness serves two phases — the model needs infinitely many transient witnesses, and the finite summary has no slot for "transient." The architecture is provably incomplete here. (Contrast DR: the analogous villain with $\exists\mathsf{DR}.A \,/\, \forall\mathsf{DR}.\neg A$ is *unrealizable* — backward forcing drags any late DR-witness back across the $\forall\mathsf{DR}.\neg A$ rungs and clashes. The gap is a PO-only phenomenon; the table itself closes it for DR.)

5.4 Why $\forall\mathsf{PO}$-freeness dissolves the gap

Look at what actually went wrong: the constant-PO edge was fine *algebraically* (a constant-PO interface closes every triangle along the chain — check: $\mathsf{PO} \in \mathrm{comp}(\mathsf{PP}, \mathsf{PO})$ and $\mathsf{PO} \in \mathrm{comp}(\mathsf{PPI}, \mathsf{PO})$, so the constant value is always among the permitted ones) and failed only *logically* — it collided with a $\forall\mathsf{PO}$ obligation at another phase. The Safe test for a PO-edge between types τ and σ has exactly two parts: the $\forall\mathsf{PO}$-universal part ("every $\forall\mathsf{PO}.E \in \tau$ must have $E \in \sigma$," and symmetrically), and propositional bookkeeping.

In a $\forall\mathsf{PO}$-free concept, no type contains any $\forall\mathsf{PO}.E$. The $\forall\mathsf{PO}$-universal part of every Safe test is vacuous — at every phase, for every witness. A witness type containing D is PO-safe for *all* phases the moment it is PO-safe for one ("automatic PO-coherence," Lemma 2 of the fragment note). The one relation the table refuses to transport is also the one relation nobody is watching. Constant-PO edges are algebraically consistent and logically unchallenged; the wandering villain needs a $\forall\mathsf{PO}$ to exist, and there are none.

5.5 Counting, and the finish line

- Descriptors: $\leq 2^{2^m}$. Witnesses: at most one per demand per descriptor, $\leq (1+m)$ each. Quotient size $Q \leq (1+m)\,2^{2^m}$; live width $K(C_0) \leq Q\,(1+m) = (1+m)^2\,2^{2^m}$. Computable. (Nobody claims it is tight — only computability matters, and no complexity bound is asserted.)
- **Completeness:** extract from any model — record recurrent types along each chain as descriptors, pick witnesses past the exhaustion index, let stabilization + backward forcing + forward absorption + automatic PO-coherence make them all-phase. Everything repeated folds into the kernels.
- **Soundness:** unfold each kernel into its infinite chain under the constant interface, and prove the unfolding is still composition-closed on *every* triple — including triples whose closure jointly forces a PO edge (the multi-path caveat of §4 is enforced, not assumed away). This **chain-unfolding lift** is the soundness crux, and it is the part that is now **kernel-checked**: `POFreeLift.lean` proves, in Lean 4 with zero sorries, that if the finite augmented network is composition-consistent and strong-EQ, then replacing the kernel by an infinite PP-chain under the constant interface preserves composition-consistency. And under abstract semantics a composition-closed total network *is* a model (§3) — so a valid certificate delivers an actual infinite model outright.

Enumerate certificates up to $K(C_0)$, check, done.

6 Route 2: the ordered-disjoint normal form (the structural argument)

(The regular-cover pivot, GPT-5.5, July 2026: `papers/rcc5_local_amalgamation_theory.tex`, probes `wp47`–`wp49`, `wp82`/`wp83`; normal form certified in both directions: the forward one and the set representation in `RCC5NormalForm.lean`, the converse in `POFreeLift.lean`.)

Route 1 fought the composition table cell by cell. Route 2 wins by changing the data structure so the fight never starts.

6.1 A model is just an order and a disjointness relation

Certified normal form. A strong-EQ atomic RCC5 network is composition-closed **iff** it is an *ordered-disjoint structure*:

- $<$ (that is, PP) is a strict partial order;
- $\#$ (that is, DR) is symmetric, irreflexive, and **downward closed**: if $x\#y$, $x' \leq x$, $y' \leq y$, then $x'\#y'$;
- comparable pairs are never disjoint;
- **PO is the residual** — it is *defined* as "neither comparable nor disjoint." It is not data. It is what's left.

(Forward direction kernel-checked for arbitrary domains in `RCC5NormalForm.lean`; converse certified via an explicit canonical set representation, cross-checked exhaustively to size four and beyond, `wp47`/`wp88`.)

Let that reframing land: sixteen composition-table cells collapse into two familiar closure laws — transitivity of an order, downward closure of a disjointness — plus one compatibility condition. To build a model you never "place" a PO edge, ever. You build an order, you build a disjointness relation, you check two closure laws, and every pair you said nothing about *is* PO, automatically, consistently. The wild relation of §4 turns out to be bookkeeping for "no constraint here."

With it come two machine-checked amalgamation facts we'll need:

- **Free amalgamation** (`wp48`): two ordered-disjoint structures glued along a shared part, with no new order or disjointness across, form an ordered-disjoint structure. Cross pairs land on the residual — PO.
- **All-cross PO is always safe** (`wp82`): declaring *every* cross pair of two closed pockets PO is always composition-closed.

6.2 The tableau, and why it terminates

Now think like a tableau designer. Your nodes will form the vertical skeleton (a tree of $<$-edges, one tree per component — the split-forest discipline); your constraints are $(<, \#)$; PO is whatever remains. Which obligations can arise, and how do they move?

Universals over $\mathsf{PP}, \mathsf{PPI}, \mathsf{DR}$ are exactly constraints on $<$ and $\#$: "everything below me satisfies D," "everything above me satisfies D," "everything disjoint from me satisfies D." How do they propagate when edges compose? The general rule: if x carries $\forall R.D$ and $x \xrightarrow{S} y$, then y must carry $\forall T.D$ whenever $\mathrm{comp}(S,T) \subseteq \{R\}$ (any T-successor of y is then a forced R-successor of x). Instantiating against the table yields the *complete* rule set (probe `wp49`, machine-checked from set semantics):

$\forall\mathsf{PP}.D$	across PP:	require D, $\forall\mathsf{PP}.D$	(transitivity of $<$)
$\forall\mathsf{PPI}.D$	across PPI:	require D, $\forall\mathsf{PPI}.D$	(transitivity, downward)
$\forall\mathsf{DR}.D$	across PP:	require $\forall\mathsf{DR}.D$	(my container's disjointnesses rain down onto me — so my container inherits my duty)
$\forall\mathsf{DR}.D$	across DR:	require D, $\forall\mathsf{PPI}.D$	(my DR-neighbor's parts are also my DR-neighbors)

— four rules, all riding the four singleton cells, and, decisively:

> **No propagation rule from a $\forall$PP, $\forall$PPI, or $\forall$DR obligation ever produces a $\forall$PO obligation.** (Checked: no $\mathrm{comp}(S, \mathsf{PO})$ is contained in $\{\mathsf{PP}\}$, $\{\mathsf{PPI}\}$, or $\{\mathsf{DR}\}$.)

So the obligation vocabulary $\{\forall\mathsf{PP}, \forall\mathsf{PPI}, \forall\mathsf{DR}\} \times \mathrm{cl}(C_0)$ is **closed under propagation**. Start $\forall$PO-free, stay $\forall$PO-free — not just syntactically in the input, but dynamically, in every label the tableau will ever write. Obligations are drawn from a fixed finite set, and they move *deterministically* along the singleton cells (the same four cells as Route 1, wearing different clothes: transitivity of $<$, downward closure of $\#$). Node labels = type + obligation set = finitely many possibilities $\Rightarrow$

standard subformula blocking on the vertical tree terminates, with the loops read as generators (§3).

What about the demands?

- $\exists$PP / $\exists$PPI / $\exists$DR**:** create the witness in the skeleton or as a sibling; its forced consequences are computed by the two closure laws — finitely, deterministically (down-closure of # is a forced flood, but a flood of *shadows*: recoverable, costless, per §3).
- $\exists$PO.D**:** here is the beautiful step. Build a satisfying structure for D separately (recursion), then glue it on declaring **no cross order and no cross disjointness at all** — free amalgamation. Every cross pair, *including the demanding node and its witness*, lands on the residual: PO. The demand is satisfied by the default itself. Is that legal? *Algebraically* always (all-cross PO is always safe, `wp82`). *Logically* — a cross-PO edge could only violate a $\forall$PO obligation, **and there are none, and there never will be any** (closure of the vocabulary). Both halves of "safe" hold, and the second half is exactly $\forall$PO-freeness.

That is the "yes!" moment for Route 2: **the always-consistent default policy (make everything unconstrained overlap) is also always obligation-free — precisely in this fragment.** The full logic's nightmare — steering PO edges jointly against watching universals — never engages, because nothing ever watches. The horizontal axis carries no obligations; all real work happens on the vertical skeleton, where the singleton cells make propagation deterministic and blocking sound.

Status, honestly: Route 2 is a *re-derivation* — its ingredients (the normal form, the propagation table, the amalgamation and cross-policy facts) are individually machine-checked, two of them kernel-certified, but the assembly into a standalone tableau-completeness proof is theorem-level prose. It independently confirms the fragment result; it does not independently certify it.

7 The boundary is exactly right — and it is not "horizontal vs. vertical"

A skeptical reader should now ask: is $\forall$PO-freeness really the boundary, or just a convenient place to stop? Four checks.

The fragment keeps a horizontal universal. Note what did *not* have to go: $\forall$DR. Disjointness is as "horizontal" as overlap, yet $\forall$DR.D is harmless. The dividing line is not horizontal-vs-vertical but **stable vs. unstable under vertical motion**: DR is transported deterministically by the singleton cells (rains down into parts); PO is transported by no singleton cell in either direction and is never the forced outcome of any single composition. The fragment excises the unstable relation's universal and nothing else. That the cut lands on a single constructor is a fact about the composition table, not a choice.

The gap on the other side is real. The wandering-witness concept of §5.3 is a *satisfiable* concept just outside the fragment (one $\forall$PO) that provably defeats the constant-interface certificate; the probe `wp86` (Part C) confirms the boundary computationally — the PO-incoherent descriptor

forces an unsatisfiable interface, the coherent ones never do. And the full logic's signature satisfiable diagnostic, the strong-EQ PO-loop $C \sqcap \exists \mathsf{PO}.\exists \mathsf{PO}.C \sqcap \forall\{\mathsf{PO}, \mathsf{DR}, \mathsf{PP}, \mathsf{PPI}\}.\neg C$, needs its $\forall \mathsf{PO}$ conjunct to force the loop closure — it, too, lives outside. Everything that has ever been *hard* here has a $\forall \mathsf{PO}$ in it.

The connection to the open problem is close. F6, the keystone of the full-logic certificate route, asks for a computable live-width bound. Both routes above *prove* one for the fragment, at theorem level (Route 1 explicitly: $K(C_0)$). And the fragment theorem is itself the sharpest available evidence about where the full problem's difficulty lives: remove *one* constructor — the universal over the one relation the singleton cells don't control — and the coordination problem that every full-logic attempt has broken on dissolves. ($\forall \mathsf{DR}$ also coordinates horizontal edges, but its coordination is *deterministic*, which is exactly why it may stay.) The fragment is thus not a lucky island: it is where the obstruction cannot arise, and its proof shows *why* the obstruction is where it is. It is not the whole of what is decidable.

What the boundary is a boundary of (added 2026-11-11, unreviewed). The checks above show that $\forall \mathsf{PO}$-freeness is where *this argument* stops: the maximally-PO completion is available exactly when nothing can object to a PO edge. They do not show that decidability stops there. Three slices containing $\forall \mathsf{PO}$ are decidable. The oldest is Wessel's coarser logic $\mathcal{ALCI}_{\mathrm{RCC3}}$ of 2003, read inside RCC5: the concepts that use PO, PP and PPI only glued together, decided through two-variable logic with equality (the reading is an elementary argument, probe `wp140`; not formalized). The second is the erasure fragment of the honesty note, where $\forall \mathsf{PO}$ is vacuous. The third — by import of a published theorem on two-variable logic, not by this project and not in Lean — is the concepts that use $\forall \mathsf{PO}$ only as $\forall \mathsf{PO}.C \sqcap \forall \mathsf{DR}.C$ and have neither $\exists \mathsf{PO}$ nor $\exists \mathsf{DR}$. In the first and the third a $\forall \mathsf{PO}$ conjunct can change the answer. In the third: three superpart witnesses can be forced into a cycle of nestings that no pairwise test sees (C_{cyc}; Lean: `ccyc_unsat`, `ccycErased_sat`). What lies just outside also has an exact name now: allowing in addition $\exists \mathsf{PO}.C \sqcup \exists \mathsf{DR}.C$ gives a fragment whose satisfiability problem is that of two-variable logic over strict partial orders with unary predicates (`poset_bridge`, `patsys_to_rcc5`; one textbook normal-form step is not formalized), and general satisfiability of that logic is open. The full logic contains that problem; no reduction the other way is known. Two more Lean-checked concepts sit there: K_2, satisfiable only with two overlap witnesses nested, and a concept without $\exists \mathsf{PP}$ or $\exists \mathsf{PPI}$ that has only infinite models.

A corollary: in the fragment, identity can never be forced. The project's knife's-edge analysis (the coincidence obstruction of the overview paper) turns on *merge-forcing*: clash out all non-EQ options between two witnesses, and EQ — identity, under strong EQ — is all that remains. Such forced merges are the raw material of grid corners and rigid addressing, the machinery every undecidability attempt needs. In the fragment the trick is inexpressible, by the same escape-valve fact one level up: machine-checked (`wp14`, part T4), **every composition cell containing EQ also contains PO** — and hence so does every *intersection* of such cells (if EQ survives a joint constraint, every constituent contained EQ, so every constituent contained PO, so PO survives too). Wherever identity is on a pair's menu, partial overlap is on it as well, and the fragment has no eraser for PO. No $\forall \mathsf{PO}$-free concept ever forces two nodes to be one. So the fragment sits provably on the "loose" side of the knife's edge: not only does the decidability proof close — the undecidability *machinery* cannot even be assembled.

8 So — was it proved twice, or three times?

Honest ledger. There are **two genuinely different argument shapes** and **three arrivals** in this explainer, plus a **third shape** that is the one actually certified (item 5 below), and the certification pass itself.

1. **April 2026 — the two-tier quotient** (Claude, reviewed through four revisions by GPT-5.4). Proves decidability for the *PO-coherent* fragment — concepts whose ∀PO obligations, if any, are uniform across phases — with ∀PO-free concepts as the clean special case, and honestly exhibits the PO gap (§5.3) as the boundary. Route 1 above.

2. **July 2026 — the cold F6/W2′ attack** (GPT-5.5, given the open problem cold, asked to attack it). Independently arrived at the ∀PO-free fragment as its "Target B" deliverable, with the $K(C_0)$ bound (`papers/po_free_fragment_ALCIRCC5.tex`). On inspection its algebra — stabilization, backward forcing, forward absorption, automatic PO-coherence — is the two-tier argument's, so it counts as an independent *re-derivation* of Route 1, not a new route: the same theorem found again by a different mind from a different starting point, which is worth something evidentially but is not a second proof shape.

3. **July 2026 — the regular-cover pivot** (GPT-5.5, later phase). Re-derives the fragment through the ordered-disjoint normal form and the propagation-closure fact (`wp49`) — Route 2 above, a genuinely different shape: no chains, no phases, no stabilization; instead a change of data structure that makes PO disappear as data.

4. **2026-07-18 — the certification pass.** After a cold review flagged that the fragment's original rationale leaned on an overstated "PO is never forced" (the calibration of §4), the fragment was re-examined: it holds, the argument enforces full composition closure, and the soundness crux — the chain-unfolding lift — was kernel-checked (`POFreeLift.lean`, zero sorries). Additionally, two separately built reasoners (the cover-tree tableau and the quasimodel reasoner, which share the concept syntax and the composition-table code) were run on 244 random and curated ∀PO-free concepts with zero mismatches (`wp87`). Neither is a decision procedure. The quasimodel reasoner is incomplete on the strong-EQ PO-loop; the tableau is incomplete on K_2 (found November 2026) and returned wrong SAT answers, some on ∀PO-free concepts, until a repair on 18 April 2026, before this run. Both known incompleteness patterns need a ∀PO and cannot arise in the fragment, which is what makes the agreement evidence; it is not a proof, and a suite with zero mismatches has twice missed a defect of the tableau (`ERRATA.md`).

5. **August 2026 — the ConeScheme route, and the one that is certified** (design: GPT-5.6 Sol, prompted by Wessel after two rounds of cold attack had refuted the previous certification architecture; Lean development: Claude). A genuinely *third* shape, and the reason the fragment is now machine-certified end to end. The move is to stop reusing nodes: a finite *cone scheme* serves only as a *control graph* of signatures (a support type together with an upper bound on the types of its strict PP-predecessors); a monotone, reductive elimination runs to a greatest fixed point; and every non-EQ existential unfolds to a *fresh occurrence*, so that nothing is ever identified or borrowed. *Why the previous architecture failed*, since it is the transferable part: reusing a node imposes a *global* condition — the order the reused edges induce must stay acyclic, and the relations they force must be *jointly* realizable — while every discipline proposed for enforcing it was a *local* test, per edge or per node or per type.

A local test cannot see what it is not looking at, and three of the four countermodels say so one axis at a time: per-edge safety removes self-loops and nothing longer (two individually safe fallbacks forming a four-cycle); a key read off an occurrence's downward cone cannot separate occurrences whose obstruction is *horizontal*; a class top defined by type alone drags one member's disjointness witness onto another's cone. That is the pointwise-versus-joint shape that had already broken three earlier architectures in this project, so the fault lay in proposing another local discipline, not in the particular ones proposed. Standard *blocking* is the same story in its most familiar form — it is exactly the local test, "same type, so let one occurrence stand for the other" — and it fails here for the same reason, since type equality cannot see whether the reuse closes a cycle in the order or puts the blocker's disjointness witness inside the blocked node's cone. The cone scheme does not test better — it removes the obligation, and the global conditions then hold structurally rather than by enforcement.

The frame conditions that had defeated the previous architecture — irreflexivity of the order, and its disjointness from the disjointness relation — then hold *structurally* rather than by a test. The *completeness* half inverts what every earlier route attempted. Those read completeness as *extraction* — given a model, build a finite certificate out of it — and that construction is where the $K(C_0)$ budgets live. Here nothing is extracted. The signature space is fixed in advance from C_0; a model point's signature is *read off* it (its type, plus the types of its strict PP-predecessors); and the signatures a model realises survive their own elimination, because for each demand the model hands over a witness. That is a *post-fixed point*, and a monotone reductive elimination puts every post-fixed point inside its greatest fixed point. Finiteness is free, the space having been finite before any model appeared. The monotonicity is not a technicality: this project once retracted a type-elimination procedure whose rule was *anti-monotone* — discarding one type could invalidate the witness justifying another — so exactly this argument was unavailable to it and its fixpoint over-eliminated. That is why the operator here asks only that each demand *have* a target, and why that was checked before anything was built on it.

What makes the route work is specific to this fragment, and is worth stating because it explains the boundary: a composition cell containing PO can always be discharged by putting the pair at PO unless some formula can object to a PO edge, and the only formula that can is $\forall \mathsf{PO}.D$; so here the maximally-PO unfolding is *always* a model, and no joint realizability across a signature's several demands is ever needed. This route does *not* use the $K(C_0)$ bound, so items 1–3 above remain independent, unformalized arguments for the same theorem. Capstones: `decidableFSat`, `decidableSat_cone`, `decidableSetSat`. The design document is `papers/cone_scheme_plan/`; the Lean development and its section-by-section provenance are `formal/POFreeLift.lean` and `ASSEMBLY_DESIGN.md` §§267–297.

6. **2026-08-29 — three cold reviews.** The certified route was attacked three times independently: at its trusted base and execution, at its completeness direction, and at its soundness direction. None found a counterexample. The second found a genuine defect — a dropped ∀PO propagation in the transition relation, vacuous on the fragment but not on the full-logic UNSAT test built from the same machinery — and the third found no defect in the development at all, its five findings all lying in the project's own probes and prose.

7. **2026-09-09 — a fourth review** (GPT-5.6 Sol): a source-level audit that found no defect in the Lean; its findings concerned the overview's framing, and it recommended the focused paper.

8. **2026-10-07 — a fifth review, and an extension** (Astra 6): no gap found; its PO-erasure theorem was verified and certified (`erase_equisat`, `decidableSat_dfrag`).

9. **2026-11-11 — not a review** (Claude Fable 5.2; unreviewed): the poset bridge and three boundary concepts outside the fragment (`formal/PosetBridge.lean`), and corrections — a cited theorem on two-variable logic had been withdrawn, and the tableau used in item 4 is incomplete (`ERRATA.md`).

What stayed constant across all three routes. Worth one paragraph, because it is the honest answer to "what was the human's idea worth in the end." Every route here presents a model the same way: a vertical skeleton of $<$-edges, one tree per component, with DR and PO as non-tree edges completed afterwards — the split-forest discipline of §6.2. The certified route (item 5) is that picture in an unusually literal form: its elements are demand *words*, so occurrences of the same type stay distinct and are never re-identified; its order is generated by exactly two moves, "prepend a PP birth" and "strip a PPI head"; and stripping the leading vertical births returns each occurrence's component root, which order edges provably preserve and DR births provably change.

One clarification, because it is easy to draw the wrong conclusion: the certified route does not *assume* split-forest models. Its completeness half takes an arbitrary model and reads a signature off it. But the shape is still what the soundness half *constructs*, and it is the content of the normal form that makes composition closure free. That a signature records vertical position fits the same picture, though as a correspondence rather than a documented design step: the cone-scheme plan does not refer to split forests. The idea's job changed — from a property to be established of an arbitrary model, which is the extraction problem the earlier routes were refuted on, to a shape to be built, which is free — and that change is why it went through.

What the routes did *not* share is the machinery. The certified one needs no patchwork appeal (composition closure comes from the ordered-disjoint axioms), no quotient (nothing is re-identified, because no particular model has to be recovered), and no width bound. Three successive architectures were each refuted at the point where they tried to *build* a finite presentation of such a forest and keep it consistent; what finally worked was to stop building one and let the syntax's own demand words be the forest. The shape was the durable contribution; the machinery was not.

A gap in Route 1, found 2026-08-28 — and what it does not touch. Re-reading the two-tier paper turned up a genuine defect in its completeness argument: Step 2 defined the relation between two kernels as a double limit $\lim_{i,j\to\infty} \rho(d_i, d_j)$, justified by external-relation stabilization "applied twice". That lemma is *one-sided*—it fixes an element and varies the chain—and the double limit need not exist ($\mathbb{Z} \times \{0,1\}$ ordered by first coordinate: every row and every column stabilizes, yet every tail carries PP, PO and PPI). It is repaired by a *simultaneous finite rectangle* in place of the limit, which is all the quotient needs since it reads only finitely many phases; the repair is machine-checked (`fused_kq_all`).

Which arrivals this touches is worth stating precisely, because it is the argument for keeping two routes:

- **Arrival 1 (Route 1)** stated the false step. Repaired.
- **Arrival 2** re-derives Route 1 and uses external-relation stabilization *one-sidedly*, as the lemma allows; it never states the double limit. It builds a two-tier quotient, so it depends on the

repaired lemma for its kernel-to-kernel edges, but it did not assert the invalid inference.

- **Arrival 3 (Route 2)** is *untouched*. It has no chains, no phases and no stabilization at all—the defect cannot be stated in its vocabulary, let alone used.

So the theorem never rested on the defective step: an independent route to it never had the defect. This is exactly the redundancy two proof shapes are for.

So: "2 (or 3?)" resolves to **two independent proof routes, three independent arrivals at the theorem** — and the fact that a cold attacker, pointed at the open problem with no steer, walked to this exact fragment on its own is perhaps the best evidence that the boundary is natural.

9 What is certified, what is checked, what is argued

Claim	Status
Composition/converse tables; the singleton and PO cells of §4	Kernel-certified (Lean, `decide`) and derived from set semantics in every probe
RCC5 normal form (network ⇔ ordered-disjoint), arbitrary domains	**Certified**, both directions (`RCC5NormalForm.lean`, `odNet_frame` in `POFreeLift.lean`, canonical representation)
Abstract = set satisfiability, *full* logic	**Certified** (`satisfiable_iff_set`); a special case of Lutz–Wolter Thm. 23. By their Thm. 24 the fragment result also holds for substructures of regular closed regions of $\mathbb{R}^n$ (cited, not formalized)
Chain-unfolding lift (finite CC certificate ⇒ CC infinite unfolding)	**Certified** (`POFreeLift.lean`, zero sorries)
Certificate-to-model soundness: a valid single-kernel two-tier certificate yields a model of the concept, through the logic (Hintikka + truth lemma on the unfolding)	**Certified** (`POFreeLift.lean` round A, 2026-07-22: `twoTier_sound`; witness `cinf_satisfiable` — the no-finite-model concept $\exists \mathsf{PP}.\top \sqcap \forall \mathsf{PP}.\exists \mathsf{PP}.\top$, satisfiable end-to-end)
Multi-kernel certificates (any family of ascending/descending kernels) and the executable first-order checker (certificates as pure list data; acceptance ⇒ model)	**Certified** (`POFreeLift.lean` rounds B–C: `multiTier_sound`, `mtAcceptB_sound`; the ascending+descending two-tower witness accepted by kernel `decide`)
Propagation closure (no non-PO universal creates a ∀PO obligation)	Machine-checked exhaustively (`wp49`)
Free amalgamation; all-cross-PO safety; non-uniform cross-policies	Machine-checked exhaustively (`wp48`, `wp82`, `wp83`)
Lift-lemma stress-test incl. multi-path PO forcing; fragment boundary	Machine-checked empirically (`wp86`)
Two separately built reasoners agree on the fragment (244 concepts)	Machine-checked empirically (`wp87`); evidence only — neither reasoner is a decision procedure (`ERRATA.md`)
Fragment decidability itself, by a *third* route (a finite control graph of signatures, a monotone elimination to a greatest fixed point, and a fresh-occurrence unfolding) — on raw input and under concrete set semantics	**Certified** (2026-08-29, `POFreeLift.lean`: `decidableFSat`, `decidableSat_cone`, `decidableSetSat`; fragment membership the only hypothesis, zero sorries). Cold-reviewed three times without a counterexample, and audited at source level by a fourth review (2026-09-09) that found no defect; a fifth (Astra 6, 2026-10-07) found no gap. Decidable, *not* runnable: the signature space is doubly exponential
PO-erasure extension: the fragment $\mathcal{D}$ (no ∃PP, ∃PO, ∀DR; ∀PO *permitted*) is decidable by erasing ∀PO	**Certified** (2026-10-08, `erase_equisat`, `decidableSat_dfrag`; contributed by the Astra 6 review, verified by `wp136`)
The two *arguments* of this paper ($K(C_0)$ bound, extraction, assembly — Routes 1 and 2)	**Theorem-level** — argued, twice, independently; *not* end-to-end formalized. The certified route above is a *different* proof of the same theorem and does not use $K(C_0)$

Added 2026-11-11, from one session and not yet reviewed; all three concern what lies outside the

fragment:

Claim	Status
What lies just outside: the incomparability fragment has the satisfiability problem of two-variable logic over strict partial orders with unary predicates	Lean-checked (2026-11-11, `formal/PosetBridge.lean`: `poset_bridge`, `patsys_to_rcc5`) except one textbook normal-form step; *unreviewed*
Two slices containing $\forall$PO decided through that bridge	Theorem-level, by import of published theorems; not formalized, cited proofs not checked
K_2, C_{cyc} and an infinity axiom without $\exists$PP/$\exists$PPI	Lean-checked (`k2_sat`, `ccyc_unsat`, `ccycErased_sat`, `spiralConcept_infinite`); *unreviewed*; all outside the fragment

How far the first route's own certification campaign got. This paragraph is a record of what *that* route certified, not a statement of what remains: the theorem was carried by a different route in August 2026 (ledger §8, item 5), and none of the machinery named here is used by it. Rounds A–D1 (2026-07-22/23) landed the entire **soundness side plus the decision architecture**: a valid two-tier certificate, with any family of ascending or descending kernels, presented as **pure first-order list data**, is accepted by a computable oracle-free Boolean checker **exactly when valid** (`mtOkB_iff`), acceptance yields a model (kernel-checked end to end; the two-tower witness's acceptance runs inside the kernel via plain `decide`), and a certified reduction (`decidableSat_of_codes`) turns any candidate-code list plus a completeness premise into Decidable satisfiability. Rounds D2a–c further certified the extraction's entire **model-side toolkit**: the stabilization theorem of §5.2 with both forcing corollaries, the infinite pigeonhole (recurrent tails, segment selection), segment coherence (cycling a type-equal chain segment into a kernel is legitimate), witness selection (late picking), and the syntactic $\forall$PO-vacuity (`pofree_cl_all`: no $\forall$PO ever appears in the fragment's closure — the escape valve, kernel-checked). Rounds E4–E6 (2026-08-06) then completed this route for three of the four quadrants — horizontal, ascending vertical and descending vertical, with the lemma `rr_covers` as the keystone — and for one mixed witness (the `decidableSat_...` family in the Lean file). Not completed on *this* route: the general mixed extraction, whose node-reuse architecture cold attack refuted (§8, item 5), and the $K(C_0)$ counting.

That is no longer the last word on the theorem, though it remains the last word on *this* argument. The fragment was carried to a machine-certified decision procedure in August 2026 by a third route (ledger §8, item 5) which does not use $K(C_0)$ at all, and which has since been through three independent cold reviews, a source-level audit and a fifth review, none of which found a counterexample. So the honest labels differ: the **theorem** is **machine-certified**; the **two arguments in this explainer** remain **strongly supported, not formalized end-to-end**; and the **full logic** remains open.

10 The one-paragraph version

$\mathcal{ALCI}_{\text{RCC5}}$ models are complete graphs with a composition law, and they are legitimately infinite, so deciding satisfiability means enumerating and checking *finite certificates* — blueprints whose loops are generators of infinite models — and the whole difficulty is bounding the certificate's genuinely-free ("live") content. The composition table transports DR, PP, PPI deterministically along the

nesting order (four singleton cells: transitivity, and disjointness raining down into parts) but refuses to transport PO in either direction, and no single composition ever forces PO. Consequently universal obligations over DR/PP/PPI are trackable — they propagate deterministically in a closed finite vocabulary — while ∀PO obligations must chase neighbors the algebra refuses to pin down; a concrete satisfiable concept with one ∀PO provably defeats that route's constant-interface certificate via "wandering witnesses" that each overlap a chain only transiently. Ban ∀PO and both known proof shapes close: the *two-tier quotient* folds each infinite chain into a kernel whose witnesses' relations stabilize and are all-phase by forced composition (with constant-PO edges algebraically consistent and, now, unchallenged), giving a computable live-width bound and enumerate-and-check decidability; the *ordered-disjoint normal form* — certified — shows a model is nothing but a strict order plus a downward-closed disjointness with PO as the residual non-constraint, so a standard tree tableau tracking only order/disjointness obligations (whose propagation calculus provably never manufactures a ∀PO obligation) terminates by ordinary blocking, discharging ∃PO by always-safe free amalgamation. Two argument shapes and three independent arrivals, and then a third shape — a finite control graph of signatures with a fresh-occurrence unfolding — which is the one that carried the theorem all the way into the kernel: since 2026-08-29 the fragment has a machine-certified *decision procedure*, on raw input and under concrete set semantics, with fragment membership its only hypothesis, and three independent cold reviews, a source-level audit and a fifth review found no counterexample. On the fragment the live-width bound that the full logic's certificate route needs (F6) is argued at theorem level rather than conjectured — though the certified procedure turns out not to need it — and the fragment's boundary, one constructor wide, is drawn by the composition table itself: the boundary of this argument, not of decidability (§7).

Companions: `papers/pofree_fragment_arxiv.pdf` *(the certified result, as a focused paper),* `WHY_ITS_HARD.md` *(the full problem, non-technical),* `papers/two_tier_quotient_ALCIRCC5.tex` *(Route 1 in full),* `papers/po_free_fragment_ALCIRCC5.tex` *(the fragment note),* `papers/rcc5_local_amalgamation_theory.tex` *(Route 2's local algebra),* `papers/overview_arxiv.tex`*, §"The win" (the calibrated summary),* `formal/POFreeLift.lean`*,* `formal/RCC5NormalForm.lean` *(the certified parts),* `formal/PosetBridge.lean` *and* `papers/poset_bridge/README.md` *(what lies just outside the fragment), and* `ERRATA.md` *(corrections). A short Markdown pointer to this note is* `papers/WHY_PO_FREE_IS_DECIDABLE.md`*. Where this document and the formal artifacts disagree, the formal artifacts win.*