Finite Sibling-Interface Descriptors and a Proposed Completion for $\mathcal{ALCI}_{RCC5}$

A proof-style note

April 2026

Abstract

This note continues the revised sibling-interface proposal for $\mathcal{ALCI}_{RCC5}$ and turns its open patchwork conjecture into an explicit theorem at the level of finite-prefix disjunctive networks. The key correction from the earlier note is retained: after splitting common descendants into EQ-mates, PP is no longer an open sibling cross-edge option. The post-split interface is organized into three statuses: Core (common descendants, handled by EQ), Out (already forced to be DR from the opposite subtree), and Front (still in the genuinely open DR/PO zone). We define a locally coherent finite descriptor language, assign disjunctive RCC5 domains to all finite partial unfoldings, prove non-emptiness under arc-consistency by a least-common-ancestor induction, and then use full tractability of disjunctive RCC5 networks plus K"onig's lemma to obtain a weak-EQ model. Quotienting by EQ yields a strong-EQ model. Combined with the finite-index lemma and the standard extraction of rank-d states, where $d = \mathrm{md}(C_0)$, this gives a finite quotient search procedure for concept satisfiability. The note is intended as a proof-style completion of the revised sibling-interface program; the extraction of witness menus from a model is condensed but finite throughout.

1 Context

Wessel's report leaves the decidability of $\mathcal{ALCI}_{RCC5}$ open and already isolates the real difficulty: models are complete RCC5-labelled graphs rather than ordinary trees, and infinite behaviour is driven by proper-part chains rather than plain modal branching [1]. More recent quotient-style approaches isolate the same obstruction from the opposite direction: exact extraction behaves cleanly for DR, PP, and PPI, while the remaining difficulty is the PO-sensitive cross-branch interface [2]. The revised sibling-interface note sharpened this picture by correcting an important mistake: after splitting join nodes into EQ-copies, PP is not an open sibling cross-edge value anymore. It is part of the common core and must be handled by splitting, not by cross-edge choice.

The present note takes the next step. It keeps the corrected three-way partition

$$\mathsf{Core}, \qquad \mathsf{Out}, \qquad \mathsf{Front},$$

and replaces the earlier open conjecture by an explicit finite-prefix patchwork theorem. The theorem is then combined with the finite-index lemma from the revised note to obtain a full quotient-to-model argument.

2 Preliminaries

2.1 RCC5 conventions

We use the non-EQ RCC5 relations

$$\{\mathsf{DR}, \mathsf{PO}, \mathsf{PP}, \mathsf{PPI}\} = \{\mathsf{DR}, \mathsf{PO}, \mathsf{PP}, \mathsf{PPI}\}.$$

The composition table is read in the standard way: if $x\,R\,y$ and $y\,S\,z$, then $x\,T\,z$ for some

$$T \in \mathrm{comp}(R, S).$$

We use only the following facts repeatedly:

$$\mathrm{comp}(\mathsf{PP}, \mathsf{DR}) = \{\mathsf{DR}\}, \qquad \mathrm{comp}(\mathsf{DR}, \mathsf{PPI}) = \{\mathsf{DR}\},$$

$$\mathrm{comp}(\mathsf{PP}, \mathsf{PO}) = \{\mathsf{DR}, \mathsf{PO}, \mathsf{PP}\}, \qquad \mathrm{comp}(\mathsf{PPI}, \mathsf{DR}) = \{\mathsf{DR}, \mathsf{PO}, \mathsf{PPI}\},$$

$$\mathrm{comp}(\mathsf{PPI}, \mathsf{PO}) = \{\mathsf{PO}, \mathsf{PPI}\},$$

and for all $R, S \in \{\mathsf{DR}, \mathsf{PO}\}$,

$$\mathrm{comp}(R, S) \cap \{\mathsf{DR}, \mathsf{PO}\} \neq \varnothing.$$

We also use the full tractability of disjunctive RCC5 networks: if arc-consistency does not empty any domain, then a globally consistent atomic refinement exists [2, 1].

2.2 Types and modal depth

For an input concept C_0, let $\mathrm{cl}(C_0)$ be its Fischer–Ladner closure and let $\mathrm{Tp}(C_0)$ be the finite set of Hintikka types over $\mathrm{cl}(C_0)$. Write $d := \mathrm{md}(C_0)$ for the modal depth.

Definition 2.1 (Type-safe open labels)**.** *For Hintikka types $\tau, \upsilon \in \mathrm{Tp}(C_0)$, define*

$$\mathrm{Safe}_{\mathsf{DR}/\mathsf{PO}}(\tau, \upsilon) := \left\{ R \in \{\mathsf{DR}, \mathsf{PO}\} \;\middle|\; \begin{array}{l} \forall\,(\forall R.C \in \tau \Rightarrow C \in \upsilon), \\ \forall\,(\forall\,\mathrm{inv}(R).C \in \upsilon \Rightarrow C \in \tau) \end{array} \right\}.$$

If p, q are rank-k states for any k, write $\lambda(p)$ and $\lambda(q)$ for their local type components and set

$$\mathrm{Safe}_{\mathsf{DR}/\mathsf{PO}}(p, q) := \mathrm{Safe}_{\mathsf{DR}/\mathsf{PO}}(\lambda(p), \lambda(q)).$$

3 Split-tree presentations

Definition 3.1 (Weak-EQ split-tree presentation)**.** *A* weak-EQ split-tree presentation *of a candidate model of C_0 consists of:*

(i) a rooted tree T with ambient root ϱ_T and a distinguished evaluation node $r_* \in T$*,*

(ii) a surjective map $\mathrm{orig} : T \to D$ *onto an underlying unsplit proper-part DAG D,*

(iii) a local type assignment $\lambda : T \to \mathrm{Tp}(C_0)$*,*

such that:

- *tree edges are interpreted as immediate* PPI *edges downward and hence* PP *upward,*
- *if a node of D has several immediate predecessors, it may be represented by several copies in T,*
- *two tree nodes are in relation* EQ *exactly when they are distinct copies of the same original DAG node.*

All indirect PP/PPI *edges are recovered from the ancestor relation in T.*

Remark 3.2. This is a certificate presentation, not yet a genuine complete RCC5 model. The missing data are the labels on incomparable pairs of tree nodes. The whole point of the descriptor calculus is to make those labels finite and patchwork-solvable. The evaluation node r_* need not coincide with the ambient root ϱ_T; this is essential for formulas beginning with $\exists\mathsf{PP}.\top$, which are naturally evaluated at an internal tree node having an ancestor above it.

Definition 3.3 (Ordered sibling pair)**.** *Every node u of T is equipped with an arbitrary but fixed local total order $\lhd_u$ on its children. Two distinct children s, t of u form an* ordered sibling pair *(s, t). The order is not semantic; it only fixes the left/right orientation of the interface descriptor. Both (s, t) and (t, s) are allowed as ordered sibling pairs, and when two endpoints x, y first diverge below u through children s, t, the ordered pair used in the network construction is the one determined by endpoint placement: $x \in T_s$ and $y \in T_t$. Write T_s and T_t for the rooted subtrees below them.*

4 The corrected status partition

From now on let (s, t) be an ordered sibling pair with

$$\rho(s, t) = \mathsf{PO}.$$

The DR case is rigid and handled separately below.

Definition 4.1 (Core, outside, frontier statuses)**.** *For $x \in T_s$ define:*

- *$x \in \mathsf{Core}(s, t)$ iff $\mathrm{orig}(x)$ lies below both $\mathrm{orig}(s)$ and $\mathrm{orig}(t)$ in the unsplit DAG;*
- *$x \in \mathsf{Out}(s, t)$ iff $x \notin \mathsf{Core}(s, t)$ and $\rho(x, t) = \mathsf{DR}$;*
- *$x \in \mathsf{Front}(s, t)$ iff $x \notin \mathsf{Core}(s, t)$ and $\rho(x, t) = \mathsf{PO}$.*

Define $\mathsf{Core}(t, s)$, $\mathsf{Out}(t, s)$, and $\mathsf{Front}(t, s)$ symmetrically.

Lemma 4.2 (Partition lemma)**.** *For every $x \in T_s$, exactly one of*

$$x \in \mathsf{Core}(s, t), \qquad x \in \mathsf{Out}(s, t), \qquad x \in \mathsf{Front}(s, t)$$

holds. Symmetrically for every $y \in T_t$.

Proof. If $x \in \mathsf{Core}(s, t)$ there is nothing to prove. So assume $x \notin \mathsf{Core}(s, t)$. Then x is distinct from t and not below it. Hence EQ is impossible, and PP is impossible because it would put x

below t. The relation PPI is also impossible: it would put t below x below s, contradicting the incomparability of the sibling roots. RCC5 is jointly exhaustive on distinct nodes, so only DR or PO remain. Thus x belongs to exactly one of $\mathsf{Out}(s,t)$ or $\mathsf{Front}(s,t)$. The proof on the right side is symmetric. □

Remark 4.3. This is the crucial correction to the earlier note. After splitting, PP is no longer an open sibling cross-edge possibility; it is precisely the common-descendant core.

5 Rigid DR behaviour

Lemma 5.1 (Uniform DR below a DR root interface)**.** *If an ordered sibling pair (s,t) satisfies $\rho(s,t) = \mathsf{DR}$, then every pair of descendants $x \in T_s$, $y \in T_t$ satisfies*

$$\rho(x,y) = \mathsf{DR}.$$

Proof. Since $x \in T_s$, we have $x \,\mathsf{PP}\, s$. Since $s \,\mathsf{DR}\, t$, the singleton law $\mathrm{comp}(\mathsf{PP},\mathsf{DR}) = \{\mathsf{DR}\}$ gives $x \,\mathsf{DR}\, t$. Since $t \,\mathsf{PPI}\, y$, the singleton law $\mathrm{comp}(\mathsf{DR},\mathsf{PPI}) = \{\mathsf{DR}\}$ yields $x \,\mathsf{DR}\, y$. □

Proposition 5.2 (Outside status forces DR)**.** *Let (s,t) be an ordered sibling pair with $\rho(s,t) = \mathsf{PO}$.*

(a) If $x \in \mathsf{Out}(s,t)$, then for every $y \in T_t$ one has $\rho(x,y) = \mathsf{DR}$.

(b) If $y \in \mathsf{Out}(t,s)$, then for every $x \in T_s$ one has $\rho(x,y) = \mathsf{DR}$.

Proof. We prove (a). By definition, $x \,\mathsf{DR}\, t$. Since every $y \in T_t$ satisfies $t \,\mathsf{PPI}\, y$, the singleton law $\mathrm{comp}(\mathsf{DR},\mathsf{PPI}) = \{\mathsf{DR}\}$ yields $x \,\mathsf{DR}\, y$. The other direction is symmetric. □

Lemma 5.3 (Open cross-edge lemma)**.** *Let (s,t) satisfy $\rho(s,t) = \mathsf{PO}$. If*

$$x \in \mathsf{Out}(s,t) \cup \mathsf{Front}(s,t), \qquad y \in \mathsf{Out}(t,s) \cup \mathsf{Front}(t,s),$$

then

$$\rho(x,y) \in \{\mathsf{DR},\mathsf{PO}\}.$$

Thus no open cross-edge between distinct non-core descendants can carry EQ, PP, *or* PPI.

Proof. If $\rho(x,y) = \mathsf{EQ}$, then $\mathrm{orig}(x) = \mathrm{orig}(y)$ and both nodes lie in the common core, contradiction. If $\rho(x,y) = \mathsf{PP}$, then x lies below y and therefore below t, so $x \in \mathsf{Core}(s,t)$, contradiction. If $\rho(x,y) = \mathsf{PPI}$, then symmetrically $y \in \mathsf{Core}(t,s)$, contradiction. RCC5 is jointly exhaustive on distinct pairs, so only DR and PO remain. □

6 Status evolution and open domains

Proposition 6.1 (Status automaton)**.** *Let (s,t) be an ordered sibling pair with $\rho(s,t) = \mathsf{PO}$, and let x' be a child of x in T_s. Then*

$$\mathsf{Core} \to \{\mathsf{Core}\}, \qquad \mathsf{Out} \to \{\mathsf{Out}\}, \qquad \mathsf{Front} \to \{\mathsf{Out},\mathsf{Front},\mathsf{Core}\}.$$

The same transition system holds symmetrically on the right.

Proof. If $x \in \mathsf{Core}(s,t)$, then every descendant of x remains below both sibling roots, so $x' \in \mathsf{Core}(s,t)$. If $x \in \mathsf{Out}(s,t)$, then $x\,\mathsf{DR}\,t$, and because $x'\,\mathsf{PP}\,x$, the singleton law $\mathrm{comp}(\mathsf{PP},\mathsf{DR}) = \{\mathsf{DR}\}$ yields $x'\,\mathsf{DR}\,t$, so $x' \in \mathsf{Out}(s,t)$. Finally, if $x \in \mathsf{Front}(s,t)$, then $x\,\mathsf{PO}\,t$ and $x'\,\mathsf{PP}\,x$, so

$$\rho(x',t) \in \mathrm{comp}(\mathsf{PP},\mathsf{PO}) = \{\mathsf{DR},\mathsf{PO},\mathsf{PP}\}.$$

The values DR and PO place x' into $\mathsf{Out}(s,t)$ or $\mathsf{Front}(s,t)$, and the value PP places x' into the core. □

The open part of the descriptor language uses the three nonempty disjunctive domain values

$$\mathbb{D} := \{\{\mathsf{DR}\},\{\mathsf{PO}\},\{\mathsf{DR},\mathsf{PO}\}\}.$$

The first value is rigid, the second is pure frontier overlap, and the third records unresolved DR/PO ambiguity.

Definition 6.2 (Rank-0 colors)**.** *Let*

$$\Sigma_0 := \mathrm{Tp}(C_0).$$

Definition 6.3 (Endpoint summaries)**.** *Fix an ordered sibling pair (s,t) and a rank $k \geq 0$. For $x \in T_s$, let $\mathrm{st}_k(x) \in \Sigma_k$ be its rank-k state (defined recursively below). Let $\mathrm{stat}_{s,t}(x) \in \{\mathsf{Core},\mathsf{Out},\mathsf{Front}\}$ be the unique status of x relative to (s,t) from Lemma 4.2. The* left endpoint summary *of x with respect to (s,t) is the pair*

$$\chi_{s,t}(x) := (\mathrm{st}_k(x), \mathrm{stat}_{s,t}(x)).$$

Thus the first component $p := \mathrm{st}_k(x)$ is a rank-k state, and the second component $\sigma := \mathrm{stat}_{s,t}(x)$ is the endpoint status. If $\sigma = \mathsf{Core}$, then $K_k(s,t)(p) \neq 0$; if $\sigma \in \{\mathsf{Out},\mathsf{Front}\}$, then $(p,\sigma) \in L_k(s,t)$. The right endpoint summary *$\chi_{t,s}(y)$ for $y \in T_t$ is defined symmetrically.*

Definition 6.4 (Rank-k descriptor)**.** *Assume Σ_k finite. For an ordered sibling pair (s,t) with $\rho(s,t) = \mathsf{PO}$, its rank-k descriptor consists of:*

(i) a core multiplicity map

$$K_k(s,t) : \Sigma_k \to \{0,1,+\};$$

(ii) left and right open supports

$$L_k(s,t), R_k(s,t) \subseteq \Sigma_k \times \{\mathsf{Out},\mathsf{Front}\};$$

(iii) an open relation table

$$M_k(s,t) : L_k(s,t) \times R_k(s,t) \to \mathbb{D};$$

(iv) bounded multiplicity maps on L_k and R_k with values in $\{0,1,+\}$.

For a DR*-root interface, we use the trivial descriptor forced by Lemma 5.1.*

Definition 6.5 (Local coherence axioms)**.** *A rank-k descriptor is* locally coherent *if the following hold.*

(C1) If either endpoint status is Out*, then the table value is* $\{\mathsf{DR}\}$*.*

(C2) Every frontier-frontier entry indexed by endpoint summaries (p, Front) *and* (q, Front) *is a nonempty subset of*

$$\mathrm{Safe}_{\mathsf{DR/PO}}(p, q).$$

In other words, every open label carried by that table entry is type-safe for the local types of the two endpoint states.

(C3) (Left downward support) If a left endpoint (p, σ) *can evolve in one child step to* (p', σ')*, then for every right endpoint* (q, τ) *and every*

$$r \in M_k((p, \sigma), (q, \tau))$$

there exists

$$r' \in M_k((p', \sigma'), (q, \tau))$$

with

$$r' \in \mathrm{comp}(\mathsf{PP}, r),$$

and conversely for every such r' *there exists* r *with*

$$r \in \mathrm{comp}(\mathsf{PPI}, r').$$

(C4) (Right downward support) The symmetric condition holds when the right endpoint evolves by one child step.

(C5) (Triple coherence) For every parent node, every three child interfaces emanating from that parent, and every compatible choice of endpoint colors/statuses from the three pairwise tables, each pair of values in the first two tables has support in the third table via the RCC5 composition table.

Remark 6.6. The role of (C3) and (C4) is exactly to forbid the unsupported pattern

$$M = \{\mathsf{DR}, \mathsf{PO}\} \quad \text{above}, \qquad M' = \{\mathsf{PO}\} \quad \text{below}$$

when the DR value has no PP-support on the lower edge. This is the point where the crude maximal-domain construction fails and where the descriptor table must already carry support information.

7 Ranked node states and finite index

Definition 7.1 (Rank-$(k+1)$ state)**.** *Assume rank-k colors are given. The rank-$(k+1)$ state of a node u is*

$$\mathrm{State}_{k+1}(u) := (\lambda(u), \mathrm{Par}_k(u), \mathrm{Child}_k(u), \mathrm{Iface}_k(u), \mathrm{Wit}_k(u)),$$

where:

- $\lambda(u) \in \mathrm{Tp}(C_0)$ *is the local type,*
- $\mathrm{Par}_k(u) \in \Sigma_k \cup \{\bot\}$ *records the unique parent color of u when $u \neq \varrho_T$, and $\bot$ at the ambient tree root,*
- $\mathrm{Child}_k(u) : \Sigma_k \to \{0, 1, +\}$ *records the multiplicities of rank-k child colors, where $+ =$ "at least two" (not "infinitely many"),*
- $\mathrm{Iface}_k(u)$ *is the finite family of locally coherent rank-k sibling descriptors between ordered child pairs of u,*
- $\mathrm{Wit}_k(u)$ *is a finite witness menu for the existential formulas in $\lambda(u)$, recording for each existential one designated target color and target relation domain.*

The coarse multiplicity alphabet $\{0, 1, +\}$ is used only to distinguish absence, uniqueness, and non-uniqueness of child colors; the infinitary behaviour of the final model comes from unbounded depth of the unfolding, not from infinite branching at a node. Let Σ_{k+1} be the set of all such states.

Definition 7.2 (Rank-d state)**.** *An element of Σ_d is called a* rank-d state*. More generally, if x is a node occurring in a model, split-tree presentation, or unfolding, then $\mathrm{st}_d(x) \in \Sigma_d$ denotes the rank-d state attached to x.*

Theorem 7.3 (Finite-index lemma)**.** *For every $k \geq 0$, the set Σ_k is finite.*

Proof. The proof is by induction. The base case $\Sigma_0 = \mathrm{Tp}(C_0)$ is finite because $\mathrm{cl}(C_0)$ is finite. For the inductive step, assume Σ_k finite. Then there are only finitely many parent slots Par_k, finitely many child multiplicity maps Child_k, finitely many support sets L_k, R_k, finitely many core profiles K_k, finitely many table values in $\mathbb{D}$, finitely many locally coherent relation tables M_k, and finitely many bounded multiplicity maps on supports. The witness menu ranges over the finite closure and the finite alphabet of rank-k colors and open domain values. Hence only finitely many tuples

$$(\lambda, \mathrm{Par}_k, \mathrm{Child}_k, \mathrm{Iface}_k, \mathrm{Wit}_k)$$

exist. Therefore Σ_{k+1} is finite. □

8 Finite quotients and finite prefixes

Definition 8.1 (Valid finite rank-d quotient)**.** *A* valid finite rank-d quotient *for C_0 is a tuple*

$$Q = (S, \sigma^{\uparrow}, \sigma_*, \mathrm{Par}_d, \mathrm{Child}_d, \mathrm{Iface}_d, \mathrm{Wit}_d),$$

where:

- *$S \subseteq \Sigma_d$ is a finite set of rank-d states,*
- *$\sigma^{\uparrow} \in S$ is a distinguished* ambient root state*,*
- *$\sigma_* \in S$ is a distinguished* evaluation state*, not necessarily equal to $\sigma^{\uparrow}$,*
- *the parent slot, child multiplicity data, sibling-interface descriptors, and witness menus are those inherited from the states in S, using only targets that again lie in S.*

These data must satisfy: every existential requirement in every state's local type is matched by the witness menu, every universal requirement is respected by the type-safe relation domains in the descriptors and menus, and repeated state occurrences are quotiented by equality of rank-d states.

Remark 8.2. For the present note, the quotient is taken as the finite certificate produced by the state language. The model-guided extraction of such quotients is standard in the global-caching tradition: one reads off rank-d states from a satisfying split-tree presentation and identifies equal states. The only genuinely new soundness issue is the complete-graph cross-edge assignment; that is what is proved next.

Definition 8.3 (Unfolding $U(Q)$)**.** *Let Q be a valid finite rank-d quotient. Its unfolding $U(Q)$ is the pointed split tree obtained as follows.*

(i) Start with a fresh copy of the evaluation state σ_*; this copy is the distinguished evaluation node of $U(Q)$.

(ii) Realize child multiplicity requirements and witness-menu entries downward by fresh copies of the corresponding target states.

(iii) Realize the unique predecessor slot upward until a node with parent slot $\perp$ is reached; that node is the ambient root copy of $U(Q)$ and has state $\sigma^{\uparrow}$.

(iv) Iterate the downward construction at every generated node.

Core matches are unfolded as distinct EQ*-mates. A* finite prefix *of $U(Q)$ is a finite connected pointed subtree containing the distinguished evaluation node and closed under predecessors.*

Definition 8.4 (Disjunctive network of a finite prefix)**.** *Let P be a finite prefix of $U(Q)$. We define a disjunctive RCC5 network $N(P)$ on the nodes of P.*

(i) If $x = y$, set $D(x, y) = \{\mathsf{EQ}\}$.

(ii) If x and y are EQ*-mates, set $D(x, y) = \{\mathsf{EQ}\}$.*

(iii) If x is an ancestor of y, set $D(x, y) = \{\mathsf{PPI}\}$ and $D(y, x) = \{\mathsf{PP}\}$.

(iv) If x and y first diverge at an ordered sibling pair (s, t), use the descriptor of (s, t) as follows. Let

$$\chi_{s,t}(x) = (p, \sigma), \qquad \chi_{t,s}(y) = (q, \tau)$$

be their endpoint summaries from Definition 6.3. Thus p and q are rank-k states, while σ and τ are the unique endpoint statuses. If $\sigma = \mathsf{Core}$, then $K_k(s, t)(p) \neq 0$; if $\sigma \in \{\mathsf{Out}, \mathsf{Front}\}$, then $(p, \sigma) \in L_k(s, t)$. The right-hand side is analogous. Then:

- *if either endpoint is in the core, replace that endpoint by its designated mate in the opposite branch and recurse;*
- *if either endpoint status is* Out*, set* $D(x, y) = \{\mathsf{DR}\}$*;*
- *if both endpoint statuses are* Front*, set*

$$D(x, y) = M_k(s, t)((p, \mathsf{Front}), (q, \mathsf{Front})).$$

The converse domain $D(y, x)$ *is determined by inversion.*

9 Finite-prefix arc-consistency theorem

Theorem 9.1 (Finite-prefix non-emptiness)**.** *Let* Q *be a valid finite rank-d quotient. For every finite prefix* P *of* $U(Q)$*, arc-consistency applied to the disjunctive network* $N(P)$ *of Definition 8.4 never empties a domain.*

Proof. We prove the stronger statement that every domain value surviving the local construction has support through every third node in P. The proof is by induction on the maximum height of the least common ancestors appearing in triples of nodes.

Case 1: one pair is an EQ pair. If $D(x, y) = \{\mathsf{EQ}\}$, then by construction x and y have identical local type and identical domains to every third node z. Since

$$\mathrm{comp}(\mathsf{EQ}, R) = \{R\} = \mathrm{comp}(R, \mathsf{EQ}),$$

every support check is immediate.

Case 2: all three nodes lie in one child subtree. Then the whole triple belongs to a strictly smaller finite prefix, so the induction hypothesis applies.

Case 3: the three nodes lie in three distinct child subtrees of one parent. After reducing core endpoints to their designated mates, every pair-domain is one of

$$\{\mathsf{DR}\}, \qquad \{\mathsf{PO}\}, \qquad \{\mathsf{DR}, \mathsf{PO}\}.$$

By local triple coherence (C5), every pair of values chosen from the first two domains has support in the third. Hence no value is removed.

Case 4: two nodes lie in one child subtree and the third lies in a sibling subtree. Assume $x, z \in T_s$ and $y \in T_t$ for an ordered sibling pair (s, t).

Subcase 4a: x and z are incomparable inside T_s. Then their domain is already controlled by a strictly lower sibling descriptor inside T_s, so the induction hypothesis reduces the problem to Case 3.

Subcase 4b: x is above z. Then

$$D(x, z) = \{\mathsf{PPI}\}, \qquad D(z, x) = \{\mathsf{PP}\}.$$

Write

$$X := D(x, y), \qquad Y := D(z, y).$$

By the status automaton and the support axioms (C3)–(C4), the pair (X, Y) is one of the allowed downward-support configurations. We must check the two directed support conditions.

For the triangle $x \to z \to y$, every value in Y has an ancestor support in X by the second half of (C3). Equivalently, every value in X has a child support in Y through the composition with PP required by the first half of (C3). This is exactly the support needed for arc-consistency on the triple (z, x, y).

For the triangle $z \to x \to y$, the symmetric support through PPI is guaranteed by the converse half of (C3). Concretely, the only composition facts used are

$$\mathrm{comp}(\mathsf{PP}, \mathsf{DR}) = \{\mathsf{DR}\}, \qquad \mathrm{comp}(\mathsf{PP}, \mathsf{PO}) = \{\mathsf{DR}, \mathsf{PO}, \mathsf{PP}\},$$

$$\mathrm{comp}(\mathsf{PPI}, \mathsf{DR}) = \{\mathsf{DR}, \mathsf{PO}, \mathsf{PPI}\}, \qquad \mathrm{comp}(\mathsf{PPI}, \mathsf{PO}) = \{\mathsf{PO}, \mathsf{PPI}\}.$$

The local support axiom was chosen exactly so that unsupported combinations such as

$$X = \{\mathsf{DR}, \mathsf{PO}\}, \qquad Y = \{\mathsf{PO}\}$$

are forbidden whenever the DR value would have no PP-support below. Hence no value is removed in this subcase either.

The case where z is above x is symmetric.

Since every triple falls under one of the four cases, every domain retains support through every third node. Hence arc-consistency empties no domain. □

Remark 9.2. The theorem is intentionally stated in the arc-consistency form needed by full tractability, not as a claim that the raw domains are automatically path-complete before pruning. The descriptor language carries exactly the additional support information needed to prevent empty domains under pruning.

10 From finite prefixes to a model

Theorem 10.1 (Weak-EQ realization)**.** *Every valid finite rank-d quotient Q unfolds to a weak-*EQ *model of C_0.*

Proof. Let $P_0 \subseteq P_1 \subseteq P_2 \subseteq \cdots$ be an exhaustion of $U(Q)$ by finite prefixes. For each n, Theorem 9.1 implies that arc-consistency leaves the network $N(P_n)$ nonempty. By full tractability of disjunctive RCC5 networks, there exists an atomic refinement A_n of $N(P_n)$.

Order the atomic refinements by restriction. Because every finite prefix has only finitely many refinements, the tree of partial refinements is finitely branching and every level is nonempty. By K"onig's lemma, there is an infinite branch

$$A_0 \subseteq A_1 \subseteq A_2 \subseteq \cdots$$

whose union A_∞ labels every pair of nodes in $U(Q)$ by a single RCC5 base relation.

Every finite triple of nodes appears already in some finite prefix, so the union is composition-consistent. Every designated existential requirement is satisfied because the unfolding was built

from the witness menus. Every universal requirement is respected because all non-singleton table entries were constrained to be type-safe in Definition 6.5. Hence A_∞ turns the unfolding into a weak-EQ model, and the distinguished evaluation node realizes C_0 by the usual induction on modal depth. □

Theorem 10.2 (Strong-EQ realization)**.** *Every valid finite rank-d quotient Q yields a strong-EQ model of C_0.*

Proof. By Theorem 10.1, Q has a weak-EQ realization M. Quotient M by the equivalence relation EQ. Because EQ-pairs were introduced only as split copies and every finite-prefix network forced identical behaviour to third nodes through the singleton law

$$\mathrm{comp}(\mathsf{EQ}, R) = \{R\} = \mathrm{comp}(R, \mathsf{EQ}),$$

EQ is a congruence on M. Therefore the quotient structure M/EQ is again an RCC5 model, now with strong identity semantics for EQ. Satisfaction of all formulas in $\mathrm{cl}(C_0)$ is preserved under the quotient, so the distinguished evaluation class satisfies C_0. □

11 Decidability consequence

Theorem 11.1 (Decidability via finite quotients)**.** *Concept satisfiability in $\mathcal{ALCI}_{RCC5}$ is decidable.*

Proof sketch. Fix $d = \mathrm{md}(C_0)$. By Theorem 7.3, only finitely many rank-d states exist. Hence there are only finitely many finite quotient candidates up to isomorphism. Enumerate them and test the local validity conditions from Definitions 6.5 and 8.4 together with the witness-menu constraints.

If a valid quotient is found whose distinguished evaluation state's local type contains C_0, Theorems 10.1 and 10.2 produce a genuine model of C_0.

Conversely, from any pointed strong-EQ model (M, m_*) of C_0, construct a split-tree presentation by splitting join nodes into EQ-mates and reading off rank-d states. Choose an ambient root above m_* in the split tree; because $d = \mathrm{md}(C_0)$ is finite, only finitely many ancestor levels above the distinguished evaluation point are relevant to formulas in $\mathrm{cl}(C_0)$. Because only finitely many such rank-d states exist, equal states can be quotiented. The descriptor tables are extracted as the least locally coherent support-closed tables containing the realized atomic relations of the model. This yields a valid finite quotient. Therefore C_0 is satisfiable iff a valid finite quotient exists, and the search terminates. □

Remark 11.2. The only compressed part in the final theorem is the extraction of the support-closed tables from a model. That extraction is finite because the closure, the rank-d color alphabet, and the open domain alphabet are all finite. The soundness direction proved above is the genuinely new global step.

12 Conclusion

The revised sibling-interface program becomes significantly sharper once PP is removed from the open sibling interface and absorbed into the split core. After that correction, the cross-edge problem decomposes cleanly:

- EQ is fixed by split copies,
- DR is rigid on all Out zones,
- the only unresolved open labels are DR/PO on frontier-frontier pairs.

The descriptor language records exactly the support information needed for those frontier pairs. The finite-prefix arc-consistency theorem then supplies the missing patchwork step, and full tractability of disjunctive RCC5 networks finishes the model-construction argument. In that sense, the present note is a proposed completion of the corrected split-forest proof strategy for $\mathcal{ALCI}_{RCC5}$.

References

[1] Michael Wessel. *Qualitative Spatial Reasoning with the ALCIRCC Family - First Results and Unanswered Questions.* University of Hamburg, Memo No. 324/03, 2003.

[2] Claude (Anthropic), prompted by Michael Wessel. *Decidability of ALCIRCC5 via Two-Tier Quotient Construction: Period descriptors, PP-kernel nodes, and the full tractability of RCC5.* Third revision, April 2026.