

A Repaired Split-Forest Decidability Proof for $\mathcal{ALCI}_{\text{RCC5}}$ Without Automata

Consolidated proof manuscript

May 2026

Abstract

This note gives a single coherent version of the repaired split-forest proof for decidability of satisfiability of $\mathcal{ALCI}_{\text{RCC5}}$ concepts over abstract complete atomic RCC5 frames. The proof keeps the original architecture: witness thinning, generated containment covers, split copies for several selected containment parents, finite side interfaces, support-closed mosaics, typed equality quotienting, and finite regular certificates. It does not use Büchi or parity automata. Instead it uses direct finite-index blocking with explicit request-closed cycles. The main repair relative to the preceding consolidated draft is that finite abstract labels are no longer indexed only by abstract position symbols. Labels are indexed by occurrence-sensitive pair shapes. Thus two occurrences in different laps of a blocking cycle may have the same profile and the same local position symbol without being EQ-identified. Semantic equality is generated only by explicit equality ports and never by blocking repetition.

Contents

1	Statement of the theorem	2
2	Abstract RCC5 frames	2
3	Closure, types, and witness thinning	3
4	Generated containment split presentations	4
5	Mosaics and side interfaces	5
6	Finite occurrence-sensitive certificates	7
7	Soundness	9
8	Completeness	10
9	Effective enumeration	12
10	Stress cases and the blocking/equality repair	13
	10.1 Infinite upward chains	13
	10.2 Several incomparable upward witnesses	13
	10.3 Residual sibling frontier	13
11	What remains of the original split-forest idea	13

1 Statement of the theorem

The concept language contains concept names, Boolean connectives in negation normal form, and modal restrictions

$$\exists R.C, \quad \forall R.C$$

where $R \in \mathbf{B} = \{\text{EQ}, \text{PP}, \text{PPI}, \text{PO}, \text{DR}\}$. The intended theorem is:

Theorem 1.1 (Decidability). *Satisfiability of $\mathcal{ALCI}_{\text{RCC5}}$ concepts over abstract complete atomic RCC5 frames with strong equality is decidable.*

The proof is by finite certificates. For a concept C_0 , we compute a finite closure $\text{Cl}(C_0)$, enumerate finite split-forest certificates over this closure, check each certificate by finitely many syntactic tests, and prove

$$C_0 \text{ is satisfiable} \iff C_0 \text{ has a valid finite split-forest certificate.}$$

Soundness constructs an abstract RCC5 frame by unfolding a valid certificate. Completeness thins any satisfying model to a witness-generated model, then extracts a finite regular certificate by direct blocking. The blocking argument is formulated as a finite request-closed cycle lemma, not as an automata construction.

2 Abstract RCC5 frames

Definition 2.1 (RCC5 base relations). *Let*

$$\mathbf{B} = \{\text{EQ}, \text{PP}, \text{PPI}, \text{PO}, \text{DR}\}.$$

The inverse operation fixes EQ, PO, DR and swaps PP with PPI. Intuitively $x\text{PP}y$ means that x is a proper part of y , and $x\text{PPI}y$ means $y\text{PP}x$.

Definition 2.2 (Abstract complete atomic RCC5 frame). *An abstract RCC5 frame is a pair $\mathfrak{F} = (\Delta, \rho)$, where $\Delta \neq \emptyset$ and $\rho : \Delta^2 \rightarrow \mathbf{B}$ satisfies:*

(F1) Strong equality: $\rho(x, y) = \text{EQ}$ iff $x = y$.

(F2) Converse: $\rho(y, x) = \text{Inv}(\rho(x, y))$.

(F3) Composition: for all $x, y, z \in \Delta$,

$$\rho(x, z) \in \text{Comp}(\rho(x, y), \rho(y, z)),$$

where Comp is the RCC5 composition table below.

The composition table used in the proof is the standard atomic RCC5 table. Each entry is a subset of $\mathbf{B}$.

Comp	EQ	PP	PPI	PO	DR
EQ	EQ	PP	PPI	PO	DR
PP	PP	PP	B	{PP, PO, DR}	DR
PPI	PPI	{EQ, PP, PPI, PO}	PPI	{PPI, PO}	{PPI, PO, DR}
PO	PO	{PP, PO}	{PPI, PO, DR}	B	{PPI, PO, DR}
DR	DR	{PP, PO, DR}	DR	{PP, PO, DR}	B

Remark 2.3. *The semantics is abstract. We do not assume a topological or geometric region space. The composition table is the only RCC5 algebraic constraint required by the frame definition. This is why the proof below can work with generated witness-cover presentations rather than Hasse diagrams of arbitrary ambient partial orders.*

Definition 2.4 (Interpretation and satisfaction). *An interpretation $\mathcal{I}$ consists of an abstract RCC5 frame $(\Delta^{\mathcal{I}}, \rho^{\mathcal{I}})$ and an assignment $A^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}}$ to each concept name. Boolean clauses are standard. Modal clauses are:*

$$\begin{aligned} x \in (\exists R.C)^{\mathcal{I}} & \text{ iff } \exists y \in \Delta^{\mathcal{I}} [\rho^{\mathcal{I}}(x, y) = R \text{ and } y \in C^{\mathcal{I}}], \\ x \in (\forall R.C)^{\mathcal{I}} & \text{ iff } \forall y \in \Delta^{\mathcal{I}} [\rho^{\mathcal{I}}(x, y) = R \Rightarrow y \in C^{\mathcal{I}}]. \end{aligned}$$

Strong equality implies $\exists \text{EQ}.C \equiv C$ and $\forall \text{EQ}.C \equiv C$. In the certificate this is treated as a preprocessing normalization or, equivalently, by using the source occurrence itself as the EQ-witness.

3 Closure, types, and witness thinning

Definition 3.1 (NNF complement and closure). *For every concept D let $\bar{D}$ be its negation-normal-form complement:*

$$\begin{aligned} \bar{\bar{A}} &= A, & \overline{\neg A} &= A, \\ \overline{D \sqcap E} &= \bar{D} \sqcup \bar{E}, & \overline{D \sqcup E} &= \bar{D} \sqcap \bar{E}, \\ \overline{\exists R.D} &= \forall R.\bar{D}, & \overline{\forall R.D} &= \exists R.\bar{D}. \end{aligned}$$

The closure $\text{Cl}(C_0)$ is the least finite set containing C_0 , all subconcepts of its NNF form, their NNF complements, and the components required by Boolean and modal subformulas. We write $n = |\text{Cl}(C_0)|$.

Definition 3.2 (Hintikka type). *A C_0 -type is a set $t \subseteq \text{Cl}(C_0)$ such that:*

- (T1) *for each $D \in \text{Cl}(C_0)$, exactly one of $D, \bar{D}$ belongs to t ;*
- (T2) *$D \sqcap E \in t$ iff $D, E \in t$;*
- (T3) *$D \sqcup E \in t$ iff $D \in t$ or $E \in t$;*
- (T4) *$\exists \text{EQ}.D \in t$ iff $D \in t$, and $\forall \text{EQ}.D \in t$ iff $D \in t$.*

A realized point x has type $\text{tp}(x) = \{D \in \text{Cl}(C_0) : x \in D^{\mathcal{I}}\}$.

Lemma 3.3 (Witness-generated submodel). *If $\mathcal{I}, a_0 \models C_0$, then there is a countable subinterpretation $\mathcal{J} \subseteq \mathcal{I}$ with $a_0 \in \Delta^{\mathcal{J}}$ such that:*

- (W1) $\mathcal{J}, a_0 \models C_0$;
- (W2) *every element of $\Delta^{\mathcal{J}}$ is either a_0 or was chosen as a witness for some existential formula $\exists R.D \in \text{Cl}(C_0)$ at an earlier generated element;*
- (W3) *for every generated x and every $\exists R.D \in \text{tp}_{\mathcal{I}}(x)$, a selected witness $w(x, \exists R.D) \in \Delta^{\mathcal{J}}$ satisfies $\rho^{\mathcal{I}}(x, w) = R$ and $w \in D^{\mathcal{I}}$.*

Moreover, for every $x \in \Delta^{\mathcal{J}}$ and every $D \in \text{Cl}(C_0)$,

$$x \in D^{\mathcal{J}} \iff x \in D^{\mathcal{I}}.$$

Proof. Build $W_0 = \{a_0\}$. Given W_i , for every $x \in W_i$ and every existential $\exists R.D \in \text{Cl}(C_0)$ true at x in $\mathcal{I}$, choose one witness $w(x, \exists R.D)$ in $\mathcal{I}$ and put it into W_{i+1} . Let $W = \bigcup_i W_i$, and let $\mathcal{J}$ be the restriction of $\mathcal{I}$ to W .

We prove preservation by induction on $D \in \text{Cl}(C_0)$. Boolean cases are immediate. For $\exists R.E$, if it is true in $\mathcal{I}$, the selected witness is retained in $\mathcal{J}$; if it is true in $\mathcal{J}$, it is true in $\mathcal{I}$ because $\mathcal{J}$ is a restriction. For $\forall R.E$, truth in $\mathcal{I}$ implies truth in $\mathcal{J}$ because fewer successors are quantified over. Conversely, if $\forall R.E$ is false in $\mathcal{I}$, then $\exists R.\bar{E}$ is true in $\mathcal{I}$, belongs to the closure, and its selected witness is retained in $\mathcal{J}$. By induction that witness still satisfies $\bar{E}$, so $\forall R.E$ is false in $\mathcal{J}$. The EQ case is strong equality and is covered by the type clauses. $\square$

Remark 3.4 (Why thinning is used). *Thinning is not a geometric assumption. It is a conservativity step. It says that arbitrary abstract models may be replaced by sparse witness-generated models. Any dense or non-Hasse behavior of an arbitrary starting model is irrelevant after thinning: the proof uses selected generated cover edges, not the semantic Hasse diagram of the starting model.*

4 Generated containment split presentations

The split presentation is containment-oriented. A vertical parent is a selected proper superpart. Thus a vertical child is PP-below its parent, and a parent is PPI-above its child in the converse direction.

Definition 4.1 (Occurrence presentation). *A weak split presentation is a tuple*

$$\mathcal{S} = (\text{Occ}, E_{\uparrow}, \equiv_{\text{EQ}}, \text{tp}, \lambda_{\text{side}})$$

where:

- (S1) Occ is a set of occurrences;
- (S2) $E_{\uparrow}(u, v)$ is a selected containment-cover edge, read as $u\text{PP}v$, so v is a selected proper superpart of u ;
- (S3) $\equiv_{\text{EQ}}$ is an explicit equivalence relation of equality mates;
- (S4) $\text{tp}(u)$ is a C_0 -type, constant on $\equiv_{\text{EQ}}$ -classes;
- (S5) λ_{side} assigns RCC5 labels to finite side-interface pairs not determined by vertical comparability.

The selected cover edge $E_{\uparrow}$ is generated by witnesses. It is not the Hasse diagram of an arbitrary original model. In the unfolded presentation, semantic vertical PP is the strict transitive closure of $E_{\uparrow}$, together with equality-mate transport as specified below.

Definition 4.2 (Occurrence-sensitive equality and vertical reachability). *For occurrences u, v , define:*

- $u \text{Reach}_{\text{PP}} v$ iff there are occurrences u', v' with $u \equiv_{\text{EQ}} u'$, $v' \equiv_{\text{EQ}} v$, and v' a strict $E_{\uparrow}$ -ancestor of u' ;
- $u \text{Reach}_{\text{PPI}} v$ iff $v \text{Reach}_{\text{PP}} u$.

The word “strict” means that the witnessing path contains at least one cover edge. Equality alone is never a strict PP or PPI witness.

Definition 4.3 (Strong quotient label). *The strong quotient of a weak split presentation is obtained by collapsing $\equiv_{\text{EQ}}$ -classes. Before quotienting, the occurrence-level label $\rho(u, v)$ is defined by the following priority order:*

- (L1) *if $u \equiv_{\text{EQ}} v$, then $\rho(u, v) = \text{EQ}$;*
- (L2) *else if $u \text{ Reach}_{\text{PP}} v$, then $\rho(u, v) = \text{PP}$;*
- (L3) *else if $u \text{ Reach}_{\text{PPI}} v$, then $\rho(u, v) = \text{PPI}$;*
- (L4) *otherwise $\rho(u, v) \in \{\text{PO}, \text{DR}\}$ is supplied by the relevant side interface or residual sibling frontier.*

A weak presentation is typed-congruent if $u \equiv_{\text{EQ}} u'$ and $v \equiv_{\text{EQ}} v'$ imply $\rho(u, v) = \rho(u', v')$, and $\text{tp}(u) = \text{tp}(u')$. Then the quotient label

$$\rho_{/\equiv_{\text{EQ}}}([u], [v]) = \rho(u, v)$$

is well-defined.

Remark 4.4 (The central round-7 repair). *Blocking repetition is not semantic equality. An occurrence is a concrete node of the unfolding. A finite state, profile, port, or abstract position symbol may repeat in many laps of a cycle. These repeated occurrences are distinct unless the explicit relation $\equiv_{\text{EQ}}$ relates them. In particular, if $u \neq v$ are two laps of the same one-state upward cycle, then they may have the same finite profile but $u \not\equiv_{\text{EQ}} v$, and the label between them is PP or PPI, not EQ.*

Lemma 4.5 (Generated split-cover presentation). *Every witness-generated model $\mathcal{J}, a_0$ has a weak split presentation $\mathcal{S}$ such that its strong quotient is isomorphic to a submodel of $\mathcal{J}$ preserving all closure types and all selected witnesses.*

Construction. Create one occurrence for the evaluation point. For every selected PPI-witness of an occurrence, add it as a vertical proper-part child; equivalently the source is its selected superpart. For every selected PP-witness, add it as a vertical selected superpart above a suitable equality mate of the source. If several PP-witnesses of the same semantic element must be incomparable, create several occurrences of that element, put them in the same explicit $\equiv_{\text{EQ}}$ -class, and place each occurrence under the required selected superpart. This is the original split-copy idea.

For selected DR or PO witnesses, attach finite side contexts containing the source occurrence, the witness occurrence, and the boundary/equality-mate occurrences needed to synchronize labels with the surrounding containment context. If a side witness is itself PP- or PPI-comparable with another side witness, include the necessary local vertical mini-context in the side interface rather than forcing the pair into the residual sibling frontier. Thus residual frontier pairs are only DR or PO; containment labels inside side interfaces are explicitly verticalized.

All labels and types are inherited from $\mathcal{J}$. Occurrences with the same origin are placed in $\equiv_{\text{EQ}}$. Because labels are inherited from $\mathcal{J}$, the congruence conditions and RCC5 composition hold. Collapsing $\equiv_{\text{EQ}}$ -classes returns the original generated elements, preserving all closure formulas. $\square$

5 Mosaics and side interfaces

Mosaics are finite snapshots of side and boundary interaction. They are not required to be geometric regions. They are finite abstract RCC5 networks satisfying the same atomic table as the global frame.

Definition 5.1 (Mosaic). *A mosaic is a tuple*

$$M = (P, \tau, L, \mathcal{V})$$

where P is a finite position set, $\tau : P \rightarrow \text{Type}(C_0)$, $L : P^2 \rightarrow \mathbb{B}$, and $\mathcal{V}$ is a finite family of declared vertical strata. It satisfies:

- (M1) $L(p, p) = \text{EQ}$, and $L(p, q) = \text{EQ}$ iff $p = q$ inside the mosaic, except for explicitly declared equality ports that are identified by the certificate equivalence;
- (M2) $L(q, p) = \text{Inv}(L(p, q))$;
- (M3) for all $p, q, r \in P$, $L(p, r) \in \text{Comp}(L(p, q), L(q, r))$;
- (M4) if $\exists R.D \in \tau(p)$ and the witness is local to this mosaic, then some $q \in P$ has $L(p, q) = R$ and $D \in \tau(q)$;
- (M5) if $\forall R.D \in \tau(p)$, then every $q \in P$ with $L(p, q) = R$ satisfies $D \in \tau(q)$;
- (M6) if $L(p, q) \in \{\text{PP}, \text{PPI}\}$, then p, q lie in a common declared vertical stratum, unless the pair is a boundary pair that is explicitly supplied by equality-aware vertical reachability in the surrounding generated tree;
- (M7) if p, q are residual sibling-frontier positions, then $L(p, q) \in \{\text{DR}, \text{PO}\}$.

Definition 5.2 (Support closure). *A finite mosaic family Mos_Q is support-closed when:*

- (SC1) *it is closed under restriction to named boundary subsets;*
- (SC2) *every selected DR or PO existential obligation names an actual mosaic and an actual witness position in that mosaic;*
- (SC3) *every side-interface position that carries a PP or PPI relation is contained in an explicit local vertical stratum;*
- (SC4) *equality-port positions have the same type and the same labels to every boundary and mosaic position;*
- (SC5) *whenever two mosaics overlap on a common boundary, the certificate contains an amalgamating mosaic or an explicit cross-label table for their union satisfying (M1)–(M7).*

All clauses are finite because every mosaic has size bounded by the certificate grammar.

Lemma 5.3 (Finite patching of support-closed mosaics). *Let F be any finite set of occurrences produced by unfolding a valid certificate. The labels on pairs in F induced by vertical reachability, equality ports, and named side mosaics satisfy strong equality, converse, and RCC5 composition.*

Proof. Strong equality and converse are immediate from the priority definition of labels and from mosaic axioms (M1)–(M2). For composition, take $u, v, w \in F$. There are finitely many possible occurrence-sensitive triple shapes for (u, v, w) : equality collapse, strict vertical chain, mixed vertical-side configuration, common side mosaic, or overlap of two side mosaics over a named boundary. Validity of the certificate includes a finite table of all coherent occurrence-sensitive triple shapes and requires the corresponding labels (R_{uv}, R_{vw}, R_{uw}) to satisfy $R_{uw} \in \text{Comp}(R_{uv}, R_{vw})$. Because the triple shape records whether two endpoints are the same concrete occurrence, equality mates, strict vertical copies, or merely repetitions of the same finite profile in different laps, no blocking copy is misclassified as EQ. Therefore the required composition inclusion holds. $\square$

6 Finite occurrence-sensitive certificates

This section is the main formal repair. The certificate has finite abstract profiles, but labels are not functions of profile or abstract position alone. They are functions of *pair shapes*. Pair shapes include an incidence tag that distinguishes same occurrence, explicit equality mate, strict vertical ancestor, strict vertical descendant, and side/frontier interaction.

Definition 6.1 (Profile and port). *A profile s consists of:*

- (P1) *a type $\lambda(s) \subseteq \text{Cl}(C_0)$;*
- (P2) *a finite set $\text{Port}(s)$ of equality and boundary ports;*
- (P3) *for each port, a declaration of whether it is a source port, equality-mate port, vertical-parent port, vertical-child port, or side-boundary port;*
- (P4) *finite lower/upper reachability summaries for PP/PPI universal propagation.*

The profile alphabet S_Q is finite.

Definition 6.2 (Concrete occurrence). *The unfolding of a finite certificate produces occurrences of the form*

$$o = (\gamma, p),$$

where γ is a finite generator path with a lap counter for repeated cycles, and p is a local port or mosaic position in the context instantiated at the end of γ . Two occurrences may have the same abstract profile and same local port while having different paths or lap counters. They are distinct occurrences unless explicitly related by $\equiv_{\text{EQ}}$.

Definition 6.3 (Incidence tags). *For two concrete occurrences u, v , their incidence tag $\iota(u, v) \in \text{Inc}$ is one of the following finite tags:*

Tag	Meaning
self	$u = v$ as concrete occurrences
eq	$u \neq v$ and $u \equiv_{\text{EQ}} v$ by explicit equality ports
up	v is a strict equality-aware superpart of u
down	v is a strict equality-aware proper part of u
side _R	the pair is named in a side mosaic with label R
front _R	the pair is residual sibling-frontier with label $R \in \{\text{DR}, \text{PO}\}$

The tags self and eq are occurrence-sensitive. Repeated laps of a blocking cycle never receive self merely because their finite profiles agree.

Definition 6.4 (Pair shape). *A pair shape is a finite tuple*

$$\alpha(u, v) = (s_u, p_u, s_v, p_v, \iota(u, v)),$$

where $s_u, s_v \in S_Q$, $p_u \in \text{Port}(s_u)$, $p_v \in \text{Port}(s_v)$, and $\iota(u, v) \in \text{Inc}$. Let Pair_Q be the finite set of pair shapes permitted by the certificate. The label function is

$$\ell_Q : \text{Pair}_Q \rightarrow \text{B}$$

with mandatory values

$$\ell_Q(\text{self}) = \text{EQ}, \quad \ell_Q(\text{eq}) = \text{EQ}, \quad \ell_Q(\text{up}) = \text{PP}, \quad \ell_Q(\text{down}) = \text{PPI},$$

and $\ell_Q(\text{side}_R) = \ell_Q(\text{front}_R) = R$.

Definition 6.5 (Triple shape). *A triple shape is a tuple*

$$\Theta = (\alpha_{12}, \alpha_{23}, \alpha_{13})$$

*of permitted pair shapes satisfying the finite coherence constraints induced by equality, vertical order, and context membership. For example, if α_{12} and α_{23} are strict upward vertical tags, then α_{13} must also be upward; if α_{12} is **self**, then $\alpha_{13} = \alpha_{23}$; if α_{12} is **eq**, then all labels from endpoints 1 and 2 to endpoint 3 must agree by typed congruence. Let Tri_Q be the finite set of coherent triple shapes.*

Definition 6.6 (No-collapse label rule). *The concrete label in the unfolding is*

$$\rho_Q(u, v) = \ell_Q(\alpha(u, v)).$$

Since $\alpha(u, v)$ contains $\iota(u, v)$, this definition is occurrence-sensitive. If $u \neq v$ are distinct laps of the same finite profile, then $\iota(u, v) \neq \text{self}$. Unless an explicit equality port relates them, $\iota(u, v) \neq \text{eq}$. Hence $\rho_Q(u, v) \neq \text{EQ}$ for strict vertical repetitions.

Definition 6.7 (Finite certificate). *A finite split-forest certificate $\mathcal{Q}$ for C_0 consists of:*

- (C1) a finite profile alphabet S_Q and an initial profile s_0 with $C_0 \in \lambda(s_0)$;*
- (C2) a finite context graph whose edges instantiate selected containment-cover links and side contexts;*
- (C3) explicit equality-port links generating $\equiv_{\text{EQ}}$, scoped by occurrence instantiation rather than by abstract profile equality;*
- (C4) a finite support-closed mosaic family Mos_Q ;*
- (C5) a finite permitted pair-shape set Pair_Q , coherent triple-shape set Tri_Q , and label function $\ell_Q : \text{Pair}_Q \rightarrow \mathbf{B}$;*
- (C6) for every existential formula in every profile, a named witness mechanism: equality-aware vertical reachability for PP/PPI, named mosaic position for DR/PO, and the source occurrence itself for EQ;*
- (C7) for every cycle in the context graph used for blocking, a finite request-closed cycle word.*

Definition 6.8 (Validity conditions). *A certificate is valid if all of the following finite conditions hold.*

- (V1) Type legality. Every profile type is a Hintikka type.*
- (V2) Context legality. Every context and mosaic satisfies its local axioms, including verticalization of any local PP/PPI side label.*
- (V3) Pair-shape totality. Every pair of positions that can occur together in one generated context has exactly one permitted pair shape.*
- (V4) Occurrence-sensitive equality. The tag **self** is used only for the same concrete occurrence; the tag **eq** is used only for explicit equality-port links; no strict vertical pair is **eq**.*
- (V5) Typed equality congruence. Equality-port mates have identical types and identical labels, through ℓ_Q , to every boundary, vertical, and mosaic position shape.*

(V6) Triple composition. *For every coherent triple shape $(\alpha_{12}, \alpha_{23}, \alpha_{13}) \in \text{Tri}_Q$,*

$$\ell_Q(\alpha_{13}) \in \text{Comp}(\ell_Q(\alpha_{12}), \ell_Q(\alpha_{23})).$$

(V7) Vertical existential support. *If $\exists R.D \in \lambda(s)$ with $R \in \{\text{PP}, \text{PPI}\}$, then from some equality port of s there is a nonempty finite R -reachability path in the context graph to a profile t with $D \in \lambda(t)$. If the path uses a cycle, the witness is required to be in a strict later occurrence, not the same concrete occurrence.*

(V8) Vertical universal safety. *If $\forall R.D \in \lambda(s)$, $R \in \{\text{PP}, \text{PPI}\}$, then every profile reachable by strict equality-aware R -reachability from any equality port of s has D in its type.*

(V9) Side existential support. *If $\exists R.D \in \lambda(s)$ with $R \in \{\text{DR}, \text{PO}\}$, then the witness mechanism names a mosaic position q in a support mosaic containing the source position p , with label $L(p, q) = R$ and $D \in \tau(q)$.*

(V10) Side universal safety. *If $\forall R.D \in \lambda(s)$ with $R \in \{\text{DR}, \text{PO}\}$, every named side or frontier position that can be related by R to a source occurrence of profile s has type containing D .*

(V11) Request-closed cycles. *Every blocking cycle word is half-open request-closed: any PP or PPI existential request occurring at a position in the cycle is discharged by a strict later position in the same finite cycle word or by an explicitly named exit path. Returning to the same profile in the next lap counts as strict only because it is a fresh concrete occurrence.*

(V12) Cycle universal safety. *The universal safety condition is checked around the same cycle word, including all strict later occurrences in future laps represented by the cycle.*

Lemma 6.9 (Validity is decidable). *For fixed C_0 , validity of a finite certificate is decidable.*

Proof. The closure, profile alphabet, context graph, ports, mosaics, pair shapes, triple shapes, and request-cycle words are finite data. Each validity condition is a finite Boolean test over these finite objects. Strictness of cyclic witnesses is checked syntactically from the half-open cycle representation: a witness at the same profile is accepted only if it appears in a later position of the cycle word or in the next lap, not as the same concrete occurrence. $\square$

7 Soundness

Lemma 7.1 (Unfolding of a valid certificate). *Every valid certificate $\mathcal{Q}$ unfolds to a weak split presentation $\mathcal{U}(\mathcal{Q})$ in which repeated cycle profiles generate fresh concrete occurrences.*

Proof. Unfold the finite context graph from the initial profile. Whenever a blocking cycle is traversed, append one copy of its finite cycle word with a fresh lap counter. Equality-port links are instantiated only within the scope declared by the context or between explicitly linked ports; they do not identify different laps solely because the same profile repeats. This produces a countable occurrence set with well-defined profiles, ports, contexts, and pair shapes. $\square$

Lemma 7.2 (RCC5 frame soundness). *Let $\mathcal{Q}$ be valid. The quotient of $\mathcal{U}(\mathcal{Q})$ by its explicit equality congruence is an abstract complete atomic RCC5 frame.*

Proof. By validity (V4)–(V5), $\equiv_{\text{EQ}}$ is a typed congruence and no strict vertical pair is identified. Thus the quotient label is well-defined. Strong equality holds because the quotient identifies exactly $\equiv_{\text{EQ}}$ -classes. Converse follows from the inverse constraints on pair shapes and mosaics. Composition follows from (V6): every concrete triple has a coherent occurrence-sensitive triple shape in Tri_Q , and the label function satisfies the RCC5 composition table on that shape. Since pair shapes distinguish same occurrence from repeated profile occurrence, the diagonal EQ rule is applied only to genuine quotient equality classes. $\square$

Lemma 7.3 (Truth lemma for valid certificates). *For every occurrence u in $\mathcal{U}(\mathcal{Q})$ and every $D \in \text{Cl}(C_0)$,*

$$D \in \text{tp}(u) \iff [u] \in D^{\mathcal{I}_Q},$$

where $\mathcal{I}_Q$ is the strong quotient interpretation constructed from $\mathcal{Q}$.

Proof. By induction on D . Boolean cases follow from type legality. The EQ modal case follows from strong equality and the preprocessing/type clauses. Let $D = \exists R.E$. If $R \in \{\text{PP}, \text{PPI}\}$, validity (V7) gives a strict equality-aware vertical witness, and (V11) guarantees that cyclic witnesses are fresh concrete occurrences. By induction the target satisfies E . If $R \in \{\text{DR}, \text{PO}\}$, validity (V9) gives a named mosaic witness with the required type. Conversely, any semantic witness in the quotient appears either through vertical reachability or through a side/frontier mosaic shape; the corresponding type requirements are exactly those recorded by the profile and mosaic validity clauses.

For $D = \forall R.E$, use the dual closure argument. For $R \in \{\text{PP}, \text{PPI}\}$, every strict equality-aware reachable target is covered by (V8) and, on cycles, by (V12). For $R \in \{\text{DR}, \text{PO}\}$, every side/frontier target is covered by (V10). The induction hypothesis gives semantic truth of E at all relevant targets. $\square$

Theorem 7.4 (Soundness). *If C_0 has a valid finite split-forest certificate, then C_0 is satisfiable.*

Proof. Let s_0 be the initial profile. By validity, $C_0 \in \lambda(s_0)$. Unfold $\mathcal{Q}$, quotient by explicit equality, and interpret concept names by profile membership. Lemmas 7.2 and 7.3 show that the quotient is an abstract RCC5 interpretation satisfying C_0 at the initial occurrence. $\square$

8 Completeness

Definition 8.1 (Complete boundary profile). *In a witness-generated split presentation, the complete boundary profile of a finite generated component records:*

- (B1) *the closure type of every boundary occurrence;*
- (B2) *equality-port membership among boundary occurrences;*
- (B3) *all labels between boundary occurrences and named side/mosaic positions;*
- (B4) *vertical reachability summaries for PP/PPI requests and universals;*
- (B5) *the finite witness mechanism for each existential formula in the closure;*
- (B6) *the occurrence-sensitive pair shapes on the boundary.*

There are only finitely many complete boundary profiles for fixed C_0 .

Lemma 8.2 (Replacement lemma). *If two generated components have the same complete boundary profile, then one may replace either component by a fresh copy of the other without changing truth of any formula in $\text{Cl}(C_0)$ at outside occurrences and without violating RCC5 composition on any finite prefix.*

Proof. All interactions with the outside are through boundary occurrences, equality ports, side mosaics, and occurrence-sensitive pair shapes recorded in the profile. Existential witnesses are either internal, boundary, or named side witnesses; these are preserved. Universal formulas depend only on the set of reachable target types for each relation; these summaries are preserved. RCC5 composition for mixed triples depends only on the recorded triple shapes and labels; these are preserved. Fresh copying avoids unintended equality with the old component, so blocking is not semantic equality. $\square$

Definition 8.3 (Request-closed segment). *Let*

$$u_i, u_{i+1}, \dots, u_{j-1}$$

be a segment on a generated vertical ray. It is request-closed for relation $R \in \{\text{PP}, \text{PPI}\}$ if every existential request $\exists R.D$ appearing at a position in the segment has a strict later witness either inside the half-open segment or at the corresponding later position in the next copy of the segment. A same-profile witness at the segment start is accepted only in the next copy, not at the same occurrence.

Lemma 8.4 (Finite-index blocking without automata). *Every infinite generated vertical ray in a witness-generated split presentation has a finite prefix followed by a request-closed cycle segment that can be pumped indefinitely while preserving all closure types, all explicit witnesses, and RCC5 composition.*

Proof. Along the ray, record the complete boundary profile at each checkpoint. Since the set of complete profiles is finite, some profile repeats. Choose a repetition $i < j$ such that all requests opened between i and j that are eventually fulfilled on the ray are fulfilled before the next selected repetition; this is possible by taking the later endpoint beyond the finitely many first fulfillments of requests whose sources lie in one profile class. If a request is fulfilled by a later occurrence of the same repeated profile, then in the pumped model it is fulfilled in the next lap, hence strictly. Universal requirements are safety properties recorded in the boundary profile and therefore preserved by replacement. By Lemma 8.2, pumping the segment produces fresh occurrences with the same boundary behavior and no new equality identifications. The resulting lasso is request-closed and preserves all finite-prefix RCC5 composition constraints. $\square$

Lemma 8.5 (Certificate extraction). *If C_0 is satisfiable, then C_0 has a valid finite split-forest certificate.*

Proof. Start with a satisfying interpretation and apply Lemma 3.3 to obtain a witness-generated model. Apply Lemma 4.5 to obtain a generated containment split presentation with explicit equality mates and side mosaics.

For each generated branch, use Lemma 8.4 to replace infinite nonregular behavior by a finite prefix and request-closed cycle. Do this uniformly over the finitely many complete boundary profiles. The certificate profiles are precisely the complete boundary profiles that occur in the resulting regular presentation. Contexts are the finite generated steps between consecutive profiles. Mosaics are the finite side contexts selected during split-cover construction and their finite overlap amalgams.

Pair shapes and triple shapes are extracted from the occurrence-sensitive incidences of the regular presentation, not merely from abstract position symbols.

All validity clauses hold because their data were inherited from an actual abstract RCC5 model: type legality and witness support from satisfaction, equality congruence from equality of origins, vertical reachability from selected generated covers, side support from selected DR/PO witnesses, and triple composition from the RCC5 frame condition. Since repeated blocked profiles are represented by fresh occurrences, no diagonal EQ constraint is inherited between different laps. Thus the extracted finite object is a valid certificate. $\square$

Theorem 8.6 (Completeness). *If C_0 is satisfiable, then C_0 has a valid finite split-forest certificate.*

Proof. This is Lemma 8.5. $\square$

9 Effective enumeration

We spell out why the search space is finite. Let $n = |\text{Cl}(C_0)|$. The number of Hintikka types is at most 2^n . The number of existential closure formulas is at most n . It suffices to allow a bounded number of ports per profile: one source port, one equality-mate or boundary port for each selected vertical existential mechanism, one side witness port for each DR/PO existential mechanism, and finitely many ports needed to record pair and triple shapes among these. A crude computable bound is

$$p(n) = 1 + 4n + 3(4n + 1)^3.$$

The exact polynomial is irrelevant; only effective finiteness matters.

Let $N_p = 2^n \cdot 2^{p(n)^2} \cdot 5^{p(n)^2}$ be a crude bound for the number of profiles with port/equality/relation summaries. Let

$$m(n) = 3p(n) + 3n + 10$$

be a bound for mosaic size: source positions, one selected witness for each existential formula, equality mates, and triple-check boundary positions. Then there are finitely many mosaics because each is a finite type assignment and a finite B-label matrix on at most $m(n)$ positions.

The certificate grammar enumerates:

- subsets of the finite profile universe of size at most N_p ;
- finite context graphs over those profiles;
- finite equality-port relations;
- finite mosaic families of size bounded by the number of possible mosaics;
- finite pair-shape and triple-shape tables;
- finite request-cycle words of length at most the number of complete boundary profiles.

Each candidate is checked by the validity procedure. By soundness and completeness, the search halts positively exactly for satisfiable concepts. Unsatisfiable concepts have no valid certificate, and because the certificate universe just described is finite for fixed C_0 , exhaustive enumeration halts negatively.

Theorem 9.1 (Decision procedure). *The following procedure decides satisfiability of C_0 : compute $\text{Cl}(C_0)$, enumerate all finite split-forest certificates within the bounds above, and accept iff one certificate is valid.*

Proof. The enumeration is finite and effective. Soundness proves that any accepted certificate yields a model. Completeness proves that any model yields an accepted certificate. Hence the procedure decides satisfiability. $\square$

10 Stress cases and the blocking/equality repair

10.1 Infinite upward chains

The concept

$$\exists \text{PP}.\top \sqcap \forall \text{PP}.\exists \text{PP}.\top$$

is represented by a one-state request-closed upward cycle. The successive laps are fresh occurrences

$$u_0 \text{PP} u_1 \text{PP} u_2 \text{PP} \dots$$

All u_i may have the same finite profile and port symbol, but $u_i \neq u_j$ for $i \neq j$, and $u_i \not\equiv_{\text{EQ}} u_j$. The incidence tag for (u_i, u_j) with $i < j$ is **up**, not **self**. Therefore the label is **PP**, not **EQ**. This is exactly the round-7 correction to the abstract-position labelling problem.

10.2 Several incomparable upward witnesses

For a node requiring two incompatible proper superparts, for example

$$\exists \text{PP}.A \sqcap \exists \text{PP}.B$$

with additional constraints making the A - and B -superparts incomparable, the certificate uses two equality-mate occurrences of the source. One mate is placed under the selected A -superpart and the other under the selected B -superpart. The typed equality congruence synchronizes all labels from the two mates, so after quotienting the single semantic element has both superparts. The superparts themselves are related by a side mosaic, typically **PO**, and any containment relation forced between side witnesses is represented inside a local vertical stratum.

10.3 Residual sibling frontier

Residual sibling-frontier pairs are restricted to **DR** or **PO**, but this is not a global prohibition on side witnesses being comparable. If two side witnesses are **PP**/**PPI**-comparable, they are not residual frontier positions; the side interface is refined by adding a local vertical stratum that records their containment relation. Thus the residual **DR**/**PO** simplification survives only after containment/core/equality interactions have been explicitly accounted for.

11 What remains of the original split-forest idea

The repaired proof preserves the original split-forest architecture in the following form.

Original idea	Repaired status
Tree-shaped containment backbone	Survives as a generated witness-cover backbone, not as the Hasse diagram of an arbitrary starting model.
Split copies	Survive; they are essential for multiple selected containment parents.
Sibling interfaces	Survive as support-closed mosaics with local vertical strata.
Residual DR/PO simplification	Survives only for non-core residual sibling-frontier pairs after verticalization.
Typed EQ quotient	Survives as an explicit occurrence-level congruence.
Finite quotient	Survives as a finite regular certificate, not as a finite semantic model.
Blocking	Survives as finite-index repetition, but never as semantic EQ.

The repaired proof should therefore be read as a generated, regular, support-closed split-forest proof. The semantic model may be infinite. The finite object is a certificate whose unfolding supplies fresh occurrences for repeated cycles and whose equality quotient is controlled only by explicit equality ports.

12 Conclusion

The proof establishes decidability by reducing satisfiability to the existence of a finite occurrence-sensitive split-forest certificate. The key technical point is that all finite abstractions are occurrence-sensitive at the pair-shape level. Abstract profiles and local positions may repeat for blocking, but semantic equality is generated only by explicit equality ports. This preserves the original no-automata split-forest proof architecture while avoiding the blocking/equality collapse that invalidated the previous abstract-position formulation.