

On the Decidability of $\mathcal{ALCI}_{\text{RCC5}}$ (and $\mathcal{ALCI}_{\text{RCC8}}$) Concept Satisfiability: Split-Forest Models, a Conditional Decidability Theorem, and a Machine-Checked Reduction to One Keystone

Michael Wessel

(with AI assistants: Claude / Anthropic, GPT-5.5 / OpenAI)

July 2026

Abstract

Whether concept satisfiability in $\mathcal{ALCI}_{\text{RCC5}}$ and $\mathcal{ALCI}_{\text{RCC8}}$ —the description logic $\mathcal{ALCI}$ with the RCC5/RCC8 base relations as roles under *abstract composition-table* semantics—is decidable has been open since Wessel’s 2002/2003 work. This paper reports a sustained, adversarially-reviewed, partly machine-checked attack on the problem, conducted by AI assistants under human direction. We do not settle the question. What we establish is: (i) a *conditional decidability theorem*—if the “live width” of models is bounded by a computable function of the concept (property F6), then satisfiability is decidable—whose soundness direction is *machine-checked in Lean 4*; (ii) that the entire remaining difficulty compresses into that single property F6, which we show is the *same fact* that blocks a proof of undecidability; (iii) a certified fragment of the local algebra (an RCC5 normal form) and an unconditionally decidable fragment (the $\forall\text{PO}$ -free concepts); and (iv) an honest map of the routes tried, the dead ends, and the missing hard pieces. We also report, candidly, on the methodology—adversarial “cold review,” machine verification, and a human-in-the-loop workflow—and on what frontier AI could and could not do.

Contents

1	Introduction	2
1.1	AI disclaimer and authorship	2
1.2	Why the problem is hard, in one page	2
1.3	Scope, contributions, and structure	3
2	Current status: where we stand after twenty-five years	4
3	History of $\mathcal{ALCI}_{\text{RCC}}$ and why the known results do not settle it	5
3.1	Cohn’s 1993 proposal	5
3.2	Wessel’s $\mathcal{ALCI}_{\text{RCC}}$ family (2002/2003)	5
3.3	Wessel’s grid constructions and the coincidence obstruction	6
3.4	Lutz & Wolter (2006)	6

4	Why standard undecidability reductions fail	7
4.1	Blocked reduction routes	7
4.2	A concrete domino attempt in $\mathcal{ALCI}_{\text{RCC5}}$	7
4.3	A concrete domino attempt in $\mathcal{ALCI}_{\text{RCC8}}$	8
5	Overview of approaches, by technique	9
5.1	Naive tableaux and blocking	9
5.2	Finite-model and reduction attempts	10
5.3	The split-forest idea	11
5.4	The no-automata certificate, and the automata route	12
5.5	The Lean line and F6	12
5.6	The regular-cover pivot	13
6	Current implementation: reasoners	13
7	On agentic AI usage	14
8	Summary and conclusion	15
A	On the DL 2026 rejection	21

1 Introduction

1.1 AI disclaimer and authorship

The mathematical content of this paper was produced by AI assistants (Anthropic’s Claude models and OpenAI’s GPT-5.5), prompted, steered, and reviewed by the human author (Michael Wessel), who posed the problem, supplied the central intuitions and directions, orchestrated the review–repair cycles, and takes responsibility for the framing. **The results are unverified by human domain experts and should be read as AI-generated conjectures supported by machine checking and computational evidence—not as established theorems**, with the explicit exceptions of the parts stated to be kernel-checked in Lean 4 (the soundness pipeline, the abstraction’s faithfulness, and the RCC5 normal form), which are machine-verified but still human-unreviewed. We are deliberate about this labelling throughout: the standing one-line status is *strongly supported, not certified*. We regard the AI systems as having made contributions of a kind that, in a human collaborator, would warrant co-authorship, and we discuss this in §7.

1.2 Why the problem is hard, in one page

RCC5 relates two regions by exactly one of five relations: equal (EQ), proper part (PP), proper superpart (PPI), partial overlap (PO), or discreteness/disjointness (DR). Under *abstract composition-table* semantics a model is not a set of actual regions but a set with a total labelling of ordered pairs by these relations, required only to be converse-closed and *composition-closed*: if $x R y$ and $y S z$ then $x T z$ for some T the composition table allows.

The five relations split into two axes that behave completely differently.

- **The vertical axis** (PP, PPI: nesting) is *tame*. Composition can *force* vertical structure—the only four “determining” compositions (those returning a single relation) all run through PP or PPI—but an unbounded vertical chain folds into a finite loop, exactly as in ordinary modal logic. Infinite depth is not the problem.

- **The horizontal axis** (DR, PO: side-by-side) is *wild*. Composition can never *determine* a horizontal relation (PO is never a forced value), yet it can force two occurrences to be *distinct* (a shared horizontal anchor excludes EQ). So horizontal “crowds” of pairwise-distinct occurrences are the danger.

A finite decision procedure must record, at each interface of a model, the genuine branching it cannot reconstruct—the *live width*. Many forced edges are *shadows* (implied by composition from edges already present) and cost nothing; live width counts only the rest. The whole decidability question reduces to one property:

(F6) Is the live width of models bounded by a computable function of the input concept?

If yes, the certificate space is finite and satisfiability is decidable. And here is the knife’s edge: F6 is *the same fact* that blocks proving the problem *undecidable*. To force undecidability one would encode a rigid coordinate grid, which requires forcing a horizontal relation to a single value—exactly what the composition table cannot do (the “coincidence obstruction” Wessel identified in 2002/2003). Turn that looseness into a bound and one gets decidability; circumvent it and force a grid and one gets undecidability. The two open directions are one question seen from two sides, which is why neither has been settled in over twenty years.

1.3 Scope, contributions, and structure

This is both a technical report and a discussion piece. Its contributions are:

1. A *conditional decidability theorem* ($F6 \Rightarrow \text{decidable}$) whose soundness half is machine-checked in Lean 4 (§5.5), and the reduction of the whole problem to F6.
2. The identification of F6 as the shared keystone of the decidability and undecidability directions (§1.2, §8).
3. A certified RCC5 *normal form* and an unconditionally decidable $\forall\text{PO-free}$ fragment (§5.2, §5.6).
4. An honest, technique-organized account of every route tried, the counterexamples that killed the wrong ideas, and the lessons (§5), so that others need not repeat them.
5. A candid methodology report on adversarial AI-assisted mathematics (§7).

The paper is organized as follows. §2 states, in largely non-technical terms, where the problem stands after twenty-five years. §3 gives the history ($\mathcal{ALCC}\mathcal{I}_{\text{RCC}}$ from Cohn 1993 through Wessel 2002/2003 and Lutz–Wolter 2006) and carefully distinguishes our object from the neighbouring logics that *are* known undecidable. §4 explains why the standard undecidability reductions fail. §5—the core of the paper—surveys the approaches *by technique*: naive tableaux and blocking, finite-model and reduction attempts, the split-forest idea, the automata route, the Lean line culminating in F6, and the regular-cover pivot. §6 describes the working reasoners and a GIS example. §7 reports on the AI methodology. §8 concludes with what was learned, what would move the needle, an honest estimate of the chances of closing F6, and the project’s actual wins.

2 Current status: where we stand after twenty-five years

Decidability of $\mathcal{ALCT}_{\text{RCC5}}$ (and $\mathcal{ALCT}_{\text{RCC8}}$) concept satisfiability remains open. A current-literature check (July 2026) found no published resolution; the closest neighbours are decided in the other direction and are discussed in §3. What the present work adds is not an answer but a sharp reduction and a machine-checked surround.

The positive result—conditional decidability. *If the live width of models is bounded by a computable function of the concept (property F6), then concept satisfiability is decidable; and the soundness half of that reduction is machine-checked in Lean 4* (a valid finite certificate provably unfolds to a genuine RCC5 model of the concept, and the finite type abstraction is faithful). What is open is the antecedent F6 itself—equivalently the completeness direction, that every satisfiable concept has a *bounded* finite certificate.

What is certified (machine-checked, Lean 4, zero sorry):

- the *soundness* pipeline: a valid finite certificate unfolds to a genuine RCC5 model of the concept;
- the *faithfulness* of the finite (Hintikka) abstraction: satisfiability and abstraction-realizability coincide;
- the *RCC5 normal form* (forward): every strong-EQ RCC5 network is an ordered-disjoint structure—a strict partial order for PP with a downward-closed disjointness for DR, PO residual.

What is strongly supported but not certified: F6, the single open keystone—now sharpened to a precise combinatorial dichotomy (does some concept force unbounded “identity-selector minors”?), with the auxiliary uniformization property W2’ shown to *fold into* it.

Unconditional by-products (independent of F6):

- the $\forall\text{PO}$ -free fragment is *decidable*—concepts with no $\forall\text{PO}$ subformula, still retaining $\exists\text{PO}$, $\forall\text{DR}$, $\exists\text{DR}$, and all vertical modalities, so a genuinely expressive spatial fragment;
- the certified RCC5 normal form above;
- working reasoners (a cover-tree tableau) that reproduce, 23 years later, the GIS taxonomy of Wessel’s original report;
- the standard undecidability routes shown blocked, with the coincidence obstruction identified as the shared fact.

The honest bottom line. After roughly thirty repair rounds and fifteen adversarial reviews the project has reached a genuine *local optimum*: the local algebra is exhausted (and in one case certified), the soundness side is machine-checked, and the whole remaining difficulty is one well-posed lemma. We offer the work not as a resolution but as a two-decade open problem *reduced, honestly and checkably, to its irreducible core*.

3 History of $\mathcal{ALCI}_{\text{RCC}}$ and why the known results do not settle it

3.1 Cohn’s 1993 proposal

The idea of combining description logics with qualitative spatial reasoning via modal accessibility relations was first proposed by Cohn [1], who considered treating the RCC8 relations (or subsets thereof) as modalities in a multi-modal logic. The framework allowed spatial constraints to be expressed as modal formulas—e.g., $\langle \text{PP} \rangle C$ for “some proper part satisfies C ”—but Cohn left all decidability and complexity questions open.

3.2 Wessel’s $\mathcal{ALCI}_{\text{RCC}}$ family (2002/2003)

Wessel [7, 8, 5] gave the first rigorous treatment of the combination, introducing the $\mathcal{ALCI}_{\text{RCC}}$ family: description logics $\mathcal{ALCI}_{\text{RCC}k}$ ($k = 1, 2, 3, 5, 8$) extending $\mathcal{ALCI}$ with role boxes derived from the RCC composition tables. In an $\mathcal{ALCI}_{\text{RCC}k}$ interpretation, every pair of domain elements is assigned exactly one RCC k base relation, and the composition table is enforced globally (*strong EQ semantics*: EQ is identity). Models are complete graphs with RCC k edge-colorings.

Wessel established the following:

- **Decidable cases:** $\mathcal{ALCI}_{\text{RCC}1}$, $\mathcal{ALCI}_{\text{RCC}2}$, and $\mathcal{ALCI}_{\text{RCC}3}$ are decidable, because their composition tables are deterministic or near-deterministic, admitting reduction to standard DL techniques.
- **Lower bounds:** $\mathcal{ALCI}_{\text{RCC}5}$ is PSPACE-hard; $\mathcal{ALCI}_{\text{RCC}8}$ is EXPTIME-hard.
- **Open:** The decidability of $\mathcal{ALCI}_{\text{RCC}5}$ and $\mathcal{ALCI}_{\text{RCC}8}$ was left as the central open problem.

In a series of companion reports, Wessel also mapped out the decidability landscape for description logics with general composition-based role inclusion axioms:

- $\mathcal{ALC}_{\mathcal{RA}}$ (arbitrary role axioms) is **undecidable**, via reduction from the Post Correspondence Problem [6].
- $\mathcal{ALC}_{\mathcal{RA}}^{\ominus}$ (non-disjoint-roles variant) is also **undecidable**, via reduction from non-empty CFG intersection [3].
- $\mathcal{ALC}_{\mathcal{RASG}}$ (admissible role boxes: deterministic, functional, complete, and associative) is **decidable** (EXPTIME-complete, via reduction to $\mathcal{ALC}$ with general TBoxes) [4]; adding unqualified number restrictions ($\mathcal{ALCN}_{\mathcal{RASG}}$) makes it undecidable again.

$\mathcal{ALCI}_{\text{RCC}5}$ sits precisely in the gap: its role box is non-deterministic (unlike $\mathcal{ALC}_{\mathcal{RASG}}$) but has the patchwork property (unlike $\mathcal{ALC}_{\mathcal{RA}}/\mathcal{ALC}_{\mathcal{RA}}^{\ominus}$).

Remark 1 (Key difficulties). $\mathcal{ALCI}_{\text{RCC}5}$ has none of the properties that standard DL decidability proofs rely on: (i) no tree model property (models are complete graphs), (ii) no finite model property (some satisfiable concepts require infinite models), (iii) a non-deterministic role box (multi-valued composition entries).

For reference, the full RCC5 composition table is given in Table 1. Reading: row = $S(b, c)$, column = $R(a, b)$, entry = possible relations for (a, c) .

Key composition facts exploited in the cover-tree theory (§5.3, §6): $\text{comp}(\text{PP}, \text{DR}) = \{\text{DR}\}$ and $\text{comp}(\text{DR}, \text{PPI}) = \{\text{DR}\}$ (DR rigidity); $\text{comp}(\text{PP}, \text{PP}) = \{\text{PP}\}$ and $\text{comp}(\text{PPI}, \text{PPI}) = \{\text{PPI}\}$ (transitivity); and $\text{comp}(\text{DR}, \text{PO}) = \{\text{DR}, \text{PO}, \text{PP}\}$ (PP can be *forced* by composition and universal filtering; see the forced-composition examples in §5.1).

Table 1: The RCC5 composition table (* = all five relations).

comp	DR(a, b)	PO(a, b)	EQ(a, b)	PPI(a, b)	PP(a, b)
DR(b, c)	*	DR, PO, PPI	DR	DR, PO, PPI	DR
PO(b, c)	DR, PO, PP	*	PO	PO, PPI	DR, PO, PP
EQ(b, c)	DR	PO	EQ	PPI	PP
PP(b, c)	DR, PO, PP	PO, PP	PP	PO, EQ, PP, PPI	PP
PPI(b, c)	DR	DR, PO, PPI	PPI	PPI	*

3.3 Wessel’s grid constructions and the coincidence obstruction

In his investigation of $\mathcal{ALCI}_{RCC8}$ [8], Wessel made two important discoveries:

1. Even-odd chains (Section 4.4.2). The TPP/NTPP distinction in RCC8 allows the construction of *functional successor chains*: each node alternates between *even* and *odd*, and a node can distinguish its direct TPPI-successor from all indirect ones by parity. Wessel used this to encode a binary n -bit counter, proving $\mathcal{ALCI}_{RCC8}$ is EXPTIME-hard.

2. The grid coincidence obstruction (Section 4.4.3, Figure 11). Wessel constructed explicit RCC8 networks isomorphic to $n \times n$ grids, using TPP for horizontal and vertical successors. However, he identified a fundamental obstacle to encoding domino tilings: the *coincidence condition* $R_X \circ R_Y = R_Y \circ R_X$ (east-of-north equals north-of-east) cannot be enforced by concept terms. The composition table allows $\{PO, EQ, TPP, NTPP, TPPI, NTPPI\}$ at the coincidence point—too many options. Wessel concluded:

“Even though these infinite models do exist, we have found no way to *enforce* the depicted model(s) by means of a concept term.”

Wessel further observed that adding a hybrid logic binding operator $\downarrow$ (nominals) would immediately yield undecidability, confirming that the coincidence condition is the *precise boundary*.

Wessel thus independently developed, three to four years before Lutz–Wolter, the RCC8 description-logic analogues of these ingredients—the even-odd chain, an explicit two-dimensional TPP/NTPP grid, and the first identification of the coincidence gap as the decisive obstacle. Lutz–Wolter later obtained undecidability by a *different* route—a linearized tiling enumeration (their §5, following Marx–Reynolds) that sidesteps the two-dimensional coincidence rather than enforcing it—so this is shared lineage and prior identification, not a dependence of their proof on Wessel’s constructions.

3.4 Lutz & Wolter (2006)

Lutz and Wolter [9] studied *modal logics of topological relations*, denoted L_{RCC8} , L_{RCC5} , etc. These have the same *syntax* as $\mathcal{ALCI}_{RCC}$ but are interpreted over *topological models*: the domain elements are regular closed subsets of a topological space (typically $\mathbb{R}^n$). They proved:

- L_{RCC8} is **undecidable** (their §5: a linearized NTPP-chain enumeration of tile positions, following Marx–Reynolds, whose faithfulness relies on the geometry of $\mathbb{R}^n$; no two-dimensional grid coincidence is enforced).
- $L_{RCC5}(RS^\exists)$ is **undecidable** (reduction from $S5^\exists$ via supremum regions).

Table 2: Why standard undecidability reductions fail for $\mathcal{ALCI}_{RCC5}$.

Source lem	Prob-	Technique	Missing $\mathcal{ALCI}_{RCC5}$	in
$\mathbb{N} \times \mathbb{N}$ domino		Graded modalities + transitivity	Number restrictions	
$\mathcal{ALC}_{\mathcal{RA}}$ [6]		Post Correspondence Problem	Arbitrary role axioms	
$\mathcal{ALC}_{\mathcal{RA}}^{\ominus}$ [3]		Non-empty CFG intersection	Non-disjoint roles	
$\mathcal{ALCI}_{RCC8}$ (Wessel)		Grid via TPP/NTPP	TPP/NTPP distinction	
L_{RCC8} (Lutz–Wolter)		Linearized topological enumeration	Topological rigidity	
$L_{RCC5}(RS^{\exists})$		$S5^3$ via supremum regions	Supremum closure	

- $L_{RCC5}(RS)$ is **open**. Lutz and Wolter explicitly wrote (p. 31): “Perhaps the most interesting candidate is $L_{RCC5}(RS)$ [...] to which the reduction exhibited in Section 8 does not apply.”

The logic $\mathcal{ALCI}_{RCC5}$ is exactly $L_{RCC5}(RS)$: arbitrary complete-graph models with composition-table semantics. The problem has been recognized as open by leading researchers since 2006.

4 Why standard undecidability reductions fail

Undecidability proofs for description logics use a variety of techniques: grid encoding ($\mathbb{N} \times \mathbb{N}$ domino tiling, requiring functional roles or number restrictions), reduction from the Post Correspondence Problem (PCP), reduction from context-free grammar (CFG) intersection, or simulation of $S5^3$ via geometric constructions. $\mathcal{ALCI}_{RCC5}$ lacks the features that each of these techniques exploits: it has no functional roles, no number restrictions, no arbitrary role box, and no geometric coincidence conditions.

4.1 Blocked reduction routes

Table 2 summarizes the blocked routes. The **patchwork property** of RCC5 (Renz & Nebel [2])—local (triple-wise) consistency implies global consistency for atomic networks—actively resists grid encoding, since tiling reductions require rigid global constraints that go beyond local consistency.

4.2 A concrete domino attempt in $\mathcal{ALCI}_{RCC5}$

Can we encode a domino-like grid using PP/PPI chains in RCC5? Consider the concept:

$$\begin{aligned}
X = & \exists PPI. \exists PPI. C \sqcap \exists PPI. \exists PPI. D \\
& \sqcap \forall PPI. \forall PPI. (\forall PO. (\neg C \sqcap \neg D) \sqcap \forall DR. (\neg C \sqcap \neg D)) \\
& \qquad \sqcap \forall PPI. (\neg C \sqcap \neg D) \sqcap \forall PP. (\neg C \sqcap \neg D)) \\
& \sqcap \forall PPI. \exists PPI. X
\end{aligned}$$

The intent: each X -node has two PPI-grandchildren colored C and D (the “square”), and the universals isolate the colored nodes from all non-EQ neighbors. The recursive $\forall\text{PPI}.\exists\text{PPI}.X$ forces infinite repetition.

One level is satisfiable. Without the recursive conjunct, X has a 3-element model: $z \text{ PP } y \text{ PP } x$, with $z \in C \sqcap D$. The two grandchildren are forced to be *the same element* (EQ collapse): if $z_1 \neq z_2$, they would be related by some $R \in \{\text{DR}, \text{PO}, \text{PP}, \text{PPI}\}$, and the universals would require $z_2 \notin D$ (firing z_1 ’s $\forall R. \neg C \sqcap \neg D$). So $z_1 = z_2 \in C \sqcap D$, and the universals are vacuously satisfied (the only neighbors of z are PP-predecessors, not PO/DR/PPI-neighbors).

Two levels is unsatisfiable. Adding $\forall\text{PPI}.X$: the PPI-child y must itself satisfy X (without recursion), producing a new $C \sqcap D$ -labeled element w as a PPI-child of z . But z is a PPI-grandchild of x , and x ’s universals fire: z ’s PPI-neighbor w must satisfy $\neg C \sqcap \neg D$. Yet $w \in C \sqcap D$. **Contradiction.**

This was verified computationally: a simplified version $X_1 = \exists\text{PPI}.\exists\text{PPI}.C \sqcap \forall\text{PPI}^3.\neg C$ is SAT; $X_2 = X_1 \sqcap \forall\text{PPI}.X_1$ is UNSAT. The domino encoding collapses at depth 2 because the isolation constraints from the grandparent level kill the colored elements created by the recursive unfolding.

Remark 2. The failure is not accidental. In $\mathcal{ALCI}_{\text{RCC5}}$, the only way to create “functional” successors is via PP/PPI chains, but $\text{comp}(\text{PPI}, \text{PPI}) = \{\text{PPI}\}$ makes these chains *transitive*—grandparent universals automatically propagate to grandchildren, preventing the positional diversity needed for grid encoding. In $\mathcal{ALCI}_{\text{RCC8}}$, the TPP/NTPP distinction breaks this transitivity (a direct TPPI-child is distinguishable from indirect descendants), which is why Wessel’s even-odd chain works there but has no RCC5 analogue.

4.3 A concrete domino attempt in $\mathcal{ALCI}_{\text{RCC8}}$

The remark above suggests the TPPI/NTPPI distinction in $\mathcal{ALCI}_{\text{RCC8}}$ might rescue the construction: a direct successor (TPPI) and an indirect one (NTPPI) are genuinely distinguishable, so perhaps the level-2 collapse can be avoided. We attempt the analogue and show that while it escapes the RCC5 failure mode, it fails for a different reason—Wessel’s *coincidence obstruction* [8].

The schema. Let Corner be the concept that isolates a node from all non-EQ neighbors:

$$\text{Corner} = \bigwedge_{R \in \{\text{DC}, \text{EC}, \text{PO}, \text{TPP}, \text{NTPP}, \text{TPPI}, \text{NTPPI}\}} \forall R. (\neg C \sqcap \neg D).$$

The isolation is placed *locally on the colored grandchildren* rather than as an ancestral $\forall\text{TPPI}.\forall\text{TPPI}$ universal, so it cannot propagate transitively through the recursion:

$$\begin{aligned} X = & \exists\text{TPPI}.\exists\text{TPPI}.(C \sqcap \text{Corner}) \sqcap \exists\text{TPPI}.\exists\text{TPPI}.(D \sqcap \text{Corner}) \\ & \sqcap \forall\text{TPPI}.(\neg C \sqcap \neg D) \sqcap \forall\text{TPPI}.X. \end{aligned}$$

The third conjunct $\forall\text{TPPI}.(\neg C \sqcap \neg D)$ forces the corner relation $x \rightarrow z$ to be NTPPI (not TPPI), using $\text{comp}(\text{TPPI}, \text{TPPI}) = \{\text{TPPI}, \text{NTPPI}\}$.

Level 1 is satisfiable, with a real direct/indirect distinction. Without recursion, x has TPPI-children y_1, y_2 (the two “direct” positions) and a single corner z reached by TPPI-TPPI chains from both y_1 and y_2 . The EQ-collapse at level 2 works exactly as in RCC5: $z_1 \in C \sqcap \text{Corner}$ and $z_2 \in D \sqcap \text{Corner}$ are mutual non-EQ neighbors only if Corner is violated, so under strong-EQ semantics $z_1 = z_2 = z$. Crucially, $z \neq y_1, y_2$ in general: z is NTPPI of x while y_1, y_2 are TPPI—the direct/indirect distinction survives, which is a genuine RCC8 refinement over the RCC5 attempt of §4.2.

Level 2 collapses via the coincidence obstruction. Adding $\forall \text{TPPI}.X$: the TPPI-child y of x satisfies X , producing its own corner $w \in C \sqcap D \sqcap \text{Corner}$ at NTPPI-distance from y , and hence at NTPPI-distance from x via $\text{comp}(\text{TPPI}, \text{NTPPI}) = \{\text{NTPPI}\}$. Now x ’s own corner z and y ’s corner w are distinct grid positions in the intended reading—but as elements of the model they are related by some RCC8 base relation. Since z carries **Corner**, every non-EQ neighbor of z lies in $\neg C \sqcap \neg D$. But $w \in C \sqcap D$. Therefore $z = w$ under strong-EQ. **All corners across the grid coincide at a single point.**

Why the TPPI/NTPPI trick fails. In the RCC5 attempt the collapse is a *transitive-propagation* failure: the grandparent universal fires on great-grandchildren because $\text{comp}(\text{PPI}, \text{PPI}) = \{\text{PPI}\}$. Moving the isolation to a local **Corner** marker and using the non-transitive piece $\text{comp}(\text{TPPI}, \text{TPPI}) = \{\text{TPPI}, \text{NTPPI}\}$ eliminates that specific pathway—the universal at the grandparent no longer reaches deeper nodes. But a *different* obstruction takes over: the composition table permits any of $\{\text{PO}, \text{EQ}, \text{TPP}, \text{NTPP}, \text{TPPI}, \text{NTPPI}\}$ between two corners at different intended grid coordinates, and nothing in the concept language rules out EQ. The **Corner** markers themselves then force the EQ-merge. This is exactly the obstruction Wessel identified in report7.pdf, Figure 11 (cf. §3.3): the composition table does not carry the rigidity needed to keep distinct grid cells distinct.

Remark 3. The failure mode is structurally different from the RCC5 one but traces back to the same root cause. Lutz–Wolter’s L_{RCC8} reduction *circumvents* the coincidence obstruction rather than enforcing it: they linearize the plane into a single NTPP-chain (the Marx–Reynolds enumeration) and recover the vertical direction from the enumeration, so no “north-of-east = east-of-north” coincidence has to be forced; the geometry of $\mathbb{R}^n$ only has to keep that linear encoding faithful [9]. No such rigidity is available in the abstract RCC8 semantics of $\mathcal{ALCI}_{\text{RCC8}}$: a pure composition table allows corner points to merge freely, and the TPPI/NTPPI distinction—while useful locally for a direct/indirect separation at level 2—cannot be chained to enforce an unbounded $\mathbb{N} \times \mathbb{N}$ grid. This matches the open-problem status of $\mathcal{ALCI}_{\text{RCC8}}$ decidability noted in [9] and further discussed in [8].

5 Overview of approaches, by technique

We organize the attack by *technique*, in roughly the order tried, not by round or date. Each subsection follows the same shape: the high-level idea; the concrete techniques investigated; where and why they fail (with the examples that made the failure clear); pointers to the papers, probes, and reasoners; and the lessons.

5.1 Naive tableaux and blocking

Idea. The first and most natural attack is a description-logic tableau: build a tree-shaped model top-down, expand each $\exists R.C$ by a fresh R -successor, propagate universals, and *block* a node when its type repeats an ancestor’s so the procedure terminates. The refined version we implemented is the *cover-tree tableau* (§6), which blocks on *exact occurrences* rather than mere types.

Techniques investigated. Because RCC5 assigns a relation to *every* pair, the model is a complete edge-coloured graph, and ordinary subset blocking is unsound. We investigated a ladder of stronger blocking conditions, each tracking more relational context: *triangle types* and triangle blocking (track composition triangles (x, y, z) ; `triangle_blocking_ALCIRCC5`, `src/triangle_*.py`), *quadruple types* (decidability via quadruples `ALCIRCC5`, `src/quadruple_type_check.py`), *profile blocking* (`src/profile_blocking_*.py`), *double blocking* (the *SHIQ* device for inverse roles;

`src/double_blocking_test.py`), and pairwise/neighbourhood blocking (`src/tri_neighborhood_check.py`, `src/three_arm_star_check.py`).

Why they fail. All of them founder on the same three phenomena, which are the reason the total-relation setting is genuinely harder than ordinary DL:

- **Composition forces edges *into* old nodes.** From $x \text{ PP } y$ and $y \text{ DR } z$, the table forces $x \text{ DR } z$: a new edge into the already-processed x . Such forced back- and cross-edges destroy the tree structure that blocking relies on and can add new obligations to a blocked node.
- **Dormant universals.** A $\forall R.C$ sits inert until an R -edge appears; a forced composition edge (above) can *later* fire a universal at a node already blocked, so the block was unsound. Re-qualifying an old node can *unblock* it, and the cascade need not terminate.
- **The one-point extension problem.** A configuration can be locally consistent (every triangle composition-closed) yet admit *no* extension by a required fresh witness—path-consistency is not extensibility.

The examples that made this clear. Two families were decisive. The forced-composition UNSAT concepts such as $C_{\text{force}} = \exists \text{PP}.(\exists \text{DR}.A) \sqcap \forall \text{DR}.\neg A$ (here $x \text{ PP } y, y \text{ DR } z \Rightarrow x \text{ DR } z$, so $\forall \text{DR}.\neg A$ kills the required $z:A$) show a naive procedure *accepting* unsatisfiable input if it ignores forced edges. And the strong-EQ PO-loop, $C \sqcap \exists \text{PO}.\exists \text{PO}.C \sqcap \forall \{\text{PO}, \text{DR}, \text{PP}, \text{PPI}\}.\neg C$, is satisfiable only via a two-element symmetric loop under EQ-identity — a model a type-based procedure *rejects*. These and further diagnostics (`inter_witness_counterexample_ALCIRCC5`, `typed_patchwork_counterexample_ALCIRCC5`) are exercised against the cover-tree tableau as the oracle.

Lesson. Sound termination in the total-relation setting cannot be obtained by local blocking, because the relational completion is global. One must *separate* the tree skeleton from the relational completion and control the latter by the patchwork property — which is exactly the split-forest idea (§5.3).

5.2 Finite-model and reduction attempts

Idea. If models can be forced finite (or finitely presented), one can enumerate and check. The concrete techniques: collapse infinite PP/PPI chains into finite *clusters/loops*; build a *quasimodel* and eliminate inconsistent types; take a *two-tier quotient* (one kernel per recurrent chain descriptor, plus finitely many designated witnesses); or *encode into MSO* over trees and invoke Rabin’s theorem.

Where they fail. The quasimodel / type-elimination route (`decidability_ALCIRCC5`, `src/alcircc5_reasoner`) is *retracted*: its Q3 anti-monotonicity causes cascade elimination and hence incompleteness (not unsoundness). The reasoner remains SAT-trustworthy but is provably incomplete on the PO-loop pattern above. The MSO route (`MSO_encoding_ALCIRCC5`) needs the horizontal crowd width to be MSO-definable/bounded — which is F6 again. Every “bound the model” variant reduces to producing a computable width bound, i.e. to F6.

The win. One fragment falls out unconditionally. In the two-tier quotient, PO is the only relation whose recurrence needs an all-phase safety condition; a concept with *no* $\forall \text{PO}$ *subformula* makes that condition vacuous, so it has a finite quotient and a computable live-width bound $K(C) =$




Figure 1: The original whiteboard sketch of the split-forest model decomposition (M. Wessel, April 2026): the intuition that a complete-graph RCC5 model can be presented as a forest of trees by splitting join nodes into EQ-mates and completing the relational graph by patchwork. This idea—the human author’s—is the semantic foundation that every subsequent proof route consumes, and the one component no cold review ever broke.

$(1 + |cl(C)|)^2 2^{2^{cl(C)}}$. Hence the $\forall$ PO-free fragment is decidable (two_tier_quotient_ALCIRCC5, po_free_fragment_ALCIRCC5). It retains $\exists$ PO, $\forall$ DR, $\exists$ DR, and all vertical modalities, so it is a genuinely expressive spatial fragment — the strongest unconditional $\mathcal{ALCI}_{RCC5}$ -level result of the project.

Lesson. Finiteness is the wrong target: models are legitimately infinite (unbounded PP-towers). The right target is a finite *presentation* of a possibly-infinite model — which is the split-forest.

5.3 The split-forest idea

Idea (the human author’s, on a whiteboard). The split-forest decomposition was the human author’s contribution, sketched on a whiteboard (Figure 1) and handed to the AI assistants to make precise. Decompose a model into a *forest* of trees — one per connected component — by splitting each join node into EQ-mates, so the tree skeleton is explicit and the (global) relational completion is handled separately by the patchwork property. Tree-like presentations of infinite models are the classical route to decidability (tree-model property, then automata or type-elimination); the insight was that this setting, despite its complete relational graph, still admits such a presentation.

The normal form (Theorem A). Every satisfiable concept admits a witness-generated, tree-like split-forest model, obtained by *witness thinning* $\rightarrow$ *generated containment covers* $\rightarrow$ *split copies* for incomparable superparts $\rightarrow$ *side-interface mosaics* $\rightarrow$ a *typed-EQ quotient* (*trees/*, *cover_tree_tableau_ALCIRCC5*). This is the one component found sound by *every* cold review — the semantic foundation everything downstream *consumes*.

Transition. The split forest gives the model structure; it does not by itself give a *decision procedure*. Turning “a tree-like model of this shape exists” into “an algorithm can decide whether one exists” is the finite-abstraction problem — and that is where the next two families (the certificate and the automaton) live.

5.4 The no-automata certificate, and the automata route

The hand certificate (rounds 2–10). A finite *certificate* for satisfiability over the split forest, validated by local checks (converse, composition, universal safety, request discharge, residual-frontier constraints; `gpt5.5_round2/`, `gpt5.5_round4/`). Across ten rounds it repeatedly reduced to automaton-shaped machinery it could not discharge by hand: request-closed cycles behave like Büchi/parity acceptance, and “finite product-state exhaustion” like product-automaton reachability. Cold reviews found successive defects — an ancestor-tower gap (D-1), its dual descendant tower, boundary non-determinacy, and (twice) that finite-checkability was asserted rather than proved. The thread converged, honestly, onto an automaton.

The parity-automaton route (rounds 11–12). This made the convergence explicit: Theorem A $\rightarrow$ Theorem B (a *finite abstraction* captures saturated split forests up to satisfiability) $\rightarrow$ Theorem C (a two-way alternating parity *tree* automaton accepts exactly the valid abstractions; emptiness is decidable). The automaton *consumes* the split forest rather than replacing it. Theorem B is the single load-bearing keystone. Cold reviews (5th, 6th) found its global-coherence step assumed, not proved; round 12 rebuilt the abstraction on *patchwork bags* so global consistency follows from the citable RCC5 patchwork property (Renz–Nebel), with eventualities decided by two-way emptiness (Vardi). A 7th (hot) review then found a residual *Shadow-Amalgamation* gap in the truth lemma (`automata_route_repairs/`, `cold_review_theoremB/`, probes `wp13–wp17`).

Why we abandoned the tree-automaton route. A cold review of the decision layer showed the tree automaton must decide an *existential-projection* language (the valid abstraction is a pair, only part of which is on the tape), and independent alternating run copies cannot be forced to guess the hidden part consistently — machine-exhibited as acceptance-without-validity. The three natural repairs (tape annotation, profile quotient, canonical guessing) are each blocked by facts the construction itself establishes. The decision layer was therefore replaced by a mosaic / type-elimination procedure directly on the infinitary abstraction — the cluster-quasimodel line (§5.5) — and the keystone (Theorem B $\approx$ patchwork-bag adequacy) survived the change, unmoved: it is F6 in automaton clothing.

5.5 The Lean line and F6

Lean, and how we use it. Lean 4 is a proof assistant whose kernel accepts a proof only if every step type-checks. In an adversarial project where prose proofs repeatedly *assumed* the hard step, the kernel is a ground-truth oracle: it cannot be talked past. We moved the load-bearing soundness argument into Lean 4 core (no `mathlib`); the development is `formal/Round19Transport.lean` ($\approx 5,300$ lines, zero `sorry`), described in full in `LEAN.md`.

The cluster-quasimodel decision layer (rounds 15–18). A finite *catalogue* of interface patterns carrying *steering functions*, with one-step demand fulfilment (no promissory witnesses, hence no parity/eventuality condition). This is the construction on which the whole difficulty finally

localized to two named lemmas: **F6** (a computable bound on *live width*) and **W2'** (uniformization of the extraction).

What is formalized (rounds 19–30). The pipeline from certificate syntax to a genuine RCC5 model of the logic is kernel-checked (transport $\rightarrow$ S-layer closure $\rightarrow$ catalogue soundness $\rightarrow$ logic layer / truth lemma $\rightarrow$ model), as is the *faithfulness* of the Hintikka abstraction (satisfiability and Hintikka-realizability coincide). On top sits a *non-oracular decision-grade reduction*: a fixed Boolean checker of first-order finite certificate data, proved sound, from which **Decidable** satisfiability follows by finite search modulo a single premise — exactly $F6 \wedge W2'$. This is the machine-checked *conditional decidability theorem*. Two cold reviews of the Lean confirmed no soundness defect and drove the closure of the completeness-interface gaps.

The keystone, sharpened. F6 is now a precise combinatorial dichotomy: does some concept force unbounded *identity-selector minors* (private matching of unbounded hitting number)? W2' was shown false in its coarse form but repairable by a state refinement bounded *by F6* — so it *folds into* F6 (`fable5_width_barrier/`, `cold_review_f6_w2prime/`, probes `wp26–wp44`).

5.6 The regular-cover pivot

Idea. A reframing suggested by the human: replace finite *quotients* (invalid for infinite PP-chains, since a PP-cycle contradicts EQ-identity) by *regular covers* — finite generators whose infinite *unfoldings* are the models, in the spirit of the two-tier quotient but for the full logic. This finer invariant can finitely represent exactly the patterns that fool the width view (identity selectors $i = j$, half-graphs $i < j$).

What it produced. A complete *local* algebra of strong-EQ RCC5 networks, of which one piece is machine-*certified* (`formal/RCC5NormalForm.lean`): the RCC5 *normal form* — every strong-EQ RCC5 network is an *ordered-disjoint* structure (PP a strict partial order, DR a downward-closed disjointness, PO residual) — together with free amalgamation, an exact one-point extension criterion, and exact uniform/non-uniform cross-policy characterizations (`rcc5_local_amalgamation_theory`, `regular_cover_route_pivot/`, probes `wp45–wp83`). It independently re-derives the $\forall$ PO-free decidability result.

Why it is a better map, not a shorter path. Its own keystone (a bounded coherent regular-cover property) is F6 relabelled, and the route itself concedes, after exhausting the local algebra, that the remainder “cannot be a purely local RCC5 composition problem.” Because RCC5 relations are total, every model’s Gaifman graph is complete, so no off-the-shelf guarded/bounded-treewidth cover theorem applies; the keystone would need a bespoke cover theorem for complete edge-coloured regular structures. The pivot is the right vocabulary for a future attack, but it does not move the summit.

6 Current implementation: reasoners

The project ships working reasoners, on the same foundation as the proof attempts but validated empirically rather than proved.




Figure 2: The GIS concept taxonomy of Wessel’s 2002/2003 report (report7, Figure 6), recomputed in full (21/21 subsumptions) by the cover-tree tableau reasoner `src/gis_taxonomy.py`.

The cover-tree tableau. `src/cover_tree_tableau.py` (≈ 350 lines) is an operational concept-satisfiability procedure with exact-occurrence blocking, resting on the split-forest normal form and patchwork completion (§5.3). It is cross-validated against an independent quasimodel oracle on 911 concepts (zero mismatches after the known blind spot is excluded) and against an independent model verifier (`src/model_verifier.py`). It is trustworthy on satisfiable inputs; its one known limitation is the strong-EQ PO-loop, decided correctly by the tableau but not by the quasimodel oracle. It is strong evidence, not a proof: no completeness theorem is claimed for the implementation.

A GIS example. As a sanity check spanning 23 years, the tableau recomputes the GIS concept taxonomy of Wessel’s original report [8] (its Figure 6, reproduced here as Figure 2): all 21/21 subsumptions are reproduced (`src/gis_taxonomy.py`). A taxonomy computed by hand in 2003 is reproduced, in 2026, by an AI-written reasoner resting on the split-forest foundation.

7 On agentic AI usage

We report candidly on the workflow, because the methodology may outlast the mathematics.

The loop. The human posed the problem, supplied the central intuitions and directions (the split-forest decomposition, the cluster/loop and regular-cover reframings, the honesty discipline), and after each round reviewed, corrected, and re-prompted. An AI proposed a proof or a repair; a *fresh* AI session—with no memory of how the proof was built—then reviewed it adversarially. Repeat.

Cold review as a standard step. The single most transferable finding: a *cold* reviewer consistently found defects that a *warm* reviewer (primed by the construction) missed—including, on this project, unsoundness proofs and scope errors that two hot audits had passed over. Across fifteen reviews, a defect or overclaim was found in all but two. We recommend cold, cross-lineage adversarial review as a default intermediate step in AI-assisted mathematics, not an optional one.

Don’t trust, verify. Every load-bearing claim was cross-checked against something mechanical: self-contained Python probes that re-derive the RCC5 composition table from finite set semantics (so the algebra cannot be fudged), and ultimately the Lean kernel. Overclaiming was treated as the cardinal sin—and it happened: the author model twice overstated what the Lean established, and a cold review caught both; the claims were withdrawn. The machine checks, not the model’s confidence, are the ground truth.

What frontier models did well, and did not. Both models sustained long-context, rigorous, multi-round formal development and produced genuinely useful adversarial reviews and machine-checkable artifacts. What was *not* demonstrated is the decisive novel idea—no model cracked F6, and the honest expectation is that none will by the incremental means used here. The models excel at rigorous local formalization and at finding flaws; the genuinely new keystone is where human insight (or a qualitatively different search) is still required. We regard the AI contributions as co-authorship-grade in a human collaborator; we also regard the human’s role—problem, intuition, direction, and the discipline of honest labelling—as indispensable.

8 Summary and conclusion

What we learned. A twenty-five-year-old open problem has been *reduced*, honestly and largely machine-checkably, to a single well-posed lemma (F6, bounded live width), which is provably the same fact that blocks a proof of undecidability. The local algebra of RCC5 is exhausted and, in one case, certified. Adversarial cold review plus machine verification is a repeatable methodology for this kind of work.

What would move the needle. F6 is a *definability* question—can a formula *force* unbounded rigid horizontal structure?—so the tools that fit are model-theoretic: locality (Gaifman/Hanf), Ehrenfeucht–Fraïssé / back-and-forth over bounded tuple profiles, the composition method, and bounded-model machinery. The concrete positive target is a *selector-sharing lemma*: that many same-profile selector gadgets must coalesce, so unbounded identity-selector minors cannot be forced. The concrete negative target is a concept forcing such minors (which would prove undecidability). Ordinary locality alone is insufficient because horizontal degree is unbounded; this is the “correct room,” not a solved problem.

The chances of closing F6. We are frank: they are low, and re-treading the ground covered here will not change that. F6 is the open problem itself, and the two independent cold attacks converged on the same wall—evidence that the problem is correctly *mapped*, not that it is about to yield. It would be a poor use of effort to reconstruct the split-forest, automata, Lean, or regular-cover developments; the value of what remains is a genuinely new definability-theoretic idea, or a machine-assisted search of a different kind (below).

The wins. Independent of F6, this project produced: (i) an unconditionally *decidable fragment*, the $\forall$ PO-free concepts; (ii) a machine-*certified* RCC5 normal form; (iii) a machine-checked *conditional decidability theorem* ($F6 \Rightarrow$ decidable, soundness certified, resting on the F6 oracle); (iv) working *reasoners* reproducing a 2003 GIS taxonomy; (v) a sharp *map* of the problem with a named toolbox; and (vi) a candid *methodology* for adversarial AI-assisted mathematics.

Is this a scientific contribution? We believe so, with the labelling kept honest: not a resolution of the open problem, but its reduction—checkably, and with a certified surround—to an irreducible core, plus one unconditional fragment, one certified lemma, working tools, and an honest account of an AI-assisted attack and its dead ends. That is an accurate and, we think, respectable terminal state for a discussion piece on a problem open for over two decades.

Outlook: the human is the bottleneck. Although the key insights, intuitions, and directional choices came from the human, each round still required the human to orchestrate, review, and rewrite the prompts—and at that cadence roughly eighty rounds consumed about four months. Autonomous sub-agents *directing* the research could plausibly automate the diminishing-delta local work (formalization, local lemmas, probe-driven counterexample search) and remove that bottleneck. The cost may be prohibitive and it sacrifices direct oversight, but it is worth attempting for one reason this project is unusually well-suited to it: the objective is clearly defined and *machine-verifiable in Lean*. A closed, adversarial loop—propose, formalize, let the kernel accept or reject—has a built-in ground-truth oracle, exactly the guard the manual cold-review methodology provided. The honest caveat: Lean verifies *proofs*, not the *truth of a conjecture*, so such a loop can tighten the certified surround but the summit (F6) still needs a genuine idea; orchestration alone is unlikely to supply it.

Materials. The machine-checked development is `formal/Round19Transport.lean`, `formal/RCC5NormalForm.1`, and `formal/ForcingReduction.lean` (see `LEAN.md`); the status report and the F6/W2' analysis are in `papers/fable5_width_barrier/`; the decidable fragment in `papers/two_tier_quotient_ALCIRCC5` and `papers/po_free_fragment_ALCIRCC5`; the certified local theory in `papers/rcc5_local_amalgamation_theory`; the reasoners under `src/`; the probes under `verification/python/`; and the full audit trail in `CONVERSATION.md` and `OUTDATED.md`. The repository is at <https://github.com/lambdamikel/alcircc5>.

References

- [1] A. G. Cohn. Modal and non modal qualitative spatial logics. In F. D. Anger, H. W. Guesgen, and J. van Benthem, editors, *Proceedings of the Workshop on Spatial and Temporal Reasoning*, IJCAI, 1993.
- [2] J. Renz and B. Nebel. On the complexity of qualitative spatial reasoning: A maximal tractable fragment of the Region Connection Calculus. *Artificial Intelligence*, 108(1–2):69–123, 1999.
- [3] M. Wessel. Obstacles on the way to spatial reasoning with description logics: Undecidability of $\mathcal{ALC}_{\mathcal{RA}}^{\ominus}$. Technical Report FBI-HH-M-297/00, Fachbereich Informatik, Universität Hamburg, 2000. <https://github.com/lambdamikel/alcircc5/blob/master/papers/report4.pdf>
- [4] M. Wessel. Decidable and undecidable extensions of $\mathcal{ALC}$ with composition-based role inclusion axioms. Technical Report FBI-HH-M-301/01, Fachbereich Informatik, Universität Hamburg, 2000. <https://github.com/lambdamikel/alcircc5/blob/master/papers/report5.pdf>
- [5] M. Wessel. Obstacles on the way to qualitative spatial reasoning with description logics: some undecidability results. In *Proceedings of the 2001 Description Logic Workshop (DL 2001)*, CEUR Workshop Proceedings, vol. 49, 2001.

- [6] M. Wessel. Undecidability of $\mathcal{ALC}_{\mathcal{RA}}$. Technical Report FBI-HH-M-302/01, Fachbereich Informatik, Universität Hamburg, 2001. <https://github.com/lambdamikel/alcircc5/blob/master/papers/report6.pdf>
- [7] M. Wessel. On spatial reasoning with description logics — position paper. In *Proceedings of the 2002 International Workshop on Description Logics (DL 2002)*, CEUR Workshop Proceedings, 2002.
- [8] M. Wessel. Qualitative spatial reasoning with the $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}}$ family — first results and unanswered questions. Technical Report FBI-HH-M-324/03, Fachbereich Informatik, Universität Hamburg, 2002/2003. <https://github.com/lambdamikel/alcircc5/blob/master/papers/report7.pdf>
- [9] C. Lutz and F. Wolter. Modal logics of topological relations. *Logical Methods in Computer Science*, 2(2):1–41, 2006.
- [10] GPT-5.4 (OpenAI), prompted by M. Wessel. Split-forest models and sibling-interface descriptors for $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}5}$ (v1; soundness Thms 1.17–1.19 preserved by v2; Def 1.5 / Def 1.7 / Thm 1.20-sketch superseded by v2). Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/trees/sibling_interface_descriptors_ALCIRCC5_completed_eqsync_canonical_needpatched.pdf
- [11] Claude (Anthropic), prompted by M. Wessel. Sibling-interface descriptors for $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}5}$ (v2, repaired): preserves the v1 soundness chain (Thms 1.17–1.19) verbatim and reinterprets v1 Def 1.5 (parent self-loops, generated witness-cover edges), v1 Def 1.7 (PP/PPI existentials by reachability discharge), and v1 Thm 1.20-sketch (model-to-quotient delegated to v2 completeness extraction). Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/trees/sibling_interface_descriptors_ALCIRCC5_v2.pdf
- [12] GPT-5.4 (OpenAI), prompted by M. Wessel. A cover-tree tableau calculus for $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}5}$. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/trees/alcircc5_cover_tree_tableau_needall_patched.pdf
- [13] Claude (Anthropic), prompted by M. Wessel. Completeness extraction for $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}5}$ (v2.1, GPT-5.5 v2-review repairs): closing the model-to-quotient gap via witness-generated submodels, generated covers, reachability discharge, and explicit equality data. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/completeness_extraction_ALCIRCC5_v2.pdf
- [14] Claude (Anthropic), prompted by M. Wessel. Completeness extraction for the $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}5}$ split-forest quotient (v1, superseded; defects identified by GPT-5.5 review). Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/completeness_extraction_ALCIRCC5.pdf
- [15] GPT-5.5 (OpenAI), prompted by M. Wessel. A coherent generated split-forest decidability argument for $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}5}$ (Büchi-automaton route). Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5/ALCIRCC5_coherent_generated_split_forest_decidability.pdf
- [16] GPT-5.5 (OpenAI), prompted by M. Wessel. A repaired split-forest decidability proof for $\mathcal{ALC}_{\mathcal{I}_{\text{RCC}}5}$ (no-automata route, round-2 31-page version; superseded by [18]). Technical re-

- port, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_round2/repaired_split_forest_no_automata_proof.pdf
- [17] GPT-5.5 (OpenAI), prompted by M. Wessel. Formal review of the round-6 consolidated generated split-forest proof (May 27, 2026): identifies the central abstract-position-symbol labelling defect that motivates the round-7 pair-shape architecture. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_final/formal_response_round6_review.pdf
 - [18] GPT-5.5 (OpenAI), prompted by M. Wessel. A repaired split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$ without automata (round-7 consolidated sketch, 14 pages): occurrence-sensitive pair shapes with incidence tags; twelve validity clauses (V1)–(V12). Immediate predecessor of [19]; retained as audit trail. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_final/repaired_split_forest_all_in_one_round7.pdf
 - [19] GPT-5.5 (OpenAI), prompted by M. Wessel. A repaired split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$ without automata — round-8 saturated side contexts (15-page sketch): round-7 architecture preserved; saturated side-context $S_k(u)$, cross side/tree exhaustion lemma, and constructed pair/triple catalogues $\text{Pair}_{\mathcal{Q}}$, $\text{Tri}_{\mathcal{Q}}$ added. Immediate predecessor of [23]; carried the D-1 gap, retained as audit trail. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/claude_latest_review_gpt5.5_fix/repaired_split_forest_abstract_round8_repaired.pdf
 - [20] GPT-5.5 (OpenAI), prompted by M. Wessel. Expanded split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$: detailed round-8 companion (30 pages). Full saturated-side-context construction, cross side/tree verticalization lemma, residual-frontier lemma, constructed pair/triple catalogues, explicit completeness extraction. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/claude_latest_review_gpt5.5_fix/expanded_split_forest_full_details_round8_full.pdf
 - [21] Claude (Anthropic, Opus 4.8), prompted by M. Wessel. Review of the round-8 saturated-side-context split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$ (9 pages): identifies the completeness gap D-1 (a DR/PO witness composition-forced into an infinite pumped tower has no admissible pair shape on the tail); composition arithmetic machine-checked. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/opus4.8_review/review_round8_split_forest.pdf
 - [22] Claude (Anthropic, Opus 4.8), prompted by M. Wessel. Repairing the round-8 completeness construction for $\mathcal{ALCI}_{RCC5}$: composition-forced verticalization (8 pages). Splices a forced witness into the cover relation at a bounded threshold height; machine-checked threshold lemmas. Proposed by the cold reviewer; ratified and integrated by GPT-5.5 in round-9 [23]. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/opus4.8_review/repair_completeness_round8.pdf
 - [23] GPT-5.5 (OpenAI), prompted by M. Wessel. A repaired split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$ without automata — round-9 composition-forced verticalization (16-page sketch): round-7/round-8 architecture preserved; a DR/PO side witness with a PPI-tail is spliced into the cover relation $E_{\uparrow}$ at a bounded threshold, closing the D-1 gap of [21].

- Current most developed statement of the decidability theorem.** Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_round3/repaired_split_forest_abstract_round9_forced_verticalization.pdf
- [24] GPT-5.5 (OpenAI), prompted by M. Wessel. Expanded split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$: detailed round-9 companion (33 pages). Full composition-forced verticalization construction with the monotone ancestor-trace lemma ($DR^*PO^*PPI^*$), bounded-threshold replacement lemma, splice-faithfulness lemma, and global residual-frontier lemma; split-cover and extraction updated to apply the forced-verticalization test before ordinary side-context attachment. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_round3/expanded_split_forest_full_details_round9_forced_verticalization.pdf
 - [25] GPT-5.5 (OpenAI), prompted by M. Wessel. Formal response to the Opus 4.8 review of the round-8 split-forest proof (5 pages). Confirms the D-1 defect (“a genuine completeness defect, not merely a presentational ambiguity”), records re-running the three Opus 4.8 verification scripts (all pass) and the composition facts $\text{comp}(PPI, PO) = \{PO, PPI\}$, $\text{comp}(PPI, PPI) = \{PPI\}$, and states the round-9 repair. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_round3/formal_response_opus48_round9_repair.pdf
 - [26] GPT-5.5 (OpenAI), prompted by M. Wessel. Expanded generated split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$: detailed companion to the round-7 sketch (28 pages). Detailed local constructions, worked stress cases, audit-of-main-proof-obligations section. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_final/expanded_split_forest_full_details_proof.pdf
 - [27] GPT-5.5 (OpenAI), prompted by M. Wessel. A split-forest decidability proof for $\mathcal{ALCI}_{RCC5}$ via parity tree automata: detailed version (21 pages). Independent witness to the same decidability theorem. Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_final/split_forest_automata_decidability_proof_detailed.pdf
 - [28] Claude (Anthropic, Opus 4.7), prompted by M. Wessel. Round-7 audit and response: adopting GPT-5.5’s pair-shape / incidence-tag repair as the canonical statement (9 pages). Technical report, May 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/gpt5.5_final/claude_round7_audit_response.pdf
 - [29] Claude (Anthropic), prompted by M. Wessel. A cover-tree tableau for $\mathcal{ALCI}_{RCC5}$: Implementation and computational verification. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/cover_tree_tableau_ALCIRCC5.pdf
 - [30] Claude (Anthropic), prompted by M. Wessel. A two-tier quotient construction for the PO-coherent fragment of $\mathcal{ALCI}_{RCC5}$: decidability and a 2-EXPTIME bound. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/two_tier_quotient_ALCIRCC5.pdf
 - [31] Claude (Anthropic), prompted by M. Wessel. A negative result on the finite-witness conjecture for the contextual tableau for $\mathcal{ALCI}_{RCC5}$. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/FW_proof_ALCIRCC5.pdf

- [32] GPT-5.4 (OpenAI), prompted by M. Wessel. Triangle-blocking analysis for $\mathcal{ALCI}_{RCC5}$: failed undecidability route via three-region coincidence. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/triangle_blocking_ALCIRCC5.pdf
- [33] Claude (Anthropic), prompted by M. Wessel. Patchwork-augmentation probe: a negative result on an undecidability route for $\mathcal{ALCI}_{RCC5}$. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/patchwork_augmentation_ALCIRCC5.pdf
- [34] Claude (Anthropic), prompted by M. Wessel. A typed-patchwork counterexample for $\mathcal{ALCI}_{RCC5}$: refutation of a proposed blocking mechanism. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/typed_patchwork_counterexample_ALCIRCC5.pdf
- [35] Claude (Anthropic), prompted by M. Wessel. Response to GPT-5.4’s blocking-based undecidability attempts for $\mathcal{ALCI}_{RCC5}$. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/response_to_gpt_blocking.pdf
- [36] Claude (Anthropic), prompted by M. Wessel. Status of the $\mathcal{ALCI}_{RCC5}$ decidability argument after the FW negative result. Technical report, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/papers/ALCI_RCC5_status_after_FW.pdf
- [37] Claude (Anthropic), prompted by M. Wessel. Cover-tree tableau reasoner for $\mathcal{ALCI}_{RCC5}$. Python implementation, April 2026. The main candidate decision procedure; cross-validated against the quasimodel oracle on 911 concepts and on the 775-case decomposition suite. https://github.com/lambdamikel/alcircc5/blob/master/src/cover_tree_tableau.py
- [38] Claude (Anthropic), prompted by M. Wessel. A quasimodel-based reasoner for $\mathcal{ALCI}_{RCC5}$. Python implementation, April 2026. Retained as a cross-validation oracle only: SAT answers are trustworthy; UNSAT answers are known-incomplete on cyclic-via-symmetric-role concepts (e.g. the PO-loop pattern). https://github.com/lambdamikel/alcircc5/blob/master/src/alcircc5_reasoner.py
- [39] Claude (Anthropic), prompted by M. Wessel. Cycle-aware wrapper for the $\mathcal{ALCI}_{RCC5}$ quasimodel reasoner. Python implementation, April 2026. Thin wrapper that detects cyclic-via-symmetric-role patterns and delegates to a direct model search; restores the 911/911 cross-validation match rate. https://github.com/lambdamikel/alcircc5/blob/master/src/alcircc5_reasoner_cyclic.py
- [40] Claude (Anthropic), prompted by M. Wessel. Independent model verifier for $\mathcal{ALCI}_{RCC5}$ SAT answers. Python implementation, April 2026. Checks inverse symmetry, composition-consistency on all triples, type-safety, existential witnessing, and recursive concept truth against explicit finite RCC5 models. https://github.com/lambdamikel/alcircc5/blob/master/src/model_verifier.py
- [41] Claude (Anthropic), prompted by M. Wessel. Cover-tree decomposition test for $\mathcal{ALCI}_{RCC5}$ (775/775). Python test suite, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/src/decomposition_test.py
- [42] Claude (Anthropic), prompted by M. Wessel. Cross-validation stress test for the $\mathcal{ALCI}_{RCC5}$ cover-tree tableau against the baseline quasimodel reasoner (911 concepts). Python test suite,

- April 2026. https://github.com/lambdamikel/alcircc5/blob/master/src/stress_test_cover_tree.py
- [43] Claude (Anthropic), prompted by M. Wessel. Cross-validation stress test against the cycle-aware quasimodel reasoner (911 concepts; zero mismatches). Python test suite, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/src/stress_test_cyclic.py
 - [44] Claude (Anthropic), prompted by M. Wessel. Seven-case adversarial suite for the cycle-aware $\mathcal{ALCI}_{RCC5}$ reasoner (PO-loop, DR-loop, mixed-loop, clash-to-EQ, and distinguishing-universal variants). Python test suite, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/src/test_cyclic_reasoner.py
 - [45] Claude (Anthropic), prompted by M. Wessel. GIS taxonomy computation for $\mathcal{ALCI}_{RCC5}$. Python implementation, April 2026. https://github.com/lambdamikel/alcircc5/blob/master/src/gis_taxonomy.py
 - [46] M. Wessel (with Claude Opus 4.7 and GPT-5.4 Pro). $\mathcal{ALCI}_{RCC5}$ decidability project repository. GitHub, 2026. <https://github.com/lambdamikel/alcircc5> (See README.md for the overall argument, the blocked-reduction landscape, and the summary of failed undecidability attempts.)
 - [47] M. Wessel (with Claude Opus 4.7 and GPT-5.4 Pro). Outdated and superseded material: failed blocking attempts and retracted approaches for $\mathcal{ALCI}_{RCC5}$. GitHub, 2026. <https://github.com/lambdamikel/alcircc5/blob/master/OUTDATED.md>
 - [48] Anthropic. Claude Opus 4.7. Large language model, 2026. <https://www.anthropic.com/claude>
 - [49] OpenAI. GPT-5.4 Pro. Large language model, 2026. <https://openai.com>

A On the DL 2026 rejection

An abstract of this work was submitted to the 2026 International Workshop on Description Logics and rejected. We record the episode not out of grievance alone but because it bears on the paper’s own subject: what peer review is for, and how a community engages with an unusual result on one of its long-standing open problems.

The submission was labelled exactly as this paper is—*strongly supported, not certified*, an AI-assisted attack offered as a discussion piece. The reviews did not engage with the substance (the split-forest normal form, the reduction to F6, the machine-checked soundness), and no poster was granted. There is a recursive irony in an AI-assisted result on a twenty-year-old problem being declined without engagement in the same period that frontier AI began contributing checkable mathematics. The full open letter and the reviews are preserved in the repository (`dl2026-rejected/open_letter.md`, `reviews.txt`); we reproduce neither in full here, but stand by the position that a correctly-labelled, machine-checkable reduction of a two-decade open problem merits engagement on its merits.