

Thanks for filling out this form: 1.Machine Learning (Week-3 to 4.3) - Set - 1

1 message

Forms Response Receipts <forms-receipts-noreply@google.com>
To: lambert.rezon@gmail.com

Fri, May 22, 2026 at 11:35 AM

Thanks for filling out this form: 1.Machine Learning (Week-3 to 4.3) - Set - 1

You're receiving this email because you filled out the following form using your email address. **This form is owned by Hope Artificial Intelligence Training Institute.** Make sure you recognize and trust this form before copying or clicking on any links. If it looks suspicious, **report it**.

Here's what was received.

[View score](#)

1.Machine Learning (Week-3 to 4.3) - Set - 1

Email *

lambert.rezon@gmail.com

Which type of machine learning is used when the output variable is continuous?

*

- ☐ a) Classification
- ☐ b) Clustering
- ☒ c) Regression
- ☐ d) Reinforcement Learning

In which scenario would you use classification instead of regression?

- ☐ a) Predicting house prices based on area
- ☒ b) Predicting whether an email is spam or not
- ☐ c) Predicting the temperature of a city
- ☐ d) Predicting the total sales of a store

Which of the following is an unsupervised learning algorithm?

- ☐ a) Decision Tree
- ☒ b) K-Means
- ☐ c) Linear Regression
- ☐ d) Logistic Regression

What does the term "overfitting" refer to in machine learning?

- ☐ a) When the model does not learn from the data
- ☒ b) When the model fits the training data too well but fails on new data
- ☐ c) When the model generalizes well to unseen data
- ☐ d) When the model cannot capture complex patterns

Which evaluation metric is most commonly used for classification problems?

- ☐ a) Mean Squared Error (MSE)
- ☐ b) R-squared
- ☒ c) Accuracy
- ☐ d) Root Mean Squared Error (RMSE)

What is the main assumption of linear regression?

- ☒ a) The relationship between dependent and independent variables is linear
- ☐ b) The data is always normally distributed
- ☐ c) There is no correlation between independent variables
- ☐ d) It can only be used for categorical data

Which clustering algorithm is best for detecting outliers?

- ☐ a) K-Means
- ☒ b) DBSCAN
- ☐ c) Hierarchical Clustering
- ☐ d) Linear Regression

Which regularization technique adds both L1 and L2 penalties to a regression model?

- ☐ a) Ridge Regression
- ☐ b) Lasso Regression
- ☒ c) Elastic Net
- ☐ d) Polynomial Regression

What is the purpose of the kernel trick in Support Vector Machines (SVM)?

- ☐ a) To reduce training time
- ☒ b) To map data into a higher-dimensional space for better classification
- ☐ c) To normalize data
- ☐ d) To make the model interpret results more easily

Which clustering algorithm does not require specifying the number of clusters in advance?

- ☐ a) K-Means
- ☒ b) DBSCAN

- ☐ c) KNN
- ☐ d) Decision Tree

What type of function does logistic regression use to convert values into probabilities?

- ☐ a) Linear function
- ☒ b) Sigmoid function
- ☐ c) Exponential function
- ☐ d) Softmax function

Which metric is commonly used to evaluate a clustering algorithm?

- ☐ a) F1-score
- ☐ b) Sum of Squared Errors (SSE)
- ☐ c) Mean Squared Error
- ☒ d) Log-Loss

If your classification model has a high recall but low precision, what does it mean?

- ☒ a) The model is predicting too many false positives
- ☐ b) The model is predicting too many false negatives
- ☐ c) The model has low accuracy
- ☐ d) The model is not generalizing well

Which technique can be used to reduce the dimensionality of a dataset before applying clustering?

- ☐ a) Support Vector Machine
- ☒ b) Principal Component Analysis (PCA)

☐ c) Logistic Regression

☐ d) Random Forest

What is the main limitation of the K-Means clustering algorithm?

☐ a) It does not scale well for large datasets

☒ b) It requires the number of clusters to be specified in advance

☐ c) It cannot handle numerical data

☐ d) It always produces overlapping clusters

[Create your own Google Form](#)

Does this form look suspicious? [Report](#)