

résultats

```
+-----+
| RDM 6 - Ossatures |
+-----+
```

Utilisateur : ENIMonastir
 Nom du projet : Nacelle ciseaux
 Date : 2 Mai 2011

```
+-----+
| Résultats : Cas 1 |
+-----+
```

```
+-----+
| Déplacements nodaux [ mm, ° ] |
+-----+
```

Noeud	dx	dy	rotz
1	-1.227E-01	5.415E-02	8.986E-02
2	-1.393E+00	-5.879E-01	9.591E-02
3	-3.450E+00	-1.789E+00	5.825E-02
4	-4.609E+00	-1.133E+00	1.697E-01
5	-6.864E+00	8.097E-02	2.504E-01
6	-9.642E+00	-1.649E+00	2.425E-01
7	-1.342E+01	-3.848E+00	
8	-1.123E+00	-7.089E-01	-1.934E-02
9	-2.529E+00	6.805E-02	1.732E-01
10	-7.728E+00	-2.828E+00	1.340E-01
11	-1.257E+01	4.385E-02	
12	0.000E+00	0.000E+00	-9.356E-03
13	-7.964E-03	-1.569E-02	1.856E-02
14	2.588E-02	0.000E+00	-5.415E-03
15	0.000E+00	0.000E+00	-8.205E-03

Déplacement maximal sur x = 1.3426E+01 mm [Noeud 7]
 Déplacement maximal sur y = 3.8475E+00 mm [Noeud 7]
 Déplacement maximal = 1.3967E+01 mm [Noeud 7]

```
+-----+
| Action(s) de liaison [ daN daN.mm ] |
+-----+
```

Noeud	7	-	Rx =	0.0	Ry =	0.0	Mz =	0.0
Noeud	11	-	Rx =	0.0	Ry =	0.0	Mz =	0.0
Noeud	12	-	Rx =	160.3	Ry =	368.3	Mz =	0.0
Noeud	14	-	Rx =	0.0	Ry =	-64.5	Mz =	0.0
Noeud	15	-	Rx =	-160.3	Ry =	40.3	Mz =	0.0

Somme des actions de liaison :

Rx = 0.0 daN
 Ry = 344.1 daN

Somme des forces appliquées à la structure :

Fx = -2.54431142820977E-0011 daN
 Fy = -1.78829395736102E-0011 daN

```
+-----+
| Efforts intérieurs [ daN daN.mm ] |
+-----+
```

N = Effort normal TY = Effort tranchant MfZ = Moment fléchissant

ELE	ori ext	No Ne	résultats		
			TYo	MfZo	dL(mm)
			TYe	MfZe	
			TYmax	MfZmax	
1	1	-18.6	-6.7	0.0	-8.454E-04
	2	-17.4	-7.3	6226.1	
			7.3	6226.1	
2	2	-276.0	158.5	126477.8	-1.165E-02
	3	-274.9	157.8	0.0	
			158.5	126477.8	
3	3	-270.6	-157.3	-0.0	-1.142E-02
	4	-269.5	-156.7	125541.4	
			157.3	125541.4	
4	4	-10.8	7.8	6852.9	-4.559E-04
	5	-9.7	8.4	-0.0	
			8.4	6852.9	
5	5	2.5	12.6	0.0	1.219E-04
	6	3.6	11.9	-9262.7	
			12.6	9262.7	
6	6	-260.9	150.7	120251.2	-1.101E-02
	7	-259.8	150.1	0.0	
			150.7	120251.2	
7	8	-293.5	-132.1	0.0	-1.376E-02
	2	-292.4	-131.5	116973.9	
			132.1	116973.9	
8	2	-9.3	-4.4	-3277.8	-3.715E-04
	9	-8.2	-3.8	-0.0	
			4.4	3277.8	
9	9	-7.4	5.2	-0.0	-2.898E-04
	4	-6.3	4.6	-3941.4	
			5.2	3941.4	
10	4	-278.4	136.4	114747.1	-1.239E-02
	10	-277.3	135.8	-0.0	
			136.4	114747.1	
11	10	-252.2	-171.1	-0.0	-1.007E-02
	6	-251.1	-170.5	129262.7	
			171.1	129262.7	
12	6	-1.1	-0.6	-251.2	-2.301E-05
	11	-0.0	0.0	0.0	
			0.6	251.2	
13	12	-400.0	-36.6	-0.0	-1.758E-02
	13	-398.9	-36.0	30166.2	
			36.6	30166.2	
14	13	-5.1	-20.0	-15086.0	-1.871E-04
	1	-4.1	-19.3	0.0	
			20.0	15086.0	
15	14	56.6	-31.0	-0.0	2.515E-03
	13	57.7	-31.6	26062.7	
			31.6	26062.7	
16	13	-271.5	182.5	139886.0	-1.100E-02
	8	-270.4	181.8	-0.0	
			182.5	139886.0	
17	15	-157.9	-48.8	-0.0	-1.344E-03
	13	-157.9	-48.8	68571.0	
			48.8	68571.0	