



Sorting (Part 1)

Lab Recap

During the Runtime Lab we should have discovered:

1. Binary Search is considerably faster than Linear Search (especially as the size of our array increases).
2. The time it takes to sort however, is much longer than Linear Search. This makes Linear Search more efficient than Binary Search if we are only searching an array one time.


Algorithmic Efficiency

This efficiency can be quantified using something called Big Oh notation (not on AP exam). Big Oh describes how the runtime of an algorithm will increase as the array size (n) increases.

Efficiency

Meaning

- $O(1)$ Takes a constant amount of time regardless of the size of n.
- $O(\log(n))$ Time increases with n, however more slowly than linear (e.g. Binary Search)
- $O(n)$ Increases linearly (e.g. Linear Search)
- $O(n\log(n))$ Increases with n, faster than linear (e.g. `Arrays.sort()`)
- $O(n^2)$ Increases to the square of n. (e.g. Insertion Sort, Selection Sort)
- $O(2^n)$ Increases exponentially



Sort Algorithms for the AP Exam

1. Selection Sort ($O(n^2)$) - Today
2. Insertion Sort ($O(n^2)$) - Today
3. Merge Sort ($O(n \log(n))$) - Chapter 10 (Recursion)

note: the n^2 runtime comes from the fact that selection/insertion rely on *double loops*, resulting in having to iterate through n things n times.

Selection Sort Pseudo-code

```
1 for each position in the array
2   find the minimum value from the current position to the end of the array.
3   if the minimum is not at the current position
4     swap the current and the min
5   move to the next position in the array.
```

Simulation

<http://www.cs.armstrong.edu/liang/animation/web/SelectionSort.html>

Selection Sort Names

Insertion Sort Pseudo-code

```
1 for each position in the array (start @ index 1)
2   insert the current value into order relative to the sorted values on its left.
3   move to the next position in the array.
```

Simulation

<https://www.hackerearth.com/practice/algorithms/sorting/insertion-sort/visualize/>

Insertion Sort Names

LAB-027

Try to implement these two algorithms with the following `static void` methods

1. `selectionSort()`: takes an `ArrayList` of names and puts them into alphabetical order using the selection sort algorithm. (see `compareTo()` if stuck on how to order)
2. `insertionSort()`: takes an `ArrayList` of names and puts them into alphabetical order using the insertion sort algorithm.
3. `shuffle()`: takes an `ArrayList` of names and puts them into a random order. (see `Knuth shuffle` if stuck)
4. In `main()` create an `ArrayList` of 10 names.
5. Test your sort algorithms at least 3 times shuffling in between each time.