

САНКТ-ПЕТЕРБУРГСКИЙ ПОЛИТЕХНИЧЕСКИЙ УНИВЕРСИТЕТ
ПЕТРА ВЕЛИКОГО

Институт компьютерных наук и технологий
Кафедра компьютерных систем и программных технологий

Отчет по лабораторной работе № 3

Дисциплина: «Базы данных»

Тема: «Генерация тестовых данных»

Выполнил студент гр. 43501/3

_____ А.Ю. Ламтев
(подпись)

Преподаватель

_____ А.В. Мяснов
(подпись)

«___» _____ 2019 г.

Санкт-Петербург
2019

Содержание

1	Цели работы	3
2	Программа работы	3
3	Разработка генератора	3
4	Выводы	8
	Приложение 1. Исходный код	8

1. Цели работы

Сформировать набор данных, позволяющий производить операции на реальных объемах данных.

2. Программа работы

1. Реализация в виде программы параметризуемого генератора, который позволит сформировать набор связанных данных в каждой таблице.
2. Частные требования к генератору, набору данных и результирующему набору данных:
 - количество записей в справочных таблицах должно соответствовать ограничениям предметной области
 - количество записей в таблицах, хранящих информацию об объектах или субъектах должно быть параметром генерации
 - значения для внешних ключей необходимо брать из связанных таблиц

3. Разработка генератора

Генератор выполнен в виде консольного приложения, разработанного на языке Java последней версии 11.0.1. Программа ожидает 2 аргумента командной строки: путь к файлу в формате `json`, в котором содержатся `url` `Postgres`-сервера, и имя пользователя, и пароль для доступа к нему; и путь к файлу в формате `json`, содержащему параметры генератора. Примеры этих 2-х файлов представлены в листингах 1 и 2.

```
1 {  
2   "url": "jdbc:postgresql://localhost:5432/postgres",  
3   "user": "postgres",  
4   "password": "postgres"  
5 }
```

Листинг 1: Пример параметров доступа к `Postgres`-серверу

```
1 {  
2   "usersCount": 10000,  
3   "femalePercentage": 55,  
4   "moviesCount": 25000,  
5   "seriesCountSeasonsEpisodes": [  
6     [100, 3, 15],  
7     [150, 4, 50],  
8     [200, 2, 25],  
9     [300, 1, 7],  
10    [100, 5, 10]  
11  ],  
12   "percentageOfUsersWhoBoughtMovies": 64,  
13   "minMoviesPerUser": 5,  
14   "maxMoviesPerUser": 100,  
15   "percentageOfUsersWhoBoughtSeries": 35,
```

```

16 "minSeriesPerUser": 2,
17 "maxSeriesPerUser": 100,
18 "yearsSinceFirstSubscription": 5,
19 "minSubscriptionsPerUser": 7,
20 "maxSubscriptionsPerUser": 25,
21 "durationPriceNMoviesMSeasons": [
22   [30, 5, 5, 1], [60, 9, 5, 1], [90, 13, 5, 1], [180, 25, 5, 1], [365, 40, 5, 1],
23   [30, 7, 10, 2], [60, 13, 10, 2], [90, 25, 10, 2], [180, 45, 10, 2], [365, 75, 10, 2],
24   [30, 10, 15, 3], [60, 18, 15, 3], [90, 35, 15, 3], [180, 65, 15, 3], [365, 100, 15, 3],
25   [30, 12, 30, 5], [60, 21, 30, 5], [90, 40, 30, 5], [180, 70, 30, 5], [365, 120, 30, 5]
26 ],
27 "moviesSubscriptionsPercentage": 25
28 }

```

Листинг 2: Пример параметров генератора

Рассмотрим подробнее параметры генератора:

- **usersCount** — число пользователей
- **femalePercentage** — процент девушек от общего числа пользователей
- **moviesCount** — число самостоятельных фильмов (эпизоды сериалов в это число не входят)
- **seriesCountSeasonsEpisodes** — массив типов сериалов, параметризуемый 3-мя значениями: числом сериалов данного типа, числом сезонов в таких сериалах и количество серий в каждом сезоне ([100, 3, 15] означает 100 сериалов, в каждом 3 сезона, состоящих из 15 серий)
- **percentageOfUsersWhoBoughtMovies** — процент пользователей, купивших хотя бы 1 фильм на постоянной основе.
- **minMoviesPerUser** — минимальное число фильмов, которые купил пользователь, входящий в группу, описываемую предыдущим параметром.
- **maxMoviesPerUser** — аналогично предыдущему параметру — максимальное число фильмов.
- **percentageOfUsersWhoBoughtSeries** — процент пользователей, купивших хотя бы 1 сериал на постоянной основе.
- **minSeriesPerUser** — минимальное число сериалов, которые купил пользователь, входящий в группу, описываемую предыдущим параметром.
- **maxSeriesPerUser** — аналогично предыдущему параметру — максимальное число сериалов
- **yearsSinceFirstSubscription** — число лет, прошедших с первой подписки
- **minSubscriptionsPerUser** — минимальное число подписок у пользователя
- **maxSubscriptionsPerUser** — максимальное число подписок у пользователя

- **moviesSubscriptionsPercentage** — процент подписок на фильмы от общего числа подписок (на фильмы и сериалы)
- **durationPriceNMoviesMSeasons** — массив типов подписок, параметризуемый 4-мя значениями: длительностью в днях, стоимостью в \$, соответствующему числу фильмов и соответствующему числу сезонов сериалов ([90, 35, 15, 3] означает, что подписка на 90 дней, стоимостью \$35, и в неё входят либо 15 фильмов, либо 3 сериала).

Для соединения с базой данных используется JDBC драйвер последней версии 42.2.5.

В качестве системы сборки и управления зависимостями проекта выбран Gradle версии 5.0, конфигурационные файлы проекта написаны на Kotlin DSL. Они представлены в листингах 3 и 4.

```

1 plugins {
2     java
3 }
4
5 group = "com.lamtev.movie-service"
6 version = "1.0.RELEASE"
7
8 repositories {
9     jcenter()
10 }
11
12 dependencies {
13     compile("com.intelliJ:annotations:12.0")
14     compile("org.postgresql:postgresql:42.2.5")
15     compile("com.github.javafaker:javafaker:0.16")
16     compile("net.sf.trove4j:trove4j:3.0.3")
17     compile("com.google.code.gson:gson:2.8.5")
18 }
19
20 configure<JavaPluginConvention> {
21     sourceCompatibility = JavaVersion.VERSION_11
22 }
23
24 val fatJar = task("fatJar", type = Jar::class) {
25     baseName = "${project.group}.${project.name}"
26     manifest {
27         attributes["Implementation-Title"] = "Movie service data generator"
28         attributes["Implementation-Version"] = version
29         attributes["Main-Class"] = "com.lamtev.movie_service.datagen.Launcher"
30     }
31     from(configurations["compile"].map { if (it.isDirectory) it else zipTree(it) })
32     with(tasks["jar"] as CopySpec)
33 }
34
35 tasks {
36     "build" {
37         dependsOn(fatJar)
38     }
39 }

```

Листинг 3: build.gradle.kts

```

1 rootProject.name = "datagen"

```

Листинг 4: settings.gradle.kts

Приложение логически разделено на 2 части:

1. Обработка аргументов командной строки и парсинг конфигурационных файлов

Состоит из класса `ArgumentsParser` с бизнес-логикой, исходный код которого приведён в листинге 6. А также классов `EndpointInfo` (листинг 7) и `Parameters` (листинг 8), которые являются моделью для входных json файлов.

Для десериализации json файлов в объекты классов используется библиотека `Gson`.

2. Генерация данных и заполнение ими БД

На рис. 3.1 представлена схема БД, состоящей из 16 таблиц.




Рис. 3.1: Схема БД

Для заполнения соответствующих таблиц были разработаны классы, реализующие интерфейс `TableGenerator` (листинг 9):

- `LanguageTableGenerator` (листинг 10) — генератор данных для таблицы `language`
- `CategoryTableGenerator` (листинг 11) — генератор данных для таблицы `category`
- `CategoryTranslationTableGenerator` (листинг 12) — генератор данных для таблицы `category_translation`
- `MovieTableGenerator` (листинг 13) — генератор данных для таблицы `movie`

- **MovieTranslationTableGenerator** (листинг 14) — генератор данных для таблицы `movie_translation`
- **MovieCategoryTableGenerator** (листинг 15) — генератор данных для таблицы `movie_category`
- **SeriesTableGenerator** (листинг 16) — генератор данных для таблицы `series`
- **SeriesTranslationTableGenerator** (листинг 17) — генератор данных для таблицы `series_translation`
- **SeriesSeasonTableGenerator** (листинг 18) — генератор данных для таблицы `series_season`
- **SeriesSeasonTranslationTableGenerator** (листинг 19) — генератор данных для таблицы `series_season_translation`
- **UserTableGenerator** (листинг 20) — генератор данных для таблицы `user`
- **UserMovieTableGenerator** (листинг 21) — генератор данных для таблицы `user_movie`
- **UserSeriesTableGenerator** (листинг 22) — генератор данных для таблицы `user_series`
- **SubscriptionTableGenerator** (листинг 23) — генератор данных для таблицы `subscription`
- **SubscriptionMovieTableGenerator** (листинг 24) — генератор данных для таблицы `subscription_movie`
- **SubscriptionSeriesSeasonTableGenerator** (листинг 25) — генератор данных для таблицы `subscription_series_season`

При формировании новых данных иногда требовались данные, уже содержащиеся в таблицах (в частности, значения внешних ключей). Для извлечения из БД этих данных было разработано 2 класса:

- **StorageDAO** (листинг 26) — класс, в котором реализованы **SELECT** запросы к базе данных, позволяющие получить число записей в произвольной таблице или получить все первичные ключи таблицы.
- **SubscriptionTableDAO** (листинг 27) — класс, в котором реализован **SELECT** запрос, специфичный только для таблицы `subscription`.

Также был разработан утилитный класс **Utils** (листинг 28), в котором реализованы вспомогательные функциональности, используемые при генерации данных для разных таблиц.

Для генерации различных данных, таких, как названия фильмов, сериалов, имена пользователей, даты и т.д. использовалась библиотека **JavaFaker**.

4. Выводы

В результате работы был разработан параметризуемый генератор, с помощью которого БД была заполнена данными. Эти данные состоят из десятков тысяч пользователей; десятков тысяч фильмов; тысяч сериалов, содержащих, десятки тысяч серий; сотен тысяч подписок...

Также был получен опыт организации взаимодействия Java-приложений с базами данных с помощью стандарта JDBC.

Приложение 1. Исходный код

```
1 package com.lamtev.movie_service.datagen;
2
3 import com.lamtev.movie_service.datagen.cli_args.ArgumentsParser;
4 import com.lamtev.movie_service.datagen.generator.LanguageTableGenerator;
5 import com.lamtev.movie_service.datagen.generator.StorageDAO;
6 import com.lamtev.movie_service.datagen.generator.Utils;
7 import com.lamtev.movie_service.datagen.generator.category.CategoryTableGenerator;
8 import com.lamtev.movie_service.datagen.generator.movie.MovieTableGenerator;
9 import com.lamtev.movie_service.datagen.generator.series.SeriesTableGenerator;
10 import com.lamtev.movie_service.datagen.generator.subscription.SubscriptionMovieTableGenerator
11 ;
12 import com.lamtev.movie_service.datagen.generator.subscription.SubscriptionSeriesSeasonTableGenerator;
13 import com.lamtev.movie_service.datagen.generator.subscription.SubscriptionTableDAO;
14 import com.lamtev.movie_service.datagen.generator.subscription.SubscriptionTableGenerator;
15 import com.lamtev.movie_service.datagen.generator.user.UserMovieTableGenerator;
16 import com.lamtev.movie_service.datagen.generator.user.UserSeriesTableGenerator;
17 import com.lamtev.movie_service.datagen.generator.user.UserTableGenerator;
18
19 import java.sql.DriverManager;
20 import java.sql.SQLException;
21
22 final class Launcher {
23     public static void main(String[] args) {
24         try {
25             Class.forName("org.postgresql.Driver");
26         } catch (ClassNotFoundException e) {
27             e.printStackTrace();
28         }
29         final var argumentsParser = new ArgumentsParser(args);
30         final var endpoint = argumentsParser.endpoint();
31         final var parameters = argumentsParser.parameters();
32         if (endpoint == null || parameters == null) {
33             System.err.println("Wrong arguments!");
34             return;
35         }
36         try (final var connection = DriverManager.getConnection(endpoint.url(), endpoint.user
37 (), endpoint.password())) {
38             final var language = new LanguageTableGenerator();
39             language.updateTableUsing(connection);
40             System.out.println("language generated");
41
42             final var category = new CategoryTableGenerator();
43             category.updateTableUsing(connection);
44             System.out.println("category generated");
45
46             final var movie = new MovieTableGenerator(parameters.moviesCount());
47             movie.updateTableUsing(connection);
48             System.out.println("movie generated");
49
50             final var series = new SeriesTableGenerator(parameters.seriesCountSeasonsEpisodes
51 ());
52             series.updateTableUsing(connection);
53             System.out.println("series generated");
```



```

53         final var user = new UserTableGenerator(parameters.usersCount(), parameters.
femalePercentage());
54         user.updateTableUsing(connection);
55         System.out.println("user generated");
56
57         final var userMovie = new UserMovieTableGenerator(parameters.
percentageOfUsersWhoBoughtMovies(), parameters.minMoviesPerUser(), parameters.
maxMoviesPerUser());
58         userMovie.updateTableUsing(connection);
59         System.out.println("user_movie generated");
60
61         final var seriesMovie = new UserSeriesTableGenerator(parameters.
percentageOfUsersWhoBoughtSeries(), parameters.minSeriesPerUser(), parameters.
maxSeriesPerUser());
62         seriesMovie.updateTableUsing(connection);
63         System.out.println("user_series generated");
64
65         final var subscription = new SubscriptionTableGenerator(parameters.usersCount(),
parameters.minSubscriptionsPerUser(), parameters.maxSubscriptionsPerUser(), parameters.
durationPriceNMoviesMSeasons(), parameters.yearsSinceFirstSubscription());
66         subscription.updateTableUsing(connection);
67         System.out.println("subscription generated");
68
69         final var subscriptionIdsNMoviesMSeasons = SubscriptionTableDAO.instance().
idsNMoviesOrMSeasons(connection, parameters.durationPriceNMoviesMSeasons());
70         final var subscriptionIdsNMovies = new int[2][0];
71         final var subscriptionIdsMSeasons = new int[2][0];
72         Utils.split(subscriptionIdsNMoviesMSeasons, parameters.
moviesSubscriptionsPercentage(), subscriptionIdsNMovies, subscriptionIdsMSeasons);
73
74         final var movieIds = StorageDAO.instance().ids(connection, "movie");
75         final var subscriptionMovie = new SubscriptionMovieTableGenerator(
subscriptionIdsNMovies, movieIds);
76         subscriptionMovie.updateTableUsing(connection);
77         System.out.println("subscription_movie generated");
78
79         final var seriesSeasonIds = StorageDAO.instance().ids(connection, "series_season")
;
80         final var subscriptionSeriesSeason = new SubscriptionSeriesSeasonTableGenerator(
subscriptionIdsMSeasons, seriesSeasonIds);
81         subscriptionSeriesSeason.updateTableUsing(connection);
82         System.out.println("subscription_series_season generated");
83     } catch (SQLException e) {
84         e.printStackTrace();
85     }
86 }
87
88 }

```

Листинг 5: Launcher.java

```

1 package com.lamtev.movie_service.datagen.cli_args;
2
3 import com.google.gson.*;
4 import org.jetbrains.annotations.NotNull;
5 import org.jetbrains.annotations.Nullable;
6
7 import java.io.FileReader;
8 import java.lang.reflect.Type;
9 import java.util.Arrays;
10
11 public class ArgumentsParser {
12     @NotNull
13     private final String[] args;
14     @NotNull
15     private final Gson gson;
16
17     public ArgumentsParser(final @NotNull String[] args) {
18         this.args = args;
19         this.gson = new GsonBuilder()
20             .serializeNulls()
21             .registerTypeAdapter(EndpointInfo.class, new Deserializer<EndpointInfo>())
22             .registerTypeAdapter(Parameters.class, new Deserializer<Parameters>())
23             .create();
24

```

```

25     }
26
27     @Nullable
28     public EndpointInfo endpoint() {
29         try (final var fileReader = new FileReader(args[0])) {
30             return gson.fromJson(fileReader, EndpointInfo.class);
31         } catch (Exception e) {
32             System.err.println(e.getMessage());
33             e.printStackTrace();
34             return null;
35         }
36     }
37
38     @Nullable
39     public Parameters parameters() {
40         try (final var fileReader = new FileReader(args[1])) {
41             return gson.fromJson(fileReader, Parameters.class);
42         } catch (Exception e) {
43             System.err.println(e.getMessage());
44             e.printStackTrace();
45             return null;
46         }
47     }
48
49     class Deserializer<T> implements JsonSerializer<T> {
50
51         public T deserialize(JsonElement json, Type typeOfT, JsonDeserializationContext
context) throws JsonParseException {
52             final T obj = new Gson().fromJson(json, typeOfT);
53
54             final var badField = Arrays.stream(obj.getClass().getDeclaredFields())
55                 .filter(field -> {
56                     try {
57                         field.setAccessible(true);
58                         return field.get(obj) == null;
59                     } catch (IllegalAccessException | IllegalArgumentException ignored) {
60                         return false;
61                     }
62                 })
63                 .findFirst();
64
65             if (badField.isPresent()) {
66                 throw new JsonParseException("Missing field: " + badField.get().getName());
67             }
68
69             return obj;
70         }
71     }
72 }
73 }

```

Листинг 6: ArgumentsParser.java

```

1 package com.lamtev.movie_service.datagen.cli_args;
2
3 import org.jetbrains.annotations.NotNull;
4
5 public class EndpointInfo {
6
7     @NotNull
8     private final String url;
9     @NotNull
10    private final String user;
11    @NotNull
12    private final String password;
13
14    public EndpointInfo(@NotNull final String url,
15                        @NotNull final String user,
16                        @NotNull final String password) {
17        this.url = url;
18        this.user = user;
19        this.password = password;
20    }
21
22    @NotNull

```

```

23     public String url() {
24         return url;
25     }
26
27     @NotNull
28     public String user() {
29         return user;
30     }
31
32     @NotNull
33     public String password() {
34         return password;
35     }
36
37 }

```

Листинг 7: EndpointInfo.java

```

1  package com.lamtev.movie_service.datagen.cli_args;
2
3  import org.jetbrains.annotations.NotNull;
4
5  public final class Parameters {
6
7      private final int usersCount;
8      private final int femalePercentage;
9      private final int moviesCount;
10
11     /**
12      * {{1000, 3, 15}, ...} - 1000 series, each consists of 3 seasons with 15 episodes
13      */
14     @NotNull
15     private final int [][] seriesCountSeasonsEpisodes;
16     private final int percentageOfUsersWhoBoughtMovies;
17     private final int minMoviesPerUser;
18     private final int maxMoviesPerUser;
19     private final int percentageOfUsersWhoBoughtSeries;
20     private final int minSeriesPerUser;
21     private final int maxSeriesPerUser;
22     private final int minSubscriptionsPerUser;
23     private final int maxSubscriptionsPerUser;
24
25     /**
26      * {{duration in days, price in USD, number of movies, number of series seasons}, ... }
27      */
28     @NotNull
29     private final int [][] durationPriceNMoviesMSeasons;
30     private final int moviesSubscriptionsPercentage;
31     private final int yearsSinceFirstSubscription;
32
33     public Parameters(int usersCount,
34                     int femalePercentage,
35                     int moviesCount,
36                     final @NotNull int [][] seriesCountSeasonsEpisodes,
37                     int percentageOfUsersWhoBoughtMovies,
38                     int minMoviesPerUser,
39                     int maxMoviesPerUser,
40                     int percentageOfUsersWhoBoughtSeries,
41                     int minSeriesPerUser,
42                     int maxSeriesPerUser,
43                     int yearsSinceFirstSubscription,
44                     int minSubscriptionsPerUser,
45                     int maxSubscriptionsPerUser,
46                     @NotNull int [][] durationPriceNMoviesMSeasons,
47                     int moviesSubscriptionsPercentage) {
48         this.usersCount = usersCount;
49         this.femalePercentage = femalePercentage;
50         this.moviesCount = moviesCount;
51         this.seriesCountSeasonsEpisodes = seriesCountSeasonsEpisodes;
52         this.percentageOfUsersWhoBoughtMovies = percentageOfUsersWhoBoughtMovies;
53         this.minMoviesPerUser = minMoviesPerUser;
54         this.maxMoviesPerUser = maxMoviesPerUser;
55         this.percentageOfUsersWhoBoughtSeries = percentageOfUsersWhoBoughtSeries;
56         this.minSeriesPerUser = minSeriesPerUser;
57         this.maxSeriesPerUser = maxSeriesPerUser;
58         this.yearsSinceFirstSubscription = yearsSinceFirstSubscription;
59         this.minSubscriptionsPerUser = minSubscriptionsPerUser;

```

```

58         this.maxSubscriptionsPerUser = maxSubscriptionsPerUser;
59         this.durationPriceNMoviesMSeasons = durationPriceNMoviesMSeasons;
60         this.moviesSubscriptionsPercentage = moviesSubscriptionsPercentage;
61     }
62
63     public int femalePercentage() {
64         return femalePercentage;
65     }
66
67     public int percentageOfUsersWhoBoughtMovies() {
68         return percentageOfUsersWhoBoughtMovies;
69     }
70
71     public int minMoviesPerUser() {
72         return minMoviesPerUser;
73     }
74
75     public int maxMoviesPerUser() {
76         return maxMoviesPerUser;
77     }
78
79     public int percentageOfUsersWhoBoughtSeries() {
80         return percentageOfUsersWhoBoughtSeries;
81     }
82
83     public int minSeriesPerUser() {
84         return minSeriesPerUser;
85     }
86
87     public int maxSeriesPerUser() {
88         return maxSeriesPerUser;
89     }
90
91     public int minSubscriptionsPerUser() {
92         return minSubscriptionsPerUser;
93     }
94
95     public int maxSubscriptionsPerUser() {
96         return maxSubscriptionsPerUser;
97     }
98
99     @NotNull
100    public int [][] durationPriceNMoviesMSeasons() {
101        return durationPriceNMoviesMSeasons;
102    }
103
104    public int moviesSubscriptionsPercentage() {
105        return moviesSubscriptionsPercentage;
106    }
107
108    public int usersCount() {
109        return usersCount;
110    }
111
112    public int moviesCount() {
113        return moviesCount;
114    }
115
116    @NotNull
117    public int [][] seriesCountSeasonsEpisodes() {
118        return seriesCountSeasonsEpisodes;
119    }
120
121    public int yearsSinceFirstSubscription() {
122        return yearsSinceFirstSubscription;
123    }
124 }

```

Листинг 8: Parameters.java

```

1 package com.lamtev.movie_service.datagen.generator;
2
3 import com.github.javafaker.Faker;
4 import org.jetbrains.annotations.NotNull;
5

```

```

6 import java.sql.Connection;
7 import java.util.Locale;
8 import java.util.Random;
9
10 public interface TableGenerator {
11     @NotNull
12     Random RANDOM = new Random(System.currentTimeMillis());
13     @NotNull
14     Faker FAKER = new Faker(Locale.US, RANDOM);
15     @NotNull
16     Utils UTILS = new Utils(RANDOM, FAKER);
17
18     /**
19      * Updates corresponding table via {@code connection} with newly generated data.
20      *
21      * @param connection {@link Connection} (session) with data base.
22      */
23     void updateTableUsing(final @NotNull Connection connection);
24 }

```

Листинг 9: TableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator;
2
3 import org.jetbrains.annotations.NotNull;
4
5 import java.sql.Connection;
6 import java.sql.SQLException;
7
8 public final class LanguageTableGenerator implements TableGenerator {
9
10     @NotNull
11     private final String[] languages;
12
13     public LanguageTableGenerator(@NotNull String[] languages) {
14         this.languages = languages;
15     }
16
17     public LanguageTableGenerator() {
18         this(new String[]{ "en-US", "ru-RU" });
19     }
20
21     @Override
22     public void updateTableUsing(final @NotNull Connection connection) {
23         try (final var statement = connection.prepareStatement(
24             "INSERT INTO language (name) VALUES (?)")
25         ) {
26             for (final var language : languages) {
27                 statement.setString(1, language);
28                 statement.addBatch();
29             }
30             statement.executeBatch();
31         } catch (SQLException e) {
32             e.printStackTrace();
33         }
34     }
35 }
36

```

Листинг 10: LanguageTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.category;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import org.jetbrains.annotations.NotNull;
5
6 import java.sql.Connection;
7 import java.sql.SQLException;
8 import java.util.LinkedHashMap;
9 import java.util.Map;
10
11 import static java.sql.Statement.RETURN_GENERATED_KEYS;
12
13 public final class CategoryTableGenerator implements TableGenerator {

```

```

14
15 private static final Map<String, String> CATEGORY_TO_SUPERCATEGORY = new LinkedHashMap<>()
16 {{
17     put("genre", "");
18     put("comedy", "genre");
19     put("drama", "genre");
20     put("thriller", "genre");
21     put("new", "");
22     put("horror", "genre");
23     put("action", "genre");
24     put("crime", "genre");
25     put("western", "genre");
26     put("popular", "");
27     put("mystery", "genre");
28     put("adventure", "genre");
29     put("classic", "");
30     put("romance", "genre");
31     put("science-fiction", "genre");
32     put("soviet", "");
33     put("hollywood", "");
34 }};
35
36 @Override
37 public void updateTableUsing(final @NotNull Connection connection) {
38     try (final var statement = connection.createStatement()) {
39         final var categoryIds = new int[CATEGORY_TO_SUPERCATEGORY.size()];
40         int i = 0;
41         for (final var entry : CATEGORY_TO_SUPERCATEGORY.entrySet()) {
42             final var category = entry.getKey();
43             final var supercategory = entry.getValue();
44
45             final var query = String.format(
46                 "INSERT INTO category (name, supercategory_id) " +
47                 "SELECT '%s', (SELECT id FROM category WHERE name = '%s' LIMIT
48                 1)", category, supercategory
49             );
50             try {
51                 statement.executeUpdate(query, RETURN_GENERATED_KEYS);
52                 final var generatedKeys = statement.getGeneratedKeys();
53                 if (generatedKeys.next()) {
54                     categoryIds[i] = generatedKeys.getInt(1);
55                 }
56                 i++;
57             } catch (SQLException e) {
58                 e.printStackTrace();
59             }
60             final var categoryTranslation = new CategoryTranslationTableGenerator(categoryIds)
61             ;
62             categoryTranslation.updateTableUsing(connection);
63         } catch (SQLException e) {
64             e.printStackTrace();
65         }
66     }
67 }

```

Листинг 11: CategoryTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.category;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import org.jetbrains.annotations.NotNull;
5
6 import java.sql.Connection;
7 import java.sql.SQLException;
8
9 public final class CategoryTranslationTableGenerator implements TableGenerator {
10
11     @NotNull
12     private final int[] categoryIds;
13
14     public CategoryTranslationTableGenerator(final @NotNull int[] categoryIds) {
15         this.categoryIds = categoryIds;
16     }
17 }

```

```

17
18 @Override
19 public void updateTableUsing(final @NotNull Connection connection) {
20     try (final var statement = connection.prepareStatement(
21         "INSERT INTO category_translation (category_id, language_id, translation)
22         VALUES (?, ?, ?)"
23     )) {
24         for (final var categoryId : categoryIds) {
25             for (int languageId = 1; languageId <= 2; ++languageId) {
26                 int i = 0;
27                 statement.setInt(++i, categoryId);
28                 statement.setInt(++i, languageId);
29                 statement.setString(++i, FAKER.lorem().word());
30                 statement.addBatch();
31             }
32         }
33         statement.executeBatch();
34     } catch (SQLException e) {
35         e.printStackTrace();
36     }
37 }
38 }

```

Листинг 12: CategoryTranslationTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.movie;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import org.jetbrains.annotations.NotNull;
5 import org.postgresql.util.PGmoney;
6
7 import java.sql.Connection;
8 import java.sql.SQLException;
9 import java.sql.Types;
10
11 import static java.sql.Statement.RETURN_GENERATED_KEYS;
12
13 public final class MovieTableGenerator implements TableGenerator {
14
15     private static final short[] MOVIE_PRICES_IN_USD = new short[]{5, 5, 5, 5, 5, 7, 7, 7, 7,
16     10, 10, 10, 15, 15, 20, 25, 35};
17     private final int movieCount;
18     private final int seriesSeasonId;
19     private final int seriesPrice;
20
21     public MovieTableGenerator(int count) {
22         this(count, 0, 0);
23     }
24
25     public MovieTableGenerator(int movieCount, int seriesSeasonId, int seriesPrice) {
26         this.movieCount = movieCount;
27         this.seriesSeasonId = seriesSeasonId;
28         this.seriesPrice = seriesPrice;
29     }
30
31     @Override
32     public void updateTableUsing(final @NotNull Connection connection) {
33         try (final var statement = connection.prepareStatement(
34             "INSERT INTO movie (price, release_date, imdb_rating, series_season_id) VALUES
35             (?, ?, ?, ?)",
36             RETURN_GENERATED_KEYS
37         )) {
38             final var moviesAreSeriesSeasonEpisodes = seriesSeasonId != 0;
39             final var date = UTILS.randomDate(50);
40             final var rating = UTILS.randomRating();
41             for (int i = 0; i < movieCount; ++i) {
42                 int j = 0;
43                 statement.setObject(++j, new PMoney("$" + (
44                     seriesPrice == 0 ?
45                     MOVIE_PRICES_IN_USD[RANDOM.nextInt(MOVIE_PRICES_IN_USD.length)]
46                     : seriesPrice
47                 )));
48                 if (moviesAreSeriesSeasonEpisodes) {

```

```

47         statement.setDate(++j, date);
48         statement.setFloat(++j, rating);
49         statement.setInt(++j, seriesSeasonId);
50     } else {
51         statement.setDate(++j, UTILS.randomDate(50));
52         statement.setFloat(++j, UTILS.randomRating());
53         statement.setNull(++j, Types.INTEGER);
54     }
55     statement.addBatch();
56 }
57 statement.executeBatch();
58
59 final var movieIds = UTILS.getIdsOfRowsInsertedWith(statement, movieCount);
60
61 final var movieTranslation = new MovieTranslationTableGenerator(movieIds,
moviesAreSeriesSeasonEpisodes);
62 movieTranslation.updateTableUsing(connection);
63
64 updateMovieCategoryTableUsing(connection, moviesAreSeriesSeasonEpisodes, movieIds)
;
65 } catch (SQLException e) {
66     e.printStackTrace();
67 }
68 }
69
70 private void updateMovieCategoryTableUsing(@NotNull Connection connection, boolean
moviesAreSeriesSeasonEpisodes, int[] movieIds) {
71     try (final var categoriesStatement = connection.createStatement()) {
72         categoriesStatement.executeQuery("SELECT COUNT(*) FROM category");
73         var result = categoriesStatement.getResultSet();
74         if (result != null && result.next()) {
75             int categoriesCount = result.getInt(1);
76             final var categoryIds = new int[categoriesCount - 1];
77             int i = 0;
78             categoriesStatement.executeQuery("SELECT id FROM category WHERE name != 'genre
");
79             result = categoriesStatement.getResultSet();
80             if (result != null) {
81                 while (result.next()) {
82                     categoryIds[i++] = result.getShort(1);
83                 }
84             }
85
86             final var movieCategory = new MovieCategoryTableGenerator(movieIds,
categoryIds, moviesAreSeriesSeasonEpisodes);
87             movieCategory.updateTableUsing(connection);
88         }
89     } catch (SQLException e) {
90         e.printStackTrace();
91     }
92 }
93
94 }

```

ЛИСТИНГ 13: MovieTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.movie;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import org.jetbrains.annotations.NotNull;
5
6 import java.sql.Connection;
7 import java.sql.SQLException;
8
9 public final class MovieTranslationTableGenerator implements TableGenerator {
10
11     private static final String VIDEO_URL_TEMPLATE = "https://blob.movie-service.lamtev.com/?
vid=";
12
13     @NotNull
14     private final int[] movieIds;
15     private final boolean moviesAreSeriesEpisodes;
16
17     public MovieTranslationTableGenerator(final @NotNull int[] movieIds, boolean
moviesAreSeriesEpisodes) {

```



```

18     this.movieIds = movieIds;
19     this.moviesAreSeriesEpisodes = moviesAreSeriesEpisodes;
20 }
21
22 @Override
23 public void updateTableUsing(final @NotNull Connection connection) {
24     try (final var statement = connection.prepareStatement(
25         "INSERT INTO movie_translation (movie_id, language_id, name, director,
26         description, file_url) " +
27         "VALUES (?, ?, ?, ?, ?, ?)"
28     )) {
29         final var director = moviesAreSeriesEpisodes ? FAKER.artist().name() : null;
30         for (int movieIdIdx = 0; movieIdIdx < movieIds.length; ++movieIdIdx) {
31             for (int languageId = 1; languageId <= 2; ++languageId) {
32                 int i = 0;
33                 statement.setInt(++i, movieIds[movieIdIdx]);
34                 statement.setInt(++i, languageId);
35                 if (moviesAreSeriesEpisodes) {
36                     statement.setString(++i, "Episode " + movieIdIdx);
37                     statement.setString(++i, director);
38                 } else {
39                     final var movie = FAKER.book();
40                     statement.setString(++i, movie.title());
41                     statement.setString(++i, movie.author());
42                 }
43                 statement.setString(++i, FAKER.lorem().paragraph(10));
44                 statement.setString(++i, randomUrl());
45                 statement.addBatch();
46             }
47         }
48         statement.executeBatch();
49     } catch (SQLException e) {
50         e.printStackTrace();
51     }
52 }
53
54 private String randomUrl() {
55     return VIDEO_URL_TEMPLATE + RANDOM.nextInt(Integer.MAX_VALUE);
56 }
57 }

```

Листинг 14: MovieTranslationTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.movie;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import gnu.trove.list.TIntList;
5 import gnu.trove.list.array.TIntArrayList;
6 import org.jetbrains.annotations.NotNull;
7
8 import java.sql.Connection;
9 import java.sql.SQLException;
10 import java.util.Arrays;
11
12 public final class MovieCategoryTableGenerator implements TableGenerator {
13
14     @NotNull
15     private final int[] movieIds;
16     @NotNull
17     private final TIntList categoryIds;
18     private final boolean sameCategoriesForAllMovies;
19
20     public MovieCategoryTableGenerator(final @NotNull int[] movieIds, final @NotNull int[]
21     categoryIds, boolean sameCategoriesForAllMovies) {
22         this.movieIds = movieIds;
23         this.categoryIds = new TIntArrayList(categoryIds.length);
24         Arrays.stream(categoryIds).forEach(this.categoryIds::add);
25         this.sameCategoriesForAllMovies = sameCategoriesForAllMovies;
26     }
27
28     @Override
29     public void updateTableUsing(final @NotNull Connection connection) {
30         try (final var statement = connection.prepareStatement(
31             "INSERT INTO movie_category (movie_id, category_id) VALUES (?, ?)"
32         )) {
33
34         }
35     }
36 }

```

```

31     )) {
32         final var categories = nRandomCategories(3);
33         for (int movieId : movieIds) {
34             final var differentCategories = nRandomCategories(3);
35             for (int j = 0; j < categories.length; ++j) {
36                 int i = 0;
37                 statement.setInt(++i, movieId);
38                 if (sameCategoriesForAllMovies) {
39                     statement.setInt(++i, categories[j]);
40                 } else {
41                     statement.setInt(++i, differentCategories[j]);
42                 }
43                 statement.addBatch();
44             }
45         }
46         statement.executeBatch();
47     } catch (SQLException e) {
48         e.printStackTrace();
49     }
50 }
51
52 @NotNull
53 private int[] nRandomCategories(int n) {
54     categoryIds.shuffle(RANDOM);
55     final var res = new int[n];
56     for (int i = 0; i < n; ++i) {
57         res[i] = categoryIds.get(i);
58     }
59
60     return res;
61 }
62
63 }

```

Листинг 15: MovieCategoryTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.series;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import com.lamtev.movie_service.datagen.generator.series.season.SeriesSeasonTableGenerator;
5 import org.jetbrains.annotations.NotNull;
6 import org.postgresql.util.PGmoney;
7
8 import java.sql.Connection;
9 import java.sql.SQLException;
10
11 import static java.sql.Statement.RETURN_GENERATED_KEYS;
12
13 public final class SeriesTableGenerator implements TableGenerator {
14
15     private static final short[] SERIES_PRICES_IN_USD = new short[]{10, 10, 10, 10, 17, 17,
16         17, 25, 25, 35};
17
18     /**
19      * [[1000, 3, 15], ...] - 1000 series, each consists of 3 seasons with 15 episodes
20      */
21     @NotNull
22     private final int[][] countSeasonsEpisodesArray;
23
24     public SeriesTableGenerator(final @NotNull int[][] countSeasonsEpisodes) {
25         this.countSeasonsEpisodesArray = countSeasonsEpisodes;
26     }
27
28     @Override
29     public void updateTableUsing(final @NotNull Connection connection) {
30         try (final var statement = connection.prepareStatement(
31             "INSERT INTO series (seasons, price) VALUES (?, ?)",
32             RETURN_GENERATED_KEYS
33         )) {
34             for (final var countSeasonsEpisodes : countSeasonsEpisodesArray) {
35                 final int seriesCount = countSeasonsEpisodes[0];
36                 final short seasons = (short) countSeasonsEpisodes[1];
37                 final var seriesPrices = new int[seriesCount];
38                 for (int seriesIdx = 0; seriesIdx < seriesCount; ++seriesIdx) {
39                     final int seriesPrice = SERIES_PRICES_IN_USD[RANDOM.nextInt(

```

```

39     SERIES_PRICES_IN_USD.length) ];
40     seriesPrices[seriesIdx] = seriesPrice;
41     int i = 0;
42     statement.setShort(++i, seasons);
43     statement.setObject(++i, new PGmoney("$" + seriesPrice));
44     statement.addBatch();
45 }
46 statement.executeBatch();
47
48 final var seriesIds = UTILS.getIdsOfRowsInsertedWith(statement, seriesCount);
49
50 final var seriesTranslation = new SeriesTranslationTableGenerator(seriesIds);
51 seriesTranslation.updateTableUsing(connection);
52
53 final int episodes = countSeasonsEpisodes[2];
54 final var seriesSeason = new SeriesSeasonTableGenerator(seriesIds,
55 seriesPrices, seasons, episodes);
56 seriesSeason.updateTableUsing(connection);
57 }
58 } catch (SQLException e) {
59     e.printStackTrace();
60 }
61 }

```

Листинг 16: SeriesTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.series;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import org.jetbrains.annotations.NotNull;
5
6 import java.sql.Connection;
7 import java.sql.SQLException;
8
9 public final class SeriesTranslationTableGenerator implements TableGenerator {
10
11     @NotNull
12     private final int[] seriesIds;
13
14     public SeriesTranslationTableGenerator(final @NotNull int[] seriesIds) {
15         this.seriesIds = seriesIds;
16     }
17
18     @Override
19     public void updateTableUsing(final @NotNull Connection connection) {
20         try (final var statement = connection.prepareStatement(
21             "INSERT INTO series_translation (series_id, language_id, name, director,
22             description) VALUES (?, ?, ?, ?, ?)"
23         )) {
24             for (final var seriesId : seriesIds) {
25                 for (int languageId = 1; languageId <= 2; ++languageId) {
26                     int i = 0;
27                     statement.setInt(++i, seriesId);
28                     statement.setInt(++i, languageId);
29                     final var series = FAKER.book();
30                     statement.setString(++i, series.title());
31                     statement.setString(++i, series.author());
32                     statement.setString(++i, FAKER.lorem().paragraph(10));
33                     statement.addBatch();
34                 }
35             }
36             statement.executeBatch();
37         } catch (SQLException e) {
38             e.printStackTrace();
39         }
40     }
41 }

```

Листинг 17: SeriesTranslationTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.series.season;

```

```

2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import com.lamtev.movie_service.datagen.generator.movie.MovieTableGenerator;
5 import org.jetbrains.annotations.NotNull;
6
7 import java.sql.Connection;
8 import java.sql.SQLException;
9
10 import static java.sql.Statement.RETURN_GENERATED_KEYS;
11
12 public final class SeriesSeasonTableGenerator implements TableGenerator {
13
14     @NotNull
15     private final int[] seriesIds;
16     @NotNull
17     private final int[] seriesPrices;
18     private final short seasonsCount;
19     private final int episodesCount;
20
21     public SeriesSeasonTableGenerator(final @NotNull int[] seriesIds,
22                                     final @NotNull int[] seriesPrices, short seasonsCount,
23                                     int episodesCount) {
24         this.seriesIds = seriesIds;
25         this.seriesPrices = seriesPrices;
26         this.seasonsCount = seasonsCount;
27         this.episodesCount = episodesCount;
28     }
29
30     @Override
31     public void updateTableUsing(final @NotNull Connection connection) {
32         try (final var statement = connection.prepareStatement(
33             "INSERT INTO series_season (series_id, number) VALUES (?, ?)",
34             RETURN_GENERATED_KEYS
35         )) {
36             for (final int id : seriesIds) {
37                 for (short season = 0; season < seasonsCount; ++season) {
38                     int i = 0;
39                     statement.setInt(++i, id);
40                     statement.setShort(++i, season);
41                     statement.addBatch();
42                 }
43             }
44             statement.executeBatch();
45
46             final var seasonIds = UTILS.getIdsOfRowsInsertedWith(statement, seriesIds.length *
47                 seasonsCount);
48
49             final var seasonTranslation = new SeriesSeasonTranslationTableGenerator(seasonIds)
50 ;
51             seasonTranslation.updateTableUsing(connection);
52
53             for (int seasonIdx = 0; seasonIdx < seasonIds.length; ++seasonIdx) {
54                 final var episode = new MovieTableGenerator(episodesCount, seasonIds[seasonIdx]
55 ], seriesPrices[seasonIdx / seasonsCount]);
56                 episode.updateTableUsing(connection);
57             }
58         } catch (SQLException e) {
59             e.printStackTrace();
60         }
61     }
62 }

```

Листинг 18: SeriesSeasonTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.series.season;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import org.jetbrains.annotations.NotNull;
5
6 import java.sql.Connection;
7 import java.sql.SQLException;
8
9 public final class SeriesSeasonTranslationTableGenerator implements TableGenerator {
10

```

```

11  @NotNull
12  private final int[] seasonIds;
13
14  public SeriesSeasonTranslationTableGenerator(final @NotNull int[] seasonIds) {
15      this.seasonIds = seasonIds;
16  }
17
18  @Override
19  public void updateTableUsing(final @NotNull Connection connection) {
20      try (final var statement = connection.prepareStatement(
21          "INSERT INTO series_season_translation (series_season_id, language_id, name,
22          description) " +
23              " VALUES (?, ?, ?, ?)"
24      )) {
25          for (int languageId = 1; languageId <= 2; ++languageId) {
26              for (final var seasonId : seasonIds) {
27                  int i = 0;
28                  statement.setInt(++i, seasonId);
29                  statement.setInt(++i, languageId);
30                  statement.setString(++i, FAKER.book().title());
31                  statement.setString(++i, FAKER.lorem().paragraph(10));
32                  statement.addBatch();
33              }
34          }
35          statement.executeBatch();
36      } catch (SQLException e) {
37          e.printStackTrace();
38      }
39  }
40 }

```

Листинг 19: SeriesSeasonTranslationTableGenerator.java

```

1  package com.lamtev.movie_service.datagen.generator.user;
2
3  import com.lamtev.movie_service.datagen.generator.TableGenerator;
4  import org.jetbrains.annotations.NotNull;
5
6  import java.sql.Connection;
7  import java.sql.SQLException;
8
9  import static java.sql.Statement.RETURN_GENERATED_KEYS;
10
11 public final class UserTableGenerator implements TableGenerator {
12
13     private static byte[] buf = null;
14     private final long count;
15     private final int femalePercent;
16
17     public UserTableGenerator(long count, int femalePercentage) {
18         this.count = count;
19         this.femalePercent = femalePercentage;
20     }
21
22     @Override
23     public void updateTableUsing(final @NotNull Connection connection) {
24         try (final var statement = connection.prepareStatement(
25             "INSERT INTO \"user\" (login, password_hash, email, birthday, sex, first_name,
26             last_name) " +
27                 "VALUES (?, ?, ?, ?, ?, ?, ?)",
28             RETURN_GENERATED_KEYS
29         )) {
30             for (int i = 0; i < count; ++i) {
31                 int j = 0;
32                 final var firstName = FAKER.name().firstName();
33                 final var lastName = FAKER.name().lastName();
34                 final var username = firstName + "." + lastName + RANDOM.nextInt(((int) count));
35                 statement.setString(++j, username);
36                 statement.setString(++j, Long.toHexString(FAKER.number().randomNumber()));
37                 statement.setString(++j, username + "@email.com");
38                 statement.setDate(++j, UTILS.randomDate(100));
39                 statement.setString(++j, randomSex());
40                 statement.setString(++j, firstName);
41                 statement.setString(++j, lastName);

```

```

41         statement.addBatch();
42     }
43     statement.executeBatch();
44 } catch (SQLException e) {
45     e.printStackTrace();
46 }
47 }
48
49 private String randomSex() {
50     if (buf == null) {
51         buf = new byte[100];
52         for (int i = 0; i < buf.length; ++i) {
53             if (i < femalePercent) {
54                 buf[i] = 0;
55             } else {
56                 buf[i] = 1;
57             }
58         }
59     }
60
61     return Byte.toString(buf[RANDOM.nextInt(100)]);
62 }
63
64 }

```

Листинг 20: UserTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.user;
2
3 import com.lamtev.movie_service.datagen.generator.StorageDAO;
4 import com.lamtev.movie_service.datagen.generator.TableGenerator;
5 import org.jetbrains.annotations.NotNull;
6 import org.jetbrains.annotations.Nullable;
7 import org.postgresql.util.PGmoney;
8
9 import java.sql.Connection;
10 import java.sql.SQLException;
11
12 public final class UserMovieTableGenerator implements TableGenerator {
13
14     private final int percentageOfUsersWhoBoughtMovies;
15     private final int minMovies;
16     private final int maxMovies;
17
18     public UserMovieTableGenerator(int percentageOfUsersWhoBoughtMovies, int minMovies, int
19 maxMovies) {
20         this.percentageOfUsersWhoBoughtMovies = percentageOfUsersWhoBoughtMovies;
21         this.minMovies = minMovies;
22         this.maxMovies = maxMovies;
23     }
24
25     @Override
26     public void updateTableUsing(final @NotNull Connection connection) {
27         final var userIds = StorageDAO.instance().ids(connection, "\"user\"");
28         final var movieIdsPrices = movieIdsPrices(connection);
29         if (userIds.length == 0 || movieIdsPrices == null) {
30             return;
31         }
32
33         try (final var statement = connection.prepareStatement(
34             "INSERT INTO user_movie (user_id, movie_id, payment) VALUES (?, ?, ?)"
35         )) {
36             for (final var userId : userIds) {
37                 if (userId % 100 < percentageOfUsersWhoBoughtMovies) {
38                     final var nMovies = RANDOM.nextInt(maxMovies - minMovies + 1) + minMovies;
39                     final var movieIdx = RANDOM.nextInt(movieIdsPrices[0].length - nMovies);
40                     for (int i = 0; i < nMovies; ++i) {
41                         int j = 0;
42                         statement.setLong(++j, userId);
43                         statement.setInt(++j, movieIdsPrices[0][movieIdx + i]);
44                         statement.setObject(++j, new PMoney("$" + movieIdsPrices[1][movieIdx
45 + i]));
46                         statement.addBatch();
47                     }
48                 }
49             }
50         }
51     }
52 }

```

```

47     }
48     statement.executeBatch();
49 } catch (SQLException e) {
50     e.printStackTrace();
51 }
52 }
53
54 @Nullable
55 private int[][] movieIdsPrices(final @NotNull Connection connection) {
56     try (final var statement = connection.createStatement()) {
57         int count = StorageDAO.instance().count(connection, "movie");
58         int[][] movieIdsPrices = new int[2][count];
59         statement.executeQuery("SELECT id, price FROM movie");
60         final var result = statement.getResultSet();
61         int i = 0;
62         if (result != null) {
63             while (result.next()) {
64                 movieIdsPrices[0][i] = result.getInt(1);
65                 movieIdsPrices[1][i] = result.getInt(2);
66                 i++;
67             }
68         }
69
70         return movieIdsPrices;
71     } catch (SQLException e) {
72         e.printStackTrace();
73     }
74
75     return null;
76 }
77
78 }

```

Листинг 21: UserMovieTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.user;
2
3 import com.lamtev.movie_service.datagen.generator.StorageDAO;
4 import com.lamtev.movie_service.datagen.generator.TableGenerator;
5 import org.jetbrains.annotations.NotNull;
6 import org.jetbrains.annotations.Nullable;
7 import org.postgresql.util.PGmoney;
8
9 import java.sql.Connection;
10 import java.sql.SQLException;
11
12 public final class UserSeriesTableGenerator implements TableGenerator {
13
14     private final int percentageOfUsersWhoBoughtSeries;
15     private final int minSeries;
16     private final int maxSeries;
17
18     public UserSeriesTableGenerator(int percentageOfUsersWhoBoughtSeries, int minSeries, int
19 maxSeries) {
20         this.percentageOfUsersWhoBoughtSeries = percentageOfUsersWhoBoughtSeries;
21         this.minSeries = minSeries;
22         this.maxSeries = maxSeries;
23     }
24
25     //TODO: get rid of duplicates
26     @Override
27     public void updateTableUsing(final @NotNull Connection connection) {
28         final var userIds = StorageDAO.instance().ids(connection, "\"user\"");
29         final var seriesIdsPrices = seriesIdsPrices(connection);
30         if (userIds.length == 0 || seriesIdsPrices == null) {
31             return;
32         }
33         try (final var statement = connection.prepareStatement(
34             "INSERT INTO user_series (user_id, series_id, payment) VALUES (?, ?, ?)"
35         )) {
36             for (final var userId : userIds) {
37                 if (userId % 100 < percentageOfUsersWhoBoughtSeries) {
38                     final var nSeries = RANDOM.nextInt(maxSeries - minSeries + 1) + minSeries;
39                     final var seriesIdx = RANDOM.nextInt(seriesIdsPrices[0].length - nSeries);
40                     for (int i = 0; i < nSeries; ++i) {

```

```

40         int j = 0;
41         statement.setLong(++j, userId);
42         statement.setInt(++j, seriesIdsPrices[0][seriesIdx + i]);
43         statement.setObject(++j, new PGmoney("$" + seriesIdsPrices[1][
seriesIdx + i]));
44         statement.addBatch();
45     }
46 }
47 }
48 statement.executeBatch();
49 } catch (SQLException e) {
50     e.printStackTrace();
51 }
52 }
53
54 @Nullable
55 private int[][] seriesIdsPrices(final @NotNull Connection connection) {
56     try (final var statement = connection.createStatement()) {
57         int count = StorageDAO.instance().count(connection, "series");
58         int[][] seriesIdsPrices = new int[2][count];
59         statement.executeQuery("SELECT id, price FROM series");
60         final var result = statement.getResultSet();
61         int i = 0;
62         if (result != null) {
63             while (result.next()) {
64                 seriesIdsPrices[0][i] = result.getInt(1);
65                 seriesIdsPrices[1][i] = result.getInt(2);
66                 i++;
67             }
68         }
69
70         return seriesIdsPrices;
71     } catch (SQLException e) {
72         e.printStackTrace();
73     }
74
75     return null;
76 }
77
78 }

```

Листинг 22: UserSeriesTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.subscription;
2
3 import com.lamtev.movie_service.datagen.generator.StorageDAO;
4 import com.lamtev.movie_service.datagen.generator.TableGenerator;
5 import org.jetbrains.annotations.NotNull;
6 import org.postgresql.util.PGmoney;
7
8 import java.sql.Connection;
9 import java.sql.Date;
10 import java.sql.SQLException;
11 import java.util.Calendar;
12
13 public final class SubscriptionTableGenerator implements TableGenerator {
14
15     private final long usersCount;
16     private final int minSubscriptionsPerUser;
17     private final int maxSubscriptionsPerUser;
18     @NotNull
19     private final int[][] durationPriceNMoviesMSeasons;
20     private final int yearsSinceFirstSubscription;
21
22     public SubscriptionTableGenerator(long usersCount, int minSubscriptionsPerUser,
23                                     int maxSubscriptionsPerUser, final @NotNull int[][]
durationPriceNMoviesMSeasons,
24                                     int yearsSinceFirstSubscription) {
25         this.usersCount = usersCount;
26         this.minSubscriptionsPerUser = minSubscriptionsPerUser;
27         this.maxSubscriptionsPerUser = maxSubscriptionsPerUser;
28         this.durationPriceNMoviesMSeasons = durationPriceNMoviesMSeasons;
29         this.yearsSinceFirstSubscription = yearsSinceFirstSubscription;
30     }
31

```



```

32  @Override
33  public void updateTableUsing(final @NotNull Connection connection) {
34      final var userIds = StorageDAO.instance().ids(connection, "\\user\\");
35      try (final var statement = connection.prepareStatement(
36          "INSERT INTO subscription (user_id, started, expires, autorenewable, payment)
VALUES (?, ?, ?, ?, ?)"
37      )) {
38          RANDOM.ints(usersCount, 0, userIds.length).forEach(idx -> {
39              final var nSubscriptions = RANDOM.nextInt(maxSubscriptionsPerUser -
minSubscriptionsPerUser + 1) + minSubscriptionsPerUser;
40              for (int j = 0; j < nSubscriptions; ++j) {
41                  int i = 0;
42                  try {
43                      statement.setLong(++i, userIds[idx]);
44                      final var started = UTILS.randomDate(yearsSinceFirstSubscription);
45                      statement.setObject(++i, started);
46                      final var calendar = Calendar.getInstance();
47                      calendar.setTimeInMillis(started.getTime());
48                      final var durationPrice = durationPriceNMoviesMSeasons[RANDOM.nextInt(
durationPriceNMoviesMSeasons.length)];
49                      calendar.add(Calendar.DATE, durationPrice[0]);
50                      statement.setObject(++i, new Date(calendar.getTimeInMillis()));
51                      statement.setBoolean(++i, RANDOM.nextBoolean());
52                      statement.setObject(++i, new PGmoney("$" + durationPrice[1]));
53                      statement.addBatch();
54                  } catch (SQLException e) {
55                      e.printStackTrace();
56                  }
57              }
58          });
59
60          statement.executeBatch();
61      } catch (SQLException e) {
62          e.printStackTrace();
63      }
64  }
65
66  }

```

ЛИСТИНГ 23: SubscriptionTableGenerator.java

```

1  package com.lamtev.movie_service.datagen.generator.subscription;
2
3  import com.lamtev.movie_service.datagen.generator.TableGenerator;
4  import org.jetbrains.annotations.NotNull;
5
6  import java.sql.Connection;
7  import java.sql.SQLException;
8
9  public final class SubscriptionMovieTableGenerator implements TableGenerator {
10
11      @NotNull
12      private final int[][] subscriptionIdsNMovies;
13      @NotNull
14      private final int[] movieIds;
15
16      public SubscriptionMovieTableGenerator(final @NotNull int[][] subscriptionIdsNMovies,
final @NotNull int[] movieIds) {
17          this.subscriptionIdsNMovies = subscriptionIdsNMovies;
18          this.movieIds = movieIds;
19      }
20
21      @Override
22      public void updateTableUsing(final @NotNull Connection connection) {
23          try (final var statement = connection.prepareStatement(
24              "INSERT INTO subscription_movie (subscription_id, movie_id) VALUES (?, ?)"
25          )) {
26              for (int j = 0; j < subscriptionIdsNMovies[0].length; ++j) {
27                  final var nMovies = subscriptionIdsNMovies[1][j];
28                  final var movieIdsIdxs = UTILS.nUniqueRandomInts(nMovies, movieIds.length);
29                  for (final var movieIdsIdx : movieIdsIdxs) {
30                      int i = 0;
31                      statement.setLong(++i, subscriptionIdsNMovies[0][j]);
32                      statement.setInt(++i, movieIds[movieIdsIdx]);
33                      statement.addBatch();

```

```

34         }
35     }
36     statement.executeBatch();
37 } catch (SQLException e) {
38     e.printStackTrace();
39 }
40 }
41
42 }

```

Листинг 24: SubscriptionMovieTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator.subscription;
2
3 import com.lamtev.movie_service.datagen.generator.TableGenerator;
4 import org.jetbrains.annotations.NotNull;
5
6 import java.sql.Connection;
7 import java.sql.SQLException;
8
9 public final class SubscriptionSeriesSeasonTableGenerator implements TableGenerator {
10
11     @NotNull
12     private final int[][] subscriptionIdsMSeasons;
13     @NotNull
14     private final int[] seriesSeasonIds;
15
16     public SubscriptionSeriesSeasonTableGenerator(final @NotNull int[][]
subscriptionIdsMSeasons, final @NotNull int[] seriesSeasonIds) {
17         this.subscriptionIdsMSeasons = subscriptionIdsMSeasons;
18         this.seriesSeasonIds = seriesSeasonIds;
19     }
20
21     @Override
22     public void updateTableUsing(final @NotNull Connection connection) {
23         try (final var statement = connection.prepareStatement(
24             "INSERT INTO subscription_series_season (subscription_id, series_season_id)
VALUES (?, ?)"
25         )) {
26             for (int j = 0; j < subscriptionIdsMSeasons[0].length; ++j) {
27                 final var nSeriesSeasons = subscriptionIdsMSeasons[1][j];
28                 final var seriesIdsIdxs = UTILS.nUniqueRandomInts(nSeriesSeasons,
seriesSeasonIds.length);
29                 for (final var seriesIdsIdx : seriesIdsIdxs) {
30                     int i = 0;
31                     statement.setLong(++i, subscriptionIdsMSeasons[0][j]);
32                     statement.setInt(++i, seriesSeasonIds[seriesIdsIdx]);
33                     statement.addBatch();
34                 }
35             }
36             statement.executeBatch();
37         } catch (SQLException e) {
38             e.printStackTrace();
39         }
40     }
41
42 }

```

Листинг 25: SubscriptionSeriesSeasonTableGenerator.java

```

1 package com.lamtev.movie_service.datagen.generator;
2
3 import org.jetbrains.annotations.NotNull;
4
5 import java.sql.Connection;
6 import java.sql.SQLException;
7
8 public final class StorageDAO {
9
10     private StorageDAO() {
11     }
12
13     public static StorageDAO instance() {
14         return Holder.INSTANCE;
15     }
16 }

```

```

15     }
16
17     public final int count(final @NotNull Connection connection, final @NotNull String
18     tableName) {
19         int count = 0;
20         try (final var statement = connection.createStatement()) {
21             statement.executeQuery("SELECT COUNT(*) FROM " + tableName);
22             var result = statement.getResultSet();
23             if (result != null && result.next()) {
24                 count = result.getInt(1);
25             }
26         } catch (SQLException e) {
27             e.printStackTrace();
28         }
29         return count;
30     }
31
32     @NotNull
33     public final int[] ids(final @NotNull Connection connection, final @NotNull String
34     tableName) {
35         try (final var statement = connection.createStatement()) {
36             final int count = count(connection, tableName);
37
38             final var ids = new int[count];
39             statement.executeQuery("SELECT id FROM " + tableName);
40
41             final var result = statement.getResultSet();
42             if (result != null) {
43                 int i = 0;
44                 while (result.next()) {
45                     ids[i++] = result.getInt(1);
46                 }
47             }
48             return ids;
49         } catch (SQLException e) {
50             e.printStackTrace();
51         }
52         return new int[0];
53     }
54
55     private static final class Holder {
56         private static final StorageDAO INSTANCE = new StorageDAO();
57     }
58 }

```

Листинг 26: StorageDAO.java

```

1 package com.lamtev.movie_service.datagen.generator.subscription;
2
3
4 import com.lamtev.movie_service.datagen.generator.StorageDAO;
5 import org.jetbrains.annotations.NotNull;
6
7 import java.sql.Connection;
8 import java.sql.SQLException;
9
10 public final class SubscriptionTableDAO {
11
12     private SubscriptionTableDAO() {
13     }
14
15     public static SubscriptionTableDAO instance() {
16         return Holder.INSTANCE;
17     }
18
19     @NotNull
20     public int[][] idsNMoviesOrMSeasons(final @NotNull Connection connection, final @NotNull
21     int[][] durationPriceNMoviesMSeasons) {
22         try (final var statement = connection.createStatement()) {
23             int count = StorageDAO.instance().count(connection, "subscription");
24             final var idsNMoviesOrMSeasons = new int[3][count];
25             statement.executeQuery("SELECT id, (expires - started), payment FROM subscription
26             GROUP BY id");
27             final var result = statement.getResultSet();

```

```

26         int i = 0;
27         if (result != null) {
28             while (result.next()) {
29                 idsNMoviesOrMSeasons[0][i] = result.getInt(1);
30                 final var mm = nMoviesMSeasons(result.getInt(2), result.getInt(3),
durationPriceNMoviesMSeasons);
31                 idsNMoviesOrMSeasons[1][i] = mm[0];
32                 idsNMoviesOrMSeasons[2][i] = mm[1];
33                 i++;
34             }
35         }
36         return idsNMoviesOrMSeasons;
37     } catch (SQLException e) {
38         e.printStackTrace();
39     }
40     return new int[0][0];
41 }
42
43 @NotNull
44 private int[] nMoviesMSeasons(int duration, int payment, final @NotNull int[][]
durationPriceNMoviesMSeasons) {
45     int n = 0;
46     int m = 0;
47     for (int[] durationPriceNMoviesMSeason : durationPriceNMoviesMSeasons) {
48         if (durationPriceNMoviesMSeason[0] == duration && durationPriceNMoviesMSeason[1]
== payment) {
49             n = durationPriceNMoviesMSeason[2];
50             m = durationPriceNMoviesMSeason[3];
51             break;
52         }
53     }
54
55     return new int[]{n, m};
56 }
57
58 private static final class Holder {
59     private static final SubscriptionTableDAO INSTANCE = new SubscriptionTableDAO();
60 }
61
62 }

```

Листинг 27: SubscriptionTableDAO.java

```

1 package com.lamtev.movie_service.datagen.generator;
2
3 import com.github.javafaker.Faker;
4 import gnu.trove.set.hash.TIntHashSet;
5 import org.jetbrains.annotations.NotNull;
6
7 import java.sql.Date;
8 import java.sql.SQLException;
9 import java.sql.Statement;
10 import java.util.Random;
11 import java.util.concurrent.TimeUnit;
12
13 public final class Utils {
14
15     @NotNull
16     private final Random random;
17     @NotNull
18     private final Faker faker;
19
20
21     public Utils(@NotNull Random random, @NotNull Faker faker) {
22         this.random = random;
23         this.faker = faker;
24     }
25
26     public static void split(final @NotNull int[][] subscriptionIdsNMoviesMSeasons, int
moviesPercentage, final @NotNull int[][] subscriptionIdsNMovies, final @NotNull int[][]
subscriptionIdsMSeasons) {
27         int moviesIdx = 0;
28         int seasonsIdx = 0;
29         int moviesLength = (int) Math.ceil((double) subscriptionIdsNMoviesMSeasons[0].length /
100) * moviesPercentage;

```

```

30     int seasonsLength = subscriptionIdsNMoviesMSeasons[0].length - moviesLength;
31     for (int i = 0; i < 2; ++i) {
32         subscriptionIdsNMovies[i] = new int[moviesLength];
33         subscriptionIdsMSeasons[i] = new int[seasonsLength];
34     }
35     for (int i = 0; i < subscriptionIdsNMoviesMSeasons[0].length; ++i) {
36         if (i % 100 < moviesPercentage) {
37             subscriptionIdsNMovies[0][moviesIdx] = subscriptionIdsNMoviesMSeasons[0][i];
38             subscriptionIdsNMovies[1][moviesIdx] = subscriptionIdsNMoviesMSeasons[1][i];
39             moviesIdx++;
40         } else {
41             subscriptionIdsMSeasons[0][seasonsIdx] = subscriptionIdsNMoviesMSeasons[0][i];
42             subscriptionIdsMSeasons[1][seasonsIdx] = subscriptionIdsNMoviesMSeasons[2][i];
43             seasonsIdx++;
44         }
45     }
46 }
47
48 @NotNull
49 public int[] getIdsOfRowsInsertedWith(final @NotNull Statement statement, int ofLength) {
50     final var keys = new int[ofLength];
51     int i = 0;
52     try (final var generatedKeys = statement.getGeneratedKeys()) {
53         while (generatedKeys.next()) {
54             keys[i++] = generatedKeys.getInt(1);
55         }
56     } catch (SQLException e) {
57         e.printStackTrace();
58     }
59
60     return keys;
61 }
62
63 @NotNull
64 public Date randomDate(int maxYearsAgo) {
65     return new Date(faker.date().past(365 * maxYearsAgo, TimeUnit.DAYS).getTime());
66 }
67
68 public float randomRating() {
69     return 5.0f + random.nextFloat() * (10.0f - 5.0f);
70 }
71
72 @NotNull
73 public int[] nUniqueRandomInts(int n, int bound) {
74     final var ints = new TIntHashSet(n);
75     while (ints.size() != n) {
76         ints.add(random.nextInt(bound));
77     }
78
79     return ints.toArray();
80 }
81
82 }

```

Листинг 28: Utils.java