

## List of schemas:

chef(chef\_id PK, name, salary,address)

meal\_prepared( chef\_id PK FK, meal\_id PK FK)

meal(meal\_id PK, name, price)

meal\_with\_ingre(meal\_id PK FK, ingredient\_id PK FK)

ingredient(ingredient\_id PK, supplier\_id FK, price, qty, description)

supplier(supplier\_id PK, name, location)

supplier\_phone(supplier\_id PK FK, phone\_number)

waiter(waiter\_id PK, name, salary, address)

customer\_served(waiter\_id PK FK, customer\_id PK FK)

order(order\_id PK, customer\_id FK, bill\_id FK, waiter\_id FK, items, qty, total\_price)

order\_line(order\_id PK FK, meal\_id PK FK)

customer(customer\_id PK, name, address)

customer\_phone(customer\_id PK FK, phone\_number)

bill(bill\_id PK, order\_id FK, customer\_id FK, totalprice, date\_paid)

## 3 pseudocode

SELECT \* FROM customer JOIN order ON customer\_id;

 ${\tt SELECT*FROM\ order\ JOIN\ order\ \_line\ ON\ order\ \_id\ JOIN\ bill\ ON\ order\ \_id;}$ 

SELECT \* FROM meal JOIN meal\_prepared ON chef\_id;