

Class 10: Structural Bioinformatics Pt.1

Lana (PID: A17013518)

The PDB Database

Here we examine the size and composition of the main database of the bio molecules structures- the PDB.

Get a csv file from the PDB and read it in R.

```
pdbstats<- read.csv("Data Export Summary.csv", row.names=1)
head(pdbstats)
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	161,663	12,592	12,337	200	74	32
Protein/Oligosaccharide	9,348	2,167	34	8	2	0
Protein/NA	8,404	3,924	286	7	0	0
Nucleic acid (only)	2,758	125	1,477	14	3	1
Other	164	9	33	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	186,898					
Protein/Oligosaccharide	11,559					
Protein/NA	12,621					
Nucleic acid (only)	4,378					
Other	206					
Oligosaccharide (only)	22					

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy

My pdbstats data frame has number with commas in them. This may cause problems.

```
pdbstats$X.ray
```

```
[1] "161,663" "9,348" "8,404" "2,758" "164" "11"
```

```
as.numeric(pdbstats$X.ray)
```

Warning: NAs introduced by coercion

```
[1] NA NA NA NA 164 11
```

```
x<- "22,200"  
as.numeric(gsub(",", "", x))
```

```
[1] 22200
```

We found a function called 'gsub' now we can figure out how it works

```
as.numeric(gsub(",", "", x))
```

```
[1] 22200
```

```
gsub(",", "", pdbstats$X.ray)
```

```
[1] "161663" "9348" "8404" "2758" "164" "11"
```

I can turn this snip-it into a function that I can use on every column.

```
commasum<- function(x){  
  sum(as.numeric(gsub(",", "", x)))  
}  
commasum(pdbstats$X.ray)
```

```
[1] 182348
```

```
totals<-apply(pdbstats, 2, commasum)  
round((totals/totals["Total"]*100),2)
```

X.ray	EM	NMR	Multiple.methods
84.54	8.72	6.57	0.11
Neutron	Other	Total	
0.04	0.02	100.00	

84.54% are solved by x-ray and 8.72 is solved by EM.

Q2: What proportion of structures in the PDB are protein?

```
(215684/249751891*100)
```

```
[1] 0.08635931
```

2. Visualizing the HIV-1 protease structure

You can use Mol* directly at the PDB website (as well as UniProt and elsewhere). However, for the latest and greatest version we will visit the Mol* homepage at: <https://molstar.org/viewer/>.

We will play with PDB code 1HSG



Back to R and working with PDB structures

```
library(bio3d)

hiv<- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
hiv
```

Call: read.pdb(file = "1hsg")

```
Total Models#: 1
  Total Atoms#: 1686,  XYZs#: 5058  Chains#: 2  (values: A B)

  Protein Atoms#: 1514  (residues/Calpha atoms#: 198)
  Nucleic acid Atoms#: 0  (residues/phosphate atoms#: 0)

  Non-protein/nucleic Atoms#: 172  (residues: 128)
  Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]
```

Protein sequence:

```
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLLTQIGCTLNF
```

```
+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
head(hiv$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40

```

5 ATOM      5      CB <NA>  PRO      A      1      <NA> 30.508 37.541 6.342 1 37.87
6 ATOM      6      CG <NA>  PRO      A      1      <NA> 29.296 37.591 7.162 1 38.40
  segid elesy charge
1  <NA>      N  <NA>
2  <NA>      C  <NA>
3  <NA>      C  <NA>
4  <NA>      O  <NA>
5  <NA>      C  <NA>
6  <NA>      C  <NA>

```

```

pdbseq(hiv)

```

```

  1   2   3   4   5   6   7   8   9  10  11  12  13  14  15  16  17  18  19  20
"P" "Q" "I" "T" "L" "W" "Q" "R" "P" "L" "V" "T" "I" "K" "I" "G" "G" "Q" "L" "K"
 21  22  23  24  25  26  27  28  29  30  31  32  33  34  35  36  37  38  39  40
"E" "A" "L" "L" "D" "T" "G" "A" "D" "D" "T" "V" "L" "E" "E" "M" "S" "L" "P" "G"
 41  42  43  44  45  46  47  48  49  50  51  52  53  54  55  56  57  58  59  60
"R" "W" "K" "P" "K" "M" "I" "G" "G" "I" "G" "G" "F" "I" "K" "V" "R" "Q" "Y" "D"
 61  62  63  64  65  66  67  68  69  70  71  72  73  74  75  76  77  78  79  80
"Q" "I" "L" "I" "E" "I" "C" "G" "H" "K" "A" "I" "G" "T" "V" "L" "V" "G" "P" "T"
 81  82  83  84  85  86  87  88  89  90  91  92  93  94  95  96  97  98  99   1
"P" "V" "N" "I" "I" "G" "R" "N" "L" "L" "T" "Q" "I" "G" "C" "T" "L" "N" "F" "P"
  2   3   4   5   6   7   8   9  10  11  12  13  14  15  16  17  18  19  20  21
"Q" "I" "T" "L" "W" "Q" "R" "P" "L" "V" "T" "I" "K" "I" "G" "G" "Q" "L" "K" "E"
 22  23  24  25  26  27  28  29  30  31  32  33  34  35  36  37  38  39  40  41
"A" "L" "L" "D" "T" "G" "A" "D" "D" "T" "V" "L" "E" "E" "M" "S" "L" "P" "G" "R"
 42  43  44  45  46  47  48  49  50  51  52  53  54  55  56  57  58  59  60  61
"W" "K" "P" "K" "M" "I" "G" "G" "I" "G" "G" "F" "I" "K" "V" "R" "Q" "Y" "D" "Q"
 62  63  64  65  66  67  68  69  70  71  72  73  74  75  76  77  78  79  80  81
"I" "L" "I" "E" "I" "C" "G" "H" "K" "A" "I" "G" "T" "V" "L" "V" "G" "P" "T" "P"
 82  83  84  85  86  87  88  89  90  91  92  93  94  95  96  97  98  99
"V" "N" "I" "I" "G" "R" "N" "L" "L" "T" "Q" "I" "G" "C" "T" "L" "N" "F"

```

Here we will do a normal mode analysis (NMA) to predict functional motions of a kinase protein.

```

adk<- read.pdb("6s36")

```

Note: Accessing on-line PDB file

PDB has ALT records, taking A only, rm.alt=TRUE

```
adk
```

```
Call: read.pdb(file = "6s36")
```

```
Total Models#: 1
```

```
Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)
```

```
Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
```

```
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)
```

```
Non-protein/nucleic Atoms#: 244 (residues: 244)
```

```
Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]
```

```
Protein sequence:
```

```
MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLV  
DELVIALVKERIAQEDCRNGFLLDGFPRTPQADAMKEAGINVDYVLEFDVPDELIVDKI  
VGRRVHAPSGRVYHVKFNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQMTAPLIG  
YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
```


```
+ attr: atom, xyz, seqres, helix, sheet,  
      calpha, remark, call
```

```
modes <- nma(adk)
```

```
Building Hessian... Done in 0.014 seconds.
```

```
Diagonalizing Hessian... Done in 0.271 seconds.
```

```
plot(modes)
```



Make a “move” called a trajectory of the predicted motions:

```
mktrj(modes, file="adk_m7.pdb")
```